

### #01\_WLAN2.4GHz\_802.11b 1Mbps\_Right Side\_10mm\_Ch6

Communication System: UID 10415 - AAA,802.11b; Frequency: 2437 MHz

Medium: HSL\_2450\_240315 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.839$  S/m;  $\epsilon_r = 39.737$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.92, 7.92, 7.92) @ 2437 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (81x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.767 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.45 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 0.853 W/kg

**SAR(1 g) = 0.455 W/kg; SAR(10 g) = 0.242 W/kg**

Smallest distance from peaks to all points 3 dB below = 15.5 mm

Ratio of SAR at M2 to SAR at M1 = 53.3%

Maximum value of SAR (measured) = 0.700 W/kg



0 dB = 0.700 W/kg = -1.55 dBW/kg

## #02\_WLAN5GHz\_802.11n-HT40 MCS0\_Back\_10mm\_Ch54

Communication System: 802.11n; Frequency: 5270.000 MHz

Medium: HSL\_5G\_240408 Medium parameters used:  $f = 5270.000$  MHz;  $\sigma = 4.77$  S/m;  $\epsilon_r = 36.5$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

### DASY8 Configuration:

- Probe: EX3DV4 - SN7822; ConvF(5.38, 5.34, 5.57); Calibrated: 2023-08-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1823; Calibrated: 2023-07-31
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2149; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WLAN, 10599-AAD

**Area Scan (140.0 mm x 120.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 0.915 W/kg; SAR (10g) = 0.329 W/kg;


**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm

Power Drift = -0.14 dB

SAR (1g) = 0.987 W/kg; SAR (8g) = 0.400 W/kg; SAR (10g) = 0.353 W/kg

Smallest distance from peaks to all points 3 dB below = 9.7 mm

Ratio of SAR at M2 to SAR at M1 = 63.6 %



### #03\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Back\_10mm\_Ch138


Communication System: UID 10544 - AAB,802.11ac; Frequency: 5690 MHz  
Medium: HSL\_5G\_240313 Medium parameters used:  $f = 5690$  MHz;  $\sigma = 5.042$  S/m;  $\epsilon_r = 35.228$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(5.1, 5.1, 5.1) @ 5690 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (151x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 1.51 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 18.57 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 2.72 W/kg  
**SAR(1 g) = 0.657 W/kg; SAR(10 g) = 0.264 W/kg**  
Smallest distance from peaks to all points 3 dB below = 12 mm  
Ratio of SAR at M2 to SAR at M1 = 61.8%  
Maximum value of SAR (measured) = 1.56 W/kg



0 dB = 1.56 W/kg = 1.93 dBW/kg

### #04\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Side\_10mm\_Ch155

Communication System: UID 10544 - AAD,802.11ac; Frequency: 5775 MHz

Medium: HSL\_5G\_240313 Medium parameters used:  $f = 5775$  MHz;  $\sigma = 5.13$  S/m;  $\epsilon = 35.097$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(5.1, 5.1, 5.1) @ 5775 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (101x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.07 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 21.25 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 3.47 W/kg

**SAR(1 g) = 0.896 W/kg; SAR(10 g) = 0.358 W/kg**

Smallest distance from peaks to all points 3 dB below = 12.1 mm

Ratio of SAR at M2 to SAR at M1 = 61.7%

Maximum value of SAR (measured) = 2.06 W/kg



0 dB = 2.06 W/kg = 3.14 dBW/kg

### #05\_WLAN6GHz\_802.11ax-HE160 MCS0\_Bottom Side\_10mm\_Ch47

Communication System: 802.11ax; Frequency: 6185.000 MHz

Medium: HSL\_6500\_240308 Medium parameters used:  $f=6185.000$  MHz;  $\sigma=5.82$  S/m;  $\epsilon_r=35.4$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY8 Configuration:

- Probe: EX3DV4 - SN7822; ConvF(5.06, 5.12, 5.2); Calibrated: 2023-08-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1823; Calibrated: 2023-07-31
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2149; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WLAN, 10755-AAC

**Area Scan (102.0 mm x 102.0 mm):** Measurement Grid: 8.5 mm x 8.5 mm

SAR (1g) = 0.177 W/kg; SAR (10g) = 0.071 W/kg;

**Zoom Scan (22.0 mm x 22.0 mm x 22.0 mm):** Measurement Grid: 3.4 mm x 3.4 mm x 1.4 mm


Power Drift = -0.03 dB

SAR (1g) = 0.192 W/kg; SAR (8g) = 0.085 W/kg; SAR (10g) = 0.075 W/kg

Smallest distance from peaks to all points 3 dB below = 17.0 mm

Ratio of SAR at M2 to SAR at M1 = 54.3 %

psAPD (1.0cm<sup>2</sup>, sq) = 1.92 [W/m<sup>2</sup>]; psAPD (4.0cm<sup>2</sup>, sq) = 1.69 [W/m<sup>2</sup>]



### #06\_Bluetooth\_1Mbps\_Back\_10mm\_Ch0


Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.302  
Medium: HSL\_2450\_240315 Medium parameters used:  $f = 2402$  MHz;  $\sigma = 1.732$  S/m;  $\epsilon_r = 39.847$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.92, 7.92, 7.92) @ 2402 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (121x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 0.0139 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 2.440 V/m; Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 0.0300 W/kg  
**SAR(1 g) = 0.00776 W/kg; SAR(10 g) = 0.00305 W/kg**  
Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 15 mm)  
Ratio of SAR at M2 to SAR at M1 = 43.2%  
Maximum value of SAR (measured) = 0.0135 W/kg



0 dB = 0.0135 W/kg = -18.70 dBW/kg

### #07\_WLAN2.4GHz\_802.11b 1Mbps\_Back\_0mm\_Ch6

Communication System: UID 10415 - AAA,802.11b; Frequency: 2437 MHz

Medium: HSL\_2450\_240315 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.839$  S/m;  $\epsilon_r = 39.737$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(7.92, 7.92, 7.92) @ 2437 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (121x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 5.39 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.58 V/m; Power Drift = -0.14 dB


Peak SAR (extrapolated) = 7.76 W/kg

**SAR(1 g) = 3.01 W/kg; SAR(10 g) = 1.18 W/kg**

Smallest distance from peaks to all points 3 dB below = 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 36.8%

Maximum value of SAR (measured) = 5.29 W/kg



0 dB = 5.29 W/kg = 7.23 dBW/kg

## #08\_WLAN5GHz\_802.11n-HT40 MCS0\_Back\_0mm\_Ch54

Communication System: 802.11n; Frequency: 5270.000 MHz

Medium: HSL\_5G\_240408 Medium parameters used:  $f = 5270.000$  MHz;  $\sigma = 4.77$  S/m;  $\epsilon_r = 36.5$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

### DASY8 Configuration:

- Probe: EX3DV4 - SN7822; ConvF(5.38, 5.34, 5.57); Calibrated: 2023-08-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1823; Calibrated: 2023-07-31
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2149; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WLAN, 10599-AAD

**Area Scan (140.0 mm x 120.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 6.08 W/kg; SAR (10g) = 1.70 W/kg;


**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm

Power Drift = -0.04 dB

SAR (1g) = 7.99 W/kg; SAR (8g) = 2.38 W/kg; SAR (10g) = 1.99 W/kg

Smallest distance from peaks to all points 3 dB below = 5.8 mm

Ratio of SAR at M2 to SAR at M1 = 63.9 %





### #09\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Back\_0mm\_Ch138

Communication System: UID 10544 - AAB,802.11ac; Frequency: 5690 MHz

Medium: HSL\_5G\_240313 Medium parameters used:  $f = 5690$  MHz;  $\sigma = 5.042$  S/m;  $\epsilon_r = 35.228$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(5.1, 5.1, 5.1) @ 5690 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (151x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 10.5 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 49.81 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 21.0 W/kg

**SAR(1 g) = 4.38 W/kg; SAR(10 g) = 1.34 W/kg**

Smallest distance from peaks to all points 3 dB below = 6.2 mm

Ratio of SAR at M2 to SAR at M1 = 61.2%

Maximum value of SAR (measured) = 11.4 W/kg



0 dB = 11.4 W/kg = 10.57 dBW/kg

### #10\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Side\_0mm\_Ch155


Communication System: UID 10544 - AAD,802.11ac; Frequency: 5775 MHz  
Medium: HSL\_5G\_240313 Medium parameters used:  $f = 5775$  MHz;  $\sigma = 5.13$  S/m;  $\epsilon_r = 35.097$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3925; ConvF(5.1, 5.1, 5.1) @ 5775 MHz; Calibrated: 2023/4/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (101x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 11.0 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 42.28 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 19.9 W/kg  
**SAR(1 g) = 4.48 W/kg; SAR(10 g) = 1.34 W/kg**  
Smallest distance from peaks to all points 3 dB below = 6.6 mm  
Ratio of SAR at M2 to SAR at M1 = 62.1%  
Maximum value of SAR (measured) = 11.8 W/kg



0 dB = 11.8 W/kg = 10.72 dBW/kg

## #11\_WLAN6GHz\_802.11ax-HE160 MCS0\_Bottom Side\_0mm\_Ch15

Communication System: 802.11ax; Frequency: 6025.000 MHz

Medium: HSL\_6500\_240308 Medium parameters used:  $f=6025.000$  MHz;  $\sigma=5.62$  S/m;  $\epsilon_r=35.7$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY8 Configuration:

- Probe: EX3DV4 - SN7822; ConvF(5.06, 5.12, 5.2); Calibrated: 2023-08-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1823; Calibrated: 2023-07-31
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2149; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: WLAN, 10755-AAC

**Area Scan (102.0 mm x 102.0 mm):** Measurement Grid: 8.5 mm x 8.5 mm

SAR (1g) = 1.00 W/kg; SAR (10g) = 0.298 W/kg;

**Zoom Scan (22.0 mm x 22.0 mm x 22.0 mm):** Measurement Grid: 3.4 mm x 3.4 mm x 1.4 mm


Power Drift = -0.05 dB

SAR (1g) = 1.05 W/kg; SAR (8g) = 0.350 W/kg; SAR (10g) = 0.303 W/kg

Smallest distance from peaks to all points 3 dB below = 6.3 mm

Ratio of SAR at M2 to SAR at M1 = 55.8 %

psAPD (1.0cm<sup>2</sup>, sq) = 10.5 [W/m<sup>2</sup>]; psAPD (4.0cm<sup>2</sup>, sq) = 7.00 [W/m<sup>2</sup>]



## #12\_Bluetooth\_1Mbps\_Back\_0mm\_Ch0

Communication System: Bluetooth; Frequency: 2402.000 MHz

Medium: HSL\_2450\_240306 Medium parameters used:  $f=2402.000$  MHz;  $\sigma=1.74$  S/m;  $\epsilon_r=39.1$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY8 Configuration:

- Probe: EX3DV4 - SN7822; ConvF(6.89, 6.89, 7.21); Calibrated: 2023-08-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1823; Calibrated: 2023-07-31
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2149; Section: Flat
- Measurement Software: 16.2.4.2524
- UID: Bluetooth, 10032-CAA

**Area Scan (100.0 mm x 120.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 0.059 W/kg; SAR (10g) = 0.028 W/kg;


**Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm):** Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm

Power Drift = -0.13 dB

SAR (1g) = 0.062 W/kg; SAR (8g) = 0.029 W/kg; SAR (10g) = 0.026 W/kg

Smallest distance from peaks to all points 3 dB below = 7.0 mm

Ratio of SAR at M2 to SAR at M1 = 76.1 %



### #13\_NFC\_Front\_0mm\_13.56MHz

Communication System: NFC; Frequency: 13.56 MHz; Duty Cycle: 1:1

Medium: HSL\_13\_240328 Medium parameters used :  $f = 13.56$  MHz;  $\sigma = 0.728$  S/m;  $\epsilon_r = 54.673$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7306; ConvF(16.9, 16.9, 16.9) @ 13.56 MHz; Calibrated: 2023/7/18
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2024/1/22
- Phantom: ELI v4.0\_Mid; Type: QDOVA001AA; Serial: TP:1026
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.00387 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.037 V/m; Power Drift = 0.07 dB



Peak SAR (extrapolated) = 0.00526 W/kg

**SAR(1 g) = 0.000764 W/kg; SAR(10 g) = 0.000228 W/kg**

Smallest distance from peaks to all points 3 dB below: 8.3 mm

Ratio of SAR at M2 to SAR at M1 = 41.3%

Maximum value of SAR (measured) = 0.00297 W/kg



0 dB = 0.00297 W/kg = -25.27 dBW/kg