



FCC TEST REPORT

(BLUETOOTH)

REPORT NO.: RF120210E04-2 R2

MODEL NO.: WT41N0

FCC ID: UZ7WT41N0

RECEIVED: Feb. 10, 2012

TESTED: Feb. 15 to Oct. 19, 2012

ISSUED: Nov. 09, 2012

APPLICANT: Motorola Solutions, Inc.

ADDRESS: One Motorola Plaza Holtsville NY 11742-1300 USA

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.

TEST LOCATION (2): No.49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.

This test report consists of 68 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION	5
2 SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	7
3 GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	12
3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	13
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3.5 DESCRIPTION OF SUPPORT UNITS.....	16
3.6 CONFIGURATION OF SYSTEM UNDER TEST	17
4 TEST PROCEDURES AND RESULTS	18
4.1 CONDUCTED EMISSION MEASUREMENT	18
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	18
4.1.2 TEST INSTRUMENTS.....	18
4.1.3 TEST PROCEDURES	19
4.1.4 DEVIATION FROM TEST STANDARD	19
4.1.5 TEST SETUP	19
4.1.6 EUT OPERATING CONDITIONS.....	20
4.1.7 TEST RESULTS TEST RESULTS (MODE 1).....	21
4.1.8 TEST RESULTS TEST RESULTS (MODE 2).....	23
4.2 RADIATED EMISSION MEASUREMENT	25
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	25
4.2.2 TEST INSTRUMENTS.....	26
4.2.3 TEST PROCEDURES	28
4.2.4 DEVIATION FROM TEST STANDARD	28
4.2.5 TEST SETUP	29
4.2.6 EUT OPERATING CONDITIONS.....	29
4.2.7 TEST RESULTS	30
4.3 NUMBER OF HOPPING FREQUENCY USED	37
4.3.1 LIMIT OF HOPPING FREQUENCY USED	37
4.3.2 TEST INSTRUMENTS.....	37
4.3.3 TEST PROCEDURES	37
4.3.4 DEVIATION FROM TEST STANDARD	37
4.3.5 TEST SETUP	38
4.3.6 TEST RESULTS	38
4.4 DWELL TIME ON EACH CHANNEL.....	41
4.4.1 LIMIT OF DWELL TIME USED	41
4.4.2 TEST INSTRUMENTS.....	41
4.4.3 TEST PROCEDURES	41
4.4.4 DEVIATION FROM TEST STANDARD	42



A D T

4.4.5	TEST SETUP	42
4.4.6	TEST RESULTS	43
4.5	CHANNEL BANDWIDTH	51
4.5.1	LIMITS OF CHANNEL BANDWIDTH	51
4.5.2	TEST INSTRUMENTS	51
4.5.3	TEST PROCEDURE	51
4.5.4	DEVIATION FROM TEST STANDARD	51
4.5.5	TEST SETUP	52
4.5.6	EUT OPERATING CONDITION	52
4.5.7	TEST RESULTS	53
4.6	HOPPING CHANNEL SEPARATION	55
4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	55
4.6.2	TEST INSTRUMENTS	55
4.6.3	TEST PROCEDURES	55
4.6.4	DEVIATION FROM TEST STANDARD	55
4.6.5	TEST SETUP	55
4.6.6	TEST RESULTS	56
4.7	MAXIMUM PEAK OUTPUT POWER	58
4.7.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	58
4.7.2	INSTRUMENTS	58
4.7.3	TEST PROCEDURES	58
4.7.4	DEVIATION FROM TEST STANDARD	58
4.7.5	TEST SETUP	59
4.7.6	EUT OPERATING CONDITION	59
4.7.7	TEST RESULTS	60
4.8	CONDUCTED OUT-BAND EMISSION MEASUREMENT	62
4.8.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	62
4.8.2	TEST INSTRUMENTS	62
4.8.3	TEST PROCEDURE	62
4.8.4	DEVIATION FROM TEST STANDARD	62
4.8.5	EUT OPERATING CONDITION	62
4.8.6	TEST RESULTS	63
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	66
6	INFORMATION ON THE TESTING LABORATORIES	67
7	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	68



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120210E04-2	Original release	July 05, 2012
RF120210E04-2 R1	1. Changed CMI display of EUT. 2. Modified the test data of radiated emissions test item: I. Radiated emissions below 1GHz II. Radiated emissions above 1GHz for worst channel of original release report.)	Oct. 31, 2012
RF120210E04-2 R2	Modified the test sample to ENGINEERING SAMPLE_DV3 for section 1.	Nov. 09, 2012



1 CERTIFICATION

PRODUCT : Wearable Terminal
BRAND NAME : MOTOROLA
MODEL NO. : WT41N0
TEST SAMPLE : ENGINEERING SAMPLE_DV3
APPLICANT : Motorola Solutions, Inc.
TESTED DATE : Feb. 15 to Oct. 19, 2012
STANDARDS : **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (Model: WT41N0) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Phoenix Huang , **DATE:** Nov. 09, 2012
(Phoenix Huang, Specialist)

APPROVED BY : May Chen , **DATE:** Nov. 09, 2012
(May Chen, Deputy Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -16.73dB at 0.69688MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.6dB at 48.00MHz.
15.247(d)	Conducted Out-Band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE:

1. Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	2.98dB
Radiated emissions	30MHz ~1000MHz	5.69 dB
	1GHz ~ 18GHz	2.19 dB
	18GHz ~ 40GHz	2.56 dB



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wearable Terminal
MODEL NO.	WT41N0
POWER SUPPLY	DC 3.7V
MODULATION TYPE	GFSK, $\pi/4$ -DQPSK, 8DPSK
MODULATION TECHNOLOGY	FHSS
DATE RATE	Up to 3Mbps
FREQUENCY RANGE	2402MHz ~ 2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	8.166 mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	Battery × 1

NOTE:

1. There are Bluetooth technology and WLAN technology used for the EUT. And the report number corresponds with EUT functions are listed as below:

Function	Report No.
WLAN	RF120210E04 R2 (15.247)
	RF120210E04-1 R2 (15.407)
	RF120210E04-3 R1 (DFS)
Bluetooth	RF120210E04-2 R2

2. The EUT has different versions, the relationship of testing sample versions are listed as below:

Sample No.	Brand	Model	Description
1	MOTOROLA	WT41N0	VOW version
2			Touch version
3			Non-Touch version

3. The EUT hardware/software information are as below:

Brand	Model	Description
Wearable Terminal	OS Version	07.00.2806
	OEM Name	MOTOROLA WT41N0
	OEM Version	00.17.0001
	HW Version	WT41N0_MB V3.0
Wireless (Fusion)	Part Number	31-FUSION-X2.00
	Version	X_2.00.0.0.93
RegTestVersion 4.10.exe	XappVersion	X_2.00.0.0.24
BTRegTestVer4.1	Version	4.1

4. The EUT could be supplied from a cradle, power adapter and battery, the information are listed as below:

Cradle 1 (1-slot, option)	
Brand:	MOTOROLA
Model No.:	CRD4000-1000UR
Part No.:	CRD4000-1000UR
Input power :	+12V ----- 3.33A
I/O Ports:	USB Port x 1
Associated Devices:	USB cable (Part No.:25-64396-01R) Adapter x 1 (Adapter 1: Part No.: 50-14000-148R)
Adapter 1 (optional for Cradle 1 power supply)	
Brand:	HIPRO
Model No.:	HP-O2040D43
Part No.:	50-14000-148R
Input power :	100-240V, 50-60Hz, 1.5A
Output power :	+12V ----- 3.33A DC output cable (unshielded, 1.8m with one core)



Battery 1	
Brand:	SYMBOL
Part No.:	82-90005-05 Rev. A (1X LiION)
Rating:	3.7V, 2400mAh, 8.88Wh
Battery 2	
Brand:	SYMBOL
Part No.:	82-90005-04 Rev. D (2X LiION)
Rating:	3.7V, 4800mAh, 17.76Wh

5. The EUT could be supplied with one laser scanner (optional). There are four options as below:

Laser scanner 1 (option)	
Brand:	MOTOROLA
Model No.:	RS409 1D Laser scanner
Laser scanner 2 (option)	
Brand:	MOTOROLA
Model No.:	RS309 1D Laser scanner
Laser scanner 3 (option)	
Brand:	MOTOROLA
Model No.:	RS507 2D Imager scanner
Description :	Wireless link (no direct wire-link to EUT)
Laser scanner 4 (option)	
Brand:	MOTOROLA
Model No.:	RS419 scanner
Description :	Type 1: Long USB cable (Length: 2.3m) Type 2: Short USB cable (Length: 0.4m)

6. The EUT antennas information:

Bluetooth Antenna Spec			
Antenna Type	Gain (dBi)	Connector Type	Frequency range (MHz)
PIFA	1.47	NA	2400~2500
WLAN Antenna Spec.			
Antenna Type	Gain (dBi)	Connector Type	Frequency range (MHz)
PIFA	1.48 (2.4G)	NA	2400~2500
	5.7 (5G)		4900~5850



7. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11a	1TX
802.11n (20MHz)	1TX

8. Radiated and Conducted emission of the simultaneous operation (Bluetooth and WLAN technology) has been evaluated and no non-compliance was found.

9. The EUT was pre-tested in chamber under following test modes :

Pre-test Mode	Description
Mode A	X_ plane: Sample_1 + Battery 1 + Laser scanner 1
Mode B	X_ plane: Sample_2 + Battery 1 + Laser scanner 1
Mode C	X_ plane: Sample_3 + Battery 1 + Laser scanner 1
Mode D	X_ plane: Sample_2 + Battery 2 + Laser scanner 1
Mode E	Y_ plane: Sample_2 + Battery 2 + Laser scanner 1
Mode F	Z_ plane: Sample_2 + Battery 2 + Laser scanner 1
Mode G	X_ plane: Sample_2 + Battery 2 + Laser scanner 2
Mode H	X_ plane: Sample_2 + Battery 2 + Laser scanner 4 (Short cable)
Mode I	X_ plane: Sample_2 + Battery 2 + Laser scanner 4 (Long cable)
Mode J	Sample_2 + Battery 2 + Laser scanner 4 (Long cable) + Cradle 1

The worse radiated emission was found in **Mode J**. Therefore only the test data of the modes were recorded in this report.

10. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.

11. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

79 channels are provided for Bluetooth.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
1	√	√	√	√	√	Cradle 1 + Battery 2
2	√	-	-	-	-	Cradle 1 + Battery 1

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ³ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	8DPSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHZ):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	8DPSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHZ):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5



ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
PLC	20deg. C, 70%RH,	120Vac, 60Hz	Mike Hsieh
RE<1G	23deg. C, 70%RH	120Vac, 60Hz	Amos Chuang
	23deg. C, 66%RH	120Vac, 60Hz	Evan Huang
RE ³ 1G	24deg. C, 69%RH	120Vac, 60Hz	Frank Liu
	22deg. C, 68%RH	120Vac, 60Hz	Evan Huang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Rex Huang
OB	25deg. C, 60%RH	120Vac, 60Hz	Rex Huang



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.5 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	Headset	MOTOROLA	Vix	BE09311114401G	NA
2	Laser Scanner	MOTOROLA	RS419 scanner	NA	NA
3	Cradle	MOTOROLA	CRD4000-100U R	NA	NA
4	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
5	iPod shuffle	Apple	MC749TA/A	CC4DMFJUDFDM	NA

No.	Signal cable description
1	Audio cable, 1m
2	Cable, 2.3m
3	NA
4	USB cable, 1.6m
5	USB cable, 0.1m

Note: The power cords of the above support units were unshielded (1.8m).

3.6 CONFIGURATION OF SYSTEM UNDER TEST



NOTE: 1. Item A is the battery.

4 TEST PROCEDURES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 08, 2012	Mar. 07, 2013
Line-Impedance Stabilization Network (for EUT)	NSLK8127	8127-522	Sep. 07, 2011	Sep. 06, 2012
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Nov. 02, 2011	Nov. 01, 2012
RF Cable (JYEBAO)	5DFB	COCCAB-001	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	3	Nov. 02, 2011	Nov. 01, 2012
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Apr. 26, 2012


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of EUT.
2. The communication partner run test program “RegTestVersion 4.10.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.



A D T


4.1.7 TEST RESULTS TEST RESULTS (MODE 1)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
--------------	----------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20078	0.07	44.74	31.65	44.81	31.72	63.58	53.58	-18.77	-21.86
2	0.29844	0.07	35.56	23.03	35.63	23.10	60.29	50.29	-24.65	-27.18
3	0.40000	0.08	30.76	22.71	30.84	22.79	57.85	47.85	-27.01	-25.06
4	0.69688	0.09	33.63	28.07	33.72	28.16	56.00	46.00	-22.28	-17.84
5	3.18950	0.27	27.50	14.37	27.77	14.64	56.00	46.00	-28.23	-31.36
6	7.98047	0.46	26.75	20.49	27.21	20.95	60.00	50.00	-32.79	-29.05

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.






A D T

PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20078	0.06	44.15	31.65	44.21	31.71	63.58	53.58	-19.37	-21.87
2	0.29844	0.07	35.38	24.16	35.45	24.23	60.29	50.29	-24.84	-26.06
3	0.40000	0.08	30.98	23.48	31.06	23.56	57.85	47.85	-26.79	-24.29
4	0.69688	0.08	34.72	29.19	34.80	29.27	56.00	46.00	-21.20	-16.73
5	2.29297	0.18	27.17	17.46	27.35	17.64	56.00	46.00	-28.65	-28.36
6	5.28906	0.27	25.10	18.83	25.37	19.10	60.00	50.00	-34.63	-30.90

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS TEST RESULTS (MODE 2)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
--------------	----------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19687	0.07	43.68	28.92	43.75	28.99	63.74	53.74	-19.99	-24.75
2	0.29844	0.07	34.63	20.31	34.70	20.38	60.29	50.29	-25.58	-29.90
3	0.39609	0.08	30.17	19.20	30.25	19.28	57.93	47.93	-27.69	-28.66
4	0.69688	0.09	32.90	25.25	32.99	25.34	56.00	46.00	-23.01	-20.66
5	3.20703	0.27	22.70	5.54	22.97	5.81	56.00	46.00	-33.03	-40.19
6	7.77734	0.45	24.31	18.26	24.76	18.71	60.00	50.00	-35.24	-31.29

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.






A D T

PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20078	0.06	42.97	27.29	43.03	27.35	63.58	53.58	-20.55	-26.23
2	0.29453	0.07	33.76	20.70	33.83	20.77	60.40	50.40	-26.57	-29.63
3	0.40000	0.08	30.11	21.02	30.19	21.10	57.85	47.85	-27.66	-26.75
4	0.69731	0.08	34.18	26.92	34.26	27.00	56.00	46.00	-21.74	-19.00
5	1.29688	0.11	26.73	18.70	26.84	18.81	56.00	46.00	-29.16	-27.19
6	7.77191	0.33	24.90	17.02	25.23	17.35	60.00	50.00	-34.77	-32.65

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.



A D T

4.2.2 TEST INSTRUMENTS

For below 1GHz and above 1GHz of GFSK channel 0:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
Pre-Selector Agilent	N9039A	MY46520310	Sep. 03, 2012	Sep. 02, 2013
Signal Generator Agilent	N5181A	MY49060347	July 24, 2012	July 23, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 15, 2011	Nov. 14, 2012
Pre-Amplifier Agilent	8449B	3008A02465	Feb. 27, 2012	Feb. 26, 2013
SPACEK LABS	SLKKa-48-6	9K16	Nov. 15, 2011	Nov. 14, 2012
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Apr. 06, 2012	Apr. 05, 2013
Horn_Antenna AISL	AIH.8018	0000220091110	Nov. 23, 2011	Nov. 22, 2012
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 27, 2011	Dec. 26, 2012
RF Cable	NA	CHHCAB_001	Oct. 07, 2012	Oct. 06, 2013
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: Oct. 16 to 19, 2012



A D T

For above 1GHz: (for other test channels)

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100036	Dec. 14, 2011	Dec. 13, 2012
Agilent PSA Spectrum Analyzer	E4446A	MY48250113	Nov. 30 , 2011	Nov. 29 , 2012
HP Pre_Amplifier	8449B	300801923	Oct. 31, 2011	Oct. 30, 2012
ROHDE & SCHWARZ Test Receiver	ESCS30	847124/029	Sep. 02, 2011	Sep. 01, 2012
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	Apr. 14, 2011	Apr. 13, 2012
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 16, 2011	Dec. 15, 2012
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 17, 2012	Jan. 16, 2013
RF Switches	EMH-011	1001	Sep. 24, 2011	Sep. 23, 2012
RF CABLE (Chaintek)	Sucoflex 106	72662/6	Jan. 19, 2012	Jan. 18, 2013
RF Cable	8DFB	STCCAB-30M-1GHz	Sep. 24, 2011	Sep. 23, 2012
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) and Spectrum Analyzer (model: FSP40) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 7450G-3.
7. Tested date: Mar. 09, 2012

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room for below 1GHz and above 1GHz of GFSK channel 0 test and 10 meters open site for above 1GHz of other test channels test.. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

BT_8DPSK

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	99.75	28.5 QP	43.5	-15.1	2.00 H	88	18.77	9.68
2	147.83	30.7 QP	43.5	-12.8	2.00 H	60	16.20	14.47
3	239.96	32.1 QP	46.0	-13.9	1.00 H	76	19.29	12.85
4	284.14	31.4 QP	46.0	-14.6	1.00 H	67	16.76	14.67
5	749.30	30.9 QP	46.0	-15.1	1.50 H	300	6.29	24.63
6	850.55	31.7 QP	46.0	-14.4	1.50 H	310	5.28	26.37

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.00	36.4 QP	40.0	-3.6	1.00 V	283	22.45	13.99
2	147.83	33.9 QP	43.5	-9.7	1.00 V	324	19.38	14.47
3	273.95	30.0 QP	46.0	-16.0	1.00 V	23	15.74	14.26
4	299.65	29.8 QP	46.0	-16.2	1.50 V	221	14.46	15.30
5	853.04	28.5 QP	46.0	-17.5	1.00 V	310	2.09	26.40
6	959.97	34.1 QP	46.0	-11.9	1.00 V	286	5.91	28.15

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.1 PK	74.0	-17.9	1.35 H	42	23.72	32.38
2	2390.00	26.0 AV	54.0	-28.0	1.35 H	42	-6.38	32.38
3	*2402.00	99.6 PK			1.42 H	23	67.18	32.42
4	*2402.00	69.5 AV			1.42 H	23	37.08	32.42
5	4804.00	57.3 PK	74.0	-16.7	1.00 H	32	15.39	41.91
6	4804.00	27.2 AV	54.0	-26.8	1.00 H	32	-14.71	41.91

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.7 PK	74.0	-19.3	1.32 V	233	22.32	32.38
2	2390.00	24.6 AV	54.0	-29.4	1.32 V	233	-7.78	32.38
3	*2402.00	100.6 PK			1.23 V	264	68.18	32.42
4	*2402.00	70.5 AV			1.23 V	264	38.08	32.42
5	4804.00	57.7 PK	74.0	-16.3	1.12 V	224	15.79	41.91
6	4804.00	27.6 AV	54.0	-26.4	1.12 V	224	-14.31	41.91

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	101.5 PK			1.18 H	37	70.15	31.35
2	*2441.00	71.4 AV			1.18 H	37	40.05	31.35
3	4882.00	58.4 PK	74.0	-15.6	1.64 H	135	18.75	39.65
4	4882.00	28.3 AV	54.0	-25.7	1.64 H	135	-11.35	39.65
5	7323.00	54.6 PK	74.0	-19.4	1.67 H	144	10.48	44.12
6	7323.00	24.5 AV	54.0	-29.5	1.67 H	144	-19.62	44.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.2 PK			1.24 V	25	71.85	31.35
2	*2441.00	73.1 AV			1.24 V	25	41.75	31.35
3	4882.00	58.6 PK	74.0	-15.4	1.21 V	121	18.95	39.65
4	4882.00	28.5 AV	54.0	-25.5	1.21 V	121	-11.15	39.65
5	7323.00	55.0 PK	74.0	-19.0	1.34 V	223	10.88	44.12
6	7323.00	24.9 AV	54.0	-29.1	1.34 V	223	-19.22	44.12

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.1 PK			1.48 H	123	69.65	31.45
2	*2480.00	71.0 AV			1.48 H	123	39.55	31.45
3	2483.50	58.2 PK	74.0	-15.8	1.38 H	114	26.74	31.46
4	2483.50	28.1 AV	54.0	-25.9	1.38 H	114	-3.36	31.46
5	4960.00	58.1 PK	74.0	-15.9	1.60 H	129	18.13	39.97
6	4960.00	28.0 AV	54.0	-26.0	1.60 H	129	-11.97	39.97
7	7440.00	54.2 PK	74.0	-19.8	1.67 H	130	9.96	44.24
8	7440.00	24.1 AV	54.0	-29.9	1.67 H	130	-20.14	44.24
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.1 PK			1.34 V	21	71.65	31.45
2	*2480.00	73.0 AV			1.34 V	21	41.55	31.45
3	2483.50	57.6 PK	74.0	-16.4	1.25 V	20	26.14	31.46
4	2483.50	27.5 AV	54.0	-26.5	1.25 V	20	-3.96	31.46
5	4960.00	58.9 PK	74.0	-15.1	1.25 V	111	18.93	39.97
6	4960.00	28.8 AV	54.0	-25.2	1.25 V	111	-11.17	39.97
7	7440.00	54.4 PK	74.0	-19.6	1.36 V	220	10.16	44.24
8	7440.00	24.3 AV	54.0	-29.7	1.36 V	220	-19.94	44.24

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.3 PK	74.0	-18.7	1.51 H	96	24.09	31.21
2	2390.00	25.2 AV	54.0	-28.8	1.51 H	96	-6.01	31.21
3	*2402.00	100.3 PK			1.43 H	125	69.05	31.25
4	*2402.00	70.2 AV			1.43 H	125	38.95	31.25
5	4804.00	55.0 PK	74.0	-19.0	1.60 H	118	15.65	39.35
6	4804.00	24.9 AV	54.0	-29.1	1.60 H	118	-14.45	39.35

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.8 PK	74.0	-17.2	1.32 V	360	25.59	31.21
2	2390.00	26.7 AV	54.0	-27.3	1.32 V	360	-4.51	31.21
3	*2402.00	101.4 PK			1.32 V	14	70.15	31.25
4	*2402.00	71.3 AV			1.32 V	14	40.05	31.25
5	4804.00	55.1 PK	74.0	-18.9	1.27 V	112	15.75	39.35
6	4804.00	25.0 AV	54.0	-29.0	1.27 V	112	-14.35	39.35

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	99.7 PK			1.42 H	103	68.35	31.35
2	*2441.00	69.6 AV			1.42 H	103	38.25	31.35
3	4882.00	54.6 PK	74.0	-19.4	1.63 H	92	14.95	39.65
4	4882.00	24.5 AV	54.0	-29.5	1.63 H	92	-15.15	39.65
5	7323.00	54.3 PK	74.0	-19.7	1.55 H	147	10.18	44.12
6	7323.00	24.2 AV	54.0	-29.8	1.55 H	147	-19.92	44.12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	101.5 PK			1.31 V	14	70.15	31.35
2	*2441.00	71.4 AV			1.31 V	14	40.05	31.35
3	4882.00	55.0 PK	74.0	-19.0	1.27 V	95	15.35	39.65
4	4882.00	24.9 AV	54.0	-29.1	1.27 V	95	-14.75	39.65
5	7323.00	52.8 PK	74.0	-21.2	1.41 V	225	8.68	44.12
6	7323.00	22.7 AV	54.0	-31.3	1.41 V	225	-21.42	44.12

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



A D T

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	100.4 PK			1.43 H	123	68.95	31.45
2	*2480.00	70.3 AV			1.43 H	123	38.85	31.45
3	2483.50	56.8 PK	74.0	-17.2	1.43 H	123	25.34	31.46
4	2483.50	26.7 AV	54.0	-27.3	1.43 H	123	-4.76	31.46
5	4960.00	53.5 PK	74.0	-20.5	1.68 H	108	13.53	39.97
6	4960.00	23.4 AV	54.0	-30.6	1.68 H	108	-16.57	39.97
7	7440.00	54.0 PK	74.0	-20.0	1.61 H	149	9.76	44.24
8	7440.00	23.9 AV	54.0	-30.1	1.61 H	149	-20.34	44.24

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.8 PK			1.32 V	11	70.35	31.45
2	*2480.00	71.7 AV			1.32 V	11	40.25	31.45
3	2483.50	56.8 PK	74.0	-17.2	1.32 V	11	25.34	31.46
4	2483.50	26.7 AV	54.0	-27.3	1.32 V	11	-4.76	31.46
5	4960.00	55.1 PK	74.0	-18.9	1.26 V	99	15.13	39.97
6	4960.00	25.0 AV	54.0	-29.0	1.26 V	99	-14.97	39.97
7	7440.00	52.0 PK	74.0	-22.0	1.39 V	230	7.76	44.24
8	7440.00	21.9 AV	54.0	-32.1	1.39 V	230	-22.34	44.24

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec 14, 2011	Dec 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. Tested date: Mar. 12, 2012


4.3.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP





4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



A D T


For GFSK






A D T

For 8DPSK



A D T



A D T

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec 14, 2011	Dec 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. Tested date: Mar. 12, 2012

4.4.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 TEST RESULTS

For GFSK:



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) *6.32=322.32 times	0.45	145.04	400
DH3	25 (times / 5 sec) *6.32=158 times	1.70	268.6	400
DH5	16 (times / 5 sec) *6.32=101.12 times	2.96	299.32	400

NOTE: Test plots of the transmitting time slot are shown on next page.



A D T



DH1





A D T



DH3





A D T

DH5





A D T

For 8DPSK:



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) *6.32=316 times	0.29	91.01	400
DH3	25 (times / 5 sec) *6.32=158 times	1.67	263.86	400
DH5	18 (times / 5 sec) *6.32=113.76 times	2.91	331.04	400

NOTE: Test plots of the transmitting time slot are shown on next page.



A D T



DH1





A D T



DH3





A D T

DH5



4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. Tested: Mar. 12, 2012


4.5.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

For GFSK:

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.93
39	2441	0.98
78	2480	0.95

CH 39






A D T

For 8DPSK:

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.36
39	2441	1.35
78	2480	1.33

CH 0



4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25 kHz or two-thirds of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date: Mar. 12, 2012


4.6.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP





A D T


4.6.6 TEST RESULTS

For GFSK

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.01	0.62	PASS
39	2441	1.01	0.65	PASS
78	2480	1.01	0.63	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



A D T




A D T

For 8DPSK

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.01	0.91	PASS
39	2441	1.00	0.90	PASS
78	2480	1.01	0.89	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Limit is 125mW.

4.7.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date: Mar. 12, 2012


4.7.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




A D T

4.7.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (mW)	PASS/FAIL
0	2402	6.607	8.20	125	PASS
39	2441	6.745	8.29	125	PASS
78	2480	7.295	8.63	125	PASS

CH 78






A D T

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (mW)	PASS/FAIL
0	2402	7.499	8.75	125	PASS
39	2441	7.603	8.81	125	PASS
78	2480	8.166	9.12	125	PASS

CH 78



A D T

4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100036	Dec. 14, 2011	Dec. 13, 2012

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date: Mar. 12, 2012

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW a of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



4.8.6 TEST RESULTS



The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

GFSK



Hopping disabled_Low Channel





Hopping disabled_High Channel



Hopping enabled_Low Channel



Hopping enabled_High Channel









A D T

8DPSK



Hopping disabled_Low Channel





Hopping disabled_High Channel



Hopping enabled_Low Channel



Hopping enabled_High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5.phtml.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---