



FCC RADIO TEST REPORT

FCC ID : UZ7WT63B0
Equipment : WT6300 Wearable Computer
Brand Name : Zebra
Model Name : WT63B0
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Aug. 12, 2020 and testing was started from Aug. 17, 2020 and completed on Sep. 17, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Location	7
1.5 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 Test Result.....	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Output Power Measurement.....	22
3.3 Power Spectral Density Measurement	24
3.4 Conducted Band Edges and Spurious Emission Measurement	32
3.5 Radiated Band Edges and Spurious Emission Measurement	41
3.6 AC Conducted Emission Measurement.....	46
3.7 Antenna Requirements.....	48
4 List of Measuring Equipment	49
5 Uncertainty of Evaluation.....	51
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR072944B	01	Initial issue of report	Sep. 29, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 4.15 dB at 2490.960 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 5.66 dB at 13.560 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Tina Chuang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	WT6300 Wearable Computer
Brand Name	Zebra
Model Name	WT63B0
FCC ID	UZ7WT63B0
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	EV2.5
SW Version	10-14-10.00-QC-U01-PRD-HEL-04
OS Version	Android 10
FW Version	FUSION_QA_2_1.3.0.006_Q
MFD	29JUL20
EUT Stage	Engineering Sample

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
AC Adapter 1	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
AC Adapter 2	Brand Name	Zebra	Part Number	PWR-WUA5V12W0WW
AC Adapter 3	Brand Name	Zebra	Part Number	PWR-BUA5V16W0WW
Battery 1	Brand Name	Zebra	Part Number	BT000262A01
Battery 2	Brand Name	Zebra	Part Number	BT-000262-50
Battery 3	Brand Name	Zebra	Part Number	BT-000362-00
AC Power Cable	Brand Name	Zebra	Part Number	50-16000-182R
DC Cable	Brand Name	Zebra	Part Number	CBL-DC-383A1-01
USB Cable	Brand Name	Zebra	Part Number	CBL-NGWT-USBCHG-01
Vibrating Cable	Brand Name	Zebra	Part Number	CBL-NGWT-HDVBAP-01
Audio Cable 1	Brand Name	Zebra	Part Number	CBL-HS2100-12S1-01
Audio Cable 2	Brand Name	Zebra	Part Number	CBL-HS3100-CUC1-01
Keyboard	Brand Name	Zebra	Part Number	KYPD-WT6XANFASM-01
Scanner 1	Brand Name	Zebra	Part Number	RS51B0-TBSNWR
Scanner 2	Brand Name	Zebra	Part Number	RS60B0-SRSTWR
Scanner 3	Brand Name	Zebra	Part Number	RS4000-HPCSWR
Scanner 4	Brand Name	Zebra	Part Number	RS5000-LCFSWR
Earphone 1	Brand Name	Zebra	Part Number	HS2100-OTH
Earphone 2	Brand Name	Zebra	Part Number	HS3100-OTH
Wrist Mount	Brand Name	Zebra	Part Number	SG-NGWT-WRMTS-01
Wrist Mount	Brand Name	Zebra	Part Number	SG-NGWT-WRMTL-01
Wrist Mount	Brand Name	Zebra	Part Number	SG-NGWT-WRMTXL-01
Hip Mount	Brand Name	Zebra	Part Number	SG-NGWT-HPMNT-01



1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	7.00 dBm (0.0050 W) for 1Mbps 7.00 dBm (0.0050 W) for 2Mbps
99% Occupied Bandwidth	1.032 MHz for 1Mbps 2.048 MHz for 2Mbps
Antenna Type / Gain	Patch Antenna with gain 2.4 dBi
Type of Modulation	Bluetooth LE : GFSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH16-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



2.2 Test Mode

Channel	Frequency	Bluetooth – LE 1Mbps RF Average Output Power	
		Data Rate / Modulation	
		GFSK	
		1Mbps	
Ch00	2402MHz	6.50 dBm	
Ch19	2440MHz	7.00 dBm	
Ch39	2480MHz	6.60 dBm	

Channel	Frequency	Bluetooth – LE 2Mbps RF Average Output Power	
		Data Rate / Modulation	
		GFSK	
		2Mbps	
Ch00	2402MHz	6.50 dBm	
Ch19	2440MHz	7.00 dBm	
Ch39	2480MHz	6.60 dBm	

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.




The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + NFC On + Color Bar + Battery 1 + Scanner 1 + Earphone 1 + Audio Cable 1 + USB Cable (Data Link with Notebook) + AC Adapter 3
Remark: 1. For Radiated Test Cases, the tests were performed with Adapter 1, Battery 1. 2. Data Link with Notebook means data application transferred mode between EUT and Notebook.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Radiated Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT4.0.00142.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	0.672	0.50	Pass
BLE	1Mbps	1	19	2440	0.672	0.50	Pass
BLE	1Mbps	1	39	2480	0.672	0.50	Pass
BLE	2Mbps	1	0	2402	1.152	0.50	Pass
BLE	2Mbps	1	19	2440	1.152	0.50	Pass
BLE	2Mbps	1	39	2480	1.160	0.50	Pass

<1Mbps>


6 dB Bandwidth Plot on Channel 00



Date: 7.SEP.2020 17:09:40




6 dB Bandwidth Plot on Channel 19



Date: 7.SEP.2020 17:12:44

6 dB Bandwidth Plot on Channel 39




Date: 7.SEP.2020 17:16:15




<2Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 7.SEP.2020 17:19:35


6 dB Bandwidth Plot on Channel 19



Date: 7.SEP.2020 17:22:58



6 dB Bandwidth Plot on Channel 39



Date: 7.SEP.2020 17:27:16




3.1.6 Test Result of 99% Occupied Bandwidth

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%

Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.022	Pass
BLE	1Mbps	1	19	2440	1.032	Pass
BLE	1Mbps	1	39	2480	1.026	Pass
BLE	2Mbps	1	0	2402	2.036	Pass
BLE	2Mbps	1	19	2440	2.048	Pass
BLE	2Mbps	1	39	2480	2.040	Pass

<1Mbps>


99% Bandwidth Plot on Channel 00



Date: 7.SEP.2020 17:11:23




99% Occupied Bandwidth Plot on Channel 19



Date: 7.SEP.2020 17:15:02

99% Occupied Bandwidth Plot on Channel 39




Date: 7.SEP.2020 17:17:51




<2Mbps>

99% Bandwidth Plot on Channel 00



Date: 7.SEP.2020 17:21:44


99% Occupied Bandwidth Plot on Channel 19



Date: 7.SEP.2020 17:24:45



99% Occupied Bandwidth Plot on Channel 39



Date: 7.SEP.2020 17:28:52

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGP-M-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Average Output Power

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.50	30.00	2.40	8.90	36.00	Pass
BLE	1Mbps	1	19	2440	7.00	30.00	2.40	9.40	36.00	Pass
BLE	1Mbps	1	39	2480	6.60	30.00	2.40	9.00	36.00	Pass
BLE	2Mbps	1	0	2402	6.50	30.00	2.40	8.90	36.00	Pass
BLE	2Mbps	1	19	2440	7.00	30.00	2.40	9.40	36.00	Pass
BLE	2Mbps	1	39	2480	6.60	30.00	2.40	9.00	36.00	Pass

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.36	-8.25	2.40	8.00	Pass
BLE	1Mbps	1	19	2440	7.04	-7.56	2.40	8.00	Pass
BLE	1Mbps	1	39	2480	6.32	-8.20	2.40	8.00	Pass
BLE	2Mbps	1	0	2402	6.35	-11.79	2.40	8.00	Pass
BLE	2Mbps	1	19	2440	7.02	-11.13	2.40	8.00	Pass
BLE	2Mbps	1	39	2480	6.33	-11.72	2.40	8.00	Pass

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%

<1Mbps>


PSD 100kHz Plot on Channel 00



Date: 7.SEP.2020 17:10:15




PSD 100kHz Plot on Channel 19



Date: 7.SEP.2020 17:13:14

PSD 100kHz Plot on Channel 39




Date: 7.SEP.2020 17:16:45




<2Mbps>

PSD 100kHz Plot on Channel 00



Date: 7.SEP.2020 17:20:15


PSD 100kHz Plot on Channel 19



Date: 7.SEP.2020 17:23:37



PSD 100kHz Plot on Channel 39




Date: 7.SEP.2020 17:27:43

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%

<1Mbps>


PSD 3kHz Plot on Channel 00



Date: 7.SEP.2020 17:10:01




PSD 3kHz Plot on Channel 19



Date: 7.SEP.2020 17:13:00

PSD 3kHz Plot on Channel 39




Date: 7.SEP.2020 17:16:29




<2Mbps>

PSD 3kHz Plot on Channel 00



Date: 7.SEP.2020 17:19:50


PSD 3kHz Plot on Channel 19



Date: 7.SEP.2020 17:23:15



PSD 3kHz Plot on Channel 39



Date: 7.SEP.2020 17:27:29

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

Test Engineer :	MINA LIU	Temperature :	23.6~24.1°C
		Relative Humidity :	53.8~54.2%


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 7.SEP.2020 17:10:31

High Band Edge Plot on Channel 39




Date: 7.SEP.2020 17:17:02




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 7.SEP.2020 17:20:38

High Band Edge Plot on Channel 39




Date: 7.SEP.2020 17:28:00




3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 7.SEP.2020 17:10:51


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 7.SEP.2020 17:11:09




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 7.SEP.2020 17:14:26


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 7.SEP.2020 17:14:41




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.SEP.2020 17:17:20


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.SEP.2020 17:17:37




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 7.SEP.2020 17:21:05


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 7.SEP.2020 17:21:20




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 7.SEP.2020 17:24:15


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 7.SEP.2020 17:24:30




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 7.SEP.2020 17:28:18

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 7.SEP.2020 17:28:33



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions above 18GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Aug. 17, 2020~ Sep. 17, 2020	Jul. 13, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0802N1D01N- 06	47020&06	30MHz to 1GHz	Oct. 12, 2019	Aug. 17, 2020~ Sep. 17, 2020	Oct. 11, 2020	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 980	18GHz~40GHz	Jan. 10, 2020	Aug. 17, 2020~ Sep. 17, 2020	Jan. 09, 2021	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Oct. 01, 2019	Aug. 17, 2020~ Sep. 17, 2020	Sep. 30, 2020	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-152 2	1G~18GHz	Sep. 19, 2019	Aug. 17, 2020~ Sep. 17, 2020	Sep. 18, 2020	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	Aug. 17, 2020~ Sep. 17, 2020	May 06, 2021	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~40GHz	Dec. 13, 2019	Aug. 17, 2020~ Sep. 17, 2020	Dec. 12, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532702 64	1GHz~26.5GHz	Dec. 11, 2019	Aug. 17, 2020~ Sep. 17, 2020	Dec.10, 2020	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY572901 11	3Hz~26.5GHz	Dec. 05, 2019	Aug. 17, 2020~ Sep. 17, 2020	Dec. 04, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/ 4PE	NA	Aug. 30, 2019	Aug. 17, 2020~ Aug. 28, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/ 4PE	NA	Aug. 29, 2020	Aug. 29, 2020~ Sep. 17, 2020	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/ 4PE	NA	Aug. 30, 2019	Aug. 17, 2020~ Aug. 28, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/ 4PE	NA	Aug. 29, 2020	Aug. 29, 2020~ Sep. 17, 2020	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300 -5757	NA	Aug. 30, 2019	Aug. 17, 2020~ Aug. 28, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300 -5757	NA	Aug. 29, 2020	Aug. 29, 2020~ Sep. 17, 2020	Aug. 28, 2021	Radiation (03CH16-HY)
Hygrometer	TECPEL	DTM-303B	TP162965	N/A	Oct. 25, 2019	Aug. 17, 2020~ Sep. 17, 2020	Oct. 24, 2020	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Aug. 17, 2020~ Sep. 17, 2020	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Aug. 17, 2020~ Sep. 17, 2020	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Aug. 17, 2020~ Sep. 17, 2020	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Aug. 17, 2020~ Sep. 17, 2020	N/A	Radiation (03CH16-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Aug. 19, 2020~ Sep. 07, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	Aug. 19, 2020~ Sep. 07, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Aug. 19, 2020~ Sep. 07, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Aug. 19, 2020~ Sep. 07, 2020	Mar. 16, 2021	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 25, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Aug. 25, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Aug. 25, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Aug. 25, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Aug. 25, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Aug. 25, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Aug. 25, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Aug. 25, 2020	Jan. 01, 2021	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7
---	-----




Appendix A. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	24~26°C
		Relative Humidity :	42~50%

EUT Information

Report NO : 072944
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	37.33	55.88	18.55	L1	OFF	19.5
0.152250	54.22	---	65.88	11.66	L1	OFF	19.5
0.165750	---	39.28	55.17	15.89	L1	OFF	19.5
0.165750	55.21	---	65.17	9.96	L1	OFF	19.5
0.181500	---	37.59	54.42	16.83	L1	OFF	19.5
0.181500	52.98	---	64.42	11.44	L1	OFF	19.5
0.206250	---	37.04	53.36	16.32	L1	OFF	19.5
0.206250	50.59	---	63.36	12.77	L1	OFF	19.5
0.226500	---	34.07	52.58	18.51	L1	OFF	19.5
0.226500	46.21	---	62.58	16.37	L1	OFF	19.5
0.248714	---	32.57	51.80	19.23	L1	OFF	19.5
0.248714	43.83	---	61.80	17.97	L1	OFF	19.5
0.265020	---	30.99	51.27	20.28	L1	OFF	19.5
0.265020	41.73	---	61.27	19.54	L1	OFF	19.5
0.299670	---	27.01	50.25	23.24	L1	OFF	19.5
0.299670	37.38	---	60.25	22.87	L1	OFF	19.5
0.701250	---	24.21	46.00	21.79	L1	OFF	19.5
0.701250	32.56	---	56.00	23.44	L1	OFF	19.5
0.755160	---	36.56	46.00	9.44	L1	OFF	19.5
0.755160	43.56	---	56.00	12.44	L1	OFF	19.5
8.338920	---	25.88	50.00	24.12	L1	OFF	19.8

8.338920	33.07	---	60.00	26.93	L1	OFF	19.8
13.560000	---	41.19	50.00	8.81	L1	OFF	19.8
13.560000	54.34	---	60.00	5.66	L1	OFF	19.8

EUT Information

Report NO : 072944
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	34.83	55.88	21.05	N	OFF	19.5
0.152250	48.90	---	65.88	16.98	N	OFF	19.5
0.161610	---	39.02	55.38	16.36	N	OFF	19.5
0.161610	54.65	---	65.38	10.73	N	OFF	19.5
0.179250	---	32.67	54.52	21.85	N	OFF	19.5
0.179250	46.62	---	64.52	17.90	N	OFF	19.5
0.204450	---	38.18	53.43	15.25	N	OFF	19.5
0.204450	49.09	---	63.43	14.34	N	OFF	19.5
0.229560	---	29.38	52.47	23.09	N	OFF	19.5
0.229560	41.08	---	62.47	21.39	N	OFF	19.5
0.251250	---	31.48	51.72	20.24	N	OFF	19.5
0.251250	42.52	---	61.72	19.20	N	OFF	19.5
0.589740	---	29.76	46.00	16.24	N	OFF	19.5
0.589740	35.30	---	56.00	20.70	N	OFF	19.5
0.707280	---	32.01	46.00	13.99	N	OFF	19.5
0.707280	38.99	---	56.00	17.01	N	OFF	19.5
0.755250	---	37.36	46.00	8.64	N	OFF	19.6
0.755250	44.05	---	56.00	11.95	N	OFF	19.6
8.296440	---	23.14	50.00	26.86	N	OFF	19.8
8.296440	28.65	---	60.00	31.35	N	OFF	19.8
13.560000	---	39.30	50.00	10.70	N	OFF	19.9

13.560000	52.31	---	60.00	7.69	N	OFF	19.9
-----------	-------	-----	-------	------	---	-----	------



Appendix B. Radiated Spurious Emission

Test Engineer :	Andy Yang, Karl Hou and CR Laio	Temperature :	20~25°C
		Relative Humidity :	50~65%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2379.615	57.58	-16.42	74	41.22	27.68	18.46	29.78	249	192	P	H	
		2327.535	46.98	-7.02	54	30.48	27.89	18.37	29.76	249	192	A	H	
	*	2402	103.41	-	-	87.1	27.6	18.5	29.79	249	192	P	H	
	*	2402	102.85	-	-	86.54	27.6	18.5	29.79	249	192	A	H	
													H	
			2347.065	58.19	-15.81	74	41.75	27.81	18.4	29.77	364	92	P	V
			2310.525	47.29	-6.71	54	30.75	27.96	18.33	29.75	364	92	A	V
	*		2402	95.53	-	-	79.22	27.6	18.5	29.79	364	92	P	V
	*		2402	95	-	-	78.69	27.6	18.5	29.79	364	92	A	V
														V
BLE CH 19 2440MHz		2322.88	57.57	-16.43	74	41.06	27.91	18.36	29.76	246	193	P	H	
		2385.18	47.17	-6.83	54	30.82	27.66	18.47	29.78	246	193	A	H	
	*	2440	104.95	-	-	88.57	27.6	18.58	29.8	246	193	P	H	
	*	2440	104.32	-	-	87.94	27.6	18.58	29.8	246	193	A	H	
			2486.7	57.36	-16.64	74	40.98	27.53	18.67	29.82	246	193	P	H
			2497.97	47.14	-6.86	54	30.78	27.5	18.69	29.83	246	193	A	H
			2324.42	57.36	-16.64	74	40.86	27.9	18.36	29.76	338	94	P	V
			2316.58	47.13	-6.87	54	30.6	27.93	18.35	29.75	338	94	A	V
	*		2440	96.98	-	-	80.6	27.6	18.58	29.8	338	94	P	V
	*		2440	96.43	-	-	80.05	27.6	18.58	29.8	338	94	A	V
			2496.99	56.83	-17.17	74	40.46	27.51	18.69	29.83	338	94	P	V
			2486.98	47.15	-6.85	54	30.77	27.53	18.67	29.82	338	94	A	V



BLE CH 39 2480MHz	*	2480	105.62	-	-	89.24	27.54	18.66	29.82	298	189	P	H
	*	2480	105.17	-	-	88.79	27.54	18.66	29.82	298	189	A	H
		2491.2	58.85	-15.15	74	42.48	27.52	18.68	29.83	298	189	P	H
		2485	47.6	-6.4	54	31.22	27.53	18.67	29.82	298	189	A	H
													H
													H
	*	2480	97.88	-	-	81.5	27.54	18.66	29.82	343	91	P	V
	*	2480	97.24	-	-	80.86	27.54	18.66	29.82	343	91	A	V
		2492.28	57.61	-16.39	74	41.24	27.52	18.68	29.83	343	91	P	V
		2484.92	47.43	-6.57	54	31.05	27.53	18.67	29.82	343	91	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	42.91	-31.09	74	57.52	31.11	13.36	59.08	100	0	P	H
													H
													H
													H
		4804	41.73	-32.27	74	56.34	31.11	13.36	59.08	100	0	P	V
													V
													V
BLE CH 19 2440MHz		4880	41.31	-32.69	74	56	31.08	13.36	59.13	100	0	P	H
		7320	46.54	-27.46	74	52.43	36.48	16.18	58.55	100	0	P	H
													H
													H
		4880	40.83	-33.17	74	55.52	31.08	13.36	59.13	100	0	P	V
		7320	46.48	-27.52	74	52.37	36.48	16.18	58.55	100	0	P	V
													V
BLE CH 39 2480MHz		4960	41.17	-32.83	74	55.73	31.26	13.36	59.18	100	0	P	H
		7440	47.07	-26.93	74	52.48	36.58	16.39	58.38	100	0	P	H
													H
													H
		4960	41.1	-32.9	74	55.66	31.26	13.36	59.18	100	0	P	V
		7440	47.21	-26.79	74	52.62	36.58	16.39	58.38	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		18175	37.89	-36.11	74	43.86	37.27	10.93	54.17	150	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			18378	37.28	-36.72	74	43.24	37.48	10.94	54.38	150	0	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BLE LF		30.97	22.31	-17.69	40	29.76	24.09	0.67	32.21	-	-	P	H	
		118.27	26.99	-16.51	43.5	40.29	17.27	1.69	32.26	-	-	P	H	
		255.04	20.13	-25.87	46	30.56	19.27	2.64	32.34	-	-	P	H	
		456.8	28.55	-17.45	46	33.82	23.31	3.56	32.14	-	-	P	H	
		556.71	27.75	-18.25	46	29.75	25.99	4	31.99	-	-	P	H	
		864.2	33.48	-12.52	46	31.43	29.03	5.1	32.08	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
			42.61	27.12	-12.88	40	40.69	17.95	0.82	32.34	100	0	P	V
			73.65	24.31	-15.69	40	42.97	12.45	1.23	32.34	-	-	P	V
			113.42	21.23	-22.27	43.5	34.77	17.09	1.63	32.26	-	-	P	V
			264.74	19.84	-26.16	46	29.45	20.04	2.7	32.35	-	-	P	V
			385.02	25.62	-20.38	46	33.34	21.24	3.26	32.22	-	-	P	V
			473.29	27.99	-18.01	46	32.93	23.56	3.62	32.12	-	-	P	V
													V	
													V	
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2375.73	56.89	-17.11	74	40.51	27.7	18.46	29.78	289	189	P	H	
		2384.655	49.21	-4.79	54	32.86	27.66	18.47	29.78	289	189	A	H	
	*	2402	103.52	-	-	87.21	27.6	18.5	29.79	289	189	P	H	
	*	2402	102.09	-	-	85.78	27.6	18.5	29.79	289	189	A	H	
													H	
														H
			2340.24	57.18	-16.82	74	40.71	27.84	18.39	29.76	365	99	P	V
			2371.425	49.24	-4.76	54	32.86	27.71	18.45	29.78	365	99	A	V
	*		2402	95.25	-	-	78.94	27.6	18.5	29.79	365	99	P	V
	*		2402	93.81	-	-	77.5	27.6	18.5	29.79	365	99	A	V
														V
													V	
BLE CH 19 2440MHz		2378.04	57.97	-16.03	74	41.6	27.69	18.46	29.78	245	197	P	H	
		2327.08	49.37	-4.63	54	32.87	27.89	18.37	29.76	245	197	A	H	
	*	2440	105.23	-	-	88.85	27.6	18.58	29.8	245	197	P	H	
	*	2440	103.87	-	-	87.49	27.6	18.58	29.8	245	197	A	H	
			2489.85	57.25	-16.75	74	40.88	27.52	18.68	29.83	245	197	P	H
			2495.87	49.04	-4.96	54	32.67	27.51	18.69	29.83	245	197	A	H
			2332.12	57.5	-16.5	74	41.02	27.87	18.37	29.76	341	86	P	V
			2378.88	49.28	-4.72	54	32.92	27.68	18.46	29.78	341	86	A	V
	*		2440	96.27	-	-	79.89	27.6	18.58	29.8	341	86	P	V
	*		2440	94.86	-	-	78.48	27.6	18.58	29.8	341	86	A	V
			2489.57	57.57	-16.43	74	41.21	27.52	18.67	29.83	341	86	P	V
		2485.72	49.13	-4.87	54	32.75	27.53	18.67	29.82	341	86	A	V	



BLE CH 39 2480MHz	*	2480	105.95	-	-	89.57	27.54	18.66	29.82	302	187	P	H
	*	2480	104.53	-	-	88.15	27.54	18.66	29.82	302	187	A	H
		2488.08	57.67	-16.33	74	41.3	27.52	18.67	29.82	302	187	P	H
		2485.68	49.79	-4.21	54	33.41	27.53	18.67	29.82	302	187	A	H
													H
													H
	*	2480	97.45	-	-	81.07	27.54	18.66	29.82	359	86	P	V
	*	2480	96.04	-	-	79.66	27.54	18.66	29.82	359	86	A	V
		2492.48	57.19	-16.81	74	40.82	27.52	18.68	29.83	359	86	P	V
		2490.96	49.85	-4.15	54	33.48	27.52	18.68	29.83	359	86	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	40.97	-33.03	74	55.53	31.11	13.41	59.08	100	0	P	H
													H
													H
													H
		4804	41.56	-32.44	74	56.12	31.11	13.41	59.08	100	0	P	V
													V
													V
BLE CH 19 2440MHz		4880	40.79	-33.21	74	55.45	31.08	13.39	59.13	100	0	P	H
		7320	46.68	-27.32	74	52.65	36.48	16.1	58.55	100	0	P	H
													H
													H
		4880	40.79	-33.21	74	55.45	31.08	13.39	59.13	100	0	P	H
		7320	46.68	-27.32	74	52.65	36.48	16.1	58.55	100	0	P	H
													V
BLE CH 39 2480MHz		4960	41.35	-32.65	74	55.92	31.26	13.35	59.18	100	0	P	H
		7440	47.78	-26.22	74	53.29	36.58	16.29	58.38	100	0	P	H
													H
													H
		4960	41.34	-32.66	74	55.91	31.26	13.35	59.18	100	0	P	V
		7440	46.74	-27.26	74	52.25	36.58	16.29	58.38	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		24209	41.66	-32.34	74	41.64	40.27	13.13	53.38	150	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			24209	39.84	-34.16	74	39.82	40.27	13.13	53.38	150	0	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BLE LF		31.94	21.77	-18.23	40	29.89	23.41	0.69	32.22	-	-	P	H	
		114.39	25.48	-18.02	43.5	38.98	17.12	1.64	32.26	-	-	P	H	
		184.23	18.4	-25.1	43.5	33.78	14.77	2.16	32.31	-	-	P	H	
		263.77	19.61	-26.39	46	29.22	20.05	2.69	32.35	-	-	P	H	
		399.57	26.46	-19.54	46	33.49	21.83	3.34	32.2	-	-	P	H	
		457.77	28.91	-17.09	46	34.15	23.33	3.57	32.14	100	0	P	H	
														H
														H
														H
														H
														H
														H
			42.61	27.43	-12.57	40	41	17.95	0.82	32.34	100	0	P	V
			74.62	24.3	-15.7	40	42.78	12.62	1.24	32.34	-	-	P	V
			116.33	22.05	-21.45	43.5	35.42	17.22	1.67	32.26	-	-	P	V
			262.8	19.45	-26.55	46	29.04	20.07	2.69	32.35	-	-	P	V
			384.05	26.43	-19.57	46	34.19	21.21	3.26	32.23	-	-	P	V
			457.77	27.93	-18.07	46	33.17	23.33	3.57	32.14	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Andy Yang, Karl Hou and CR Laio	Temperature :	20~25°C
		Relative Humidity :	50~65%





Note symbol

-L	Low channel location
-R	High channel location







<1Mbps>





2.4GHz 2400~2483.5MHz
BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
Horizontal		Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>
Avg.	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
Avg	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Horizontal	Fundamental
Peak	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HV Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HV Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
Avg.	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HV Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HV Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWF:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000kHz VBW:3.000kHz SWF:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Vertical	Fundamental
Peak	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
Avg.	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-08-31</p> <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 072944</p>	Left blank
Avg.	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWF:Auto Detector : Peak Project : 072944</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Horizontal	Fundamental
<p>Peak</p>	<p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
<p>Avg.</p>	<p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Vertical	Fundamental
Peak	<p> Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944 </p>	<p> Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944 </p>
Avg.	<p> Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944 </p>	<p> Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 072944 </p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 072944</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 072944</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 072944</p>



Emission above 18GHz
2.4GHz BLE (SHF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-14Y Condition : PEAK_74 Im SHF HORN 88H49170584 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-14Y Condition : PEAK_74 Im SHF HORN 88H49170584 VERTICAL Detector : Peak Project : 072944</p>







Emission below 1GHz
2.4GHz BLE (LF)

Table with 2 columns: Horizontal and Vertical. Each column contains a graph of Level (dBuV/m) vs Frequency (MHz) for 2.4GHz BLE (LF). The graphs show a blue signal line and a red QP limit line. The left graph is for Horizontal polarization and the right for Vertical polarization. Both graphs include site and condition details at the bottom.







<2Mbps>





2.4GHz 2400~2483.5MHz
BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
Horizontal		Fundamental
Peak	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>
Avg.	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
Avg	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HV Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HV Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
Avg.	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HV Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Date: 2020-09-01</p> <p>Site : 03CH16-HV Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000kHz VBW:30.000kHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
<p>Avg.</p>	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:30.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Left blank</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Horizontal	Fundamental
<p>Peak</p>	<p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
<p>Avg.</p>	<p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
	Vertical	Fundamental
<p>Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK_BE_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 072944</p>
<p>Avg.</p>	 <p>Site : 03CH16-HY Condition : AVG_BE_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-HY Condition : AVG_54 3m 91200_1522 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 072944</p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-1FY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 072944</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 HORIZONTAL Detector : Peak Project : 072944</p>	<p>Site : 03CH16-HY Condition : PEAK_74 3m 91200_1522 VERTICAL Detector : Peak Project : 072944</p>





Emission above 18GHz
2.4GHz BLE (SHF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
<p>QP / Peak</p>	 <p>Site : 03CH16-14Y Condition : PEAK_74 In SHF HORN 88H49170584 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-14Y Condition : PEAK_74 In SHF HORN 88H49170584 VERTICAL Detector : Peak Project : 072944</p>



Emission below 1GHz
2.4GHz BLE (LF)


BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
<p>QP / Peak</p>	 <p>Site : 03CH16-14Y Condition : QP 3m 81LOG_47020406 HORIZONTAL Detector : Peak Project : 072944</p>	 <p>Site : 03CH16-14Y Condition : QP 3m 81LOG_47020406 VERTICAL Detector : Peak Project : 072944</p>



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE for 1Mbps	62.18	388	2.58	3kHz	2.09
Bluetooth -LE for 2Mbps	31.41	196	5.10	10kHz	4.88


Bluetooth - LE for 1Mbps



Date: 19.AUG.2020 17:30:54



Bluetooth – LE for 2Mbps



Date: 19.AUG.2020 17:32:16