



CTK Co., Ltd.  
The Power Leader of Global Regulatory Compliance

## CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501

www.e-ctk.com

### RF EXPOSURE EVALUATION

<b>Applicant</b>	MobiFren Co., Ltd.
<b>Applicant Address</b>	(Gupyeong Dong), 88, Indong 52 Gil, Gumi, Gyeongbuk, 39445, Korea
<b>FCC ID</b>	UZCMFB-HC7700
<b>Product Description</b>	Bluetooth bone-conduction Earphone
<b>Basic model</b>	MFB-HC7700
<b>Variant Model name</b>	-
<b>Operating Frequency</b>	2 402 MHz - 2 480 MHz
<b>Antenna type</b>	FPC Antenna
<b>Antenna gain</b>	-0.13 dBi
<b>Power Source</b>	DC 3.7 V (Battery)
<b>Number of channels</b>	79



## **\*\* RF Exposure Evaluation \*\***

### **Exemption Limits for Routine Evaluation**

#### **SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and $\leq 50$ mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table, The equation and threshold in Note 1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	
150	232	271	310	349	387	<i>SAR Test Exclusion Threshold (mW)</i>
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Note 1 :

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by :



CTK Co., Ltd.  
The Power Leader of Global Regulatory Compliance

# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970 Fax: +82-31-624-9501  
www.e-ctk.com

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1f) is applied to determine SAR test exclusion.

Output Power :

Mode	Frequency (MHz)	Measured conducted power (dBm)	Power tolerance [dB]	Maximum conducted power (dBm)	Maximum conducted power (mW)	SAR Test Exclusion Threshold (mW)
Bluetooth Classic BDR	2 441	-5.30	+ 1.5	-3.80	0.417	10

Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances  $\leq 50$ mm is defined by the following equation :

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$   
 $[\sqrt{f(\text{GHz})}] \leq 3.0$

Base on the maximum conducted power of the antenna to use separation distance, SAR was not required;

**Bluetooth Classic BDR :  $[(0.417 / 5) * \sqrt{2.441}] = 0.130 (\leq 3.0)$**

Result : As a result of the calculation above, the SAR test is exempt