

# **RF EXPOSURE REPORT**

REPORT NO.: SA121010C01
MODEL NO.: E512
FCC ID: UZI-E512
RECEIVED: Oct. 11, 2012
TESTED: Oct. 21 ~ Oct. 25, 2012
ISSUED: Nov. 06, 2012

APPLICANT: BandRich Inc.

ADDRESS: 6F., No. 71, Zhouzi St., Neihu Dist., Taipei City 11493, Taiwan (R.O.C.)

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

- LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)
- **TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



# TABLE OF CONTENTS

RELEA	ASE CONTROL RECORD	3
	CERTIFICATION	
2.	RF EXPOSURE	5
2.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	5
	MPE CALCULATION FORMULA	
2.3	CLASSIFICATION	5
2.4	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	5



### **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED	
SA121010C01	Original release	Nov. 06, 2012	



### **1. CERTIFICATION**

**PRODUCT:** LTE Outdoor CPE **MODEL NO.:** E512 **BRAND:** BandLuxe APPLICANT: BandRich Inc. **TEST SAMPLE:** ENGINEERING SAMPLE **TESTED:** Oct. 21 ~ Oct. 25, 2012 STANDARDS: FCC Part 2 (Section 2.1091) FCC OET Bulletin 65, Supplement C (01-01) **IEEE C95.1** 

The above equipment (Model: E512) has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY

Ivonne Wu / Senior Specialist

APPROVED BY

Ken Liu / Manager

Lin , DATE : Nov. 06, 2012



## 2. RF EXPOSURE

### 2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCYELECTRIC FIELDRANGE (MHz)STRENGTH (V/m)		MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)						
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE										
300-1500			F/1500	30						
1500-100,000			1.0	30						

F = Frequency in MHz

### 2.2 MPE CALCULATION FORMULA

 $Pd = (Pout^*G) / (4^*pi^*r^2)$ 

where

 $Pd = power density in mW/cm^2$ 

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

#### 2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY (MHz)	ERP (dBm)	EIRP (dBm)	DISTANCE (cm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT (mW/cm²)
698MHz ~ 716MHz	29.74	31.89	20	0.308	0.465