



Excellence in Compliance Testing

---

## **Certification Exhibit**

**FCC ID: V2A-TR2**

**IC: 7566A-TR2**

**FCC Rule Part: 15.247**  
**IC Radio Standards Specification: RSS-210**

**ACS Report Number: 08-0053 - 15C**

Manufacturer: Infinity Metering, Inc.  
Model: TR2  
Brand/Trade Name: Tesla ARM

## **RF Exposure**

**General Information:**

Applicant: Infinity Metering, Inc.  
 ACS Project: 08-0053  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information:**

Antenna Type: helical monopole  
 Antenna Gain: 0dBi  
 Maximum Transmitter Output Power: 16.75dBm (Radiated)  
 Maximum System EIRP: 16.75dBm

**MPE Calculation:**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )
915	16.75	0.61	47.32	0	1.000	20	0.009

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.