

TEST REPORT

of

FCC Part 15 Subpart C §15.247
IC RSS-247 Issue 2 and RSS-Gen Issue 5

FCC ID: V2R-BN0300
IC Certification: 10488A-BN0300

Equipment Under Test : Bluetooth Noise cancelling Headphone
Model Name : BN0300
Variant Model Name(s) : -
Applicant : Cresyn Co., Ltd.
Manufacturer : Cresyn Co., Ltd.
Date of Receipt : 2022.12.20
Date of Test(s) : 2022.12.23 ~ 2023.01.17
Date of Issue : 2023.01.17

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Taek Kim

Technical
Manager:



Inho Park

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

| <u>Table of Contents</u> | Page |
|--|------|
| 1. General Information ----- | 3 |
| 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions ---- | 10 |
| 3. 20 dB Bandwidth & 99 % Bandwidth ----- | 30 |
| 4. Maximum Peak Conducted Output Power ----- | 39 |
| 5. Carrier Frequency Separation ----- | 41 |
| 6. Number of Hopping Frequencies ----- | 43 |
| 7. Time of Occupancy(Dwell Time) ----- | 45 |
| 8. AC Power Line Conducted Emission ----- | 53 |
| 9. Antenna Requirement ----- | 58 |

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : Cresyn Co., Ltd.

Address : 5 Gangnam-daero 107-gil, Seocho-gu, Seoul, South Korea, 06524

Contact Person : Lee, Ji-hyeon

Phone No. : +82 2 2041 2843

1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

1.4. Description of EUT

| | |
|---------------------------------|---|
| Kind of Product | Bluetooth Noise cancelling Headphone |
| Model Name | BN0300 |
| Serial Number | Conducted Sample: 001 Radiated Sample: 002 |
| Power Supply | DC 3.8 V |
| Frequency Range | 2 402 MHz ~ 2 480 MHz (Bluetooth) |
| Modulation Technique | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Number of Channels | 79 channels (Bluetooth) |
| Antenna Type | Multilayer Chip Antenna |
| Antenna Gain[*] | 3.06 dB i |
| H/W Version | 1.0 |
| S/W Version | 1.0 |
| FVIN | N/A |

1.5. Declaration by the Manufacturer

- Adaptive Frequency Hopping is supported and use at least 20 channels.

1.6. Information about the FHSS characteristics:

1.6.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

1.6.2. Equal Hopping Frequency Use

The channels of this system will be used equally over the long-term distribution of the hopsets.

1.6.3. Example of a 79 hopping sequence in data mode:

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55

1.6.4. System Receiver Input Bandwidth

Each channel bandwidth is 1 MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

1.6.5. Equipment Description

15.247(a) (1) that the Rx input bandwidths shift frequencies in synchronization with the transmitted signals.

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

1.7. Test Equipment List

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Interval | Cal. Due |
|--------------------------|---------------------------------|--------------------------------------|---------------------------|---------------|-----------------|---------------|
| Signal Generator | R&S | SMA100B | 106887 | Oct. 13, 2022 | Annual | Oct. 13, 2023 |
| Signal Generator | R&S | SMBV100A | 255834 | May 25, 2022 | Annual | May 25, 2023 |
| Spectrum Analyzer | R&S | FSV30 | 103210 | Dec. 07, 2022 | Annual | Dec. 07, 2023 |
| Spectrum Analyzer | Agilent | N9020A | MY53421758 | Aug. 26, 2022 | Annual | Aug. 26, 2023 |
| Bluetooth Tester | TESCOM | TC-3000C | 3000C000560 | Sep. 14, 2022 | Annual | Sep. 14, 2023 |
| Directional Coupler | KRYTAR | 152613 | 122660 | Jul. 06, 2022 | Annual | Jul. 06, 2023 |
| BRIDGE COUPLER | MARKI MICROWAVE INC | CBR16-0012 | 1542 | May 06, 2022 | Annual | May 06, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX3.0/18G-6SS | 21 | Jun. 09, 2022 | Annual | Jun. 09, 2023 |
| High Pass Filter | Wainwright Instrument GmbH | WHNX7.5/26.5G-6SS | 15 | May 31, 2022 | Annual | May 31, 2023 |
| Low Pass Filter | Mini-Circuits | NLP-1200+ | V 8979400903-2 | Feb. 10, 2022 | Annual | Feb. 10, 2023 |
| Power Sensor | R&S | NRP-Z81 | 100669 | May 06, 2022 | Annual | May 06, 2023 |
| DC Power Supply | R&S | HMP2020 | 020089489 | May 17, 2022 | Annual | May 17, 2023 |
| Preamplifier | H.P. | 8447F | 2944A03909 | Aug. 04, 2022 | Annual | Aug. 04, 2023 |
| Signal Conditioning Unit | R&S | SCU-18 | 10117 | Jun. 13, 2022 | Annual | Jun. 13, 2023 |
| Preamplifier | TESTEK | TK-PA1840H | 130016 | Jan. 11, 2023 | Annual | Jan. 11, 2024 |
| Loop Antenna | Schwarzbeck Mess- Elektronik | FMZB 1519 | 1519-039 | Aug. 23, 2021 | Biennial | Aug. 23, 2023 |
| Bilog Antenna | Schwarzbeck Mess- Elektronik | VULB 9163 | 01126 | Feb. 07, 2022 | Annual | Feb. 07, 2023 |
| Horn Antenna | R&S | HF906 | 100326 | Feb. 18, 2022 | Annual | Feb. 18, 2023 |
| Horn Antenna | Schwarzbeck Mess- Elektronik | BBHA 9170 | 9170-540 | Nov. 30, 2022 | Annual | Nov. 30, 2023 |
| EMI Test Receiver | R&S | ESCI 7 | 100911 | Feb. 23, 2022 | Annual | Feb. 23, 2023 |
| Two-Line V-Network | R&S | ENV216 | 100190 | May 13, 2022 | Annual | May 13, 2023 |
| Turn Table | Innco systems GmbH | DS 1200 S | N/A | N.C.R. | N/A | N.C.R. |
| Controller | Innco systems GmbH | CONTROLLER CO3000- 4P | CO3000/963/383 30516/L | N.C.R. | N/A | N.C.R. |
| Antenna Mast | Innco systems GmbH | MA4640-XP-ET | MA4640/536/383 30516/L | N.C.R. | N/A | N.C.R. |
| Anechoic Chamber | SY Corporation | L x W x H (9.6 m x 6.4 m x 6.6 m) | N/A | N.C.R. | N/A | N.C.R. |
| Coaxial Cable | RFONE | MWX221-NMSNMS (4 m) | J1023142 | Oct. 04, 2022 | Semi- Annual | Apr. 04, 2023 |
| Coaxial Cable | Qualwave Inc. | QA500-18-NN-10 (10 m) | 22200114 | Oct. 04, 2022 | Semi- Annual | Apr. 04, 2023 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182287 | Aug. 18, 2022 | Semi- Annual | Feb. 18, 2023 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182288 | Aug. 18, 2022 | Semi- Annual | Feb. 18, 2023 |
| Coaxial Cable | RADIALL | TESTPRO 3 | 182291 | Aug. 18, 2022 | Semi- Annual | Feb. 18, 2023 |

Note;

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

► **Support Equipment**

| Description | Manufacturer | Model | S/N |
|----------------|----------------------------|----------|-----|
| TRAVEL ADAPTER | SOLUM VINA COMPANY LIMITED | EP-TA800 | - |

1.8. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part15 Subpart C, IC RSS-247 Issue 2 and RSS-Gen Issue 5 | | | |
|--|---|---|----------|
| Section in FCC | Section in IC | Test Item(s) | Result |
| 15.205(a) 15.209 15.247(d) | RSS-247 Issue 2 5.5 RSS-Gen Issue 5 8.9 | Transmitter Radiated Spurious Emissions and Conducted Spurious Emission | Complied |
| 15.247(a)(1) | RSS-247 Issue 2 5.1(b) RSS-Gen Issue 5 6.7 | 20 dB Bandwidth and 99 % Bandwidth | Complied |
| 15.247(a)(1) 15.247(b)(1) | RSS-247 Issue 2 5.1(b) 5.4(b) | Maximum Peak Conducted Output Power | Complied |
| 15.247(a)(1) | RSS-247 Issue 2 5.1(b) | Carrier Frequency Separation | Complied |
| 15.247(a)(1)(iii) | RSS-247 Issue 2 5.1(d) | Number of Hopping Frequencies | Complied |
| 15.247(a)(1)(iii) | RSS-247 Issue 2 5.1(d) | Time of Occupancy (Dwell Time) | Complied |
| 15.207 | RSS-Gen Issue 5 8.8 | AC Power Line Conducted Emission | Complied |

1.9. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

1.10. Sample Calculation

Where relevant, the following sample calculation is provided:

1.10.1. Conducted Test

Offset value (dB) = Directional coupler (dB) + Cable loss (dB)

1.10.2. Radiation Test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB) + Duty factor (dB)

1.11. Information of software for test

- Using the software of BlueTest3 (Version 3.3.10) to testing of EUT.

1.12. Test Report Revision

| Revision | Report Number | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0 | F690501-RF-RTL003702 | 2023.01.17 | Initial |

1.13. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty | |
|------------------------------------|-------------|---------|
| RF Output Power | 0.32 dB | |
| Occupied Bandwidth | 3.90 kHz | |
| Conducted Spurious Emission | 0.61 dB | |
| AC Conducted Emission | 4.00 dB | |
| Radiated Emission, 9 kHz to 30 MHz | H | 3.40 dB |
| | V | 3.40 dB |
| Radiated Emission, below 1 GHz | H | 4.50 dB |
| | V | 5.10 dB |
| Radiated Emission, above 1 GHz | H | 3.70 dB |
| | V | 3.90 dB |

All measurement uncertainty values are shown with a coverage factor $k = 2$ to indicate a 95 % level of confidence.

1.14. Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

| Operation Mode | Data Rate (Mbps) | Channel | Frequency (MHz) | RF Peak Output Power (dB m) |
|----------------|------------------|---------|-----------------|-----------------------------|
| GFSK | 1 | Low | 2 402 | <u>4.08</u> |
| | | Middle | 2 441 | 3.43 |
| | | High | 2 480 | 3.81 |
| $\pi/4$ DQPSK | 2 | Low | 2 402 | 5.75 |
| | | Middle | 2 441 | 5.56 |
| | | High | 2 480 | <u>6.03</u> |
| 8DPSK | 3 | Low | 2 402 | 6.22 |
| | | Middle | 2 441 | 5.89 |
| | | High | 2 480 | <u>6.53</u> |

Note;


1. For transmitter radiated spurious emissions, conducted spurious emission, carrier frequency separation and number of hopping frequencies, GFSK / DH5 and 8DPSK / 3DH5 are tested as worst condition.
2. For 20 dB bandwidth and maximum peak conducted output power, GFSK / DH5, $\pi/4$ DQPSK / 2DH5 and 8DPSK / 3DH5 are tested as worst condition.
3. For Time of Occupancy, GFSK / DH1, DH3, DH5 and 8DPSK / 3DH1, 3DH3, 3DH5 are tested as worst condition.

1.15. Duty Cycle Correction Factor of EUT

According to KDB 558074 D01 15.247 Meas Guidance v05r02, 9, as a “duty cycle correction factor”, pulse averaging with 20 log (worst case dwell time / 100 ms) has to be used for average result.

3DH5 on time (One Pulse) Plot on Channel 39

3DH5 on time (Count Pulses) Plot on Channel 39



In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time 3DH5 packet is observed;
 the period to have 3DH5 packet completing one hopping sequence is $2.89 \text{ ms} \times 20 \text{ channels} = 57.80 \text{ ms}$

There cannot be 2 complete hopping sequences within 100 ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100 \text{ ms} / 57.80 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time:


$$20 \times \log (5.78 \text{ ms}/100 \text{ ms}) = -24.76 \text{ dB}$$

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions


2.1. Test Setup

2.1.1. Transmitter Radiated Spurious Emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.1.2. Conducted Spurious Emissions



2.2. Limit

2.2.1. FCC

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ($\mu\text{V/m}$) | Measurement Distance (Meters) |
|-----------------|------------------------------------|-------------------------------|
| 0.009-0.490 | 2 400/F(kHz) | 300 |
| 0.490-1.705 | 24 000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.2.2. IC

According to RSS-247 Issue 2, 5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen Issue 5, 8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General Field Strength Limits at frequencies above 30 MHz

| Frequency (MHz) | Field Strength ($\mu\text{V}/\text{m}$ at 3 m) |
|-----------------|---|
| 30-88 | 100 |
| 88-216 | 150 |
| 216-960 | 200 |
| Above 960 | 500 |

Table 6 – General Field Strength Limits at frequencies below 30 MHz

| Frequency | Magnetic Field Strength (H-Field) ($\mu\text{A}/\text{m}$) | Measurement Distance (meters) |
|------------------------|--|-------------------------------|
| 9-490 kHz ¹ | 6.37/F (F in kHz) | 300 |
| 490-1 705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705-30 MHz | 0.08 | 30 |

Note¹: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.
6. For measurements Above 1 GHz resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

Note;

1. Definition of DUT Axis.
The test orthogonal plan of EUT was investigated with three axis described in the test setup photo.
The Y-axis was worst-case, all radiated testing of EUT was performed with Y-axis.

2.3.3. Test Procedures for Conducted Spurious Emissions

2.3.3.1. Band-edge Compliance of RF Conducted Emissions

The transmitter output was connected to the spectrum analyzer.

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \geq 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

2.3.3.2. Spurious RF Conducted Emissions

The transmitter output was connected to the spectrum analyzer.

RBW = 1 MHz

VBW = 3 MHz

Sweep = auto

Detector function = peak

Trace = max hold

2.3.3.3. TDF function

- For plots showing conducted spurious emissions from 9 kHz to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.

So, the reading values shown in plots were final result.

2.4. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

2.4.1. Radiated Spurious Emission below 1 000 MHz


The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

| Radiated Emissions | | | Ant. | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP + CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 51.70 | 28.80 | Peak | V | 19.63 | -27.47 | 20.96 | 40.00 | 19.04 |
| 531.98 | 34.00 | Peak | H | 23.54 | -26.06 | 31.48 | 46.00 | 14.52 |
| Above 600.00 | Not detected | - | - | - | - | - | - | - |

Remark;

- Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
- Reported spurious emissions are in **EDR / 3DH5 / High channel** as worst case among other modes.
- Radiated spurious emission measurement as below.
(Actual = Reading + AF + AMP + CL)
- According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plot



2.4.2. Radiated Spurious Emission above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak values.

Operating Mode: GFSK

A. Low Channel (2 402 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 310.00 | 24.56 | Peak | H | 27.80 | 6.37 | - | 58.73 | 74.00 | 15.27 |
| *2 310.00 | - | Average | - | - | - | -24.76 | 33.97 | 54.00 | 20.03 |
| *2 314.63 | 27.58 | Peak | H | 27.80 | 6.36 | - | 61.74 | 74.00 | 12.26 |
| *2 314.63 | - | Average | - | - | - | -24.76 | 36.98 | 54.00 | 17.02 |
| *2 390.00 | 25.33 | Peak | H | 28.04 | 6.63 | - | 60.00 | 74.00 | 14.00 |
| *2 390.00 | - | Average | - | - | - | -24.76 | 35.24 | 54.00 | 18.76 |

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |

B. Middle Channel (2 441 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |

C. High Channel (2 480 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 483.50 | 25.38 | Peak | H | 28.13 | 6.35 | - | 59.86 | 74.00 | 14.14 |
| *2 483.50 | - | Average | - | - | - | -24.76 | 35.10 | 54.00 | 18.90 |
| *2 491.57 | 27.53 | Peak | H | 28.12 | 6.34 | - | 61.99 | 74.00 | 12.01 |
| *2 491.57 | - | Average | - | - | - | -24.76 | 37.23 | 54.00 | 16.77 |
| *2 500.00 | 25.04 | Peak | H | 28.10 | 6.32 | - | 59.46 | 74.00 | 14.54 |
| *2 500.00 | - | Average | - | - | - | -24.76 | 34.70 | 54.00 | 19.30 |

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |

Operating Mode: 8DPSK

A. Low Channel (2 402 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 310.00 | 24.67 | Peak | H | 27.80 | 6.37 | - | 58.84 | 74.00 | 15.16 |
| *2 310.00 | - | Average | - | - | - | -24.76 | 34.08 | 54.00 | 19.92 |
| *2 385.03 | 26.87 | Peak | H | 28.01 | 6.58 | - | 61.46 | 74.00 | 12.54 |
| *2 385.03 | - | Average | - | - | - | -24.76 | 36.70 | 54.00 | 17.30 |
| *2 390.00 | 26.33 | Peak | H | 28.04 | 6.63 | - | 61.00 | 74.00 | 13.00 |
| *2 390.00 | - | Average | - | - | - | -24.76 | 36.24 | 54.00 | 17.76 |

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |

B. Middle Channel (2 441 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |

C. High Channel (2 480 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 483.50 | 25.47 | Peak | H | 28.13 | 6.35 | - | 59.95 | 74.00 | 14.05 |
| *2 483.50 | - | Average | - | - | - | -24.76 | 35.19 | 54.00 | 18.81 |
| *2 486.07 | 28.09 | Peak | H | 28.13 | 6.35 | - | 62.57 | 74.00 | 11.43 |
| *2 486.07 | - | Average | - | - | - | -24.76 | 37.81 | 54.00 | 16.19 |
| *2 500.00 | 24.68 | Peak | H | 28.10 | 6.32 | - | 59.10 | 74.00 | 14.90 |
| *2 500.00 | - | Average | - | - | - | -24.76 | 34.34 | 54.00 | 19.66 |

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Above 1 000.00 | Not detected | - | - | - | - | - | - | - | - |


Remark;

1. "*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.


- Test plots

Operating Mode: GFSK

Low channel band edge (Peak)




High channel band edge (Peak)




Operating Mode: 8DPSK


Low channel band edge (Peak)




High channel band edge (Peak)




2.4.3. Plot of Spurious Conducted Emissions
Operating Mode: GFSK_hopping function turned off
 Low channel




Middle channel




High channel




Operating Mode: GFSK_hopping function turned on
Band edge compliance
 Low channel






High channel






Operating Mode: 8DPSK_hopping function turned off
 Low channel




Middle channel




High channel



Operating Mode: 8DPSK_hopping function turned on
Band edge compliance
 Low channel




High channel



3. 20 dB Bandwidth and 99 % Bandwidth

3.1. Test Setup



3.2. Limit

Limit: Not Applicable

3.3. Test Procedure

3.3.1. 20 dB Bandwidth

The test follows ANSI C63.10-2013.

The 20 dB bandwidth was measured with a spectrum analyzer connected to RF antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

Use the following spectrum analyzer setting:

1. Span = approximately 2 to 5 times the 20 dB bandwidth.
2. RBW \geq 1 % to 5 % of the 20 dB bandwidth.
3. VBW \geq 3 x RBW
4. Sweep = auto
5. Detector = peak
6. Trace = max hold

The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is 20 dB bandwidth of the emission.

3.3.2. 99 % Bandwidth

- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99 % emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99 % emission bandwidth).

3.4. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


| Operation Mode | Data Rate (Mbps) | Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) | 99 % Bandwidth (MHz) |
|----------------|------------------|---------|-----------------|-----------------------|----------------------|
| GFSK | 1 | Low | 2 402 | 0.965 | 0.881 |
| | | Middle | 2 441 | 0.977 | 0.884 |
| | | High | 2 480 | 0.962 | 0.881 |
| π/4DQPSK | 2 | Low | 2 402 | 1.349 | 1.184 |
| | | Middle | 2 441 | 1.340 | 1.190 |
| | | High | 2 480 | 1.340 | 1.184 |
| 8DPSK | 3 | Low | 2 402 | 1.331 | 1.190 |
| | | Middle | 2 441 | 1.337 | 1.190 |
| | | High | 2 480 | 1.334 | 1.184 |

- Test plots


20 dB Bandwidth

Operating Mode: GFSK


Low Channel



Middle Channel




High Channel




Operating Mode: $\pi/4$ DQPSK


Low Channel



Middle Channel




High Channel




Operating Mode: 8DPSK


Low Channel



Middle Channel



High Channel




99 % Bandwidth

Operating Mode: GFSK


Low Channel



Middle Channel




High Channel



Operating Mode: $\pi/4$ DQPSK


Low Channel



Middle Channel




High Channel



Operating Mode: 8DPSK

Low Channel



Middle Channel



High Channel

