



NVLAP Lab Code 200087-0

SUBMITTAL APPLICATION REPORT

For Class 2 Permissible Changes
Grant of Certification
FOR
Model: WMR400
2412.0 - 2462.0 and 5745.0 - 5825.0 MHz
Broadband Wireless Data Transmitter
FCC ID: V2U-WMR400

FOR

WILIBOX DELIBERANT GROUP

1440 Dutch Valley Place, Suite 1155
Atlanta, GA 30324


Test Report Number: 080623

Authorized Signatory: *Scot D. Rogers*
Scot D. Rogers

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Wilibox Deliberant Group
Model: WMR400
Test #: 080623
Test to: CFR47 (2.1043 and 15.247)
File: WDG WMR400 TestRpt

FCC ID#: V2U-WMR400
SN: ENG1
Page 1 of 22
Date: June 27, 2008

**ROGERS LABS, INC.**

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

**ENGINEERING TEST REPORT
FOR
CLASS 2 PERMISSIVE CHANGES**

FOR
CFR47, PART 15C - INTENTIONAL RADIATORS
Paragraph 15.247
Low Power License Exempt Intentional Radiator

For

WILIBOX DELIBERANT GROUP

1440 Dutch Valley Place, Suite 1155
Atlanta, GA 30324
Mr. Matt Hardy

Model: WMR400
Broadband Wireless Data Transmitter
Frequency Range 2412.0 - 2462.0 and 5745.0 - 5825.0 MHz
FCC ID#: V2U-WMR400

Test Date: June 23, 2008

Certifying Engineer: *Scot D. Rogers*

Scot D. Rogers
ROGERS LABS, INC.
4405 West 259th Terrace
Louisburg, KS 66053
Phone: (913) 837-3214
FAX: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product endorsement by NVLAP, NIST, or
any agency of the U.S. Government.

Table of Contents

TABLE OF CONTENTS.....	3
FORWARD	4
OPINION / INTERPRETATION OF RESULTS	4
ENVIRONMENTAL CONDITIONS.....	4
EQUIPMENT TESTED.....	4
2.1033(B) APPLICATION FOR CERTIFICATION	5
APPLICABLE STANDARDS & TEST PROCEDURES	5
EQUIPMENT FUNCTION AND TESTING PROCEDURES	6
CHANGE TO EQUIPMENT	6
EQUIPMENT AND CABLE CONFIGURATIONS	7
Radiated Emission Test Procedure.....	7
LIST OF TEST EQUIPMENT	7
UNITS OF MEASUREMENTS	8
TEST SITE LOCATIONS	8
SUBPART C – INTENTIONAL RADIATORS	8
Radiated EMI	8
Data: 2.4 GHz Transmitter Radiated Emissions 24 dBi Grid	9
Data: 2.4 GHz Transmitter Radiated Emissions 19 dBi Panel	10
Data: 2.4 GHz Transmitter Radiated Emissions 12 dBi Omni	11
Data: 5.8 GHz Transmitter Radiated Emissions 32.5 dBi Dish.....	12
Data: 5.8 GHz Transmitter Radiated Emissions 27 dBi Grid.....	13
Data: 5.8 GHz Transmitter Radiated Emissions 23 dBi Panel	14
Data: 5.8 GHz Transmitter Radiated Emissions 12 dBi Omni	15
Summary of Results for Radiated Emissions	16
Statement of Modifications and Deviations	16
ANNEX.....	17
Annex A Measurement Uncertainty Calculations.....	18
Annex B Test Equipment List For Rogers Labs, Inc.....	20
Annex C Qualifications.....	21
Annex D FCC Site Registration Letter	22



NVLAP Lab Code 200087-0

Forward

This report documents the supporting information for requesting a Class 2 permissible change. The request offers alternate antenna structures for use with the certified equipment. The electromagnetic emissions compatibility tests required for demonstration of continued compliance with the CFR47 Dated October 1, 2007, Paragraphs 2.1043, and 15.247 have been conducted on the WMR400. The results have been reviewed and found to meet all the requirements investigated for this report.

Name of Applicant:

WILIBOX DELIBERANT GROUP
1440 Dutch Valley Place, Suite 1155
Atlanta, GA 30324

Model: WMR400

FCC I.D.: V2U-WMR400
Frequency Range: 2412.0 – 2462.0 MHz.

Operating Power: 0.363 Watts antenna conducted power
Frequency Range: 5745.0 – 5825.0 MHz.
Operating Power: 0.38 Watts antenna conducted power

Opinion / Interpretation of Results

Tests Performed	Results
Emissions Tests	
Emissions as per CFR47 paragraphs 2 and 15.205	Complies
Emissions as per CFR47 paragraphs 2 and 15.247	Complies

Environmental Conditions

Ambient Temperature 23.9° C
Relative Humidity 45%
Atmospheric Pressure 29.76 in Hg

Equipment Tested

Equipment	Model	FCC I.D.#
EUT	WMR400	V2U-WMR500
Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214 Revision 1	Wilibox Deliberant Group Model: WMR400 Test #: 080623 Test to: CFR47 (2.1043 and 15.247) File: WDG WMR400 TestRpt	FCC ID#: V2U-WMR400 SN: ENG1 Page 4 of 22 Date: June 27, 2008



NVLAP Lab Code 200087-0

2.1033(b) Application for Certification

(1) Manufacturer: WILIBOX DELIBERANT GROUP
1440 Dutch Valley Place, Suite 1155
Atlanta, GA 30324

(2) Identification: Model: WMR400
FCC I.D.: V2U-WMR400

(3) Instruction Book:
Refer to original submittal Exhibit for Instruction Manual.

(4) Description of Circuit Functions:
Refer to original submittal Exhibit of Operational Description.

(5) Block Diagram with Frequencies:
Refer to original submittal Exhibit of Operational Description.

(6) Report of Measurements:
Report of measurements follows in this Report.

(7) Photographs: Construction, Component Placement, etc.:
Refer to original submittal Exhibit for photographs of equipment.

(8) Peripheral Equipment included interfacing with a computer network system.

(9) Transition Provisions of 15.37 are not being requested.

(10) Not Applicable. The unit is not a scanning receiver.

(11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.

Applicable Standards & Test Procedures

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2007, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1043, and applicable parts of paragraph 15, and Part 15C Paragraph 15.247, the following information is submitted.

Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in the ANSI 63.4-2003 Document FCC, documents DA00-1407 and DA00-705 and/or TIA/EIA 603-1.



NVLAP Lab Code 200087-0

Equipment Function and Testing Procedures

The EUT is a board band transmitter operating in 2400-2483.5 and 5725-5875 MHz frequency bands used to transmit data in applications offering broadband wireless connectivity. The unit is marketed for use to incorporate a wireless link to exchange data information from one point to another. For testing purposes the WMR400 transceiver was connected to each requested antenna configuration and operated for testing purposes. The device is marketed for professionally installed use and the additional antennas continue to comply with requirements.

Change to Equipment

The change to the equipment, in relation to the original equipment submittal, increasing the antenna options available for use. Testing was performed to verify the equipment continues to meet all the applicable rules and requirements of the CFR47. Testing confirmed the changes made do not degrade the characteristics allowable and acceptable by the Commission. No change to transmitter or other specifications were affected by the antenna change.

Antennas covered in this report include 2.4 and 5.8 GHz as listed below.

2.4 GHz Antennas	
24 dBi (Dish)	HyperGain model HG2524G
19 dBi (Panel)	model ARC-IA2419B02
12 dBi (Omni)	HyperGain model HG2412U
5.8 GHz	
32.5 dBi (Dish)	HyperGain model HG5833D
27 dBi (Grid)	Hwayaotek model GA-5775-27
23 dBi (Panel)	model ARC-5A5823B01
12 dBi (Omni)	Pac Wireless model OD58M-12

Equipment and Cable Configurations

Radiated Emission Test Procedure

The EUT was placed on a rotating 1 x 1.5-meter wooden platform, 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. Refer to photographs in the exhibits for EUT placement.

List of Test Equipment

A Hewlett Packard 8591EM Spectrum Analyzer was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

HP 8591 EM ANALYZER SETTINGS		
CONDUCTED EMISSIONS:		
RBW	AVG. BW	DETECTOR FUNCTION
9 kHz	30 kHz	Peak / Quasi Peak
RADIATED EMISSIONS:		
RBW	AVG. BW	DETECTOR FUNCTION
120 kHz	300 kHz	Peak / Quasi Peak
HP 8562A ANALYZER SETTINGS		
RBW	VIDEO BW	DETECTOR FUNCTION
100 kHz	100 kHz	PEAK
1 MHz	1 MHz	Peak / Average

EQUIPMENT	MFG.	MODEL	CAL. DATE	DUE.
LISN	Comp. Design	FCC-LISN-2-MOD.CD	10/07	10/08
LISN	Comp. Design	1762	2/08	2/09
Antenna	ARA	BCD-235-B	10/07	10/08
Antenna	EMCO	3147	10/07	10/08
Antenna	EMCO	3143	5/08	5/09
Analyzer	HP	8591EM	5/08	5/09
Analyzer	HP	8562A	5/08	5/09
Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214	Wilibox Deliberant Group Model: WMR400 Test #: 080623 Test to: CFR47 (2.1043 and 15.247)		FCC ID#: V2U-WMR400 SN: ENG1 Page 7 of 22	
Revision 1	File: WDG WMR400 TestRpt		Date: June 27, 2008	

Units of Measurements

Conducted EMI	Data is in dB μ V; dB referenced to one microvolt.
Radiated EMI	Data is in dB μ V/m; dB/m referenced to one microvolt per meter.

Test Site Locations

Conducted EMI	The AC power line conducted emissions tests were performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259 th Terrace, Louisburg, KS.
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259 th Terrace, Louisburg, KS.
Site Approval	Refer to Appendix for FCC Site Approval Letter, Reference # 90910.

Subpart C – Intentional Radiators

Radiated EMI

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. The highest radiated emission was maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 30 MHz to 60,000 MHz was searched for radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 5 GHz and or, pyramidal horns and mixers from 4 GHz to 60 GHz, notch filters and appropriate amplifiers were utilized.



NVLAP Lab Code 200087-0

Sample Calculations:

RFS = Radiated Field Strength

dB μ V/m @ 3 m = dB μ V + A.F. - Amplifier Gain

$$\begin{aligned} \text{dB}\mu\text{V/m} @ 3 \text{ m} &= 86.8 + 32.8 - 0 \\ &= 19.6 \end{aligned}$$

Data: 2.4 GHz Transmitter Radiated Emissions 24 dBi Grid

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
2412.0	86.8	96.7	32.8	0	119.6	129.5	133.0
4824.0	19.8	20.5	41.4	30	31.2	31.9	54.0
7236.0	21.0	23.4	36.0	30	27.0	29.4	54.0
9648.0	21.5	22.0	38.1	30	29.6	30.1	54.0
12060.0	20.0	21.5	40.0	30	30.0	31.5	54.0
2442.0	85.0	95.8	33.2	0	118.2	129.0	133.0
4884.0	18.7	19.3	41.2	30	29.9	30.5	54.0
7326.0	19.5	23.3	36.0	30	25.5	29.3	54.0
9768.0	19.0	22.0	38.1	30	27.1	30.1	54.0
12210.0	18.5	20.8	40.0	30	28.5	30.8	54.0
2462.0	86.7	96.7	33.4	0	120.1	130.1	130.1
4924.0	18.5	21.0	42.1	30	30.6	48.4	33.1
7386.0	21.3	22.6	36.0	30	27.3	40.5	28.6
9848.0	18.0	21.2	38.1	30	26.1	41.4	29.3
12310.0	20.5	23.3	40.0	30	30.5	41.0	33.3
Band Edge							
2400.0	20.0	22.6	32.9	30	22.9	25.5	54.0
2483.5	21.8	22.5	33.3	30	25.1	25.8	54.0
Restricted Bands of Operation							
4824.0	19.8	20.5	41.4	30	31.2	31.9	54.0
4884.0	18.7	19.3	41.2	30	29.9	30.5	54.0
4924.0	18.5	21.0	42.1	30	30.6	33.1	54.0
7236.0	21.0	23.4	36.0	30	27.0	29.4	54.0
7326.0	19.5	23.3	36.0	30	25.5	29.3	54.0
7386.0	21.3	22.6	36.0	30	27.3	28.6	54.0
12060.0	20.0	21.5	40.0	30	30.0	31.5	54.0
12210.0	18.5	20.8	40.0	30	28.5	30.8	54.0
12310.0	20.5	23.3	40.0	30	30.5	33.3	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Wilibox Deliberant Group
Model: WMR400
Test #: 080623
Test to: CFR47 (2.1043 and 15.247)
File: WDG WMR400 TestRpt

FCC ID#: V2U-WMR400
SN: ENG1
Page 9 of 22
Date: June 27, 2008



NVLAP Lab Code 200087-0

Data: 2.4 GHz Transmitter Radiated Emissions 19 dBi Panel

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
2412.0	83.7	91.3	32.8	0	116.5	124.1	133.0
4824.0	20.1	22.0	41.4	30	31.5	33.4	54.0
7236.0	21.1	23.3	36.0	30	27.1	29.3	54.0
9648.0	20.0	22.8	38.1	30	28.1	30.9	54.0
12060.0	21.3	21.3	40.0	30	31.3	31.3	54.0
2442.0	82.5	90.0	33.2	0	115.7	123.2	133.0
4884.0	20.5	22.3	41.2	30	31.7	33.5	54.0
7326.0	19.8	24.8	36.0	30	25.8	30.8	54.0
9768.0	21.6	22.0	38.1	30	29.7	30.1	54.0
12210.0	20.5	21.5	40.0	30	30.5	31.5	54.0
2462.0	83.8	88.2	33.4	0	117.2	121.6	133.0
4924.0	19.5	22.1	42.1	30	31.6	34.2	54.0
7386.0	21.0	24.5	36.0	30	27.0	30.5	54.0
9848.0	22.8	22.5	38.1	30	30.9	30.6	54.0
12310.0	21.5	22.7	40.0	30	31.5	32.7	54.0
Band Edge							
2400.0	21.7	23.3	32.9	30	24.6	26.2	54.0
2483.5	21.1	22.0	33.3	30	24.4	25.3	54.0
Restricted Bands of Operation							
4824.0	20.1	22.0	41.4	30	31.5	33.4	54.0
4884.0	20.5	22.3	41.2	30	31.7	33.5	54.0
4924.0	19.5	22.1	42.1	30	31.6	34.2	54.0
7236.0	21.1	23.3	36.0	30	27.1	29.3	54.0
7326.0	19.8	24.8	36.0	30	25.8	30.8	54.0
7386.0	21.0	24.5	36.0	30	27.0	30.5	54.0
12060.0	21.3	21.3	40.0	30	31.3	31.3	54.0
12210.0	20.5	21.5	40.0	30	30.5	31.5	54.0
12310.0	21.5	22.7	40.0	30	31.5	32.7	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Wilibox Deliberant Group
Model: WMR400
Test #: 080623
Test to: CFR47 (2.1043 and 15.247)
File: WDG WMR400 TestRpt

FCC ID#: V2U-WMR400
SN: ENG1
Page 10 of 22
Date: June 27, 2008



NVLAP Lab Code 200087-0

Data: 2.4 GHz Transmitter Radiated Emissions 12 dBi Omni

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
2412.0	74.3	84.8	32.8	0	107.1	117.6	133.0
4824.0	18.8	20.0	41.4	30	30.2	31.4	54.0
7236.0	21.3	21.5	36.0	30	27.3	27.5	54.0
9648.0	20.5	21.0	38.1	30	28.6	29.1	54.0
12060.0	20.5	21.0	40.0	30	30.5	31.0	54.0
2442.0	72.7	82.8	33.2	0	105.9	116.0	133.0
4884.0	20.6	21.5	41.2	30	31.8	32.7	54.0
7326.0	20.6	22.6	36.0	30	26.6	28.6	54.0
9768.0	20.8	21.7	38.1	30	28.9	29.8	54.0
12210.0	20.1	22.3	40.0	30	30.1	32.3	54.0
2462.0	72.5	84.2	33.4	0	105.9	117.6	133.0
4924.0	19.3	20.1	42.1	30	31.4	32.2	54.0
7386.0	19.0	20.1	36.0	30	25.0	26.1	54.0
9848.0	19.8	21.5	38.1	30	27.9	29.6	54.0
12310.0	19.3	22.0	40.0	30	29.3	32.0	54.0
Band Edge							
2400.0	20.8	20.3	32.9	30	23.7	23.2	54.0
2483.5	20.8	21.5	33.3	30	24.1	24.8	54.0
Restricted Bands of Operation							
4824.0	18.8	20.0	41.4	30	30.2	31.4	54.0
4884.0	20.6	21.5	41.2	30	31.8	32.7	54.0
4924.0	19.3	20.1	42.1	30	31.4	32.2	54.0
7236.0	21.3	21.5	36.0	30	27.3	27.5	54.0
7326.0	20.6	22.6	36.0	30	26.6	28.6	54.0
7386.0	19.0	20.1	36.0	30	25.0	26.1	54.0
12060.0	20.5	21.0	40.0	30	30.5	31.0	54.0
12210.0	20.1	22.3	40.0	30	30.1	32.3	54.0
12310.0	19.3	22.0	40.0	30	29.3	32.0	54.0

Other emissions present had amplitudes at least 20 dB below the limit.



NVLAP Lab Code 200087-0

Data: 5.8 GHz Transmitter Radiated Emissions 32.5 dBi Dish

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
5745.0	64.2	92.9	34.0	0	98.2	126.9	133.0
11490.0	20.0	20.8	39.9	30	29.9	30.7	54.0
17235.0	23.3	26.5	48.1	30	41.4	44.6	54.0
22980.0	22.3	20.8	22.0	30	14.3	12.8	54.0
5785.0	63.5	91.8	34.0	0	97.5	125.8	133.0
11570.0	19.8	21.3	39.9	30	29.7	31.2	54.0
17355.0	22.8	24.7	48.1	30	40.9	42.8	54.0
23140.0	22.0	21.1	22.0	30	14.0	13.1	54.0
5825.0	62.5	91.2	34.0	0	96.5	125.2	133.0
11650.0	19.3	21.0	39.9	30	29.2	30.9	54.0
17475.0	22.8	24.2	48.1	30	40.9	42.3	54.0
23300.0	22.6	22.0	22.0	30	14.6	14.0	54.0
Band Edge							
5725.0	20.5	21.3	34.0	30	24.5	25.3	54.0
5875.0	19.6	21.5	34.0	30	23.6	25.5	54.0
Restricted Bands of Operation							
11490.0	20.0	20.8	39.9	30	29.9	30.7	54.0
11570.0	19.8	21.3	39.9	30	29.7	31.2	54.0
11650.0	19.3	21.0	39.9	30	29.2	30.9	54.0
22980.0	22.3	20.8	22.0	30	14.3	12.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit.



NVLAP Lab Code 200087-0

Data: 5.8 GHz Transmitter Radiated Emissions 27 dBi Grid

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
5745.0	55.0	89.5	34.0	0	89.0	123.5	133.0
11490.0	17.5	19.5	39.9	30	27.4	29.4	54.0
17235.0	23.4	21.1	48.1	30	41.5	39.2	54.0
22980.0	23.8	21.8	22.0	30	15.8	13.8	54.0
5785.0	55.5	88.8	34.0	0	89.5	122.8	133.0
11570.0	18.8	21.7	39.9	30	28.7	31.6	54.0
17355.0	22.5	24.3	48.1	30	40.6	42.4	54.0
23140.0	22.6	23.8	22.0	30	14.6	15.8	54.0
5825.0	54.2	88.0	34.0	0	88.2	122.0	133.0
11650.0	18.6	21.5	39.9	30	28.5	31.4	54.0
17475.0	22.4	22.1	48.1	30	40.5	40.2	54.0
23300.0	22.3	23.0	22.0	30	14.3	15.0	54.0
Band Edge							
5725.0	19.8	19.5	34.0	30	23.8	23.5	54.0
5875.0	18.6	19.3	34.0	30	22.6	23.3	54.0
Restricted Bands of Operation							
11490.0	17.5	19.5	39.9	30	27.4	29.4	54.0
11570.0	18.8	21.7	39.9	30	28.7	31.6	54.0
11650.0	18.6	21.5	39.9	30	28.5	31.4	54.0
22980.0	23.8	21.8	22.0	30	15.8	13.8	54.0

Other emissions present had amplitudes at least 20 dB below the limit.



NVLAP Lab Code 200087-0

Data: 5.8 GHz Transmitter Radiated Emissions 23 dBi Panel

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
5745.0	48.7	85.5	34.0	0	82.7	119.5	133.0
11490.0	18.8	21.8	39.9	30	28.7	31.7	54.0
17235.0	22.8	23.5	48.1	30	40.9	41.6	54.0
22980.0	21.5	22.3	22.0	30	13.5	14.3	54.0
5785.0	48.0	84.8	34.0	0	82.0	118.8	133.0
11570.0	19.0	20.3	39.9	30	28.9	30.2	54.0
17355.0	20.5	22.8	48.1	30	38.6	40.9	54.0
23140.0	22.5	23.3	22.0	30	14.5	15.3	54.0
5825.0	48.3	84.0	34.0	0	82.3	118.0	133.0
11650.0	18.5	20.5	39.9	30	28.4	30.4	54.0
17475.0	22.3	22.8	48.1	30	40.4	40.9	54.0
23300.0	21.3	22.3	22.0	30	13.3	14.3	54.0
Band Edge							
5725.0	17.5	20.5	34.0	30	21.5	24.5	54.0
5875.0	17.0	19.3	34.0	30	21.0	23.3	54.0
Restricted Bands of Operation							
11490.0	18.8	21.8	39.9	30	28.7	31.7	54.0
11570.0	19.0	20.3	39.9	30	28.9	30.2	54.0
11650.0	18.5	20.5	39.9	30	28.4	30.4	54.0
22980.0	21.5	22.3	22.0	30	13.5	14.3	54.0

Other emissions present had amplitudes at least 20 dB below the limit.



NVLAP Lab Code 200087-0

Data: 5.8 GHz Transmitter Radiated Emissions 12 dBi Omni

Frequency in MHz	FSM Horz. (dB μ V)	FSM Vert. (dB μ V)	A.F. (dB/m)	Amp. Gain (dB)	RFS Horz. @ 3 m (dB μ V/m)	RFS Vert. @ 3 m (dB μ V/m)	FCC Class B Limit @ 3 m (dB μ V/m)
5745.0	45.2	62.0	34.0	0	79.2	96.0	133.0
11490.0	18.7	20.0	39.9	30	28.6	29.9	54.0
17235.0	23.0	24.5	48.1	30	41.1	42.6	54.0
22980.0	19.5	22.3	22.0	30	11.5	14.3	54.0
5785.0	44.2	59.8	34.0	0	78.2	93.8	133.0
11570.0	18.0	19.3	39.9	30	27.9	29.2	54.0
17355.0	22.3	23.5	48.1	30	40.4	41.6	54.0
23140.0	23.0	23.0	22.0	30	15.0	15.0	54.0
5825.0	43.2	58.8	34.0	0	77.2	92.8	133.0
11650.0	19.3	19.8	39.9	30	29.2	29.7	54.0
17475.0	23.1	24.6	48.1	30	41.2	42.7	54.0
23300.0	21.8	23.8	22.0	30	13.8	15.8	54.0
Band Edge							
5725.0	19.8	20.3	34.0	30	23.8	24.3	54.0
5875.0	23.5	24.0	34.0	30	27.5	28.0	54.0
Restricted Bands of Operation							
11490.0	18.7	20.0	39.9	30	28.6	29.9	54.0
11570.0	18.0	19.3	39.9	30	27.9	29.2	54.0
11650.0	19.3	19.8	39.9	30	29.2	29.7	54.0
22980.0	19.5	22.3	22.0	30	11.5	14.3	54.0

Other emissions present had amplitudes at least 20 dB below the limit.



NVLAP Lab Code 200087-0

Summary of Results for Radiated Emissions

The general radiated emissions for the EUT meet the requirements for CISPR 22 and FCC Part 15B CLASS B Digital Devices. The model WMR400 had a 26.0 dB minimum margin below the quasi-peak limit at band edges. The model WMR400 had a 9.4 dB margin for harmonic emissions. The model WMR400 had a 19.8 dB minimum margin below the restricted band of operation quasi-peak limit. Other emissions were present with amplitudes at least 20 dB below the limit.

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to comply with emissions requirements of CFR47 15C requirements. There were no deviations or exceptions to the specifications.

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Wilibox Deliberant Group
Model: WMR400
Test #: 080623
Test to: CFR47 (2.1043 and 15.247)
File: WDG WMR400 TestRpt

FCC ID#: V2U-WMR400
SN: ENG1
Page 16 of 22
Date: June 27, 2008



NVLAP Lab Code 200087-0

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment List.
- Annex C Rogers Qualifications.
- Annex D FCC Site Registration Letter.

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Wilibox Deliberant Group
Model: WMR400
Test #: 080623
Test to: CFR47 (2.1043 and 15.247)
File: WDG WMR400 TestRpt

FCC ID#: V2U-WMR400
SN: ENG1
Page 17 of 22
Date: June 27, 2008

Annex A Measurement Uncertainty Calculations

Radiated Emissions Measurement Uncertainty Calculation

Measurement of vertically polarized radiated field strength over the frequency range 30 MHz to 1 GHz on an open area test site at 3m and 10m includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Antenna factor calibration	normal (k = 2)	±0.58
Cable loss calibration	normal (k = 2)	±0.2
Receiver specification	rectangular	±1.0
Antenna directivity	rectangular	±0.1
Antenna factor variation with height	rectangular	±2.0
Antenna factor frequency interpolation	rectangular	±0.1
Measurement distance variation	rectangular	±0.2
Site Imperfections	rectangular	±1.5

Combined standard uncertainty $u_c(y)$ is

$$U_c(y) = \pm \sqrt{\left[\frac{1.0}{2}\right]^2 + \left[\frac{0.2}{2}\right]^2 + \left[\frac{1.0^2 + 0.1^2 + 2.0^2 + 0.1^2 + 0.2^2 + 1.5^2}{3}\right]}$$

$$U_c(y) = \pm 1.6 \text{ dB}$$

It is probable that $u_c(y) / s(q_k) > 3$, where $s(q_k)$ is estimated standard deviation from a sample of n readings unless the repeatability of the EUT is particularly poor, and a coverage factor of $k = 2$ will ensure that the level of confidence will be approximately 95%, therefore:

$$s(q_k) = \sqrt{\frac{1}{(n-1)} \sum_{k=1}^n (q_k - \bar{q})^2}$$

$$U = 2 U_c(y) = 2 \times \pm 1.6 \text{ dB} = \pm 3.2 \text{ dB}$$

Notes:

- 1.1 Uncertainties for the antenna and cable were estimated, based on a normal probability distribution with $k = 2$.
- 1.2 The receiver uncertainty was obtained from the manufacturer's specification for which a rectangular distribution was assumed.
- 1.3 The antenna factor uncertainty does not take account of antenna directivity.
- 1.4 The antenna factor varies with height and since the height was not always the same in use as when the antenna was calibrated an additional uncertainty is added.
- 1.5 The uncertainty in the measurement distance is relatively small but has some effect on the received signal strength. The increase in measurement distance as the antenna height is increased is an inevitable consequence of the test method and is therefore not considered a contribution to uncertainty.
- 1.6 Site imperfections are difficult to quantify but may include the following contributions:
 - Unwanted reflections from adjacent objects.
 - Ground plane imperfections: reflection coefficient, flatness, and edge effects.
 - Losses or reflections from "transparent" cabins for the EUT or site coverings.
 - Earth currents in antenna cable (mainly effect biconical antennas).

The specified limits for the difference between measured site attenuation and the theoretical value (± 4 dB) were not included in total since the measurement of site attenuation includes uncertainty contributions already allowed for in this budget, such as antenna factor.



NVLAP Lab Code 200087-0

Conducted Measurements Uncertainty Calculation

Measurement of conducted emissions over the frequency range 9 kHz to 30 MHz includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Receiver specification	rectangular	±1.5
LISN coupling specification	rectangular	±1.5
Cable and input attenuator calibration	normal (k=2)	±0.5

Combined standard uncertainty $u_c(y)$ is

$$U_c(y) = \pm \sqrt{\left[\frac{0.5}{2}\right]^2 + \frac{1.5^2 + 1.5^2}{3}}$$

$$U_c(y) = \pm 1.2 \text{ dB}$$

As with radiated field strength uncertainty, it is probable that $u_c(y) / s(qk) > 3$ and a coverage factor of $k = 2$ will suffice, therefore:

$$U = 2 U_c(y) = 2 \times \pm 1.2 \text{ dB} = \pm 2.4 \text{ dB}$$



NVLAP Lab Code 200087-0

Annex B Test Equipment List For Rogers Labs, Inc.

The test equipment used is maintained in calibration and good operating condition. Use of this calibrated equipment ensures measurements are traceable to national standards.

List of Test Equipment	Calibration Date
Oscilloscope Scope: Tektronix 2230	2/08
Wattmeter: Bird 43 with Load Bird 8085	2/08
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140	2/08
H/V Power Supply: Fluke Model: 408B (SN: 573)	2/08
R.F. Generator: HP 606A	2/08
R.F. Generator: HP 8614A	2/08
R.F. Generator: HP 8640B	2/08
Spectrum Analyzer: HP 8562A,	5/08
Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W	
HP Adapters: 11518, 11519, 11520	
Spectrum Analyzer: HP 8591EM	5/08
Frequency Counter: Leader LDC825	2/08
Antenna: EMCO Biconilog Model: 3143	5/08
Antenna: EMCO Log Periodic Model: 3147	10/07
Antenna: Antenna Research Biconical Model: BCD 235	10/07
Antenna: EMCO Dipole Set 3121C	2/08
Antenna: C.D. B-101	2/08
Antenna: Solar 9229-1 & 9230-1	2/08
Antenna: EMCO 6509	2/08
Audio Oscillator: H.P. 201CD	2/08
R.F. Power Amp 65W Model: 470-A-1010	2/08
R.F. Power Amp 50W M185- 10-501	2/08
R.F. PreAmp CPPA-102	2/08
LISN 50 μ Hy/50 ohm/0.1 μ f	10/07
LISN Compliance Eng. 240/20	2/08
LISN Fischer Custom Communications FCC-LISN-50-16-2-08	2/08
Peavey Power Amp Model: IPS 801	2/08
Power Amp A.R. Model: 10W 1010M7	2/08
Power Amp EIN Model: A301	2/08
ELGAR Model: 1751	2/08
ELGAR Model: TG 704A-3D	2/08
ESD Test Set 2010i	2/08
Fast Transient Burst Generator Model: EFT/B-101	2/08
Current Probe: Singer CP-105	2/08
Current Probe: Solar 9108-1N	2/08
Field Intensity Meter: EFM-018	2/08
KEYTEK Ecat Surge Generator	2/08



NVLAP Lab Code 200087-0

Annex C Qualifications

SCOT D. ROGERS, ENGINEER

ROGERS LABS, INC.

Mr. Rogers has approximately 17 years experience in the field of electronics. Six years working in the automated controls industry and 6 years working with the design, development and testing of radio communications and electronic equipment.

POSITIONS HELD:

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

EDUCATIONAL BACKGROUND:

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Scot D. Rogers

Annex D FCC Site Registration Letter**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046**

May 16, 2006

Registration Number: 90910

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053


Attention: Scot Rogers

Re: Measurement facility located at Louisburg
3 & 10 meter site
Date of Renewal: May 16, 2006

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parish
Information Technician