

Standalone SAR test exclusion considerations

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BT	BDR(1Mbps)	2 480.00	5.0	-0.08	5.50	3.548 1	1.12	3.00
BT	EDR(2, 3Mbps)	2 480.00	5.0	-0.08	2.00	1.584 9	0.50	3.00
BLE	GFSK(1Mbps)	2 480.00	5.0	-0.08	5.00	3.162 3	1.00	3.00

Note1. Please refer to the operation description for tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1g SAR and ≤ 7.5 for 10g extremity SAR

Sample Calculation

$$= [(3.5481\text{mW} / 5\text{mm})] \times [\sqrt{2.48\text{GHz}}] = 1.12$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required