

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2010-0324

2. Customer

- Name (FCC) : Point Mobile Co., LTD. / Name (IC) : POINTMOBILE CO.,LTD
- Address (FCC) : B-9F, Kabul Great Valley 32 Digital-ro 9-gil, Geumcheon-gu Seoul South Korea 153-709
Address (IC) : B-9F Kabul Great Valley, 32, Digital-ro 9-gil, Geumcheon-gu Seoul Korea (Republic Of)

3. Use of Report : FCC & IC Certification

4. Product Name / Model Name : Mobile POS terminal / PM500

FCC ID : V2X-PM500

IC : 10664A-PM500

5. FCC Regulation(s) : FCC Part 15.407

IC Standards(s) : RSS-247 Issue 2, RSS-GEN Issue 5

Test Method Used : KDB789033 D02v02r01, ANSI C 63.10-2013



6. Date of Test : 2020.09.07 ~ 2020.10.07

7. Location of Test : Permanent Testing Lab On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Affirmation	Tested by Name : JungWoo Kim 	Reviewed by Name : JaeJin Lee  (Signature)
-------------	---	--

2020 . 10 . 22 .

DT&C Co., Ltd.

Unconnected with KS Q ISO / IEC 17025 and KOLAS accreditation

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2010-0324	Oct. 22, 2020	Initial issue	JungWoo Kim	JaeJin Lee

CONTENTS

1. EUT DESCRIPTION.....	4
2. Information about test items	5
2.1 Transmitting configuration of EUT	5
2.2 Tested Channel Information.....	5
2.3 Testing Environment.....	6
2.4 EMI Suppression Device(s)/Modifications	6
2.5 Measurement Uncertainty	6
3. SUMMARY OF TESTS.....	7
4. TEST METHODOLOGY.....	8
4.1 EUT configuration.....	8
4.2 EUT exercise.....	8
4.3 General test procedures.....	8
4.4 Description of test modes.....	8
5. INSTRUMENT CALIBRATION.....	9
6. FACILITIES AND ACCREDITATIONS	9
6.1 Facilities	9
6.2 Equipment	9
7. ANTENNA REQUIREMENTS.....	9
8. TEST RESULT	10
8.1 Emission Bandwidth (26 dB Bandwidth) & Occupied BW (99 %).....	10
8.2 Minimum Emission Bandwidth (6 dB Bandwidth) & Occupied BW (99 %)	26
8.3 Maximum Conducted Output Power.....	37
8.4 Maximum Power Spectral Density.....	40
8.5 Radiated Spurious Emission Measurements.....	64
8.6 AC Conducted Emissions.....	71
9. LIST OF TEST EQUIPMENT	80
APPENDIX I.....	81
APPENDIX II.....	82
APPENDIX III.....	85

1. EUT DESCRIPTION

Equipment Class	Unlicensed National Information Infrastructure (UNII)
Product Name	Mobile POS terminal
Model Name(FCC, IC)	PM500
Add Model Name	NA
Software Version	50.00
Test Device Serial Number	Conducted : 2021310012 / Radiated: 2021210051
Power Supply	DC 7.6 V
Modulation type	OFDM
Antenna Specification	Antenna type: PCB Antenna Antenna gain U-NII 1: -0.09 dBi U-NII 2A: 1.19 dBi U-NII 2C: 0.98 dBi U-NII 3: -0.25 dBi

5GHz Band	Mode	Tx frequency (MHz)	Max power (dBm)	E.I.R.P(dBm)
U-NII 1	802.11a	5 180 ~ 5 240	12.19	12.10
	802.11n(HT20)	5 180 ~ 5 240	13.63	13.54
	802.11n(HT40)	5 190 ~ 5 230	12.83	12.74
U-NII 2A	802.11a	5 260 ~ 5 320	12.45	13.64
	802.11n(HT20)	5 260 ~ 5 320	13.80	14.99
	802.11n(HT40)	5 270 ~ 5 310	13.02	14.21
U-NII 2C	802.11a	5 500 ~ 5 700	12.89	13.87
	802.11n(HT20)	5 500 ~ 5 700	12.38	13.36
	802.11n(HT40)	5 510 ~ 5 670	12.28	13.26
U-NII 3	802.11a	5 745 ~ 5 825	11.58	11.33
	802.11n(HT20)	5 745 ~ 5 825	11.56	11.31
	802.11n(HT40)	5 755 ~ 5 795	10.45	10.20

2. Information about test items

2.1 Transmitting configuration of EUT

Mode	Data rate
802.11a	6 Mbps ~ 54 Mbps
802.11n(HT20)	MCS 0 ~ 7
802.11n(HT40)	MCS 0 ~ 7

2.2 Tested Channel Information

5GHz Band	802.11a			802.11n(HT20)			802.11n(HT40)		
	Channel	Frequency [MHz]	Power Setting	Channel	Frequency [MHz]	Power Setting	Channel	Frequency [MHz]	Power Setting
U-NII 1	36	5 180	12	36	5 180	13	38	5 190	12
	40	5 200	12	40	5 200	13	-	-	-
	48	5 240	12	48	5 240	13.5	46	5 230	13
U-NII 2A	52	5 260	12	52	5 260	13.5	54	5 270	13
	60	5 300	12	60	5 300	13.5	-	-	-
	64	5 320	12	64	5 320	13.5	62	5 310	9
U-NII 2C	100	5 500	15	100	5 500	14.5	102	5 510	11.5
	116	5 580	16	116	5 580	15.5	110	5 550	13.5
	140	5 700	16	140	5 700	15	134	5 670	16
U-NII 3	149	5 745	12	149	5 745	12	151	5 755	11
	157	5 785	12	157	5 785	12	-	-	-
	165	5 825	12	165	5 825	11.5	159	5 795	11

Operation test setup for EUT

- Test Software Version: QRCT / v 3.0-00277

2.3 Testing Environment

Temperature	: 21 °C ~ 25 °C
Relative humidity content	: 35 % ~ 42 %
Details of power supply	: DC 7.6 V

2.4 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing
 → None

2.5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014 and ANSI C 63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Antenna-port conducted emission	0.9 dB (The confidence level is about 95 %, $k = 2$)
AC power-line conducted emission	3.6 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz ~ 18 GHz)	5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

3. SUMMARY OF TESTS

FCC Part Section(s)	RSS Section(s)	Parameter	Limit	Test Condition	Status Note 1
15.407(a)	RSS-247[6.2]	Emission Bandwidth (26 dB Bandwidth)	N/A	Conducted	C
15.407(e)	RSS-247[6.2]	Minimum Emission Bandwidth (6 dB Bandwidth)	> 500 kHz in 5725 ~ 5850 MHz		C
-	RSS GEN[6.7]	Occupied Bandwidth (99 %)	N/A		C
15.407(a)	RSS-247[6.2]	Maximum Conducted Output Power	FCC Part 15.407(a) (Refer to the section 8.3)		C
15.407(a)	RSS-247[6.2]	Peak Power Spectral Density	FCC Part 15.407(a) (Refer to the section 8.4)		C
15.407(h)	RSS-247[6.3]	Dynamic Frequency Selection	FCC 15.407(h) (Refer to the DFS test report)		C Note 3
15.205 15.209 15.407(b)	RSS-247[6.2] RSS-GEN[8.9] RSS-GEN[8.10]	Undesirable Emissions	FCC Part 15.209, 15.407(b) (Refer to the section 8.5)	Radiated	C Note 4
15.207	RSS-GEN[8.8]	AC Conducted Emissions	FCC 15.207 (Refer to the section 8.6)	AC Line Conducted	C
15.203	-	Antenna Requirements	FCC 15.203 (Refer to the section 4)	-	C

Note 1: **C** = Comply **NC** = Not Comply **NT** = Not Tested **NA** = Not Applicable

Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.

Note 3: Refer to the DFS test report.

Note 4: These test items were performed in each axis and the worst case data was reported.

4. TEST METHODOLOGY

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB 7899033 D02v02r01 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB789033 D02v02r01. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

4.1 EUT configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E.

4.3 General test procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB789033 D02v02r01. So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB789033 D02v02r01. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on KDB789033 D02v02r01.

The EUT is placed on a non-conductive table, which is 0.8 m above ground plane. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 1 m or 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axis.

4.4 Description of test modes

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode with maximum fixed duty cycle. The worst case data rate was determined as below test mode according to the power measurements.

Test mode	Mode	Worst case data rate
TM 1	802.11a	6 Mbps
TM 2	802.11n(HT20)	MCS 0
TM 3	802.11n(HT40)	MCS 0

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 Facilities

DT&C Co., Ltd.	
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.	
<ul style="list-style-type: none"> - FCC & ISED MRA Designation No. : KR0034 - ISED#: 5740A 	
www.dtnc.net	
Telephone	: + 82-31-321-2664
FAX	: + 82-31-321-1664

6.2 Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, loop, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna is permanently attached on the device.

Therefore this E.U.T Complies with the requirement of §15.203

8. TEST RESULT

8.1 Emission Bandwidth (26 dB Bandwidth) & Occupied BW (99 %)

■ Test Requirements

- Emission Bandwidth (26 dB Bandwidth)

The bandwidth at 26 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The 26 dB bandwidth is used to determine the conducted output power limit.

- Occupied BW (99 %)

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

- Emission Bandwidth (26 dB Bandwidth)

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = approximately **1 %** of the EBW.
2. Set the video bandwidth (**VBW**) **> RBW**.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

- Occupied BW (99 %) : RSS-Gen[6.7]

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.


■ Test Results: Comply

Mode	Band	Channel	Frequency [MHz]	Test Result 26 dB BW [MHz]	Test Result 99 % BW [MHz]
TM 1	U-NII 1	36	5 180	21.34	16.73
		40	5 200	21.53	16.75
		48	5 240	21.40	16.78
	U-NII 2A	52	5 260	21.75	16.74
		60	5 300	22.42	16.78
		64	5 320	21.69	16.74
	U-NII 2C	100	5 500	23.79	16.90
		116	5 580	26.40	16.96
		140	5 700	21.43	16.86
TM 2	U-NII 1	36	5 180	22.24	17.86
		40	5 200	22.37	17.92
		48	5 240	23.68	17.94
	U-NII 2A	52	5 260	25.37	17.96
		60	5 300	25.60	17.94
		64	5 320	24.77	17.90
	U-NII 2C	100	5 500	22.87	17.91
		116	5 580	24.05	17.93
		140	5 700	23.69	17.91
TM 3	U-NII 1	38	5 190	42.59	36.26
		46	5 230	47.20	36.18
	U-NII 2A	54	5 270	49.27	36.20
		62	5 310	42.41	36.13
	U-NII 2C	102	5 510	42.57	36.10
		110	5 550	44.83	36.17
		134	5 670	54.73	36.28

Result Plots


26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.36




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.40




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.48




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.52




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.60




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.64




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.100




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.116




26 dB Bandwidth & Occupied BW

Test Mode: TM 1 & Ch.140




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.36




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.40




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.48




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.52




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.60




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.64




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.100




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.116




26 dB Bandwidth & Occupied BW

Test Mode: TM 2 & Ch.140




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.38




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.46




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.54




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.62




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.102




26 dB Bandwidth & Occupied BW

Test Mode: TM 3 & Ch.110



26 dB Bandwidth & Occupied BW

Test Mode: 802.11n HT40 & Ch.134



8.2 Minimum Emission Bandwidth (6 dB Bandwidth) & Occupied BW (99 %)

■ Test Requirements

- Emission Bandwidth (6 dB Bandwidth)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

- Occupied BW (99 %)

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

- Emission Bandwidth (6 dB Bandwidth)

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB789033 D02v02r01**.

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth $\geq 3 \times \text{RBW}$.
3. Detector = **Peak**.
4. Trace mode = **max hold**.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

- Occupied BW (99 %) : RSS-Gen[6.7]

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately $3 \times \text{RBW}$.


■ Test Results: **Comply**

Mode	Band	Channel	Frequency [MHz]	Test Result 6 dB BW [MHz]	Test Result 99 % BW [MHz]
TM 1	U-NII 3	149	5 745	16.40	16.76
		157	5 785	16.39	16.77
		165	5 825	16.39	16.70
TM 2	U-NII 3	149	5 745	17.58	17.89
		157	5 785	17.60	17.85
		165	5 825	17.59	17.86
TM 3	U-NII 3	151	5 755	35.37	36.14
		159	5 795	35.23	36.11

Result Plots


6 dB Bandwidth

Test Mode: TM 1 & Ch.149




6 dB Bandwidth

Test Mode: TM 1 & Ch.157




6 dB Bandwidth

Test Mode: TM 1 & Ch.165




6 dB Bandwidth

Test Mode: TM 2 & Ch.149




6 dB Bandwidth

Test Mode: TM 2 & Ch.157




6 dB Bandwidth

Test Mode: TM 2 & Ch.165




6 dB Bandwidth

Test Mode: TM 3 & Ch.151



6 dB Bandwidth


Test Mode: TM 3 & Ch.159



RESULT PLOTS


Occupied Bandwidth

Test Mode: TM 1 & Ch.149




Occupied Bandwidth

Test Mode: TM 1 & Ch.157




Occupied Bandwidth

Test Mode: TM 1 & Ch.165




Occupied Bandwidth

Test Mode: TM 2 & Ch.149




Occupied Bandwidth

Test Mode: TM 2 & Ch.157




Occupied Bandwidth

Test Mode: TM 2 & Ch.165




Occupied Bandwidth

Test Mode: TM 3 & Ch.151



Occupied Bandwidth

Test Mode: TM 3 & Ch.159



8.3 Maximum Conducted Output Power

■ Test Requirements

Part. 15.407(a)

(1) For the band 5.15 GHz - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15 GHz - 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15 GHz - 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25 GHz - 5.35 GHz and 5.47 GHz - 5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725 GHz - 5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247[6.2]
(1) For band 5 150 MHz – 5 250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

(2) For band 5 250 MHz – 5 350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.


(3) For band 5 470 MHz – 5 600 MHz and 5 650 MHz – 5 725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5 725 MHz – 5 850 MHz

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Configuration


Method PM-G

■ Test Procedure
Method PM-G of KDB789033 D02v02r01

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Test Results: Comply
- Output Power

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
TM 1	36	5 180	11.85	-0.09	11.76
	40	5 200	12.02	-0.09	11.93
	48	5 240	12.19	-0.09	12.10
	52	5 260	12.28	1.19	13.47
	60	5 300	12.45	1.19	13.64
	64	5 320	12.03	1.19	13.22
	100	5 500	11.82	0.98	12.80
	116	5 580	12.89	0.98	13.87
	140	5 700	12.56	0.98	13.54
	149	5 745	11.36	-0.25	11.11
	157	5 785	11.58	-0.25	11.33
	165	5 825	11.22	-0.25	10.97

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
TM 2	36	5 180	12.83	-0.09	12.74
	40	5 200	12.85	-0.09	12.76
	48	5 240	13.63	-0.09	13.54
	52	5 260	13.75	1.19	14.94
	60	5 300	13.80	1.19	14.99
	64	5 320	13.49	1.19	14.68
	100	5 500	11.87	0.98	12.85
	116	5 580	12.38	0.98	13.36
	140	5 700	11.45	0.98	12.43
	149	5 745	11.56	-0.25	11.31
	157	5 785	11.50	-0.25	11.25
	165	5 825	10.70	-0.25	10.45

Mode	CH	Freq.[MHz]	Conducted Output Power[dBm]	Antenna Gain[dBi]	e.i.r.p ^{Note1} [dBm]
TM 3	38	5 190	12.15	-0.09	12.06
	46	5 230	12.83	-0.09	12.74
	54	5 270	13.02	1.19	14.21
	62	5 310	9.60	1.19	10.79
	102	5 510	8.53	0.98	9.51
	110	5 550	10.29	0.98	11.27
	134	5 670	12.28	0.98	13.26
	151	5 755	10.33	-0.25	10.08
	159	5 795	10.45	-0.25	10.20

Note 1: e.i.r.p = Conducted Output Power + Antenna Gain

8.4 Maximum Power Spectral Density

■ Test requirements

Part. 15.407(a)

(1) For the band 5.15 GHz - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 GHz - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 GHz - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 GHz - 5.35 GHz and 5.47 GHz - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 GHz - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1,note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

RSS-247[6.2]

(1) For band 5 150 MHz – 5 250 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. **The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.**

(2) For band 5 250 MHz – 5 350 MHz

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

Devices, other than devices installed in vehicles, shall comply with the following:

a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less.

The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;

b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(3) For band 5 470 MHz – 5 600 MHz and 5 650 MHz – 5 725 MHz

The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. **The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.**

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

(4) For band 5 725 MHz - 5850 MHz

The maximum conducted output power shall not exceed 1 W. **The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.**

■ Test Configuration

Refer to the APPENDIX I.

■ Test procedure

Maximum Power Spectral Density is measured using Measurement Procedure of **KDB789033 D02v02r01**

- 1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA - 1, SA - 2, SA - 3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- 2) Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- 3) Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) If Method SA - 2 or SA - 2 Alternative was used, add $10 \log(1 / x)$, where x is the duty cycle, to the peak of the spectrum.**
 - b) If Method SA - 3 Alternative was used and the linear mode was used in step II.E.2.g (viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- 4) The result is the Maximum PSD over 1 MHz reference bandwidth.
- 5) For devices operating in the bands 5.15 GHz - 5.25 GHz, 5.25 GHz - 5.35 GHz, and 5.47 GHz - 5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in §15.407(a)(5). For devices operating in the band 5.725 GHz - 5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 - a) Set $RBW \geq 1 / T$, where T is defined in section II.B.1.a). (Refer to Appendix II)
 - b) Set $VBW \geq 3 RBW$.
 - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz} / RBW)$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log(1 \text{ MHz} / RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW = 100 kHz is available on nearly all spectrum analyzers.

■ Test results: **Comply**

Mode	Channel	Frequency [MHz]	Reading [dBm]	T.F ^{Note 1} [dB]	Power Spectral Density[dBm]	Antenna Gain [dBi]	e.i.r.p Spectral Density [dBm]
TM 1	36	5 180	-0.22	0.59	0.37	-0.09	0.28
	40	5 200	0.36		0.95	-0.09	0.86
	48	5 240	0.62		1.21	-0.09	1.12
	52	5 260	1.26		1.85	1.19	3.04
	60	5 300	1.29		1.88	1.19	3.07
	64	5 320	1.08		1.67	1.19	2.86
	100	5 500	1.77		2.36	0.98	3.34
	116	5 580	2.40		2.99	0.98	3.97
	140	5 700	1.19		1.78	0.98	2.76
	149	5 745	-9.01	7.58	-1.43	-0.25	-1.68
	157	5 785	-9.33		-1.75	-0.25	-2.00
	165	5 825	-9.34		-1.76	-0.25	-2.01
TM 2	36	5 180	0.90	0.63	1.53	-0.09	1.44
	40	5 200	1.38		2.01	-0.09	1.92
	48	5 240	1.87		2.50	-0.09	2.41
	52	5 260	2.19		2.82	1.19	4.01
	60	5 300	2.21		2.84	1.19	4.03
	64	5 320	1.98		2.61	1.19	3.80
	100	5 500	0.53		1.16	0.98	2.14
	116	5 580	1.34		1.97	0.98	2.95
	140	5 700	0.10		0.73	0.98	1.71
	149	5 745	-9.30	7.62	-1.68	-0.25	-1.93
	157	5 785	-9.93		-2.31	-0.25	-2.56
	165	5 825	-9.85		-2.23	-0.25	-2.48
TM 3	38	5 190	-3.38	1.19	-2.19	-0.09	-2.28
	46	5 230	-1.98		-0.79	-0.09	-0.88
	54	5 270	-1.82		-0.63	1.19	0.56
	62	5 310	-4.97		-3.78	1.19	-2.59
	102	5 510	-6.06		-4.87	0.98	-3.89
	110	5 550	-3.75		-2.56	0.98	-1.58
	134	5 670	-1.79		-0.60	0.98	0.38
	151	5 755	-13.01	8.18	-4.83	-0.25	-5.08
	159	5 795	-13.90		-5.72	-0.25	-5.97

Note 1: "U-NII 1, 2A, 2C [T.F] = DCCF"

"U-NII 3 [T.F] = 10*LOG(500 kHz/100 kHz) + DCCF"

For DCCF(Duty Cycle Correction Factor) please refer to appendix II.

Note 2: Test Result = Measurement Data + T.F


Note 3: e.i.r.p Spectral Density= Power spectral density + Antenna Gain

RESULT PLOTS

- Power spectral density


Maximum Power Spectral Density

Test Mode: TM 1 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.40




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.48




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.52




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.60




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.64




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.100




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.116




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.140




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.149




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.157




Maximum Power Spectral Density

Test Mode: TM 1 & Ch.165




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.36




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.40




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.48




Maximum Power Spectral Density

Test Mode: TM 2 & Ch.52



Maximum Power Spectral Density

Test Mode: TM 2 & Ch.60



Maximum Power Spectral Density

Test Mode: TM 2 & Ch.64

