







ISO/IEC17025 Accredited Lab.

Report No: FCC 0904193 File reference No: 2009-04-28

Applicant: WIN ACCORD LTD.

Product: Digital Photo Frame

Brand Name: N/A

Model No: DF10405-14-XXX (X=A-Z, 0-9, a-z)

Test Standards: FCC Part 15 Subpart B: 2008

Test result:

It is herewith confirmed and found to comply with the requirements

set up by ANSI C63.4&FCC Part 15 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: April 28, 2009

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. Chegongmiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0904193 Page 2 of 55

Date: 2009-04-28



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 55

Report No: 0904193 Date: 2009-04-28



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Test Uncertainty	4
1.5	Submitted Sample	4
1.6	Test Duration	4
2.0	List of Measurement Equipment.	5
2.1	Conducted Emission Test.	5
2.2	Radiated electromagnetic disturbance test.	5
2.3	Auxiliary Equipment	5
3.0	Technical Details	6
3.1	Investigations Requested	6
3.2	Test Standards	6
4.0	Power line Conducted Emission Test.	7
5.0	Radiated Disturbance Test	25
6.0	FCC ID Label	43
7.0	Photo of testing	44

Date: 2009-04-28



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

1.2 Applicant Details

Applicant: WIN ACCORD LTD.

Address: 12F, NO.225, SEC 5, 105 SONG SHAN DIST., NAN JING EAST ROAD, TAIPEI,

TAIWAN

Telephone: 02-2749 3837 Fax: 02-2749-3918

1.3 Description of EUT

Product: Digital Photo Frame
Manufacturer: WIN ACCORD LTD.

Address: 12F, NO.225, SEC 5, 105 SONG SHAN DIST., NAN JING EAST ROAD, TAIPEI,

TAIWAN

Brand Name: N/A

Model Number: DF10405-14-XXX (X=A-Z, 0-9, a-z)

Additional Model Number: MITPF10

The adapter Model No.: XKD-C1500IC12.0-18C-US (Made by MOSO)
Rating: Input: 100-240V, 0.7A Max, 50/60Hz Output: 12V, 1.5A
The adapter Model No.: ADS-18C-12N 12018GPCU (Made by HONOR)
Rating: Input: 100-240V, 0.6A Max, 50/60Hz Output: 12V, 1.5A

Remark: Just model names and appearance color are different.

Rating: Input: DC 12V, Current 1.5A

1.4 Submitted Sample(s): 1 Sample

1.5 Test Duration: 2009-04-24 to 2009-04-28

1.6 Test Uncertainty


Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 5 of 55

Report No: 0904193 Date: 2009-04-28





Print Name: Terry Tang

2.0 List of Measurement Equipment

2.1 Conducted Emission Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESCS30	830245/009	RS	2009.2.23	1Year
Coaxial Switch	MP59B	M70585	ANRITSU	N/A	N/A
LISN	NTFM8132	8132137	SCHWARZBECK	2009.2.24	1Year
LISN	NTFM8134	8134109	SCHWARZBECK	2009.2.24	1Year
LISN	NTFM8136	8136102	SCHWARZBECK	2009.2.24	1Year

2.2 Radiated electromagnetic disturbance test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESCS30	830245/009	RS	2009.2.23	1Year
Coaxial Switch	MP59B	M70585	ANRITSU	N/A	N/A
Spectrum Analyzer(with					
Tracking Generator)	MS2661C	MT72089	ANRITSU	2009.2.23	1Year
Amplifier	MH648A	M20494	ANRITSU	2009.2.24	1Year
Bilog Antenna	CBL6101C	2576	CHASE	2009.2.23	1Year

2.3 Auxiliary Equipment

2.5 Tuxiii	ary Equipment				
Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
				Data cable of	
				2m length	
				Ziii lengui	
Keyboard	KB-0225	1211815	IBM	unshielded	FCC DOC
				Data cable of	
				2m length	
				unshielded	
				and 1.8m length	
Printer	LaserJet 1015	CNFG029476	HP	AC Mains cable	DOC

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



i	İ.			į i	ĺ
				Data cable of	
				2m length	
				unshielded	
				and 1.8m length	
Printer	LaserJet 1022	CNBG591GM7	HP	AC Mains cable	DOC
				Data cable of	
				1.5m length	
				unshielded and	
				1.8m length AC	
Monitor	FP51G	ET47604175CLO	BENQ	Mains cable	FCC DOC
				Data cable of	
				1.5m length	
				unshielded and	
				1.8m length AC	
Monitor	6331-4CN	23-DNWX3	IBM	Mains cable	FCC DOC

			1.8m length	
PC	8434	 IBM	AC Mains cable	FCC DOC
			Data cable of	
Mouse	M-F105	 S.SElectron	1.5m length	FCC DOC

3.0 Technical Details

3.1 Investigations Requested

Perform Electromagnetic Interference [EMI] tests for FCC Requirement.


3.2 Test Standards

FCC Part 15 Subpart B: 2008



4.0 Conducted Power line Test

4.1 Schematics of the test




EUT: Equipment Under Test

4.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003. Cables and peripherals were moved to find the maximum emission levels for each frequency.

Block diagram of Test setup



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 8 of 55

Report No: 0904193 Date: 2009-04-28



4.3 Power line conducted Emission Limit

Emagyamay/MHg)	Class A Li	mits dB(μV)	Class B Limits dB(µV)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
0.15 ~ 0.50	79.00	66.00	66.00~56.00*	56.00~46.00*	
$0.50 \sim 5.00$	73.00	60.00	56.00	46.00	
5.00 ~ 30.00	73.00	60.00	60.00	50.00	

Notes:

- 1. *decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

4.4 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.




EUT set Condition: Memory

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eroguanav	Reading(dB μ V)				Limit	
1 1	Frequency Live		Neutral		$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.179	41.93	24.13			64.50	54.50




B: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Memory


Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Engavener		Reading	Limi	t		
Frequency (MHz)	Live		Neutral		(dB µ V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.185			44.64	35.04	64.25	54.25




EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav		Reading	Limi	t		
Frequency (MHz)	Live		Neutr	al	(dB μ	V)
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.183	48.94	20.54	-		64.34	54.34
10.009	40.60	33.10			60.00	50.00




D: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play SD


Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanay		Reading	Limi	t		
Frequency (MHz)	Live	;	Neutr	al	$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.180			44.13	30.93	64.45	54.45
10.054			32.90	25.40	60.00	50.00




EUT set Condition: Play USB

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eroguanav	Reading(dB μ V)				Limit	
Frequency (MHz)	Live		Neutral		(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.181	43.03	26.13			64.42	54.42




F: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play USB

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Reading(dB \(\mu \)					Limit		
Frequency Live (MHz)		;	Neutr	al	(dB µ	(dB \(\mu \) V) uasi-peak Average	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.182			44.13	35.53	64.37	54.37	
9.028	-1		34.61	26.51	60.00	50.00	


G: Conducted Emission on Live Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Connected to PC

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eroguanav		Reading	Limit			
Frequency (MHz)	ave		Neutral		(dB µ V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.184	43.24	29.94	-		64.30	54.30
4.892	35.56	28.06			56.00	46.00




H: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Connected to PC


Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav	Reading(dB \(\mu \)					
Frequency (MHz)	live		Neutr	al	$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.185			43.74	35.24	64.23	54.23
4.878			25.35	19.75	56.00	46.00




EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanay			Limit				
Frequency (MHz)	Live		Neutr	Neutral		(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.194	43.85	34.25			63.85	53.85	
11.817	35.36	26.26			60.00	50.00	




J: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Memory


Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanay	Reading(dB \(\mu \)					Limit	
Frequency (MHz)	Live		Neutral		(dB µ V)		
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.196			44.55	34.75	63.77	53.77	
11.848			40.96	24.16	60.00	50.00	




EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Engguenav		Reading	Limit			
Frequency (MHz)	Live		Neutr	al	(dB µ V)	
(WITZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.195	43.45	34.25			63.79	53.79
0.821	34.61	20.11			56.00	46.00
12.228	40.46	31.46			60.00	50.00




L: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play SD


Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Reading(dB μ V)					Limit	
Frequency Live		;	Neutr	al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.194			43.15	34.15	63.85	53.85
12.063			41.86	26.16	60.00	50.00




EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Fraguenay		Reading		Limit		
Frequency (MHz)	Live		Neutr	al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.192	42.14	32.14			63.94	53.94
11.998	40.06	30.86			60.00	50.00




N: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play USB


Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav	Limit					
(MHz)	Frequency Live		Neutr	al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.194			43.65	34.65	63.83	53.83
12.064			40.26	25.66	60.00	50.00




EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguana	• ,		Reading	Limit			
Frequenc (MHz)		Live		Neutr	al	$(dB \mu V)$	
(IVITIZ)		Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.189		49.14	29.64			64.08	54.08
5.846		40.64	26.94			60.00	50.00




P: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav		Reading	(dB μ V)		Limi	t
(MHz)	Frequency Live		Neutr	al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.191			39.04	29.74	63.98	53.98
5.340			42.86	31.06	60.00	50.00


Page 25 of 55

Report No: 0904193 Date: 2009-04-28



5.0 Radiated Disturbance Test


5.1 Schematics of the test




5.2 Test Method and test Procedure:

The EUT was tested according to ANSI C63.4 –2003, The frequency spectrum from 30MHz to 1GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak 0values with a resolution bandwidth of 120KHz. All readings are above 1GHz, peak values with a resolution bandwidth of 1MHz. Measurements were made at 3 meters.

Block diagram of Test setup







5.3 Radiated Emission Limit

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.00
88-216	3	43.50
216-960	3	46.00
Above 960	3	54.00

Note: The lower limit shall apply at the transition frequencies

5.4 Test result

The frequency spectrum from 30MHz to 1GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120KHz. All readings are above 1GHz, peak values with a resolution bandwidth of 1MHz. Measurements were made at 3 meters.

Page 27 of 55

Report No: 0904193 Date: 2009-04-28



Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Memory

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B **Results: PASS**


Please refer to following diagram for individual

Picture of the test

RBW 120 kHz Marker 1 [T1] МТ 50 µs 32.42 dBµV/m

359.480000000 MHz





Comment: H

27.APR.2009 08:34:45 Date:

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m (dBµV/m)
320.360	38.39	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



B: Radiated Disturbance In Vertical (30MHz --- 1000MHz)

EUT set Condition: Memory

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B
Results: PASS


Please refer to following diagram for individual

Picture of the test

%

RBW 120 kHz Marker 1 [T1]

MT 50 μs 31.76 $dB\mu V/m$



Comment: H

Date: 27.APR.2009 08:32:04

	Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
ſ	78.440	31.48	V	40.00
ſ	359.680	35.82	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



C: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

Date: 27.APR.2009 09:04:49

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	$Limit@3m\ (dB\mu V/m)$
320.080	38.16	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



D: Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H


30 MHz

Date: 27.APR.2009 09:06:36

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
78.720	31.43	V	40.00
359.480	35.87	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.





Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Play USB


Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B **Results: PASS**

Please refer to following diagram for individual

Picture of the test

RBW 120 kHz Marker 1 [T1] мт 50 µs



Comment: H

Date: 27.APR.2009 09:13:17

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
319.960	38.35	Н	46.00
960.120	42.08	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Radiated Disturbance In Vertical (30MHz --- 1000MHz)


EUT set Condition: Play USB


Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B **Results: PASS**

Please refer to following diagram for individual

Picture of the test





Comment: H

27.APR.2009 09:10:49 Date:

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
79.480	31.76	V	40.00
359.640	35.84	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



G Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Connect to PC

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test





Comment: H

30 MHz

Date: 27.APR.2009 09:17:19

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
168.000	37.96	Н	43.50
320.240	39.30	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



H Radiated Disturbance In Vertical (30MHz---1000MHz)

EUT set Condition: Connect to PC

Adaptor used for test Model No.: ADS-18C-12N 12018GPCU

Level: Class B
Results: PASS


Please refer to following diagram for individual

Picture of the test



RBW 120 kHz Marker 1 [T1]

MT 50 μs 34.32 dBμV/m



Comment: H

30 MHz

Date: 27.APR.2009 09:23:49

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
78.480	31.28	V	40.00
231.080	34.32	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



I Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

30 MHz

Date: 27.APR.2009 09:38:40

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
168.000	35.81	Н	43.50
239.840	40.91	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



J Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

30 MHz

Date: 27.APR.2009 09:33:08

I	Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
	240.040	33.61	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

1 GHz

Report No: 0904193 Date: 2009-04-28



K Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



RBW 120 kHz Marker 1 [T1] MT 50 μs 39.16

MT 50 µs 39.16 dBµV/m PREAMP OFF 320.560000000 MHz

Comment: H

30 MHz

Date: 27.APR.2009 10:04:28

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m (dBµV/m)
320.560	39.16	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



L Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

Date: 27.APR.2009 10:02:31

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
		V	

⁻The test data shows much less than the limit, no necessary to take down the records.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 39 of 55

Report No: 0904193 Date: 2009-04-28



M Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

Date: 27.APR.2009 10:16:36

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	$Limit@3m (dB\mu V/m)$
319.040	37.06	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



N Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

Date: 27.APR.2009 10:14:37

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
359.520	35.63	V	46.00

The report refers only to the sample tested and does not apply to the bulk.



O Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Comment: H

Date: 27.APR.2009 10:06:38

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
320.400	38.36	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



P Radiated Disturbance In Vertical (30MHz --- 1000MHz

EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C1500IC12.0-18C-US

Level: Class B **Results: PASS**


Please refer to following diagram for individual

Picture of the test

RBW 120 kHz Marker 1 [T1]

МТ 50 µs 35.96 dBµV/m





Comment: H

27.APR.2009 10:11:59 Date:

Frequency	(MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
359.6	80	35.96	V	46.00

The report refers only to the sample tested and does not apply to the bulk.

Page 43 of 55

Report No: 0904193 Date: 2009-04-28



6.0 FCC ID Label

FCC ID: V37-6222-104

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:






Photo of testing

Conducted test View—

Connect to PC



Page 45 of 55

Report No: 0904193 Date: 2009-04-28



7.2 Radiated emission test view--

Connect to PC




Page 46 of 55

Report No: 0904193 Date: 2009-04-28




7.3 Photo for the EUT



Page 47 of 55





Page 48 of 55





Page 49 of 55



Page 50 of 55





Page 51 of 55





Page 52 of 55





Page 53 of 55





Page 54 of 55





Page 55 of 55





-End of the report-