







ISO/IEC17025 Accredited Lab.

Report No: FCC 0904138 File reference No: 2009-04-29

Applicant: WIN ACCORD LTD.

Product: Digital Photo Frame

Brand Name: N/A

Model No: DF07105-05-XXX (X=A-Z, 0-9, a-z)

Test Standards: FCC Part 15 Subpart B: 2008

Test result:

It is herewith confirmed and found to comply with the requirements

set up by ANSI C63.4&FCC Part 15 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: April 29, 2009

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. Chegongmiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0904138 Page 2 of 62

Date: 2009-04-29



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 62

Report No: 0904138 Date: 2009-04-29



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Test Uncertainty	4
1.5	Submitted Sample	4
1.6	Test Duration.	4
2.0	List of Measurement Equipment	5
2.1	Conducted Emission Test.	5
2.2	Radiated electromagnetic disturbance test.	5
2.3	Auxiliary Equipment	5
3.0	Technical Details	6
3.1	Investigations Requested	6
3.2	Test Standards.	6
4.0	Power line Conducted Emission Test.	7
5.0	Radiated Disturbance Test	25
6.0	FCC ID Label	43
7.0	Photo of testing	44

Date: 2009-04-29

Report No: 0904138



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

1.2 Applicant Details

Applicant: WIN ACCORD LTD.

Address: 12F, NO. 225, SEC 5, 105 SONG SHAN DIST., NAN JING EAST ROAD, TAIPEI,

TAIWAN

Telephone: 02-2749 3837 Fax: 02-2749-3918

1.3 Description of EUT

Product: Digital Photo Frame
Manufacturer: WIN ACCORD LTD.

Address: 12F, NO. 225, SEC 5, 105 SONG SHAN DIST., NAN JING EAST ROAD,

AIPEI, TAIWAN

Brand Name: N/A

Model Number: DF07105-05-XXX (X=A-Z, 0-9, a-z)

Additional Model Number: PAN7000DW

The adapter Model No.: XKD-C2000IC5.0-12W (Made by MOSO)

Rating: Input: 100-240V, 0.5A Max, 50/60Hz Output: 5V, 2A The adapter Model No.: ADS-12G-06 05010GPCU (Made by HONOR) Rating: Input: 100-240V, 0.3A Max, 50/60Hz Output: 5V, 2A

Remark: Just the model names and appearance color are different.

Rating: Input: DC 5V, Current 2A

1.4 Submitted Sample(s): 1 Sample

1.5 Test Duration: 2009-04-20 to 2009-04-29

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 5 of 62

Report No: 0904138 Date: 2009-04-29



1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

2.0 List of Measurement Equipment

2.1 Conducted Emission Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESCS30	830245/009	RS	2009.2.23	1Year
Coaxial Switch	MP59B	M70585	ANRITSU	N/A	N/A
LISN	NTFM8132	8132137	SCHWARZBECK	2009.2.24	1Year
LISN	NTFM8134	8134109	SCHWARZBECK	2009.2.24	1Year
LISN	NTFM8136	8136102	SCHWARZBECK	2009.2.24	1Year

2.2 Radiated electromagnetic disturbance test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESCS30	830245/009	RS	2009.2.23	1Year
Coaxial Switch	MP59B	M70585	ANRITSU	N/A	N/A
Spectrum Analyzer(with					
Tracking Generator)	MS2661C	MT72089	ANRITSU	2009.2.23	1Year
Amplifier	MH648A	M20494	ANRITSU	2009.2.24	1Year
Bilog Antenna	CBL6101C	2576	CHASE	2009.2.23	1Year

2.3 Auxiliary Equipment

2.5 Transmar	<u>j Equipinent</u>				
N	M. LIN	C ' IN	M C	C 11	
Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
				Data cable of	
				2m length	
Keyboard	KB-0225	1211815	IBM	unshielded	FCC DOC
				Data cable of	
				1.5m length	
				unshielded and	
				1.8m length AC	
Printer	LaserJet 1015	CNFG029476	HP	Mains cable	DOC

The report refers only to the sample tested and does not apply to the bulk.

Page 6 of 62

Report No: 0904138 Date: 2009-04-29

				Data cable of	
				1.5m length	
				unshielded and	
				1.8m length AC	
Printer	LaserJet 1022	CNBG591GM7	HP	Mains cable	DOC
				Data cable of	
				1.5m length	
				unshielded and	
				1.8m length AC	
Monitor	6331-4CN	23-DNWX3	IBM	Mains cable	FCC ID

				1.8m length	
PC	8434		IBM	AC Mains cable	FCC DOC
				Data cable of	
Mouse	OM860XC	HM0509	BIGCOW	1.5m length	FCC DOC

3.0 Technical Details

3.1 Investigations Requested
Perform Electromagnetic Interference [EMI] tests for FCC Requirement.


3.2 Test Standards

FCC Part 15 Subpart B: 2008



4.0 Conducted Power line Test

4.1 Schematics of the test




EUT: Equipment Under Test

4.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003. Cables and peripherals were moved to find the maximum emission levels for each frequency. Test Voltage; 120V~, 60Hz

Block diagram of Test setup



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 8 of 62

Report No: 0904138 Date: 2009-04-29



4.3 Power line conducted Emission Limit


E(MII-)	Class A Li	mits dB(μV)	Class B Limits $dB(\mu V)$		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
0.15 ~ 0.50	79.00	66.00	66.00~56.00*	56.00~46.00*	
$0.50 \sim 5.00$	73.00	60.00	56.00	46.00	
5.00 ~ 30.00	73.00	60.00	60.00	50.00	

Notes:

- 1. *decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

4.4 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.




EUT set Condition: Memory

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Empayonary		Reading		Limit		
Frequency (MHz)	Live	;	Neutral		$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.313	56.98	42.20			59.89	49.89
0.384	52.05	41.45			58.19	48.19
0.574	51.22	40.15			56.00	46.00
0.756	50.90	38.19			56.00	46.00
1.064	52.53	40.16			56.00	46.00
2.264	48.66	38.97			56.00	46.00




B: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Memory

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav		Reading	Limit			
Frequency (MHz)	Live		Neutral		$(dB \mu V)$	
(IVITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.314			54.30	41.75	59.85	49.85
0.380			46.57	31.79	58.28	48.28
0.767			45.77	37.03	56.00	46.00
1.492			49.80	36.69	56.00	46.00
1.887			50.32	39.39	56.00	46.00


C: Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav		Reading	Limit			
Frequency	Live	2	Neutral		$(dB \mu V)$	
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.313	56.87	43.35			59.89	49.89
0.570	49.45	41.95			56.00	46.00
0.858	52.38	37.89			56.00	46.00
1.073	50.26	39.70			56.00	46.00
1.300	51.41	40.41			56.00	46.00
1.993	47.37	38.17			56.00	46.00
3.918	51.75	39.37			56.00	46.00




D: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav		Reading	Limit			
Frequency (MHz)	Live	;	Neutral		$(dB \mu V)$	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.315			55.78	43.18	59.83	49.83
0.572			53.47	42.79	56.00	46.00
0.623			50.58	42.99	56.00	46.00
0.973			50.14	39.02	56.00	46.00
1.501			51.34	39.96	56.00	46.00
1.733			50.35	38.68	56.00	46.00




E: Conducted Emission on Live Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play USB (Adapter made by HONOR)
Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass

Please refer to following diagram for individual



Eraguanav		Reading		Limit		
Frequency (MHz)	Live		Neutral		$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.308	56.50	44.87			60.02	50.02
0.566	52.26	41.66			56.00	46.00
0.719	50.27	37.57			56.00	46.00
1.726	49.01	40.49			56.00	46.00




F: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play USB

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live	;	Neutral		(dB μ	V)
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.298			56.74	46.27	60.30	50.30
0.307			57.57	43.17	60.05	50.05
0.382			55.11	43.27	58.23	48.23
0.748			49.87	36.06	56.00	46.00
1.246			47.79	37.67	56.00	46.00
1.456			45.90	35.10	56.00	46.00


G: Conducted Emission on Live Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play CF (Adapter made by HONOR)
Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass

Please refer to following diagram for individual



Engavanav		Reading	Limit			
Frequency (MHz)	Live	;	Neutr	Neutral		V)
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.312	57.14	43.12			59.92	49.92
0.567	52.45	39.03			56.00	46.00
0.809	48.89	41.15			56.00	46.00
1.044	51.70	41.04			56.00	46.00
1.576	51.15	41.46			56.00	46.00
3.314	48.14	39.40			56.00	46.00




H: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play CF


Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live	Live		Neutral		V)
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.307			57.74	44.98	60.04	50.04
0.388			50.07	38.68	58.10	48.10
0.563			52.12	37.38	56.00	46.00
0.721			51.91	40.81	56.00	46.00
1.025			50.88	42.82	56.00	46.00
1.924			49.63	41.73	56.00	46.00




EUT set Condition: Connected to PC

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		$(dB \mu V)$	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.315	52.68	38.28			59.83	49.83
0.392	50.96	36.26			58.01	48.01
0.588	49.66	35.76			56.00	46.00
0.814	49.40	38.30			56.00	46.00
4.170	52.17	42.97			56.00	46.00




J: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Connected to PC

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live	;	Neutral		(dB µ	V)
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.315			52.97	42.97	59.83	49.83
0.385			50.85	42.25	58.16	48.16
0.777			50.96	40.46	56.00	46.00
1.308			51.62	25.02	56.00	46.00
2.965			50.89	37.89	56.00	46.00
4.102			52.54	41.44	56.00	46.00


K: Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.167	57.03	50.35			65.11	55.11
0.175	56.57	26.96			64.68	54.68
0.234	49.65	43.33			62.28	52.28




L: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Memory


Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.176			56.47	46.37	64.67	54.67
0.235			49.88	32.50	62.25	52.25




EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.170	56.15	43.37			64.94	54.94
0.225	49.63	40.42			62.63	52.63




N: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.169			56.59	46.83	65.01	55.01
0.225			48.82	40.33	62.62	52.62




EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.180	55.56	44.85			64.46	54.46




P: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.177			55.47	45.00	64.62	54.62
0.235			48.69	43.53	62.27	52.27




EUT set Condition: Play CF

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Frequency (MHz)		Reading	Limit			
	Live		Neutral		(dB µ V)	
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.176	55.59	45.62			64.63	54.63
0.232	48.96	33.97			62.37	52.37




R: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Play CF

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Eraguanav	Reading(dB µ V)			Limit		
Frequency (MHz)	Live	Live Neutral		al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.168			54.68	45.77	65.06	55.06
0.229			49.58	32.67	62.48	52.48




EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Eroguanav	Reading(dB μ V)				Limit	
Frequency (MHz)	Live		Neutral		(dB µ V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.169	55.43	38.19			65.00	55.00
0.583	41.11	33.11			56.00	46.00
6.491	51.47	40.99			60.00	50.00




T: Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Connect to PC (Adapter made by MOSO)
Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Working Voltage: 120V~ 60Hz

Results: Pass



Ema avvam avv	Reading(dB µ V)			Limit		
Frequency (MHz)	Live	Live Neutral		al	(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.169			55.70	45.70	64.98	54.98
0.230			48.81	37.59	62.44	52.44
6.226			49.82	38.69	60.00	50.00


Page 29 of 62

Report No: 0904138 Date: 2009-04-29



5.0 Radiated Disturbance Test


5.1 Schematics of the test




5.2 Test Method and test Procedure:

The EUT was tested according to ANSI C63.4 –2003, The frequency spectrum from 30MHz to 1GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak 0values with a resolution bandwidth of 120KHz. All readings are above 1GHz, peak values with a resolution bandwidth of 1MHz. Measurements were made at 3 meters.

Test Voltage: 120V~, 60Hz Block diagram of Test setup







5.3 Radiated Emission Limit

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.00
88-216	3	43.50
216-960	3	46.00
Above 960	3	54.00

Note: The lower limit shall apply at the transition frequencies

5.4 Test result

The frequency spectrum from 30MHz to 1GHz was investigated. All reading from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120KHz. All readings are above 1GHz, peak values with a resolution bandwidth of 1MHz. Measurements were made at 3 meters.

Page 31 of 62

Report No: 0904138 Date: 2009-04-29



A: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Memory

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 10:56:53

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
954.600	39.76	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

Page 32 of 62

Report No: 0904138 Date: 2009-04-29



B: Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Memory

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 10:59:06

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
954.680	38.93	V	46.00
95.680	29.70	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

1 GHz

Report No: 0904138 Date: 2009-04-29



C: Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Play SD

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test

%

RBW 120 kHz Marker 1 [T1] MT 50 μs 32.56 dBμV/m

Date: 21.APR.2009 11:07:21

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
954.680	39.76	Н	43.50

The report refers only to the sample tested and does not apply to the bulk.



D: Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Play SD


Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test





Date: 21.APR.2009 11:09:22

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
954.640	39.51	V	46.00
104.360	28.92	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

Page 35 of 62

Report No: 0904138 Date: 2009-04-29



E: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Play CF

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 10:50:18

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
104.480	27.90	Н	43.50
460.360	35.18	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

Page 36 of 62

1 GHz

Report No: 0904138 Date: 2009-04-29



F: Radiated Disturbance In Vertical (30MHz---1000MHz)

EUT set Condition: Play CF


Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test

RBW 120 kHz MT 50 µs Att 0 dB PREAMP OFF



Date: 21.APR.2009 10:47:03

30 MHz

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m (dBµV/m)
104.520	33.64	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

Page 37 of 62

Report No: 0904138 Date: 2009-04-29



Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Play USB


Model No.: ADS-12G-06 05010GPCU Adaptor used for test

Level: Class B **PASS Results:**

Please refer to following diagram for individual

Picture of the test





21.APR.2009 11:04:38 Date:

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
354.600	39.91	Н	46.00
460.280	35.72	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



H: Radiated Disturbance In Vertical (30MHz----1000MHz)

EUT set Condition: Play USB

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS


Please refer to following diagram for individual

Picture of the test

%

RBW 120 kHz Marker 1 [T1]

MT 50 μs 27.08 $dB\mu V/m$



Date: 21.APR.2009 11:02:11

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
954.600	39.38	V	46.00
95.640	27.08	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



I: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Connect to PC

Adaptor used for test Model No.: ADS-12G-06 05010GPCU

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:45:19

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
95.640	32.11	Н	43.50
144.000	33.00	Н	43.50
168.000	33.85	Н	43.50
306.920	34.47	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Radiated Disturbance In Vertical (30MHz----1000MHz) J:

EUT set Condition: Connect to PC


Model No.: ADS-12G-06 05010GPCU Adaptor used for test

Level: Class B **PASS Results:**

Please refer to following diagram for individual

Picture of the test





21.APR.2009 11:47:34 Date:

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
95.640	33.92	V	43.50
168.000	30.28	V	43.50
307.000	32.22	V	46.00

The report refers only to the sample tested and does not apply to the bulk.



K: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:40:36

	Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
	95.680	32.03	Н	43.50
	104.360	31.94	Н	43.50
Ī	144.000	33.42	Н	43.50
	460.400	34.97	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



Radiated Disturbance In Vertical (30MHz----1000MHz) L:

EUT set Condition: Connect to PC

Adaptor used for test Model No.: XKD-C2000IC5.0-12W


Level: Class B **PASS Results:**

Please refer to following diagram for individual

Picture of the test



120 kHz Marker 1 [T1] RBW



Date: 21.APR.2009 11:37:52

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
95.640	32.03	V	43.50
144.000	29.27	V	43.50

The report refers only to the sample tested and does not apply to the bulk.



M: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:31:21

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
460.400	34.52	Н	46.00
153.480	29.22	Н	43.50

The report refers only to the sample tested and does not apply to the bulk.



N: Radiated Disturbance In Vertical (30MHz----1000MHz)


EUT set Condition: Memory

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:33:17

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
95.640	32.43	V	43.50
133.160	30.64	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

Page 45 of 62

Report No: 0904138 Date: 2009-04-29



O: Radiated Disturbance In Horizontal (30MHz----1000MHz)

EUT set Condition: Play SD

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual


Picture of the test



RBW 120 kHz Marker 1 [T1]

MT 50 μs 26.92 dBμV/m

PREAMP OFF 104.800000000 MHz



Date: 21.APR.2009 11:17:59

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
104.480	26.93	Н	43.50
460.400	34.43	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.

1 GHz

Report No: 0904138 Date: 2009-04-29



P: Radiated Disturbance In Vertical (30MHz----1000MHz)


EUT set Condition: Play SD


Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B **PASS Results:**

Please refer to following diagram for individual

Picture of the test





Date: 21.APR.2009 11:14:59

30 MHz

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
95.640	32.85	V	43.50
104.320	31.62	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

Page 47 of 62

Report No: 0904138 Date: 2009-04-29



Radiated Disturbance In Horizontal (30MHz----1000MHz) O:

EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B **PASS Results:**


Please refer to following diagram for individual

Picture of the test



120 kHz Marker 1 [T1] RBW

50 µs мт 34.36 dBµV/m



Date: 21.APR.2009 11:20:56

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
460.360	34.36	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



R: Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Play USB

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:23:01

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m (dBµV/m)
95.640	32.40	V	43.50

The report refers only to the sample tested and does not apply to the bulk.



S: Radiated Disturbance In Horizontal (30MHz----1000MHz)


EUT set Condition: Play CF

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:27:45

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m ($dB\mu V/m$)
306.880	29.95	Н	46.00
460.320	32.41	Н	46.00

The report refers only to the sample tested and does not apply to the bulk.



T: Radiated Disturbance In Vertical (30MHz---1000MHz)


EUT set Condition: Play CF

Adaptor used for test Model No.: XKD-C2000IC5.0-12W

Level: Class B
Results: PASS

Please refer to following diagram for individual

Picture of the test



Date: 21.APR.2009 11:25:10

Frequency (MHz)	Level@3m ($dB\mu V/m$)	Antenna Polarity	Limit@3m (dBµV/m)
95.640	31.10	V	43.50

The report refers only to the sample tested and does not apply to the bulk.

Page 51 of 62

Report No: 0904138 Date: 2009-04-29



6.0 FCC ID Label

FCC ID: V37-6226-7DWINCH

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:





Photo of testing

Conducted test View—

Connect to PC



Page 53 of 62

Report No: 0904138 Date: 2009-04-29



7.2 Radiated emission test view--

Connect to PC



Page 54 of 62

Report No: 0904138 Date: 2009-04-29



7.3 Photo for the EUT



Page 55 of 62

Report No: 0904138 Date: 2009-04-29






The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 56 of 62





Page 57 of 62





Page 58 of 62





Page 59 of 62





Page 60 of 62





Page 61 of 62





Page 62 of 62

Report No: 0904138 Date: 2009-04-29





-End of the report-