



# FCC 47 CFR PART 15 SUBPART C

## TEST REPORT

*For*

**Applicant :** Win Accord Ltd.

**Address :** 12F., No. 225, Sec. 5, Nanjing E. Rd., Songshan Dist, Taipei City  
105, Taiwan

**Product Name :** Tablet PC

**Model Name :** PTT-826D, PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G

**Brand Name :** N/A

**FCC ID :** V37-PTT826D

**Report No. :** MTE/DAL/D12091286

**Date of Issue :** Dec. 20, 2012

**Issued by :** Most Technology Service Co., Ltd.

**Address :** No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan,  
Shenzhen, Guangdong, China

**Tel :** 86-755-8617 0306

**Fax :** 86-755-8617 0310

*The report consists 60 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.*

**TABLE OF CONTENTS**

**1. VERIFICATION OF CONFORMITY ..... 4**

**2. GENERAL INFORMATION..... 5**

2.1 Product Information ..... 5

2.2 Objective ..... 6

2.3 Test Standards and Results ..... 6

2.4 Environmental Conditions ..... 6

2.5 MEASUREMENT UNCERTAINTY ..... 6

**3. TEST FACILITY ..... 7**

3.2 Test Conditions ..... 8

3.3 Channel List ..... 8

3.4 Description of Test Modes ..... 8

3.5 Table of Parameters of Text Software Setting ..... 8

**4. TEST EQUIPMENT LIST ..... 9**

**5. 47 CFR Part 15 C 15.247 Requirements..... 10**

**5.1 6dB Bandwidth ..... 10**

5.1.1 Definition ..... 10

5.1.2 Limit..... 10

5.1.3 Test Configuration..... 10

5.1.4 Test Procedure..... 10

5.1.5 Test Result..... 10

**5.2 Peak Output Power ..... 16**

5.2.1 Definition ..... 16

5.2.2 Limit..... 16

5.2.3 Test Configuration..... 16

5.2.4 Test Procedure..... 16

5.2.5 Test Result..... 16

**5.3 Conducted Spurious Emission ..... 18**

5.3.1 Definition ..... 18

5.3.2 Test Description ..... 18

5.3.3 Test Result..... 18

**5.4 Band Edge ..... 23**

5.4.1 Definition ..... 23

5.4.2 Test Configuration..... 23

5.4.3 Test Result..... 23

**5.5 Power Spectral Density (PSD)..... 31**

5.5.1 Definition ..... 31

5.5.2 Limit..... 31

5.5.4 Test Configuration..... 31

5.5.3 Test Description ..... 31

5.5.4 Test Configuration..... 31

5.5.3 Operation Condition..... 31

5.5.6 Test Result..... 31

**5.6 Conducted Emission ..... 37**  
5.6.1 Definition ..... 37  
5.6.2 Test Description ..... 37  
5.6.3 Test Result..... 37  
**5.7 Radiated Emission ..... 42**  
5.7.1 Definition ..... 42  
5.7.2 Test Description ..... 43  
5.7.3 Test Result..... 44  
**APPENDIX 1 ..... 59**  
**PHOTOGRAPHS OF TEST SETUP ..... 59**

# 1. VERIFICATION OF CONFORMITY

**Equipment Under Test:** Tablet PC

**Brand Name:** N/A

**Model Number:** PTT-826D

**Series Model Number:** PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G

**FCC ID:** V37-PTT826D

**Applicant:** Win Accord Ltd.  
12F., No. 225, Sec. 5, Nanjing E. Rd., Songshan Dist, Taipei City 105, Taiwan

**Manufacturer:** Win Accord Ltd.  
7F., Garden City Cyber Port, Nanhai Road A, No. 1079, Nanshan Dist., Shenzhen, China

**Technical Standards:** 47 CFR Part 15 Subpart C

**File Number:** MTE/DAL/D12091286

**Date of test:** Aug. 24-Dec. 20, 2012

**Deviation:** None

**Condition of Test Sample:** Normal

**Test Result:** PASS

The above equipment was tested by *MOST* for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared by (+ signature):

*Dona*

\_\_\_\_\_  
Dona Liu

Sep. 10, 2012

Review by (+ signature):

*Elva*

\_\_\_\_\_  
Elva Wong

Dec. 20, 2012



Approved by (+ signature):

*Yvette*

\_\_\_\_\_  
Yvette Zhou

Dec. 20, 2012

## 2. GENERAL INFORMATION

### 2.1 Product Information

Description:	Tablet PC
Model Name:	PTT-826D
Series Number:	PT08002-51-XXX(X=a-z, 0-9, A-Z), IDxD8, IDxD8 3G
Model Difference description:	The series models are different in model name with the same functions.
Frequency Range:	802.11b/g/n:2412MHz – 2462MHz
Number of Channels:	IEEE 802.11b/g/nmode: 11 Channels
Modulation Technique:	IEEE 802.11b mode: CCK (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) 802.11n Standard-20 MHz Channel mode: OFDM (6.5, 13, 19.5,26, 39, 52, 58.5, 65.0Mbps)
Antenna Type:	Internal Fixed
Antenna Gain:	3.0dBi
Power Supply:	DC 5V Adaptor Input AC 100-240V, 50/60Hz DC 3.7V by battery
Temperature Range:	0°C ~ +40°C

**NOTE:**

1. For a more detailed features description about the EUT, please refer to User's Manual.

## 2.2 Objective

Perform FCC Part 15 Subpart C tests for FCC Marking.

## 2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.247(a)(2)	6dB Bandwidth	PASS	2012/08/24
2	15.247(b)(3)	Peak Output Power	PASS	2012/11/27
3	15.247(d)	conducted spurious emission	PASS	2012/08/24
4	15.247(d)	Band Edge	PASS	2012/12/20
5	15.247(e)	Power Spectral Density	PASS	2012/11/29
6	15.207	Conducted Emission	PASS	2012/08/24
7	15.247(d) 15.205 15.209	Radiated Emission	PASS	2012/08/27

Note: 1. The test result judgment is decided by the limit of measurement standard  
2. The information of measurement uncertainty is available upon the customer's request.

## 2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- HuTablet PCity: 30-60 %
- Atmospheric pressure: 86-106 kPa

## 2.5 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

The report uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , Providing a level of confidence of approximately 95%

- Uncertainty of Conducted Emission,  $U_c = \pm 1.8\text{dB}$
- Uncertainty of Radiated Emission,  $U_c = \pm 3.2\text{dB}$

### 3. TEST FACILITY

Test Site:	Most Technology Service Co., Ltd.
Location:	No.5, Nangshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen, Guangdong, China
Description:	<p>There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 and CISPR 16 requirements.</p> <p>The FCC Registration Number is <b>490827</b>.</p>
Site Filing:	The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.
Ground Plane:	Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.
558074 D01 DTS Meas Guidance v01 :	provides Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under CFR Title 47 15.247

### 3.2 Test Conditions

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

### 3.3 Channel List

Channel List for 802.11b/g/n(20MHz)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412MHz	05	2432MHz	09	2452MHz
02	2417MHz	06	2437MHz	10	2457MHz
03	2422MHz	07	2442MHz	11	2462MHz
04	2427MHz	08	2447MHz		

### 3.4 Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level, Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively

Pre-test Mode	Description
Mode 1	802.11b CH01/CH07/CH11
Mode 2	802.11g CH01/CH07/CH11
Mode 3	802.11n(20MHz)CH01/CH07/CH11

Note:

- (1) The measurements are performed at the highest, Middle, lowest available channels.
- (2) The measurements are performed at all bit rate of transmitter, the worst data was reported.

With individual Verifying, the maximum output power was found at 1Mbps data for 802.11b mode, 6Mbps data rate for 802.11g mode. MSC0 for 802.11n/20MHz mode, The final test were executed under these conditions

### 3.5 Table of Parameters of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level, the RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software Version	Test program:N/A		
802.11b	2412MHz	2442MHz	2462MHz
802.11g	2412MHz	2442MHz	2462MHz
802.11n(20MHz)	2412MHz	2442MHz	2462MHz

#### 4. TEST EQUIPMENT LIST

**Instrumentation:** The following list contains equipment used at MOST for testing. The equipment conforms to the CISPR 16-1/ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calibration date	Calibration Interval
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
2	Spectrum Analyzer	Agilent	E7405A	US44210471	2012/03/14	1 Year
3	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14	1 Year
4	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
5	Terminator	Hubersuhner	50Ω	No.1	2012/03/14	1 Year
6	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14	1 Year
7	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14	1 Year
8	Bilog Antenna	Sunol	JB3	A121206	2012/03/14	1 Year
9	Horn Antenna	TRC	N/A	N/A	2012/03/14	1 Year
10	Cable	Resenberger	N/A	NO.1	2012/03/14	1 Year
11	Cable	SchwarzBeck	N/A	NO.2	2012/03/14	1 Year
12	Cable	SchwarzBeck	N/A	NO.3	2012/03/14	1 Year
13	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14	1 Year
14	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14	1 Year
15	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14	1 Year
16	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
17	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14	1 Year
18	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
19	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14	1 Year
20	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14	1 Year
21	Line Impedance Network	Kikusui	LIN40MA-PCR-L	LM002352	2012/03/14	1 Year
22	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14	1 Year
23	EMC PRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14	1 Year
24	Signal Generator	IFR	2032	203002/100	2012/03/14	1 Year
25	Amplifier	A&R	150W1000	301584	2012/03/14	1 Year
26	CDN	FCC	FCC-801-M2-25	47	2012/03/14	1 Year
27	CDN	FCC	FCC-801-M3-25	107	2012/03/14	1 Year
28	EM Injection Clamp	FCC	F-2031-23mm	403	2012/03/14	1 Year
29	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14	1 Year
30	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14	1 Year
31	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14	1 Year
32	8 Loop Antenna	ARA	PLA-1030/B	1029	2012/02/19	1 Year
33	Power Meter	R&S	NRVS	100444	2012/03/14	1 Year
34	Power Sensor (AV)	R&S	URV5-Z4	0395.1619.07	2012/03/14	1 Year

**NOTE:** Equipments listed above have been calibrated and are in the period of validation.

## 5. 47 CFR Part 15 C 15.247 Requirements

### 5.1 6dB Bandwidth

#### 5.1.1 Definition

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 5.1.2 Limit

FCC Part15(15.247)				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB Bandwidth)	2400-2483.5	PASS

#### 5.1.3 Test Configuration




Figure 1: RF Test Setup

#### 5.1.4 Test Procedure

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	$>$ Measurement bandwidth or channel separation
RB	1-5% of the emission bandwidth(EBW)
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 50Ohm.

#### 5.1.5 Test Result

The lowest, Middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.


##### 5.1.5.1 802.11b Test Mode

The minimum occupied bandwidth for the fundamental frequency 2442 MHz is 11.10 MHz. This occupied bandwidth complies with the FCC requirement.


**A. Test Verdict:**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	11.10	≥500	PASS
7	2442	11.48	≥500	PASS
11	2462	11.63	≥500	PASS


**B. Test Plot:**



(CH Low)



(CH Mid)



(CH High)


### 5.1.5.2 802.11g Test Mode

The minimum occupied bandwidth for the fundamental frequency 2412MHz is 16.13MHz. This occupied bandwidth complies with the FCC requirement.


#### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.13	≥500	PASS
7	2442	16.43	≥500	PASS
11	2462	16.28	≥500	PASS


#### B. Test Plot:



(CH Low)



(CH Mid)



(CH High)


### 5.1.5.3 802.11n Test Mode

The minimum occupied bandwidth for the fundamental frequency 2442MHz is 17.40MHz. This occupied bandwidth complies with the FCC requirement.


#### A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.63	≥500	PASS
7	2442	17.40	≥500	PASS
11	2462	17.48	≥500	PASS


#### B. Test Plot:



(CH Low)



(CH Mid)



(CH High)

## 5.2 Peak Output Power


### 5.2.1 Definition

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

### 5.2.2 Limit

FCC Part15(15.247)				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(b)(1)	Peak Output Power	30dBm	2400-2483.5	PASS

### 5.2.3 Test Configuration



### 5.2.4 Test Procedure

The EUT which is powered by AC adapter, is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

### 5.2.5 Test Result

The EUT operates at maximum output power mode. The lowest, Tablet PCdle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

#### 5.2.5.1 802.11b Test Mode

The maximum output power for the fundamental frequency 2462MHz is 16.03dBm. This power complies with the FCC requirement.

##### A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.12	0.032	30	1	PASS
5	2442	15.38	0.034			PASS
11	2462	16.03	0.040			PASS

#### 5.2.5.2 802.11g Test Mode

The maximum output power for the fundamental frequency 2442 MHz is 15.11dBm. This power complies with the FCC requirement.

##### A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.05	0.031	30	1	PASS
5	2442	15.11	0.032			PASS
11	2462	14.89	0.030			PASS

### 5.2.5.3 802.11n Test Mode

The maximum output power for the fundamental frequency 2462 MHz is 14.02dBm. This power complies with the FCC requirement.

#### A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	13.85	0.024	30	1	PASS
5	2442	13.56	0.022			PASS
11	2462	14.02	0.025			PASS

### 5.3 Conducted Spurious Emission

#### 5.3.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### 5.3.2 Test Description


See section 5.1.2 of this report.

#### 5.3.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, Tablet PCdle and highest channels are tested to verify the spurious emissions.

##### 5.3.3.1 802.11b Test Mode


Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kHz to 25GHz)

**Note:**


1. The power of the Module transmitting frequency should be ignored.

### 5.3.2. 802.11g Test Mode


Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kHz to 25GHz)

**Note:**


1. The power of the Module transmitting frequency should be ignored.

**5.3.3. 802.11n Test Mode**


**Test Plot:**



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kHz to 25GHz)

## 5.4 Band Edge

### 5.4.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 5.4.2 Test Configuration




### 5.4.3 Test Result

The EUT operates at continuous transmit test mode. The lowest and highest channels are tested to verify the band edge emissions.


#### 5.4.3.1 802.11b Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	41.34	35.28	41.70	35.78
		2400MHz		30.84	26.74	30.80	25.96
	High Channel	2483.5MHz		41.29	36.30	41.72	34.39
		2500MHz		41.53	37.02	41.53	36.57


Test Plot:




(CH Low, Vertical, Peak)



(CH Low, Horizontal, Peak)



(CH High, Vertical, Peak)




(CH High, Horizontal, Peak)


### 5.4.3.2 802.11g Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	36.07	31.59	34.70	30.20
		2400MHz		28.10	23.85	27.73	24.39
	High Channel	2483.5MHz		27.81	23.84	27.89	22.89
		2500MHz		39.71	35.82	40.72	35.47


**Test Plot:**




(CH Low, Horizontal, Peak )



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)




(CH High, Vertical, Peak)


### 5.4.3.3 802.11n Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	34.50	30.23	35.41	30.03
		2400MHz		28.62	23.23	27.11	23.78
	High Channel	2483.5MHz		29.74	24.89	29.43	25.28
		2500MHz		41.06	36.20	40.80	36.84


Test Plot:




(CH Low, Horizontal, Peak )



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)



(CH High, Vertical, Peak)

### 5.5 Power Spectral Density (PSD)

#### 5.5.1 Definition

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band.

#### 5.5.2 Limit

FCC Part15(15.247)				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2402-2483.5	PASS

#### 5.5.4 Test Configuration



#### 5.5.3 Test Description

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	5-30% greater than the EBW
RB	100kHz
VB	300KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

- a. The EUT was directly connectd to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=300KHz, Sweep time=Auto. Span to 5-30% greater than EBW
- c. Scale the observed power level to an equivalent value in 3kHz by adjusting(reducing) the measured power by a bandwidth correction factor(BWCF) where  $BWCF=10\log(3\text{kHz}/100\text{kHz}=-15.2\text{dB})$ .
- d. Use peak detector+BWCF.
- f. The resulting peak PSD level must be  $\leq 8\text{dBm}$ .

#### 5.5.4 Test Configuration



#### 5.5.3 Operation Condition

The EUT tested system was configured as the statements of 2.1 unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.5.6 Test Result


The lowest, Tablet PCdle and highest channels are tested to verify the power spectral density.

### 5.5.6.1 802.11b Test Mode


#### A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-9.23	≤8	PASS
7	2442	-7.37	≤8	PASS
11	2462	-7.66	≤8	PASS


#### B. Test Plot:



(CH Low)



(CH Mid)




(CH High)

### 5.5.6.2 802.11g Test Mode


#### A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-14.97	≤8	PASS
7	2442	-14.45	≤8	PASS
11	2462	-14.34	≤8	PASS


#### B. Test Plot:



(CH Low)



(CH Mid)




(CH High)

### 5.5.6.3 802.11n Test Mode


#### A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-14.01	≤8	PASS
7	2442	-15.19	≤8	PASS
11	2462	-14.30	≤8	PASS


#### B. Test Plot:



(CH Low)



(CH Mid)



(CH High)

## 5.6 Conducted Emission

### 5.6.1 Definition

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).


Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

**Note:**

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

### 5.6.2 Test Description

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power.



### 5.6.3 Test Result


A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The Wifi model was carried out for 802.11b/g/n modulation types with two adapters, 802.11b High channel modulation type was the worst case condition, The test data was shown on the summary data page.



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
 Guangdong, China  
 Tel: 0755-86170306 Fax: 0755-86170310

**Conducted Emission Measurement**



Site Chamber #1      Phase: **N**      Temperature: 26  
 Limit: FCC Part15 B Class B QP      Power: DC 5V Adapter AC 120V/60Hz      Humidity: 60 %  
 EUT: Tablet PC  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: MPAS-U012050E

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2467	37.04	11.69	48.73	61.86	-13.13	QP	
2		0.2467	27.03	11.69	38.72	51.86	-13.14	AVG	
3	*	0.4860	36.15	10.09	46.24	56.24	-10.00	QP	
4		0.4860	24.77	10.09	34.86	46.24	-11.38	AVG	
5		0.6108	31.95	10.00	41.95	56.00	-14.05	QP	
6		0.6108	23.08	10.00	33.08	46.00	-12.92	AVG	
7		0.8340	34.33	10.00	44.33	56.00	-11.67	QP	
8		0.8340	18.73	10.00	28.73	46.00	-17.27	AVG	
9		4.9099	30.14	11.91	42.05	56.00	-13.95	QP	
10		4.9099	10.37	11.91	22.28	46.00	-23.72	AVG	
11		6.0539	33.69	11.37	45.06	60.00	-14.94	QP	
12		6.0539	12.61	11.37	23.98	50.00	-26.02	AVG	


\*:Maximum data    x:Over limit    !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
 Guangdong, China  
 Tel: 0755-86170306 Fax: 0755-86170310

**Conducted Emission Measurement**



Site Chamber #1 Phase: **L1** Temperature: 26  
 Limit: FCC Part15 B Class B QP Power: DC 5V Adapter AC 120V/60Hz Humidity: 60 %  
 EUT: Tablet PC  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: MPAS-U012050E

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.3634	35.27	10.91	46.18	58.65	-12.47	QP	
2	0.3634	24.85	10.91	35.76	48.65	-12.89	AVG	
3 *	0.4786	36.57	10.14	46.71	56.36	-9.65	QP	
4	0.4786	25.00	10.14	35.14	46.36	-11.22	AVG	
5	0.6140	36.18	10.00	46.18	56.00	-9.82	QP	
6	0.6140	22.72	10.00	32.72	46.00	-13.28	AVG	
7	0.9180	35.11	10.00	45.11	56.00	-10.89	QP	
8	0.9180	22.16	10.00	32.16	46.00	-13.84	AVG	
9	1.2220	36.10	9.78	45.88	56.00	-10.12	QP	
10	1.2220	20.22	9.78	30.00	46.00	-16.00	AVG	
11	4.9459	33.21	11.95	45.16	56.00	-10.84	QP	
12	4.9459	20.28	11.95	32.23	46.00	-13.77	AVG	


\*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310

**Conducted Emission Measurement**



Site Chamber #1 Phase: **N** Temperature: 26  
 Limit: FCC Part15 B Class B QP Power: DC 5V Adapter AC 120V/60Hz Humidity: 60 %  
 EUT: Tablet PC  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: GP302E-050-200

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1785	41.79	10.71	52.50	64.55	-12.05	QP	
2	0.1785	28.87	10.71	39.58	54.55	-14.97	AVG	
3	0.3115	36.27	11.26	47.53	59.93	-12.40	QP	
4	0.3115	26.01	11.26	37.27	49.93	-12.66	AVG	
5	0.4940	33.82	10.04	43.86	56.10	-12.24	QP	
6 *	0.4940	24.93	10.04	34.97	46.10	-11.13	AVG	
7	1.1940	25.60	9.81	35.41	56.00	-20.59	QP	
8	1.1940	16.23	9.81	26.04	46.00	-19.96	AVG	
9	2.6780	26.37	9.68	36.05	56.00	-19.95	QP	
10	2.6780	18.63	9.68	28.31	46.00	-17.69	AVG	
11	4.3019	23.70	11.30	35.00	56.00	-21.00	QP	
12	4.3019	14.68	11.30	25.98	46.00	-20.02	AVG	


\*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
 Guangdong, China  
 Tel: 0755-86170306 Fax: 0755-86170310

**Conducted Emission Measurement**



Site Chamber #1 Phase: **L1** Temperature: 26  
 Limit: FCC Part15 B Class B QP Power: DC 5V Adapter AC 120V/60Hz Humidity: 60 %  
 EUT: Tablet PC  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: GP302E-050-200

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2508	37.40	11.66	49.06	61.73	-12.67	QP	
2		0.2508	26.65	11.66	38.31	51.73	-13.42	AVG	
3		0.4300	33.22	10.47	43.69	57.25	-13.56	QP	
4		0.4300	22.39	10.47	32.86	47.25	-14.39	AVG	
5		0.8460	27.15	10.00	37.15	56.00	-18.85	QP	
6		0.8460	16.35	10.00	26.35	46.00	-19.65	AVG	
7		1.4620	26.77	9.54	36.31	56.00	-19.69	QP	
8		1.4620	15.14	9.54	24.68	46.00	-21.32	AVG	
9		2.8740	27.67	9.87	37.54	56.00	-18.46	QP	
10		2.8740	11.49	9.87	21.36	46.00	-24.64	AVG	
11		4.6939	22.48	11.69	34.17	56.00	-21.83	QP	
12		4.6939	5.19	11.69	16.88	46.00	-29.12	AVG	

\*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen

## 5.7 Radiated Emission

### 5.7.1 Definition

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.


### 5.7.2 Test Description

#### A. Test Configuration:



#### Below 1GHz:



**Above 1GHz:****B. Test procedures**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
  - Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
  - Above 1GHz : (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

**5.7.3 Test Result**

The Wifi model was carried out for 802.11b/g/n modulation types with two adapters, 802.11b High channel modulation type was the worst case condition, The test data was shown on the summary data page.

**From 9KHz to 30MHz:**

EUT:	TABLET PC	Model Name. :	PTT-826D
Temperature:	20 °C	Relative Humidity: Mobility Tableting:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V by Adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $20 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**Conclusion: PASS**

**Below 1 GHz**



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310

**Radiated Emission Measurement**



Site Chamber #1 Polarization: **Vertical** Temperature: 26  
 Limit: FCC Part 15 B 3M Radiation Power: DC 5V Adapter AC 120V/60Hz Humidity: 61 %  
 EUT: Tablet PC Distance:  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		35.8200	12.81	20.27	33.08	40.00	-6.92	QP		
2	*	84.3198	22.25	11.32	33.57	40.00	-6.43	QP		
3		145.4299	17.74	16.87	34.61	43.50	-8.89	QP		
4		475.2300	13.79	21.41	35.20	46.00	-10.80	QP		
5		608.1200	10.06	23.20	33.26	46.00	-12.74	QP		
6		775.9299	8.81	26.08	34.89	46.00	-11.11	QP		

\*:Maximum data x:Over limit !:over margin


Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
 Guangdong, China  
 Tel: 0755-86170306 Fax: 0755-86170310

**Radiated Emission Measurement**

File: PTT-826D Data: #13 Date: 2012-8-27 Time: 15:17:41



Site Chamber #1 Polarization: **Horizontal** Temperature: 26  
 Limit: FCC Part 15 B 3M Radiation Power: DC 5V Adapter AC 120V/60Hz Humidity: 61 %  
 EUT: Tablet PC Distance:  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: MPAS-U012050E

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	78.5000	21.78	11.47	33.25	40.00	-6.75	QP		
2		138.6399	10.44	17.27	27.71	43.50	-15.79	QP		
3		303.5400	11.86	18.34	30.20	46.00	-15.80	QP		
4		424.7900	14.78	20.29	35.07	46.00	-10.93	QP		
5		506.2700	17.64	21.43	39.07	46.00	-6.93	QP		
6		613.9400	15.82	23.32	39.14	46.00	-6.86	QP		


\*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310

**Radiated Emission Measurement**



Site Chamber #1 Polarization: **Vertical** Temperature: 26  
 Limit: FCC Part 15 B 3M Radiation Power: DC 5V Adapter AC 120V/60Hz Humidity: 61 %  
 EUT: Tablet PC Distance:  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: GP302E-050-200

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Detector	Comment
1	*	33.8800	14.67	21.81	36.48	40.00	-3.52			QP	
2	!	74.6200	24.44	11.65	36.09	40.00	-3.91			QP	
3		97.9000	22.11	12.72	34.83	43.50	-8.67			QP	
4		163.8600	13.18	17.23	30.41	43.50	-13.09			QP	
5		384.0500	15.41	18.18	33.59	46.00	-12.41			QP	
6		557.6798	14.15	22.70	36.85	46.00	-9.15			QP	

\*:Maximum data x:Over limit !:over margin


Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park  
Guangdong, China  
Tel: 0755-86170306 Fax: 0755-86170310

**Radiated Emission Measurement**

File: PTT-826D Data: #19 Date: 2012-8-27 Time: 15:49:27



Site Chamber #1 Polarization: **Horizontal** Temperature: 26  
 Limit: FCC Part 15 B 3M Radiation Power: DC 5V Adapter AC 120V/60Hz Humidity: 61 %  
 EUT: Tablet PC Distance:  
 M/N: PTT-826D  
 Mode: WIFI Mode  
 Note: GP302E-050-200

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Detector	Comment
1	*	73.6500	19.87	11.66	31.53	40.00	-8.47			QP	
2		156.0999	14.75	16.91	31.66	43.50	-11.84			QP	
3		219.1500	19.30	16.26	35.56	46.00	-10.44			QP	
4		249.2199	15.80	17.40	33.20	46.00	-12.80			QP	
5		384.0500	15.45	18.18	33.63	46.00	-12.37			QP	
6		545.0700	14.93	22.30	37.23	46.00	-8.77			QP	

\*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen

**Above 1 GHz**

**Operation Mode:** TX/ IEEE 802.11b/CH Low      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4824.0	H	34.01	24.02	23.67	57.68	47.69	74.00	54.00	-7.31
N/A	H								
4824.0	V	33.26	23.59	22.94	56.20	46.53	74.00	54.00	-7.47
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11b/CH MID      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak	AV			
					(dBuV/m)	(dBuV/m)			
4884.0	H	37.07	27.15	23.54	60.61	50.69	74.00	54.00	-4.69
N/A	H								
4884.0	V	36.34	26.28	23.36	59.70	49.64	74.00	54.00	-4.36
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11b/CH High      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4924.0	H	33.50	22.39	23.54	57.04	45.93	74.00	54.00	-8.07
N/A	H								
4924.0	V	33.04	23.32	23.36	56.40	46.68	74.00	54.00	-7.32
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11g/CH Low      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4824.0	H	32.24	23.97	23.78	56.02	47.75	74.00	54.00	-7.25
N/A	H								
4824.0	V	32.23	22.18	24.01	56.24	46.19	74.00	54.00	-8.81
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11g/CH MID      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4884.0	H	33.35	24.04	23.78	57.13	47.82	74.00	54.00	-6.18
N/A	H								
4884.0	V	32.50	23.65	24.01	56.51	47.66	74.00	54.00	-7.34
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11g/CH High      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4924.0	H	33.22	23.19	23.78	57.00	46.97	74.00	54.00	-7.03
N/A	H								
4924.0	V	33.06	21.14	24.01	57.07	45.15	74.00	54.00	-8.85
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11n/CH Low      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4824.0	H	31.30	23.93	24.02	55.32	47.95	74.00	54.00	-6.05
N/A	H								
4824.0	V	32.00	22.06	24.68	56.68	46.74	74.00	54.00	-7.26
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11n/CH MID      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4884.0	H	31.98	22.71	24.02	56.00	46.73	74.00	54.00	-7.27
N/A	H								
4884.0	V	31.04	21.12	24.68	55.72	45.80	74.00	54.00	-8.20
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6 Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX/ IEEE 802.11n/CH High      **Test Date:** Aug. 27, 2012  
**Temperature:** 20°C      **Tested by:** Habby Guo  
**HuTablet PCity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4924.0	H	31.23	23.82	24.02	55.25	47.84	74.00	54.00	-6.16
N/A	H								
4924.0	V	30.06	21.94	24.68	54.74	45.62	74.00	54.00	-8.38
N/A	V								

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**APPENDIX 1**  
**PHOTOGRAPHS OF TEST SETUP**

CONDUCTED SPURIOUS EMISSION TEST SETUP



-----END OF REPORT-----