



No. 1 Workshop, M-10, Middle Section, Science & Technology Park,
District Shenzhen, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: sgs_internet_operations@sgs.com
FEDERAL COMMUNICATIONS COMMISSION
Registration number: 556682

Report No.: SZEMO09070439701
Page: 1 of 21

TEST REPORT

Application No.: SZEMO090704397RF
Applicant: Shenzhen Fuyeda Industry Development Corp.
Manufacturer/ Factory: Shenzhen Fuyeda Industry Development Corp.
Buyer: Lenovo (Beijing) Limited
FCC ID: V4P-KB803RF
Fundamental Carrier Frequency : 2.402GHz to 2.480GHz

Equipment Under Test (EUT):

Name: Keyboard

Model: KM401/KB-803RF ♣



Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Standards: FCC PART 15: 2008

Date of Receipt: 30 July 2009

Date of Test: 05 to 13 August 2009

Date of Issue: 17 August 2009

| | |
|----------------------|---------------|
| Test Result : | PASS * |
|----------------------|---------------|

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Test Summary

| Test | Test Requirement | Standard Paragraph | Result |
|--|--------------------|---|--------|
| Flid Strength of Fundamental | FCC PART 15 : 2008 | Section 15.249 (a) | PASS |
| Flid Strength of Harmonics or other Frequency Emission | FCC PART 15 : 2008 | Section 15.249 (a) Section 15.209/15.205 | PASS |
| Occupied Bandwidth | FCC PART 15 : 2008 | Section 15.249 | PASS |

Remark:

Item No.: KM401/KB-803RF

Only the Item KM401 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items.



3 Contents

| | Page |
|---|-------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 CLIENT INFORMATION | 4 |
| 4.2 GENERAL DESCRIPTION OF E.U.T | 4 |
| 4.3 DESCRIPTION OF SUPPORT UNITS | 4 |
| 4.4 STANDARDS APPLICABLE FOR TESTING | 4 |
| 4.5 TEST LOCATION | 4 |
| 4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 4 |
| 4.7 TEST FACILITY | 5 |
| 5 TEST RESULTS | 6 |
| 5.1 TEST INSTRUMENTS | 6 |
| 5.2 E.U.T. OPERATION | 7 |
| 5.3 TEST PROCEDURE & MEASUREMENT DATA | 8 |
| 5.3.1 Radiated Emissions | 8 |
| 5.3.2 Transmit spurious emissions | 10 |
| 5.3.3 Occupied Bandwidth | 20-21 |



4 General Information

4.1 Client Information

Applicant: Shenzhen Fuyeda Industry Development Corp.
Manufacturer/ Factory: Shenzhen Fuyeda Industry Development Corp.
Address of Applicant: No.1 NEWMEN ROAD. TONGSHENG VILLAGE, DALANG STREET, BAO'AN, SHENZHEN, CHINA
Address of Manufacturer/ Factory: No.1 NEWMEN ROAD. TONGSHENG VILLAGE, DALANG STREET, BAO'AN, SHENZHEN, CHINA
Buyer: Lenovo (Beijing) Limited
Address of Buyer: No.6 Shang Di Chuang Ye Road, Haidian District, Beijing, China

4.2 General Description of E.U.T

Product Name: Keyboard
Model: KM401/KB-803RF
Power Supply: DC3.0V(2*1.5V"AAA"Size Batteries)
Power Cord: N/A-

4.3 Description of Support Units

The EUT was tested with associated equipment below:

| Description | Manufacturer | Model No. | Remark |
|----------------|--------------|--------------|--------|
| PC | DELL | OPTIPLEX 755 | DoC |
| LCD-displaying | DELL | E1909WF | DoC |
| KEYBOARD | DELL | SK-8115 | DoC |

4.4 Standards Applicable for Testing

The customer requested FCC tests for a 2.4G wireless keyboard.

The standard used was FCC PART 15, SUBPART C: 2008 section 15.249.

4.5 Test Location

All tests were performed at:

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.6 Other Information Requested by the Customer

None.

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations

- **CNAS (No. CNAS L2929)**
CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.
- **VCCI**
The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.
Date of Registration: September 29, 2008. Valid until September 28, 2011.
- **FCC – Registration No.: 556682**
SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.
- **Industry Canada (IC)**
The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.



5 Test Results

5.1 Test Instruments

| RE in Chamber | | | | | | |
|---------------|--------------------------------|----------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (dd-mm-yy) | Cal.Due date (dd-mm-yy) |
| 1 | 3m Semi-Anechoic Chamber | ETS-LINDGREN | N/A | SEL0017 | 16-06-2009 | 15-06-2010 |
| 2 | EMI Test Receiver | Rohde & Schwarz | ESIB26 | SEL0023 | 12-12-2008 | 11-12-2009 |
| 3 | EMI Test software | AUDIX | E3 | SEL0050 | N/A | N/A |
| 4 | Coaxial cable | SGS | N/A | SEL0028 | 18-06-2009 | 17-06-2010 |
| 5 | BiConiLog Antenna (26-3000MHz) | ETS-LINDGREN | 3142C | SEL0014 | 12-08-2009 | 11-08-2010 |
| 6 | Pre-amplifier (0.1-1300MHz) | Agilent Technologies | 8447D | SEL0053 | 18-06-2009 | 17-06-2010 |
| 7 | Double-ridged horn (1-18GHz) | ETS-LINDGREN | 3117 | SEL0005 | 12-08-2009 | 11-08-2010 |
| 8 | Horn Antenna (18-26GHz) | ETS-LINDGREN | 3160 | SEL0076 | 12-08-2009 | 11-08-2010 |
| 9 | Pre-amplifier (1-18GHz) | Rohde & Schwarz | AFS42-00101 800-25-S-42 | SEL0081 | 18-06-2009 | 17-06-2010 |
| 10 | Pre-amplifier (18-26GHz) | Rohde & Schwarz | AFS33-18002 650-30-8P-44 | SEL0080 | 18-06-2009 | 17-06-2010 |
| 11 | Band filter | Amindeon | 82346 | SEL0094 | 18-06-2009 | 17-06-2010 |
| 12 | Active Loop Antenna | Beijing Daze | ZN30900A | SEL0097 | 15-06-2009 | 14-06-2010 |



5.2 E.U.T. Operation

| | |
|------------------------|-----------------------------------|
| Input voltage: | DC3.0V(2*1.5V"AAA"Size Batteries) |
| Operating Environment: | |
| Temperature: | 24°C |
| Humidity: | 50 % RH |
| Atmospheric Pressure: | 1010 mbar |
| EUT Operation: | Test in transmitting mode: |
| | 1. For lowest channel: 2.402GHz. |
| | 2. For middle channel: 2.448GHz. |
| | 3. For highest channel: 2.480GHz. |

5.3 Test Procedure & Measurement Data

5.3.1 Radiated Emissions

Test Requirement: FCC Part15.209
 Test Method: ANSI C63.4: 2003
 Measurement Distance: 3m (Semi-Anechoic Chamber)
 Frequency range: 30 MHz – 25GHz
 operation mode: Keep the EUT connected to other device.
 Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)
 Test Range: 30MHz to 25GHz

| Frequency range | RBW | VBW | Dector |
|-----------------|--------|--------|--------|
| 30MHz-1GHz | 120KHz | 300KHz | QP |
| above 1GHz | 1MHz | 3MHz | Peak |

Limit:

40.0 dB μ V/m between 30MHz & 88MHz
 43.5 dB μ V/m between 88MHz & 216MHz
 46.0 dB μ V/m between 216MHz & 960MHz
 54.0 dB μ V/m between 960Hz & 1GHz
 above 1GHz: Average value Limit 54.0 dB μ V/m
 Peak value Limit 74.0 dB μ V/m.

Operation: Receive antenna scan height 1 - 4 m, polarization Vertical/ Horizontal

Test Procedure:

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
- 7 The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.



Operation mode

Vertical:

| Frequency (MHz) | Cable Loss (dB) | Antenn a Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Remark |
|-----------------|-----------------|------------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------|
| 98.870 | 1.19 | 9.06 | 27.89 | 28.27 | 10.63 | 43.50 | -32.87 | QP |
| 129.910 | 1.28 | 7.70 | 27.61 | 29.50 | 10.87 | 43.50 | -32.63 | QP |
| 431.580 | 2.33 | 16.52 | 27.51 | 30.15 | 21.49 | 46.00 | -24.51 | QP |
| 656.620 | 2.82 | 20.84 | 27.42 | 33.94 | 30.18 | 46.00 | -15.82 | QP |
| 709.000 | 2.93 | 21.60 | 27.25 | 32.96 | 30.24 | 46.00 | -15.76 | QP |
| 797.270 | 3.19 | 22.09 | 26.95 | 34.96 | 33.29 | 46.00 | -12.71 | QP |
| 1365.00 | 4.48 | 26.69 | 38.99 | 40.24 | 32.42 | 74.00 | -41.58 | PK |
| 1365.00 | 4.48 | 26.69 | 38.99 | 28.5 | 20.68 | 54.00 | -33.32 | AV |
| 2705.00 | 6.19 | 31.03 | 39.03 | 39.78 | 37.97 | 74.00 | -36.03 | PK |
| 2705.00 | 6.19 | 31.03 | 39.03 | 32.4 | 30.59 | 54.00 | -23.41 | AV |

Horizontal

| Frequency (MHz) | Cable Loss (dB) | Antenn a Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Remark |
|-----------------|-----------------|------------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------|
| 32.910 | 0.60 | 13.84 | 28.16 | 35.36 | 21.64 | 40.00 | -18.36 | QP |
| 63.950 | 0.80 | 7.07 | 28.03 | 35.42 | 15.26 | 40.00 | -24.74 | QP |
| 109.540 | 1.23 | 8.62 | 27.78 | 33.54 | 15.61 | 43.50 | -27.89 | QP |
| 122.150 | 1.26 | 7.85 | 27.67 | 33.57 | 15.01 | 43.50 | -28.49 | QP |
| 382.110 | 2.15 | 16.08 | 27.30 | 27.25 | 18.18 | 46.00 | -27.82 | QP |
| 797.270 | 3.19 | 22.09 | 26.95 | 36.40 | 34.73 | 46.00 | -11.27 | QP |
| 1235.00 | 4.4 | 26.2 | 39.15 | 41.77 | 33.22 | 74.00 | -40.87 | PK |
| 1235.00 | 4.4 | 26.2 | 39.15 | 30.81 | 22.26 | 54.00 | -31.74 | AV |
| 2795.00 | 6.42 | 31.32 | 39.01 | 40.72 | 39.45 | 74.00 | -34.55 | PK |
| 2795.00 | 6.42 | 31.32 | 39.01 | 28.6 | 27.33 | 54.00 | -26.67 | AV |

5.3.2 Transmit spurious emissions

Test Requirement: FCC Part15.249,15.209 and 15.205
 Test Method: ANSI C63.4: 2003
 Test channel: The lowest channel, the middle channel, the highest channel.
 Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)
 Test Range: 30MHz to 25GHz

| Frequency range | RBW | VBW | Remark |
|-----------------|--------|--------|---------|
| 30MHz-1GHz | 120KHz | 300KHz | QP |
| above 1GHz | 1MHz | 3MHz | Peak |
| | 1MHz | 10Hz | average |

Limit:
 40.0 dB μ V/m between 30MHz & 88MHz
 43.5 dB μ V/m between 88MHz & 216MHz
 46.0 dB μ V/m between 216MHz & 960MHz
 54.0 dB μ V/m between 960Hz & 1GHz
 above 1GHz: Average value Limit 54.0 dB μ V/m
 Peak value Limit 74.0 dB μ V/m.

Operation: Receive antenna scan height 1 - 4 m, polarization Vertical/ Horizontal

| Fundamental Frequency (MHz) | Field Strength of Fundamental (dB μ V/m @ 3m) | Field Strength of Harmonics and Spurious Emissions (dB μ V/m @ 3m) |
|--------------------------------|---|--|
| 902 to 928 | 94.0 | 54.0 |
| 2400 to 2483.5 | 94.0 | 54.0 |
| 5725 to 5875 | 94.0 | 54.0 |
| 24000 to 24250 | 108.0 | 68.0 |

The fundamental frequency of the EUT is 2.402GHz to 2.480GHz

The limit for average field strength dB μ V/m for the fundamental frequency = 94.0 dB μ V/m.


No fundamental is allowed in the restricted bands.

Test Procedure:


1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
- 7 The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Configuration:

Below 1GHz



Above 1GHz





SGS-CSTC Standards Technical Services Co., Ltd.

Report No.: SZEMO09070439701

Page: 12 of 21

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

1. The following test results were performed at below 1GHz

For 2402MHz

| Frequency (MHz) | Cable Loss (dB) | Antenna Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-----------------|-----------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------------|
| 96.18 | 1.16 | 8.95 | 27.91 | 29.70 | 11.90 | 43.50 | -31.60 | Vertical |
| 365.28 | 2.11 | 15.78 | 27.20 | 29.74 | 20.43 | 46.00 | -25.57 | Vertical |
| 439.38 | 2.37 | 16.68 | 27.54 | 31.01 | 22.52 | 46.00 | -23.48 | Vertical |
| 199.53 | 1.40 | 10.19 | 27.15 | 32.29 | 16.73 | 43.50 | -26.77 | Horizontal |
| 233.65 | 1.59 | 11.79 | 26.99 | 35.02 | 21.41 | 46.00 | -24.59 | Horizontal |
| 873.25 | 3.50 | 22.92 | 26.57 | 30.81 | 30.66 | 46.00 | -15.34 | Horizontal |

For 2448MHz

| Frequency (MHz) | Cable Loss (dB) | Antenna Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-----------------|-----------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------------|
| 150.78 | 1.32 | 9.04 | 27.45 | 29.65 | 12.56 | 43.50 | -30.94 | Vertical |
| 191.73 | 1.39 | 10.11 | 27.20 | 38.47 | 22.77 | 43.50 | -20.73 | Vertical |
| 744.55 | 3.04 | 21.68 | 27.12 | 31.49 | 29.09 | 46.00 | -16.91 | Vertical |
| 89.35 | 1.10 | 8.64 | 27.95 | 29.55 | 11.34 | 43.50 | -32.16 | Horizontal |
| 455.95 | 2.43 | 17.09 | 27.58 | 30.85 | 22.79 | 46.00 | -23.21 | Horizontal |
| 733.83 | 3.00 | 21.63 | 27.16 | 29.88 | 27.35 | 46.00 | -18.65 | Horizontal |

For 2480MHz

| Frequency (MHz) | Cable Loss (dB) | Antenna Factor (dB/m) | Preamp Factor (dB) | Read Level (dBuV) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-----------------|-----------------------|--------------------|-------------------|----------------|---------------------|-----------------|--------------|
| 173.20 | 1.36 | 9.63 | 27.30 | 33.61 | 17.30 | 43.50 | -26.20 | Vertical |
| 311.65 | 1.94 | 14.33 | 26.81 | 35.37 | 24.83 | 46.00 | -21.17 | Vertical |
| 610.00 | 2.72 | 20.05 | 27.58 | 30.12 | 25.31 | 46.00 | -20.69 | Vertical |
| 140.05 | 1.30 | 8.10 | 27.52 | 29.54 | 11.42 | 43.50 | -32.08 | Horizontal |
| 326.28 | 1.99 | 14.83 | 26.93 | 29.02 | 18.91 | 46.00 | -27.09 | Horizontal |
| 581.73 | 2.68 | 19.27 | 27.63 | 29.56 | 23.88 | 46.00 | -22.12 | Horizontal |

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2. The following test results were performed at above 1GHz

For 2402MHz:

Harmonics & Spurious Emissions

Peak Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2402.10 | 4.97 | 32.25 | 0.00 | 60.75 | 97.97 | 114.00 | -16.03 | Vertical |
| 2198.50 | 4.71 | 32.13 | 44.71 | 60.17 | 52.30 | 74.00 | -21.70 | Vertical |
| 2398.73 | 4.97 | 32.25 | 44.75 | 59.99 | 52.46 | 74.00 | -21.54 | Vertical |
| 2400.00 | 4.97 | 32.25 | 44.75 | 60.54 | 53.01 | 74.00 | -20.99 | Vertical |
| 4808.00 | 6.61 | 34.04 | 45.40 | 48.35 | 43.60 | 74.00 | -30.40 | Vertical |
| 7222.00 | 7.63 | 36.29 | 44.49 | 44.71 | 44.14 | 74.00 | -29.86 | Vertical |
| 9619.00 | 8.53 | 36.99 | 42.20 | 43.61 | 46.93 | 74.00 | -27.07 | Vertical |
| 2402.10 | 4.97 | 32.25 | 0.00 | 48.46 | 85.68 | 114.00 | -28.32 | Horizontal |
| 2245.50 | 4.77 | 32.16 | 44.72 | 51.77 | 43.98 | 74.00 | -30.02 | Horizontal |
| 2398.73 | 4.97 | 32.25 | 44.75 | 52.19 | 44.66 | 74.00 | -29.34 | Horizontal |
| 2400.00 | 4.97 | 32.25 | 44.75 | 53.68 | 46.15 | 74.00 | -27.85 | Horizontal |
| 4808.00 | 6.61 | 34.04 | 45.40 | 48.81 | 44.06 | 74.00 | -29.94 | Horizontal |
| 7222.00 | 7.63 | 36.29 | 44.49 | 45.71 | 45.14 | 74.00 | -28.86 | Horizontal |
| 9619.00 | 8.53 | 36.99 | 42.20 | 44.34 | 47.66 | 74.00 | -26.34 | Horizontal |



Average Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2402.10 | 4.97 | 32.25 | 0.00 | 27.49 | 64.71 | 94.00 | -29.29 | Vertical |
| 2257.35 | 4.80 | 32.16 | 44.72 | 36.32 | 28.56 | 54.00 | -25.44 | Vertical |
| 2397.73 | 4.97 | 32.25 | 44.75 | 35.55 | 28.02 | 54.00 | -25.98 | Vertical |
| 2400.00 | 4.97 | 32.25 | 44.75 | 37.28 | 29.75 | 54.00 | -24.25 | Vertical |
| 4808.00 | 6.61 | 34.04 | 45.40 | 34.43 | 29.68 | 54.00 | -24.32 | Vertical |
| 7222.00 | 7.63 | 36.29 | 44.49 | 34.20 | 33.63 | 54.00 | -20.37 | Vertical |
| 9619.00 | 8.53 | 36.99 | 42.20 | 29.93 | 33.25 | 54.00 | -20.75 | Vertical |
| 2402.10 | 4.97 | 32.25 | 0.00 | 27.39 | 64.61 | 94.00 | -29.39 | Horizontal |
| 2257.25 | 4.80 | 32.16 | 44.72 | 36.45 | 28.69 | 54.00 | -25.31 | Horizontal |
| 2398.37 | 4.97 | 32.25 | 44.75 | 35.58 | 28.05 | 54.00 | -25.95 | Horizontal |
| 2400.00 | 4.97 | 32.25 | 44.75 | 37.99 | 30.46 | 54.00 | -23.54 | Horizontal |
| 4808.00 | 6.61 | 34.04 | 45.40 | 34.43 | 29.68 | 54.00 | -24.32 | Horizontal |
| 7222.00 | 7.63 | 36.29 | 44.49 | 34.20 | 33.63 | 54.00 | -20.37 | Horizontal |
| 9619.00 | 8.53 | 36.99 | 42.20 | 29.93 | 33.25 | 54.00 | -20.75 | Horizontal |



For 2448MHz:

. Harmonics & Spurious Emissions

Peak Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2448.71 | 5.03 | 32.27 | 0.00 | 46.08 | 83.38 | 114.00 | -30.62 | Vertical |
| 4876.00 | 6.64 | 34.02 | 45.42 | 50.18 | 45.42 | 74.00 | -28.58 | Vertical |
| 7324.00 | 7.58 | 36.10 | 44.39 | 44.73 | 44.02 | 74.00 | -29.98 | Vertical |
| 9772.00 | 8.65 | 37.12 | 42.06 | 43.10 | 46.81 | 74.00 | -27.19 | Vertical |
| 12220.00 | 10.17 | 38.93 | 43.59 | 43.15 | 48.66 | 74.00 | -25.34 | Vertical |
| 14634.00 | 11.34 | 39.60 | 45.40 | 47.56 | 53.10 | 74.00 | -20.90 | Vertical |
| 17082.00 | 12.83 | 41.08 | 42.95 | 42.18 | 53.14 | 74.00 | -20.86 | Vertical |
| 2448.71 | 5.03 | 32.27 | 0.00 | 43.55 | 80.85 | 114.00 | -33.15 | Horizontal |
| 4876.00 | 6.64 | 34.02 | 45.42 | 50.20 | 45.44 | 74.00 | -28.56 | Horizontal |
| 7324.00 | 7.58 | 36.10 | 44.39 | 43.92 | 43.21 | 74.00 | -30.79 | Horizontal |
| 9772.00 | 8.65 | 37.12 | 42.06 | 43.55 | 47.26 | 74.00 | -26.74 | Horizontal |
| 12220.00 | 10.17 | 38.93 | 43.59 | 43.01 | 48.52 | 74.00 | -25.48 | Horizontal |
| 14447.00 | 11.23 | 39.45 | 45.53 | 45.10 | 50.25 | 74.00 | -23.75 | Horizontal |
| 17082.00 | 12.83 | 41.08 | 42.95 | 43.07 | 54.03 | 74.00 | -19.97 | Horizontal |



Average Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2448.71 | 5.08 | 32.29 | 0.00 | 39.70 | 77.07 | 94.00 | -16.93 | Vertical |
| 4876.00 | 6.64 | 34.02 | 45.42 | 34.93 | 30.17 | 54.00 | -23.83 | Vertical |
| 7324.00 | 7.58 | 36.10 | 44.39 | 31.96 | 31.25 | 54.00 | -22.75 | Vertical |
| 9772.00 | 8.65 | 37.12 | 42.06 | 30.67 | 34.38 | 54.00 | -19.62 | Vertical |
| 12220.00 | 10.17 | 38.93 | 43.59 | 30.51 | 36.02 | 54.00 | -17.98 | Vertical |
| 14685.00 | 11.39 | 39.67 | 45.36 | 32.86 | 38.56 | 54.00 | -15.44 | Vertical |
| 17082.00 | 12.83 | 41.08 | 42.95 | 31.22 | 42.18 | 54.00 | -11.82 | Vertical |
| 2448.71 | 5.08 | 32.29 | 0.00 | 40.00 | 77.37 | 94.00 | -16.63 | Horizontal |
| 4876.00 | 6.64 | 34.02 | 45.42 | 34.95 | 30.19 | 54.00 | -23.81 | Horizontal |
| 7324.00 | 7.58 | 36.10 | 44.39 | 31.97 | 31.26 | 54.00 | -22.74 | Horizontal |
| 9772.00 | 8.65 | 37.12 | 42.06 | 30.70 | 34.41 | 54.00 | -19.59 | Horizontal |
| 12220.00 | 10.17 | 38.93 | 43.59 | 30.54 | 36.05 | 54.00 | -17.95 | Horizontal |
| 14634.00 | 11.34 | 39.60 | 45.40 | 32.71 | 38.25 | 54.00 | -15.75 | Horizontal |
| 17082.00 | 12.83 | 41.08 | 42.95 | 31.24 | 42.20 | 54.00 | -11.80 | Horizontal |



For 2480MHz:

Harmonics & Spurious Emissions

Peak Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2480.00 | 5.08 | 32.29 | 0.00 | 49.70 | 87.07 | 114.00 | -26.93 | Vertical |
| 2483.50 | 5.08 | 32.29 | 44.77 | 50.70 | 43.30 | 74.00 | -30.70 | Vertical |
| 2492.25 | 5.10 | 32.30 | 44.78 | 45.71 | 38.33 | 74.00 | -35.67 | Vertical |
| 4961.00 | 6.68 | 34.01 | 45.44 | 47.25 | 42.50 | 74.00 | -31.50 | Vertical |
| 7443.00 | 7.52 | 35.91 | 44.26 | 46.94 | 46.11 | 74.00 | -27.89 | Vertical |
| 9925.00 | 8.77 | 37.23 | 41.92 | 42.17 | 46.25 | 74.00 | -27.75 | Vertical |
| 12424.00 | 10.24 | 39.06 | 43.85 | 45.20 | 50.65 | 74.00 | -23.35 | Vertical |
| 2480.00 | 5.08 | 32.29 | 0.00 | 50.24 | 87.61 | 114.00 | -26.39 | Horizontal |
| 2483.50 | 5.08 | 32.29 | 44.77 | 48.00 | 40.60 | 74.00 | -33.40 | Horizontal |
| 2492.25 | 5.10 | 32.32 | 44.78 | 45.11 | 37.75 | 74.00 | -36.25 | Horizontal |
| 4961.00 | 6.68 | 34.01 | 45.44 | 47.77 | 43.02 | 74.00 | -30.98 | Horizontal |
| 7443.00 | 7.52 | 35.91 | 44.26 | 47.17 | 46.34 | 74.00 | -27.66 | Horizontal |
| 9925.00 | 8.77 | 37.23 | 41.92 | 42.15 | 46.23 | 74.00 | -27.77 | Horizontal |
| 12424.00 | 10.24 | 39.06 | 43.85 | 45.58 | 51.03 | 74.00 | -22.97 | Horizontal |



Average Measurement

| Frequency (MHz) | Cable loss (dB) | Antenna factors (dB/m) | Preamplifier factor (dB) | Reading Level (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over limit | polarization |
|-----------------|-----------------|------------------------|--------------------------|----------------------|-------------------------|----------------|------------|--------------|
| 2480.00 | 5.08 | 32.29 | 0.00 | 27.10 | 64.47 | 94.00 | -29.53 | Vertical |
| 2483.50 | 5.08 | 32.29 | 44.77 | 39.10 | 31.70 | 54.00 | -22.30 | Vertical |
| 2492.25 | 5.10 | 32.30 | 44.78 | 36.73 | 29.35 | 54.00 | -24.65 | Vertical |
| 4961.00 | 6.68 | 34.01 | 45.44 | 35.01 | 30.26 | 54.00 | -23.74 | Vertical |
| 7443.00 | 7.52 | 35.91 | 44.26 | 32.00 | 31.17 | 54.00 | -22.83 | Vertical |
| 9925.00 | 8.77 | 37.23 | 41.92 | 29.98 | 34.06 | 54.00 | -19.94 | Vertical |
| 12424.00 | 10.24 | 39.06 | 43.85 | 31.04 | 36.49 | 54.00 | -17.51 | Vertical |
| 2480.00 | 5.08 | 32.29 | 0.00 | 27.71 | 65.08 | 94.00 | -28.92 | Horizontal |
| 2483.50 | 5.08 | 32.29 | 44.77 | 39.00 | 31.60 | 54.00 | -22.40 | Horizontal |
| 2492.25 | 5.10 | 32.30 | 44.78 | 36.64 | 29.26 | 54.00 | -24.74 | Horizontal |
| 4961.00 | 6.68 | 34.01 | 45.44 | 35.01 | 30.26 | 54.00 | -23.74 | Horizontal |
| 7443.00 | 7.52 | 35.91 | 44.26 | 32.00 | 31.17 | 54.00 | -22.83 | Horizontal |
| 9925.00 | 8.77 | 37.23 | 41.92 | 29.96 | 34.04 | 54.00 | -19.96 | Horizontal |
| 12424.00 | 10.24 | 39.06 | 43.85 | 31.04 | 36.49 | 54.00 | -17.51 | Horizontal |



N/A: refer to remark 1).

Remark:

- 1). For this intentional radiator operates below 10 GHz, the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the fifth harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 6th harmonic.
- 2). According to 15.249 (e) As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

TEST RESULTS: The unit does meet the FCC requirements.



5.3.3 Occupied Bandwidth


Test Requirement: FCC Part 15.249

Test Method: ANSI C63.4: 2003

Operation within the band 2400– 2483.5GHz


The occupied bandwidth as below:

1. For 2402MHz:




Date: 6.AUG.2009 23:17:45

2. For 2448MHz:



Date: 6.AUG.2009 23:19:10

3. For 2480MHz:



Date: 6.AUG.2009 23:20:45