Г	1	2	3			4			5	6	
A				65 m	ım		_				A
В	}	- 40 mm	Operation is su (1) this device (2) this device	 1A R5500UN	&68 of the F ng two condi mful interfere terference re	itions: ence eceived,					В
с										Դ๏ TONE 3278C TONE 424C	С
D	 (Material:50#Bright white e no bubble,UV coated,adhe 3. 原材料及后处理工艺均能 (Raw materials and the corres) 	Γ,耐85度高温测试不起泡,过 embossing PET,Heat resistant o	of at least 85 °C, 長求 eet requirements	TOL± Z RANGE C1 0~6 0.1 6~30 0.2 30~80 0.2 80~180 0.3 180~315 0.5 315~500 0.7 500~800 0.5 ANG.TOL± 0*-30	1 C2 1 0.1 2 0.3 5 0.5 3 0.8 5 1.3 7 1.5 9 1.8	C3 C4 0.15 0.2 0.4 0.5 0.9 1.2 1.2 1.5 1.8 3 2.5 4 3 5 3° 60°-90°/0.5°	サレン TITLE: 印刷盒 床标贴 UNIT'S mm MAT'L XXXX FINISH N/A	VER: SCALE	M R5500 ^{A0} N/A		
	1	2	3			4			5	6	

