



Engineering and Testing for EMC and Safety Compliance



Accredited under A2LA Testing Certificate # 2653.01

FCC Part 15.231 Certification Application Report

Test Lab:		Applicant:	
Rhein Tech Laboratories, Inc.	Phone: 703-689-0368	Sequel Technologies, LLC	Phone: 651-342-0390
360 Herndon Parkway	Fax: 703-689-2056	8014 Olson Memorial Highway	
Suite 1400	Web: www.rheintech.com	Suite 401	
Herndon, VA 20170		Golden Valley, MN 55427	
Email: atcbinfo@rheintech.com		Contact: Ted Nesse	
FCC ID	V4X-STEX01	Test Report Date	June 29, 2008
Platform	N/A	RTL Work Order Number	2008068
Model #	STCP-STE	RTL Quote Number	QRTL08-208
FCC Classification	DSC – Part 15 Security/Remote Control Transmitter		
FCC Rule Part(s)	Part 15.231: Periodic operation in the band 40.66 – 40.70 MHz and above 70 MHz (10-01-07)		
Procedure or Other Guidance	ANSI C63.4-2003 Standard for Methods of Measurement of Radio-Noise Emissions		
Digital Interface Information	Digital Interface was found to be compliant		
Receiver Information	Receiver was found to be compliant		
Frequency Range (MHz)	Output Power (W)	Frequency Tolerance	Emission Designator
319.5 and 345.0	N/A	N/A	N/A

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. Modifications made to the equipment during testing in order to achieve compliance with these standards are listed in the report.

Furthermore, there was no deviation from, additions to, or exclusions from the applicable parts of FCC Part 2, FCC Part 15 and ANSI C63.4.

Signature:

Date: June 29, 2008

Typed/Printed Name: Desmond A. Fraser

Position: President

This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and Sequel Technologies. The test results reported relate only to the item tested.

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Table of Contents

1	General Information	5
1.1	Scope	5
1.2	Modifications	5
1.3	Test Facility	5
1.4	Related Submittal(s)/Grant(s)	5
2	Test Information	6
2.1	Test Justification	6
2.2	Exercising the EUT	6
2.3	Test Result Summary	6
2.4	Test System Details	6
2.5	Configuration of Tested System	7
3	Duty Cycle Calculation - FCC §15.35(c)	7
4	Transmitter Deactivation – FCC §15.231(a)(2)	9
5	Modulated Bandwidth – FCC §15.231(c)	10
5.1	Modulated Bandwidth Test Procedure	10
5.2	FCC §15.231(c) Limits	10
5.3	Modulated Bandwidth Test Data	10
6	Radiated Emissions – FCC §15.209, §15.231	13
6.1	Radiated Fundamental Emissions Test Procedure	13
6.1.1	Radiated Fundamental Emissions Limits Test Data	13
6.2	Radiated Harmonics/Spurious Emissions – FCC §15.231	13
6.2.1	Radiated Emissions Harmonics/Spurious Test Procedure	13
7	Conducted Emissions	17
7.1	Site and Test Description	17
7.2	Test Limits	17
7.3	Conducted Emissions Test Results	18
8	Conclusion	19

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Table Index

Table 2-1:	Test Result Summary with FCC Rules and Regulations	6
Table 2-2:	Equipment Under Test (EUT).....	6
Table 5-1:	20 dB Modulated Bandwidths	10
Table 5-2:	Modulated Bandwidth Test Equipment	12
Table 6-1:	Radiated Fundamental Emissions	13
Table 6-2:	Radiated Spurious Harmonics; 319.5 MHz	14
Table 6-3:	Radiated Spurious Harmonics; 345 MHz	15
Table 6-4:	Radiated Emissions Test Equipment	16
Table 7-1:	Conducted Emissions – Neutral (Line 1).....	18
Table 7-2:	Conducted Emissions – Hot (Line 2).....	18
Table 7-3:	AC Line Conducted Emissions Test Equipment.....	19

Figure Index

Figure 2-1:	Worst Case Configuration of System under Test.....	7
-------------	--	---

Plot Index

Plot 3-1:	Total Pulse Train Length – 21.67 ms.....	8
Plot 3-2:	Total Pulse on Time within 21.67 ms Pulse Train Less than 47%.....	8
Plot 4-1:	Transmitter Deactivation	9
Plot 5-1:	Modulated Bandwidth – 319.5 MHz.....	11
Plot 5-2:	Modulated Bandwidth – 345.0 MHz.....	11

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Appendix Index

Appendix A:	FCC/TCB Agency Authorization Letter	20
Appendix B:	FCC Confidentiality Request Letter	21
Appendix C:	ID Label and Label Location	22
Appendix D:	Operational Description	23
Appendix E:	Schematics	24
Appendix F:	Block Diagram	25
Appendix G:	Manual	26
Appendix H:	Test Photographs	27
Appendix I:	External Photographs	30
Appendix J:	Internal Photographs	32

Photograph Index

Photograph 1:	ID Label Sample and Location	22
Photograph 2:	Radiated Emissions - Front	27
Photograph 3:	Radiated Emissions - Back	28
Photograph 4:	AC Line Conducted Emissions	29
Photograph 5:	Front	30
Photograph 6:	Back	31
Photograph 7:	Cover Removed	32
Photograph 8:	Front of Transmitter Showing Antenna	33
Photograph 9:	Top of TX PCB	34
Photograph 10:	Bottom of TX PCB	35
Photograph 11:	Front of Digital PCB	36
Photograph 12:	Back of Digital PCB	37
Photograph 13:	Front of Keypad and PCB	38
Photograph 14:	Back of Keypad and PCB	39

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

1 General Information

1.1 Scope

FCC Rules Part 15.231: Periodic operation in the band 40.66–40.70 MHz and above 70 MHz.

1.2 Modifications

N/A

1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Rhein Tech Laboratories, Inc. (RTL), 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4 2003).

1.4 Related Submittal(s)/Grant(s)

This is an original certification application for Sequel Technologies, LLC Model STCP-STE, FCC ID: V4X-STEX01.

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

2 Test Information

2.1 Test Justification

The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT's frequencies were tested and investigated from 9 kHz to the 10th harmonic. The test results relate only to the item that was tested.

The antenna transmits, receives, and is externally attached. The IF, LO, and up to the 2nd LO, were investigated and tested, and found to be compliant for unintentional emissions compliance.

2.2 Exercising the EUT

The EUT was adapted to continuously transmit with a 30 ms long train of pulses within 100 ms for testing purposes. The carrier was also checked to verify that the information was being transmitted. The unit was reprogrammed for normal operation for the duty cycle plots and transmission requirement of 15.231(a)(2).

There were no deviations from the test standard(s) and/or methods.

2.3 Test Result Summary

Table 2-1: Test Result Summary with FCC Rules and Regulations

Standard	Test	Pass/Fail Or N/A
FCC 15.207	AC Conducted Emissions	Pass
FCC 15.231(a)(2)	Transmitter Deactivation	Pass
FCC 15.231(b)	Radiated Emissions	Pass
FCC 15.231(c)	20 dB Bandwidth	Pass

2.4 Test System Details

The test samples were received by RTL on March 3 and April 10, 2008. The FCC Identifiers for all equipment, plus descriptions of all cables used in the tested system, are shown in the following table.

Table 2-2: Equipment Under Test (EUT)


Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
Transmitter	Sequel Technologies	STCP-STE	N/A	V4X-STEX01	N/A	18370

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

2.5 Configuration of Tested System

Figure 2-1: Worst Case Configuration of System under Test




3 Duty Cycle Calculation - FCC §15.35(c)


A standard transmission consists of firmware limiting the timing to a 10 ms pulse within a 100 ms timeframe.

$$20 \log (10/100) = -20 \text{ dB}$$

Plot 3-1: Total Pulse Train Length – 21.67 ms



Plot 3-2: Total Pulse on Time within 21.67 ms Pulse Train Less than 47%



Test Personnel:

Daniel Baltzell
Test Engineer



Signature

March 21, 2008
Date of Test

4 Transmitter Deactivation – FCC §15.231(a)(2)

A transmitter activated automatically shall cease transmission within 5 seconds after activation.

Plot 4-1: Transmitter Deactivation



Test Personnel:

Daniel Baltzell
Test Engineer



Signature

March 21, 2008
Date of Test

5 Modulated Bandwidth – FCC §15.231(c)

5.1 Modulated Bandwidth Test Procedure

The minimum 20 dB bandwidth was measured using a 50 ohm spectrum analyzer with the resolution bandwidth set at 100 KHz, and the video bandwidth set at 1 MHz. The spectrum analyzer's display line was set to -20 dB using max hold until the spectrum was filled and a plot taken.

Since the device operates at two frequencies, the aggregate bandwidth must be considered. This was done by adding the two discrete bandwidths together and comparing against the more stringent of the two discrete calculated limits.

5.2 FCC §15.231(c) Limits

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.3 Modulated Bandwidth Test Data


Table 5-1: 20 dB Modulated Bandwidths

Frequency (MHz)	20 dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
319.5	376	0.25% of 319500 = 798.75	N/A
345.0	376	0.25% of 345000 = 862.5	N/A
aggregate	752	798.75	-46.75


Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Plot 5-1: Modulated Bandwidth – 319.5 MHz



Plot 5-2: Modulated Bandwidth – 345.0 MHz



Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Table 5-2: Modulated Bandwidth Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
900931	Hewlett Packard	8566B	Spectrum Analyzer (100 Hz - 22 GHz)	3138A07771	5/22/08

Test Personnel:

Daniel Baltzell
Test Engineer



Signature

March 5, 2008
Date of Test

6 Radiated Emissions – FCC §15.209, §15.231

6.1 Radiated Fundamental Emissions Test Procedure

Radiated emissions of the fundamentals were tested at three meters, and meet the requirements of average mode, and 20 dB higher in peak mode. The limit is calculated from a linear interpolation between 3,750 and 12,500 uV/m, and from 260 - 470 MHz. The EUT was tested in all three orthogonal planes. Measurement was based on a peak detector and an average level was calculated. The average level was compared to the average limit as per 15.231(b) and the peak level was compared to the average limit + 20 dB per 15.35(b).

6.1.1 Radiated Fundamental Emissions Limits Test Data

Table 6-1: Radiated Fundamental Emissions

Frequency (MHz)	Analyzer Reading (dBuV)	Polarity	Site Correction Factor (dBm)	Peak Level Corrected (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)	Duty Cycle Correction (dB)	Calculated Average Level (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
319.5	107.5	H	-17.1	90.4	95.9	-5.5	-20.0	70.4	75.9	-5.5
319.5	101.9	V	-17.1	84.8	95.9	-11.1	-20.0	64.8	75.9	-11.1
345.0	101.0	H	-16.4	84.6	97.3	-12.7	-20.0	64.6	77.3	-12.7
345.0	96.0	V	-16.4	79.6	97.3	-17.7	-20.0	59.6	77.3	-17.7

6.2 Radiated Harmonics/Spurious Emissions – FCC §15.231

6.2.1 Radiated Emissions Harmonics/Spurious Test Procedure

Radiated emissions of the harmonics were tested at three meters. The EUT was tested in the three orthogonal planes with the receive antenna in both polarities. The emissions were maximized per ANSI C63.4:2003 8.3.1.2; that is, the measurement antenna height was varied between 1 and 4 m, and the EUT was rotated through 360° on a rotating turntable until the maximum emissions were found. Both horizontal and vertical measurement antenna polarizations were used. A resolution bandwidth of 100 kHz was used for frequencies less than 1000 MHz, and 1 MHz for frequencies greater than or equal to 1000 MHz.

Rhein Tech Laboratories, Inc.
 360 Herndon Parkway
 Suite 1400
 Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
 Model: STCP-STE
 Standard: FCC 15.231
 FCC ID: V4X-STEX01
 Report #: 2008068

Table 6-2: Radiated Spurious Harmonics; 319.5 MHz

Peak Limit = 75.9 dBuV/m; Duty Cycle Correction = 20 dB; Average Limit = 55.9 dBuV/m

Frequency (MHz)	Analyzer Reading (dBuV)	Polarity	Site Correction Factor	Peak Level Corrected (dBuV/m)	Peak Margin (dB)	Calculated Average Level (dBuV/m)	Average Margin (dB)
639.0	73.4	H	-10.1	63.3	-12.6	43.3	-12.6
639.0	70.0	V	-10.1	59.9	-16.0	39.9	-16.0
958.5	66.7	H	-5.8	60.9	-15.0	40.9	-15.0
958.0	59.7	V	-5.8	53.9	-22.0	33.9	-22.0
1278.0	50.8	H	-3.0	47.8	-28.1	27.8	-28.1
1278.0	49.8	V	-3.0	46.8	-29.1	26.8	-29.1
1597.5	41.4	H	-0.6	40.8	-35.1	20.8	-35.1
1597.5	41.1	V	-0.6	40.5	-35.4	20.5	-35.4
1917.0	38.9	H	2.2	41.1	-34.8	21.1	-34.8
1917.0	35.3	V	2.2	37.5	-38.4	17.5	-38.4
2236.5	41.0	H	-3.2	37.8	-38.1	17.8	-38.1
2236.5	39.4	V	-3.2	36.2	-39.7	16.2	-39.7
2556.0	44.2	H	-2.9	41.3	-34.6	21.3	-34.6
2556.0	34.7	V	-2.9	31.8	-44.1	11.8	-44.1
2875.5	49.6	H	-1.8	47.8	-28.1	27.8	-28.1
2875.5	47.6	V	-1.8	45.8	-30.1	25.8	-30.1
3195.0	38.0	H	-1.3	36.7	-39.2	16.7	-39.2
3195.0	36.5	V	-1.3	36.7	-39.2	16.7	-39.2

Rhein Tech Laboratories, Inc.
 360 Herndon Parkway
 Suite 1400
 Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
 Model: STCP-STE
 Standard: FCC 15.231
 FCC ID: V4X-STEX01
 Report #: 2008068

Table 6-3: Radiated Spurious Harmonics; 345 MHz

Peak Limit = 77.3 dBuV/m; Duty Cycle Correction = 20 dB; Average Limit = 57.3 dBuV/m

Frequency (MHz)	Analyzer Reading (dBuV)	Polarity	Site Correction Factor	Peak Level Corrected (dBuV/m)	Peak Margin (dB)	Calculated Average Level (dBuV/m)	Average Margin (dB)
690.0	69.4	H	-9.6	59.8	-17.5	39.8	-17.5
690.0	67.0	V	-9.6	57.4	-19.9	37.4	-19.9
1035.0	62.1	H	-5.1	57.0	-20.3	37.0	-20.3
1035.0	62.8	V	-5.1	57.7	-19.6	37.7	-19.6
1380.0	46.6	H	-2.4	44.2	-33.1	24.2	-33.1
1380.0	42.1	V	-2.4	39.7	-37.6	19.7	-37.6
1725.0	42.2	H	0.6	42.8	-34.5	22.8	-34.5
1725.0	42.1	V	0.6	42.7	-34.6	22.7	-34.6
2070.0	38.5	H	-2.5	36.0	-41.3	16.0	-41.3
2070.0	38.5	V	-2.5	36.0	-41.3	16.0	-41.3
2415.0	45.9	H	-2.9	43.0	-34.3	23.0	-34.3
2415.0	42.6	V	-2.9	39.7	-37.6	19.7	-37.6
2760.0	48.2	H	-2.4	45.8	-31.5	25.8	-31.5
2760.0	50.1	V	-2.4	47.7	-29.6	27.7	-29.6
3105.0	40.0	H	-2.0	38.0	-39.3	18.0	-39.3
3105.0	38.1	V	-2.0	36.1	-41.2	16.1	-41.2
3450.0	35.1	H	-1.6	33.5	-43.8	13.5	-43.8
3450.0	34.5	V	-1.6	33.5	-43.8	13.5	-43.8

Rhein Tech Laboratories, Inc.
 360 Herndon Parkway
 Suite 1400
 Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
 Model: STCP-STE
 Standard: FCC 15.231
 FCC ID: V4X-STEX01
 Report #: 2008068

Table 6-4: Radiated Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
900791	Chase	CBL6111B	Bilog Antenna (30 MHz – 2000 MHz)	N/A	9/21/08
901365	MITEQ	JS4-00102600-41-5P	Amplifier, 0.1-26 GHz, 30 dB gain	N/A	10/8/08
900772	EMCO	3161-02	Horn Antenna (2 - 4 GHz)	9804-1044	6/14/10
901215	Hewlett Packard	8596EM	Portable Spectrum Analyzer (9 kHz – 12.8 GHz)	3826A00144	10/17/08
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	10/5/08
901425	Insulated Wire Inc.	KPS-1503-2400-KPS	RF cable, 20'	NA	10/5/08
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	Not Required

Test Personnel:

Daniel Baltzell
 Test Engineer



Signature

June 27, 2008
 Date of Tests

7 Conducted Emissions

7.1 Site and Test Description

The power line conducted emissions measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm/50 microhenry Line Impedance Stabilization Network (LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50 ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 100 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 100 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. Video filter less than 10 times the resolution bandwidth is not used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. The limits for Class A and Class B are contained therein.

7.2 Test Limits

Class A Line-Conducted Emissions		
Limit (dB μ V)		
Frequency (MHz)	Quasi-Peak	Average
0.15 to 0.50	79	66
0.50 to 30.0	73	60

Class B Line-Conducted Emissions		
Limit (dB μ V)		
Frequency (MHz)	Quasi-Peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5.00	56	46
5.00 to 30.00	60	50

Rhein Tech Laboratories, Inc.
 360 Herndon Parkway
 Suite 1400
 Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
 Model: STCP-STE
 Standard: FCC 15.231
 FCC ID: V4X-STEX01
 Report #: 2008068

7.3 Conducted Emissions Test Results

Table 7-1: Conducted Emissions – Neutral (Line 1)

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	CISPR B QP Limit (dBuV)	CISPR B QP Margin (dBuV)	CISPR B AV Limit (dBuV)	CISPR B AV Margin (dBuV)	Pass/Fail
0.285	Pk	35.9	0.2	36.1	60.7	-24.6	50.7	-14.6	Pass
0.320	Pk	30.0	0.2	30.2	59.7	-29.5	49.7	-19.5	Pass
1.560	Pk	26.1	0.8	26.9	56.0	-29.1	46.0	-19.1	Pass
15.040	Pk	19.3	2.2	21.5	60.0	-38.5	50.0	-28.5	Pass
25.340	Pk	22.3	2.7	25.0	60.0	-35.0	50.0	-25.0	Pass
28.530	Pk	23.4	2.8	26.2	60.0	-33.8	50.0	-23.8	Pass

Table 7-2: Conducted Emissions – Hot (Line 2)

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	CISPR B QP Limit (dBuV)	CISPR B QP Margin (dBuV)	CISPR B AV Limit (dBuV)	CISPR B AV Margin (dBuV)	Pass/Fail
0.292	Pk	33.5	0.2	33.7	60.5	-26.8	50.5	-16.8	Pass
0.438	Pk	17.4	0.2	17.6	57.1	-39.5	47.1	-29.5	Pass
0.500	Pk	29.1	0.2	29.3	56.0	-26.7	46.0	-16.7	Pass
1.530	Pk	29.6	0.8	30.4	56.0	-25.6	46.0	-15.6	Pass
15.600	Pk	26.6	2.3	28.9	60.0	-31.1	50.0	-21.1	Pass
28.440	Pk	22.7	2.8	25.5	60.0	-34.5	50.0	-24.5	Pass

Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: Sequel Technologies, LLC
Model: STCP-STE
Standard: FCC 15.231
FCC ID: V4X-STEX01
Report #: 2008068

Table 7-3: AC Line Conducted Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
900901	Hewlett Packard	85650A	Quasi-Peak Adapter	3145A01599	4/2/09
900896	Hewlett Packard	85662A	Display Section	2816A16471	4/2/09
900897	Hewlett Packard	8567A	Spectrum Analyzer (10 KHz - 1.5 GHz)	2727A00535	4/2/09
901082	AFJ International	LS16	16A LISN	1.6E+10	2/4/09

Test Personnel:

Daniel Baltzell
Test Engineer



Signature

April 25, 2008
Date of Test

8 Conclusion

The data in this measurement report shows that Sequel Technologies, LLC Model STCP-STE; FCC ID: V4X-STEX01, complies with all the applicable requirements of Parts 2 and 15 of the FCC Rules.