



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Bird Technologies

Model: DDRXXX

Description: Public Safety Fiber DAS Remote (33dBm)

Serial Number: 10636

FCC ID: V5FDDR002

To

FCC Part 1.1310

Date of Issue: November 11, 2015

On the behalf of the applicant:

Bird Technologies
30303 Aurora Road
Solon, OH 44139

Attention of:

Amy Sanvido, RF Engineer
Ph: (440)519-2179
E-Mail: asanvido@bird-technologies.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1580020

Shawn McMillen
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	September 29, 2015	Shawn McMillen	Original Document
2.0	November 5, 2015	Shawn McMillen	MPE revised
3.0	November 11, 2015	Shawn McMillen	Corrected Separation Distance for 763MHz, Corrected Output Power Used to Compute MPE for 851MHz

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: DDRXXX

Description: Public Safety Fiber DAS Remote (33dBm)

Firmware: N/A

Software: N/A

S/N: 10636

Additional Information: N/A

Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
150	891 mW	100	891 mW
470	2,213 mW	100	2,213 mW
763	1,968 mW	100	1,968 mW
851	1,730 mW	100	1,730 mW



MPE Evaluation

This is a fixed/mobile device used in Uncontrolled/general population Exposure environment.

**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	150	
Power, Conducted, mW (P)	891 + 20%	
Antenna Gain Isotropic	8.41dBd max	10.55dBi max
Antenna Gain Numeric (G)	11.3	
Antenna Type	Omni	
Distance (R)	20 cm	

$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm ²	Power mW (P)
	1069.2

Power Density (S) = 2.404
Limit =(from above table) = 0.2

Note: Power density exceeds limit therefore separation distance necessary is 69.4cm



**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	470	
Power, Conducted, mW (P)	2213 + 20%	
Antenna Gain Isotropic	-5.57dBd Max	-3.43 dBi Max
Antenna Gain Numeric (G)	0.45	
Antenna Type	Omni	
Distance (R)	20 cm	

$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm ²	Power mW (P)
	2655.7

Power Density (S) = 0.24
Limit =(from above table) = 0.3



**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	763	
Power, Conducted, mW (P)	1968 + 20%	
Antenna Gain Isotropic	3.43dBd Max	5.57dBi max
Antenna Gain Numeric (G)	3.6	
Antenna Type	Omni	
Distance (R)	20 cm	

$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm ²	Power mW (P)
	2361.6

Power Density (S) = 1.69
Limit =(from above table) = 0.51

Note: Power density exceeds limit therefore separation distance necessary is 36.4cm



**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	851	
Power, Conducted, mW (P)	1730 + 20%	
Antenna Gain Isotropic	-1.61dBd Max	0.53dBi max
Antenna Gain Numeric (G)	1.13	
Antenna Type	Omni	
Distance (R)	20 cm	

$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm ²	Power mW (P)
	2076

Power Density (S) = 0.47
Limit =(from above table) = 0.57

END OF TEST REPORT