



FCC RF Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Smart Mobile Payment Terminal
BRAND NAME : PAX
MODEL NAME : A920
FCC ID : V5PA920-2019
STANDARD : FCC Part 15 Subpart C §15.225
CLASSIFICATION : (DXX) Low Power Communication Device Transmitter

The product was received on Dec. 18, 2018 and testing was completed on Feb. 20, 2019. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

Approved by: Eric Shih / Manager



Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China**



TABLE OF CONTENTS

TABLE OF CONTENTS2
REVISION HISTORY3
SUMMARY OF THE TEST RESULT4
1. GENERAL DESCRIPTION5
1.1 Applicant.....5
1.2 Manufacturer5
1.3 Product Feature of Equipment Under Test5
1.4 Product Specification of Equipment Under Test6
1.5 Modification of EUT6
1.6 Testing Location7
1.7 Applicable Standards.....7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST8
2.1 Descriptions of Test Mode8
2.2 Connection Diagram of Test System9
2.3 Table for Supporting Units9
2.4 EUT Operation Test Setup9
3. TEST RESULTS10
3.1 AC Power Line Conducted Emissions Measurement10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....12
3.3 Frequency Stability Measurement13
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....14
3.5 Radiated Emissions Measurement16
3.6 Antenna Requirements.....19
4. LIST OF MEASURING EQUIPMENT20
5. UNCERTAINTY OF EVALUATION21
APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST
APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)
APPENDIX D. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR8D1822D	Rev. 01	Initial issue of report	Feb. 27, 2019



SUMMARY OF THE TEST RESULT

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 6.90 dB at 0.63MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 75.19 dB μ V/m at 13.56 MHz
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 2.86 dB at 40.67MHz for Quasi-Peak
3.6	15.203	Antenna Requirements	Complies	-



1. General Description

1.1 Applicant

PAX Technology Limited

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

1.2 Manufacturer

PAX Computer Technology (Shenzhen) Co., Ltd.

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Mobile Payment Terminal
Brand Name	PAX
Model Name	A920
FCC ID	V5PA920-2019
EUT supports Radios application	WCDMA/HSPA/DC-HSDPA/HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth BR / EDR / LE NFC/GNSS
IMEI Code	Conducted: 352110098999965 352110098999973 Conduction/Radiation:352110098996946/352110098996953
HW Version	N/A
SW Version	N/A
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.57 KHz
99%OBW	2.19 KHz
Antenna Type	PCB Antenna
Type of Modulation	ASK

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0).

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen City, Guangdong Province 518055, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.		FCC designation No.
	TH01-SZ	CO01-SZ	CN5018
Test Engineer	Jensen Wu	Zhang Xu	
Temperature	24~26°C	22~25°C	
Relative Humidity	50~53%	50~55%	
			FCC Test Firm Registration No. 337463

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District, Shenzhen City, Guangdong Province 518055, China TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC designation No.
	03CH01-SZ		CN5019
Test Engineer	Reid Huang		
Temperature	24~25°C		
Relative Humidity	48~49%		
			FCC Test Firm Registration No. 577730

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013



2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in four NFC type, A, B. The worst type (type A) was recorded in this report.

Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: LTE Band 4 Idle + Bluetooth Link + WLAN (2.4G) Link + NFC Tx + Battery 1 + USB Cable (Charging from Adapter)
Remark:	
1. The worst case of conducted emission is mode 1; only the test data of it was reported.	
2. For Radiated Test Cases, The tests were performed with Adapter, Battery 1 and USB Cable.	

2.2 Connection Diagram of Test System



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	WLAN AP	D-Link	DIR-820L	KA21R820LA1	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Samsung	EO-MG900	N/A	N/A	N/A
5.	SD Card	N/A	MicroSD HC	FCC DoC	N/A	N/A

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.



3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 19, 2018	Jan. 16, 2019	Apr. 18, 2019	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 22, 2018	Jan. 16, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 22, 2018	Jan. 16, 2019	Dec. 21, 2019	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260 185	20Hz~26.5GHz	Aug. 30, 2018	Feb. 01, 2019	Aug. 29, 2019	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 29, 2018	Feb. 01, 2019	May 28, 2019	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Jun. 05, 2018	Feb. 01, 2019	Jun. 04, 2019	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2018	Feb. 01, 2019	Apr. 19, 2019	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	6160100 01985	N/A	NCR	Feb. 01, 2019	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 01, 2019	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Feb. 14, 2019~ Feb. 20, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	0010391 2	9kHz~30MHz	Oct. 18, 2018	Feb. 14, 2019~ Feb. 20, 2019	Oct. 17, 2019	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	0010389 2	9kHz~30MHz	Dec. 23, 2018	Feb. 14, 2019~ Feb. 20, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	6160200 00891	100Vac~250Vac	Jul. 18, 2018	Feb. 14, 2019~ Feb. 20, 2019	Jul. 17, 2019	Conduction (CO01-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.6 dB
---	--------


Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB
---	--------



Appendix A. Test Results of Conducted Emission Test

Test Engineer :	ZhangXu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20180719_L LINE


	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.49	32.90	-13.33	46.23	22.80	0.02	10.08	Average
2	0.49	47.10	-9.13	56.23	37.00	0.02	10.08	QP
3	0.56	29.10	-16.90	46.00	19.00	0.02	10.08	Average
4	0.56	43.60	-12.40	56.00	33.50	0.02	10.08	QP
5	0.63	32.60	-13.40	46.00	22.50	0.02	10.08	Average
6	0.63	49.10	-6.90	56.00	39.00	0.02	10.08	QP
7	0.72	29.51	-16.49	46.00	19.41	0.02	10.08	Average
8	0.72	45.71	-10.29	56.00	35.61	0.02	10.08	QP
9	0.87	27.74	-18.26	46.00	17.60	0.05	10.09	Average
10	0.87	41.14	-14.86	56.00	31.00	0.05	10.09	QP
11	13.55	47.06	-2.94	50.00	36.20	0.47	10.39	Average
12 *	13.55	60.26	0.26	60.00	49.40	0.47	10.39	QP

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	ZhangXu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-SZ
 Condition: FCC 15C_QP LISN_20180719_N NEUTRAL


	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.50	24.00	-22.05	46.05	13.90	0.02	10.08	Average
2	0.50	38.90	-17.15	56.05	28.80	0.02	10.08	QP
3	0.56	26.70	-19.30	46.00	16.60	0.02	10.08	Average
4	0.56	42.00	-14.00	56.00	31.90	0.02	10.08	QP
5	0.63	27.80	-18.20	46.00	17.70	0.02	10.08	Average
6	0.63	43.00	-13.00	56.00	32.90	0.02	10.08	QP
7	0.72	24.80	-21.20	46.00	14.70	0.02	10.08	Average
8	0.72	39.60	-16.40	56.00	29.50	0.02	10.08	QP
9	1.22	20.34	-25.66	46.00	10.20	0.05	10.09	Average
10	1.22	36.34	-19.66	56.00	26.20	0.05	10.09	QP
11	13.55	45.68	-4.32	50.00	35.00	0.29	10.39	Average
12 *	13.55	59.18	-0.82	60.00	48.50	0.29	10.39	QP

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	ZhangXu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20180719_L LINE


	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.63	41.60	-4.40	46.00	31.50	0.02	10.08	Average
2	0.63	46.10	-9.90	56.00	36.00	0.02	10.08	QP
3	0.83	31.13	-14.87	46.00	21.00	0.04	10.09	Average
4	0.83	38.53	-17.47	56.00	28.40	0.04	10.09	QP
5	1.34	32.38	-13.62	46.00	22.19	0.09	10.10	Average
6	1.34	41.18	-14.82	56.00	30.99	0.09	10.10	QP
7	2.40	24.55	-21.45	46.00	14.30	0.13	10.12	Average
8	2.40	33.05	-22.95	56.00	22.80	0.13	10.12	QP
9	11.02	35.05	-14.95	50.00	24.30	0.40	10.35	Average
10	11.02	49.95	-10.05	60.00	39.20	0.40	10.35	QP
11	14.21	31.89	-18.11	50.00	21.00	0.49	10.40	Average
12	14.21	42.99	-17.01	60.00	32.10	0.49	10.40	QP

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



Test Engineer :	ZhangXu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20180719_N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.64	32.50	-13.50	46.00	22.40	0.02	10.08	Average
2 *	0.64	42.90	-13.10	56.00	32.80	0.02	10.08	QP
3	0.87	20.52	-25.48	46.00	10.39	0.04	10.09	Average
4	0.87	31.52	-24.48	56.00	21.39	0.04	10.09	QP
5	1.41	25.75	-20.25	46.00	15.60	0.05	10.10	Average
6	1.41	35.05	-20.95	56.00	24.90	0.05	10.10	QP
7	3.68	22.50	-23.50	46.00	12.29	0.05	10.16	Average
8	3.68	33.50	-22.50	56.00	23.29	0.05	10.16	QP
9	10.68	30.44	-19.56	50.00	19.90	0.19	10.35	Average
10	10.68	46.84	-13.16	60.00	36.30	0.19	10.35	QP
11	12.92	31.35	-18.65	50.00	20.70	0.27	10.38	Average
12	12.92	44.95	-15.05	60.00	34.30	0.27	10.38	QP

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56																																																																
<table border="1"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>13.56021 MHz</td> <td>-5.55 dBm</td> <td>ndB down</td> <td>2.567 kHz</td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td></td> <td>13.558901 MHz</td> <td>-25.44 dBm</td> <td>ndB</td> <td>20.00 dB</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td></td> <td>13.561469 MHz</td> <td>-25.51 dBm</td> <td>Q factor</td> <td>5281.6</td> </tr> </tbody> </table>		Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			13.56021 MHz	-5.55 dBm	ndB down	2.567 kHz	T1	1			13.558901 MHz	-25.44 dBm	ndB	20.00 dB	T2	1			13.561469 MHz	-25.51 dBm	Q factor	5281.6	<table border="1"> <thead> <tr> <th>Marker</th> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td></td> <td>13.56018 MHz</td> <td>-5.71 dBm</td> <td></td> <td></td> </tr> <tr> <td>T1</td> <td>1</td> <td></td> <td></td> <td>13.5590809 MHz</td> <td>-20.23 dBm</td> <td>Occ Bw</td> <td>2.187812188 kHz</td> </tr> <tr> <td>T2</td> <td>1</td> <td></td> <td></td> <td>13.5612687 MHz</td> <td>-20.20 dBm</td> <td></td> <td></td> </tr> </tbody> </table>		Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1			13.56018 MHz	-5.71 dBm			T1	1			13.5590809 MHz	-20.23 dBm	Occ Bw	2.187812188 kHz	T2	1			13.5612687 MHz	-20.20 dBm		
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																												
M1	1			13.56021 MHz	-5.55 dBm	ndB down	2.567 kHz																																																												
T1	1			13.558901 MHz	-25.44 dBm	ndB	20.00 dB																																																												
T2	1			13.561469 MHz	-25.51 dBm	Q factor	5281.6																																																												
Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																												
M1	1			13.56018 MHz	-5.71 dBm																																																														
T1	1			13.5590809 MHz	-20.23 dBm	Occ Bw	2.187812188 kHz																																																												
T2	1			13.5612687 MHz	-20.20 dBm																																																														
20dB Bandwidth (kHz)	2.57	99% OccupiedBW(kHz)	2.19																																																																
Frequency range (MHz)	$f_L > 13.553$	13.558901	Test Result																																																																
	$f_H < 13.567$	13.561469	Complies																																																																

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



B2. Test Result of Frequency Stability

B3. Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
3.55	13.560185	-20	13.560185
3.7	13.560185	-10	13.560180
4.2	13.560185	0	13.560180
-	-	10	13.560180
-	-	20	13.560175
-	-	30	13.560175
-	-	40	13.560175
-	-	50	13.560180
Max.Deviation (MHz)	0.000185	Max.Deviation (MHz)	0.000185
Max.Deviation (ppm)	13.6431	Max.Deviation (ppm)	13.6431
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS



Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56																																
Site : 03CH01-SZ Condition : 15.225 LIMIT 3m LOOP ANT_1806 HORIZONTAL																																			
	<table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>ReadAntenna Level Factor</th> <th>Cable Loss</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>13.56</td> <td>75.19</td> <td>-48.81</td> <td>124.00</td> <td>55.65</td> <td>19.09</td> <td>0.45</td> <td>---</td> </tr> </tbody> </table>	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	13.56	75.19	-48.81	124.00	55.65	19.09	0.45	---							
Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	A/Pos	T/Pos	Remark																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																											
1	13.56	75.19	-48.81	124.00	55.65	19.09	0.45	---																											
Site : 03CH01-SZ Condition : 15.225 LIMIT 3m LOOP ANT_1806 VERTICAL																																			
	<table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>ReadAntenna Level Factor</th> <th>Cable Loss</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>13.56</td> <td>72.16</td> <td>-51.84</td> <td>124.00</td> <td>52.62</td> <td>19.09</td> <td>0.45</td> <td>---</td> </tr> </tbody> </table>	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	13.56	72.16	-51.84	124.00	52.62	19.09	0.45	---							
Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	A/Pos	T/Pos	Remark																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																											
1	13.56	72.16	-51.84	124.00	52.62	19.09	0.45	---																											



C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx		Polarization :			Horizontal		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.00936	50.05	-78.13	128.18	30.9	19.1	0.05	-	-	Average
0.07287	36.99	-73.36	110.35	17.63	19.3	0.06	-	-	Average
0.09942	46.35	-61.3	107.65	26.68	19.6	0.07	-	-	QP
0.14934	39.78	-64.34	104.12	20.11	19.57	0.1	-	-	Average
0.15	51.97	-52.11	104.08	32.3	19.57	0.1	-	-	Average
2.114	35.98	-34.02	70	16.29	19.51	0.18	-	-	QP
13.672	54.76	-15.24	70	35.24	19.07	0.45	-	-	QP
21.796	35.64	-34.36	70	15.32	19.77	0.55	-	-	QP
25.85	35.88	-34.12	70	15.67	19.6	0.61	-	-	QP

Test Mode :		NFC Tx		Polarization :			Vertical		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01053	49.06	-78.1	127.16	29.91	19.1	0.05	-	-	Average
0.06249	37.3	-74.39	111.69	17.94	19.3	0.06	-	-	Average
0.11511	42.38	-64	106.38	22.71	19.59	0.08	-	-	Average
0.1491	35.48	-68.65	104.13	15.81	19.57	0.1	-	-	Average
0.1537	47.5	-56.37	103.87	27.83	19.57	0.1	-	-	Average
2.258	37.01	-32.99	70	17.31	19.51	0.19	-	-	QP
13.776	50.67	-19.33	70	31.17	19.05	0.45	-	-	QP
17.719	44.76	-25.24	70	24.89	19.37	0.5	-	-	QP
28.02	35.19	-34.81	70	15.55	19	0.64	-	-	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
3. Limit line = specific limits (dBμV) + distance extrapolation factor.



C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :		NFC Tx			Polarization :			Horizontal			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark	
33.88	33.38	-6.62	40	42.6	22.08	0.3	31.6	136	125	Peak	
40.67	25.54	-14.46	40	38.41	18.19	0.39	31.45	-	-	Peak	
67.83	20.65	-19.35	40	38.87	12.82	0.56	31.6	-	-	Peak	
99.84	22.38	-21.12	43.5	36.43	16.7	0.85	31.6	-	-	Peak	
149.31	27.24	-16.26	43.5	40.61	16.73	1.3	31.4	-	-	Peak	
989.33	30.03	-23.97	54	29.8	27.3	4.15	31.22	-	-	Peak	

Test Mode :		NFC Tx			Polarization :			Vertical			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark	
40.67	37.14	-2.86	40	50.01	18.19	0.39	31.45	154	184	QP	
67.83	31.18	-8.82	40	49.4	12.82	0.56	31.6	-	-	Peak	
94.99	28.04	-15.46	43.5	43.15	15.7	0.79	31.6	-	-	Peak	
156.1	28.45	-15.05	43.5	42.22	16.27	1.35	31.39	-	-	Peak	
317.12	24.18	-21.82	46	33.82	19.62	2.1	31.36	-	-	Peak	
978.66	30.31	-23.69	54	30.25	27.21	4.1	31.25	-	-	Peak	

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.