


FCC SAR Test Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Smart Tablet
BRAND NAME : PAX
MODEL NAME : Aries6
FCC ID : V5PAR6
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Apr. 11, 2019 and testing was started from Jun. 16, 2019 and completed on Jun. 22, 2019. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Long Liang / Supervisor



Approved by: Johnny Chen / Manager



Sporton International (ShenZhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China**



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied.....	5
4. Equipment Under Test (EUT) Information.....	6
4.1 General Information	6
4.2 General LTE SAR Test and Reporting Considerations	7
5. RF Exposure Limits.....	9
5.1 Uncontrolled Environment.....	9
5.2 Controlled Environment.....	9
6. Specific Absorption Rate (SAR).....	10
6.1 Introduction	10
6.2 SAR Definition.....	10
7. System Description and Setup	11
7.1 E-Field Probe	12
7.2 Data Acquisition Electronics (DAE)	12
7.3 Phantom.....	13
7.4 Device Holder.....	14
8. Measurement Procedures	15
8.1 Spatial Peak SAR Evaluation.....	15
8.2 Power Reference Measurement.....	16
8.3 Area Scan	16
8.4 Zoom Scan.....	17
8.5 Volume Scan Procedures.....	17
8.6 Power Drift Monitoring.....	17
9. Test Equipment List.....	18
10. System Verification	19
10.1 Tissue Simulating Liquids.....	19
10.2 Tissue Verification	20
10.3 System Performance Check Results.....	21
11. RF Exposure Positions	22
11.1 SAR Testing for Tablet	22
12. Conducted RF Output Power (Unit: dBm).....	23
13. Antenna Location	46
14. SAR Test Results	48
14.1 Body SAR	50
15. Repeated SAR Measurement	54
16. Simultaneous Transmission Analysis.....	55
16.1 Body Exposure Conditions	56
17. Uncertainty Assessment	57
18. References.....	58
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA941109	01	Initial issue of report	Aug. 02, 2019

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **PAX Technology Limited, Smart Tablet, Aries6**, are as follows.

Highest 1g SAR Summary				
Equipment Class	Frequency Band		Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
			Body (Separation 0mm)	
			1g SAR (W/kg)	
Licensed	WCDMA	Band V	0.35	1.54
		Band II	1.36	
	LTE	Band 12/Band 17	0.41	
		LTE Band 5	0.34	
		LTE Band 4	0.55	
		LTE Band 2	1.10	
DTS	WLAN	2.4GHz WLAN	0.42	1.49
NII		5GHz WLAN	0.47	1.54
DSS	Bluetooth	Bluetooth	<0.10	1.37
Date of Testing:		2019/6/16 ~2019/6/22		
Remark: This device supports LTE B17 and B12. Since the supported frequency span for LTE B17 falls completely within the supports frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B12.				

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory		
Test Firm	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1256	421272

Applicant	
Company Name	PAX Technology Limited
Address	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02

4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Smart Tablet
Brand Name	PAX
Model Name	Aries6
FCC ID	V5PAR6
IMEI Code	866732039393286
Wireless Technology and Frequency Range	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	RMC 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is not supported) LTE: QPSK, 16QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz : 802.11a/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
HW Version	N/A
SW Version	N/A
EUT Stage	Production Unit
Remark: 1. WLAN operating in 5600~5650MHz is notched. 2. This device does not support voice function. 3. 802.11n-HT40 is not supported in 2.4GHz WLAN.	

4.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	V5PAR6							
Equipment Name	Smart Tablet							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz							
Channel Bandwidth	LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz							
Uplink Modulations Used	QPSK / 16QAM							
LTE Voice / Data requirements	Data only							
LTE Release Version	R8, Cat4							
CA Support	Not Supported							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
	256 QAM	≥ 1						≤ 5
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 17												
	Bandwidth 5 MHz					Bandwidth 10 MHz						
	Channel #		Freq.(MHz)			Channel #		Freq. (MHz)				
L	23755		706.5			23780		709				
M	23790		710			23790		710				
H	23825		713.5			23800		711				

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

7.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

7.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE


7.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

7.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

**9. Test Equipment List**

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1099	2018/12/6	2019/12/5
SPEAG	835MHz System Validation Kit	D835V2	4d162	2018/12/5	2019/12/4
SPEAG	1750MHz System Validation Kit	D1750V2	1137	2018/7/30	2019/7/29
SPEAG	1900MHz System Validation Kit	D1900V2	5d182	2018/12/7	2019/12/6
SPEAG	2450MHz System Validation Kit	D2450V2	736	2018/8/31	2019/8/30
SPEAG	5000MHz System Validation Kit	D5GHzV2	1167	2018/8/3	2019/8/2
SPEAG	Data Acquisition Electronics	DAE4	715	2019/1/23	2020/1/22
SPEAG	Dosimetric E-Field Probe	EX3DV4	3819	2019/3/1	2020/2/29
SPEAG	ELI4 Phantom	ELI5.0	1225	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201300653	2018/7/18	2019/7/17
Anritsu	Radio communication analyzer	MT8821C	6201692204	2018/12/22	2019/12/21
Agilent	Wireless Communication Test Set	E5515C	MY50267224	2018/9/11	2019/9/10
Agilent	Network Analyzer	E5071C	MY46523671	2018/10/18	2019/10/17
Speag	Dielectric Assessment KIT	DAK-3.5	1071	2018/11/20	2019/11/19
Agilent	Signal Generator	N5181A	MY50145381	2018/12/22	2019/12/21
Anritsu	Power Sensor	MA2411B	1306099	2018/7/30	2019/7/29
Anritsu	Power Meter	ML2495A	1349001	2018/7/26	2019/7/25
Anritsu	Power Sensor	MA2411B	1207253	2018/12/22	2019/12/21
Anritsu	Power Meter	ML2495A	1218010	2018/12/22	2019/12/21
R&S	CBT BLUETOOTH TESTER	CBT	100963	2018/12/22	2019/12/21
R&S	Spectrum Analyzer	FSP7	100818	2018/7/18	2019/7/17
LKM electronic	Hygrometer	DTM3000	3241	2018/8/10	2019/8/9
Anymetre	Thermo-Hygrometer	JR593	2015102801	2018/12/22	2019/12/21
ARRA	Power Divider	A3200-2	N/A	Note	
PASTERNAK	Dual Directional Coupler	PE2214-10	N/A	Note	
Agilent	Dual Directional Coupler	778D	50422	Note	
MCL	Attenuation1	BW-S10W5	N/A	Note	
Weinschel	Attenuation2	3M-20	N/A	Note	
Zhongjilianhe	Attenuation3	MVE2214-03	N/A	Note	
AR	Amplifier	5S1G4	0333096	Note	
mini-circuits	Amplifier	ZVE-3W-83+	599201528	Note	

Note: Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1.



Fig 10.1 Photo of Liquid Height for Body SAR

10.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	Head	22.5	0.879	40.957	0.89	41.90	-1.24	-2.25	±5	2019/6/22
835	Head	22.6	0.877	41.373	0.90	41.50	-2.56	-0.31	±5	2019/6/22
1750	Head	22.8	1.398	41.384	1.37	40.10	2.04	3.20	±5	2019/6/21
1900	Head	22.6	1.385	39.053	1.40	40.00	-1.07	-2.37	±5	2019/6/20
2450	Head	22.6	1.872	38.404	1.80	39.20	4.00	-2.03	±5	2019/6/19
5250	Head	22.7	4.496	37.058	4.71	35.95	-4.54	3.08	±5	2019/6/16
5600	Head	22.8	4.850	36.497	5.07	35.50	-4.34	2.81	±5	2019/6/17
5750	Head	22.8	5.013	36.309	5.22	35.35	-3.97	2.71	±5	2019/6/17

10.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2019/6/22	750	Head	250	1099	3819	715	2.01	8.52	8.04	-5.63
2019/6/22	835	Head	250	4d162	3819	715	2.40	9.61	9.60	-0.10
2019/6/21	1750	Head	250	1137	3819	715	8.76	36.50	35.04	-4.00
2019/6/20	1900	Head	250	5d182	3819	715	9.42	39.60	37.68	-4.85
2019/6/19	2450	Head	250	736	3819	715	14.10	52.70	56.40	7.02
2019/6/16	5250	Head	100	1167	3819	715	7.55	77.00	75.50	-1.95
2019/6/17	5600	Head	100	1167	3819	715	7.67	80.80	76.70	-5.07
2019/6/17	5750	Head	100	1167	3819	715	7.52	76.90	75.20	-2.21




Fig 10.3.1 System Performance Check Setup



Fig 10.3.2 Setup Photo



11. RF Exposure Positions

11.1 SAR Testing for Tablet

- (a) To position the device parallel to the phantom surface with all surfaces of the device.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 0 cm.

Please refer to Appendix D for the test setup photos.

12. Conducted RF Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- The EUT was connected to Base Station referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Base Station with following setting * :
 - Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - Set Cell Power = -86 dBm
 - Set Channel Type = 12.2k + HSPA
 - Set UE Target Power
 - Power Ctrl Mode= Alternating bits
 - Set and observe the E-TFCI
 - Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

Band		WCDMA Band II			Tune-up Limit (dBm)	WCDMA Band V			Tune-up Limit (dBm)
Tx Channel		9262	9400	9538		4132	4182	4233	
Rx Channel		9662	9800	9938		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	22.77	22.62	22.53	23.50	23.00	23.04	22.99	23.50
3GPP Rel 6	HSDPA Subtest-1	21.84	21.75	21.77	22.50	22.09	22.15	22.09	22.50
3GPP Rel 6	HSDPA Subtest-2	21.91	21.85	21.91	22.50	22.15	22.10	22.05	22.50
3GPP Rel 6	HSDPA Subtest-3	21.38	21.35	21.43	22.00	21.64	21.60	21.55	22.00
3GPP Rel 6	HSDPA Subtest-4	21.38	21.35	21.44	22.00	21.62	21.60	21.54	22.00
3GPP Rel 8	DC-HSDPA Subtest-1	21.25	21.28	21.29	21.50	21.35	21.38	21.31	21.50
3GPP Rel 8	DC-HSDPA Subtest-2	21.18	21.17	21.16	21.50	21.28	21.27	21.26	21.50
3GPP Rel 8	DC-HSDPA Subtest-3	21.00	20.79	20.88	21.00	20.98	20.86	20.74	21.00
3GPP Rel 8	DC-HSDPA Subtest-4	20.67	20.65	20.49	21.00	20.64	20.59	20.55	21.00
3GPP Rel 6	HSUPA Subtest-1	21.01	21.16	21.05	22.50	21.54	21.34	21.33	22.50
3GPP Rel 6	HSUPA Subtest-2	20.57	20.22	20.70	21.00	20.47	20.58	20.72	21.00
3GPP Rel 6	HSUPA Subtest-3	20.35	20.22	20.30	21.50	20.81	20.64	20.82	21.50
3GPP Rel 6	HSUPA Subtest-4	20.96	20.81	20.85	21.00	20.99	20.91	20.88	21.00
3GPP Rel 6	HSUPA Subtest-5	21.80	21.70	21.70	22.50	22.10	22.00	22.00	22.50

<LTE Conducted Power>**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 / B12 / B17 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE B17 SAR test was covered by B12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	22.02	21.84	21.98		
20	QPSK	1	49	22.07	21.93	22.03	23	0
20	QPSK	1	99	21.73	21.92	21.96	22	1
20	QPSK	50	0	21.24	21.09	21.19		
20	QPSK	50	24	21.27	21.15	21.23		
20	QPSK	50	50	21.03	21.18	21.17		
20	QPSK	100	0	21.23	21.11	21.21	22	1
20	16QAM	1	0	21.18	20.94	21.06		
20	16QAM	1	49	20.87	20.96	21.11		
20	16QAM	1	99	20.83	20.99	21.18	21	2
20	16QAM	50	0	20.11	20.21	20.29		
20	16QAM	50	24	19.88	20.29	20.35		
20	16QAM	50	50	19.94	20.11	20.13		
20	16QAM	100	0	20.02	20.21	20.17	22	1
Channel				18675	18900	19125		
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.01	22.04	22.03	23	0
15	QPSK	1	37	22.01	21.95	21.97		
15	QPSK	1	74	21.93	21.93	21.91		
15	QPSK	36	0	21.32	21.15	21.40	22	1
15	QPSK	36	20	21.01	21.16	21.30		
15	QPSK	36	39	21.07	21.17	21.27		
15	QPSK	75	0	21.13	21.13	21.33		
15	16QAM	1	0	21.38	21.37	21.17	22	1
15	16QAM	1	37	21.28	21.37	21.27		
15	16QAM	1	74	21.39	20.97	21.33		
15	16QAM	36	0	20.42	20.05	20.37	21	2
15	16QAM	36	20	19.95	20.29	20.42		
15	16QAM	36	39	19.99	20.10	20.41		
15	16QAM	75	0	20.15	20.26	20.37		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.05	21.97	22.04	23	0
10	QPSK	1	25	22.01	21.95	22.02		
10	QPSK	1	49	21.81	21.93	21.91		
10	QPSK	25	0	21.28	21.12	21.31	22	1
10	QPSK	25	12	21.05	21.17	21.30		
10	QPSK	25	25	20.94	21.14	21.25		
10	QPSK	50	0	21.21	21.16	21.32	22	1
10	16QAM	1	0	21.05	21.04	21.17		
10	16QAM	1	25	20.89	20.93	21.17		
10	16QAM	1	49	20.85	20.91	21.18	21	2
10	16QAM	25	0	20.51	20.14	20.44		
10	16QAM	25	12	20.26	20.19	20.44		
10	16QAM	25	25	20.13	20.26	20.38	21	2
10	16QAM	50	0	20.14	20.19	20.28		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	21.91	21.99	22.07	23	0
5	QPSK	1	12	22.05	22.01	21.98		
5	QPSK	1	24	21.89	22.02	21.92		
5	QPSK	12	0	21.49	21.05	21.30	22	1
5	QPSK	12	7	21.39	21.12	21.15		
5	QPSK	12	13	21.43	21.11	21.24		
5	QPSK	25	0	21.47	21.06	21.25	22	1
5	16QAM	1	0	21.08	20.87	21.05		
5	16QAM	1	12	21.02	20.89	20.92		
5	16QAM	1	24	20.73	20.70	21.11	21	2
5	16QAM	12	0	20.31	19.96	20.10		
5	16QAM	12	7	20.33	20.02	20.22		
5	16QAM	12	13	20.37	20.07	20.07	21	2
5	16QAM	25	0	20.50	20.08	20.25		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	21.93	22.07	21.93	23	0
3	QPSK	1	8	22.04	21.87	22.03		
3	QPSK	1	14	22.01	21.94	21.99		
3	QPSK	8	0	21.56	21.19	21.39	22	1
3	QPSK	8	4	21.53	21.14	21.22		
3	QPSK	8	7	21.55	21.19	21.21		
3	QPSK	15	0	21.47	21.10	21.32	22	1
3	16QAM	1	0	21.18	20.91	21.13		
3	16QAM	1	8	21.24	20.86	20.87		
3	16QAM	1	14	21.09	20.93	20.96	21	2
3	16QAM	8	0	20.60	20.37	20.37		
3	16QAM	8	4	20.58	20.28	20.35		
3	16QAM	8	7	20.66	20.18	20.27	21	2
3	16QAM	15	0	20.50	20.00	20.46		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	22.01	21.87	21.89	23	0
1.4	QPSK	1	3	22.03	21.92	21.97		
1.4	QPSK	1	5	21.99	22.03	21.94		
1.4	QPSK	3	0	22.06	21.96	21.97		
1.4	QPSK	3	1	21.94	21.98	22.03		
1.4	QPSK	3	3	22.05	21.93	21.92	22	1
1.4	QPSK	6	0	21.50	21.10	21.32		
1.4	16QAM	1	0	20.96	21.02	21.26	22	1
1.4	16QAM	1	3	21.24	21.01	21.22		
1.4	16QAM	1	5	21.35	20.95	21.05		
1.4	16QAM	3	0	21.47	21.19	21.44		
1.4	16QAM	3	1	21.60	21.25	21.25		
1.4	16QAM	3	3	21.58	21.35	21.37	21	2
1.4	16QAM	6	0	20.59	20.19	20.41		

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300	22.5	0
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	21.66	21.83	21.78	22.5	0
20	QPSK	1	49	21.76	21.89	21.50		
20	QPSK	1	99	21.49	21.67	21.65		
20	QPSK	50	0	20.69	20.87	20.78	21.5	1
20	QPSK	50	24	20.63	20.72	20.69		
20	QPSK	50	50	20.54	20.73	20.56		
20	QPSK	100	0	20.63	20.77	20.59	21.5	1
20	16QAM	1	0	20.43	20.30	20.74		
20	16QAM	1	49	20.29	20.51	20.49		
20	16QAM	1	99	20.42	20.34	20.43	20.5	2
20	16QAM	50	0	19.64	19.60	19.90		
20	16QAM	50	24	19.61	19.64	19.69		
20	16QAM	50	50	19.59	19.56	19.58	20.5	2
20	16QAM	100	0	19.38	19.52	19.83		
Channel				20025	20175	20325	22.5	0
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	21.78	21.50	21.78	22.5	0
15	QPSK	1	37	21.71	21.62	21.63		
15	QPSK	1	74	21.51	21.57	21.50		
15	QPSK	36	0	20.60	20.60	20.72	21.5	1
15	QPSK	36	20	20.58	20.66	20.72		
15	QPSK	36	39	20.58	20.56	20.58		
15	QPSK	75	0	20.56	20.71	20.62	21.5	1
15	16QAM	1	0	20.44	20.47	20.69		
15	16QAM	1	37	20.36	20.54	20.28		
15	16QAM	1	74	20.48	20.46	20.35	20.5	2
15	16QAM	36	0	19.57	19.69	19.53		
15	16QAM	36	20	19.51	19.67	19.49		
15	16QAM	36	39	19.41	19.58	19.50	20.5	2
15	16QAM	75	0	19.66	19.61	19.54		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	21.61	21.66	21.49	22.5	0
10	QPSK	1	25	21.35	21.64	21.54		
10	QPSK	1	49	21.43	21.44	21.61		
10	QPSK	25	0	20.50	20.74	20.73	21.5	1
10	QPSK	25	12	20.59	20.67	20.67		
10	QPSK	25	25	20.54	20.63	20.65		
10	QPSK	50	0	20.58	20.57	20.62	21.5	1
10	16QAM	1	0	20.41	20.44	20.53		
10	16QAM	1	25	20.31	20.52	20.44		
10	16QAM	1	49	20.33	20.32	20.50	20.5	2
10	16QAM	25	0	19.49	19.66	19.67		
10	16QAM	25	12	19.52	19.69	19.70		
10	16QAM	25	25	19.44	19.55	19.56	20.5	2
10	16QAM	50	0	19.44	19.49	19.65		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	21.48	21.58	21.53	22.5	0
5	QPSK	1	12	21.53	21.74	21.52		
5	QPSK	1	24	21.35	21.47	21.88		
5	QPSK	12	0	20.50	20.70	20.60	21.5	1
5	QPSK	12	7	20.50	20.66	20.67		
5	QPSK	12	13	20.45	20.70	20.73		
5	QPSK	25	0	20.48	20.67	20.62	21.5	1
5	16QAM	1	0	20.33	20.51	20.55		
5	16QAM	1	12	20.10	20.37	20.34		
5	16QAM	1	24	20.22	20.40	20.55	20.5	2
5	16QAM	12	0	19.33	19.82	19.44		
5	16QAM	12	7	19.32	19.63	19.38		
5	16QAM	12	13	19.28	19.63	19.48	20.5	2
5	16QAM	25	0	19.46	19.69	19.42		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	21.54	21.49	21.34	22.5	0
3	QPSK	1	8	21.51	21.75	21.54		
3	QPSK	1	14	21.45	21.84	21.66		
3	QPSK	8	0	20.47	20.69	20.55	21.5	1
3	QPSK	8	4	20.56	20.68	20.59		
3	QPSK	8	7	20.51	20.69	20.58		
3	QPSK	15	0	20.52	20.64	20.56	21.5	1
3	16QAM	1	0	20.46	20.57	20.39		
3	16QAM	1	8	20.09	20.44	20.33		
3	16QAM	1	14	20.37	20.51	20.44	20.5	2
3	16QAM	8	0	19.49	19.86	19.51		
3	16QAM	8	4	19.54	19.65	19.51		
3	16QAM	8	7	19.60	19.75	19.64	20.5	2
3	16QAM	15	0	19.54	19.51	19.59		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	21.52	21.66	21.36	22.5	0
1.4	QPSK	1	3	21.63	21.70	21.67		
1.4	QPSK	1	5	21.68	21.66	21.53		
1.4	QPSK	3	0	21.56	21.82	21.52		
1.4	QPSK	3	1	21.82	21.69	21.74		
1.4	QPSK	3	3	21.46	21.70	21.75		
1.4	QPSK	6	0	20.55	20.61	20.57	21.5	1
1.4	16QAM	1	0	20.33	20.60	20.35	21.5	1
1.4	16QAM	1	3	20.31	20.51	20.54		
1.4	16QAM	1	5	20.31	20.48	20.49		
1.4	16QAM	3	0	20.47	20.67	20.44		
1.4	16QAM	3	1	20.62	20.72	20.58		
1.4	16QAM	3	3	20.61	20.65	20.59	20.5	2
1.4	16QAM	6	0	19.13	19.61	19.54		

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600	24	0
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.93	23.14	22.80	24	0
10	QPSK	1	25	23.11	23.17	22.83		
10	QPSK	1	49	23.13	22.85	22.87		
10	QPSK	25	0	22.23	22.54	22.19	23	1
10	QPSK	25	12	22.31	22.59	22.15		
10	QPSK	25	25	22.39	22.41	22.09		
10	QPSK	50	0	22.29	22.50	22.08	23	1
10	16QAM	1	0	21.96	22.19	21.85		
10	16QAM	1	25	22.11	22.22	21.79		
10	16QAM	1	49	22.25	21.75	21.96	22	2
10	16QAM	25	0	21.33	21.41	20.95		
10	16QAM	25	12	21.35	21.31	20.96		
10	16QAM	25	25	21.44	21.27	20.96	22	2
10	16QAM	50	0	21.22	21.39	20.98		
Channel				20425	20525	20625	24	0
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.97	23.04	22.89	24	0
5	QPSK	1	12	23.15	23.11	22.91		
5	QPSK	1	24	22.76	23.11	22.95		
5	QPSK	12	0	22.19	22.59	22.11	23	1
5	QPSK	12	7	22.25	22.61	22.11		
5	QPSK	12	13	22.28	22.53	22.19		
5	QPSK	25	0	22.16	22.51	22.06	23	1
5	16QAM	1	0	22.01	22.13	21.88		
5	16QAM	1	12	22.23	22.21	21.83		
5	16QAM	1	24	21.85	21.87	21.81	22	2
5	16QAM	12	0	21.20	21.41	21.00		
5	16QAM	12	7	21.35	21.55	21.03		
5	16QAM	12	13	21.30	21.43	21.13	22	2
5	16QAM	25	0	21.26	21.44	21.08		

Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.88	22.87	22.82	24	0
3	QPSK	1	8	23.15	23.01	22.97		
3	QPSK	1	14	22.80	23.13	22.83		
3	QPSK	8	0	22.36	22.71	22.28	23	1
3	QPSK	8	4	22.21	22.60	22.17		
3	QPSK	8	7	22.21	22.53	22.42		
3	QPSK	15	0	22.22	22.55	22.25	23	1
3	16QAM	1	0	22.12	22.14	21.77		
3	16QAM	1	8	22.22	22.01	21.76		
3	16QAM	1	14	22.02	22.05	21.98	22	2
3	16QAM	8	0	21.22	21.51	21.15		
3	16QAM	8	4	21.17	21.54	21.34		
3	16QAM	8	7	21.26	21.57	21.48	22	2
3	16QAM	15	0	21.34	21.45	21.28		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	23.04	23.12	23.14	24	0
1.4	QPSK	1	3	23.15	23.09	23.09		
1.4	QPSK	1	5	22.91	23.11	23.03		
1.4	QPSK	3	0	23.08	23.11	22.94		
1.4	QPSK	3	1	23.13	23.11	23.09		
1.4	QPSK	3	3	23.13	23.09	23.08		
1.4	QPSK	6	0	22.14	22.52	22.38	23	1
1.4	16QAM	1	0	22.06	22.11	22.08	23	1
1.4	16QAM	1	3	22.22	22.21	22.08		
1.4	16QAM	1	5	21.89	22.25	21.97		
1.4	16QAM	3	0	22.15	22.48	22.24		
1.4	16QAM	3	1	22.24	22.54	22.35		
1.4	16QAM	3	3	22.19	22.49	22.31	22	2
1.4	16QAM	6	0	21.29	21.47	21.30		

<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	23.5	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.51	22.47	22.50		
10	QPSK	1	25	22.65	22.96	22.91	22.5	1
10	QPSK	1	49	22.68	22.89	22.62		
10	QPSK	25	0	21.66	21.83	21.89		
10	QPSK	25	12	21.72	21.97	21.96	22.5	1
10	QPSK	25	25	21.88	21.99	21.83		
10	QPSK	50	0	21.80	21.86	21.82		
10	16QAM	1	0	21.67	21.64	21.60	22.5	1
10	16QAM	1	25	21.51	21.54	21.91		
10	16QAM	1	49	21.67	21.82	21.51		
10	16QAM	25	0	20.65	20.63	20.91	21.5	2
10	16QAM	25	12	20.75	20.75	20.98		
10	16QAM	25	25	20.98	20.88	20.89		
10	16QAM	50	0	20.83	20.75	20.78	23.5	0
Channel				23035	23095	23155		
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.50	22.86	22.78	23.5	0
5	QPSK	1	12	22.82	22.92	22.84		
5	QPSK	1	24	22.51	22.85	22.51		
5	QPSK	12	0	21.90	21.87	21.95	22.5	1
5	QPSK	12	7	21.73	21.95	21.79		
5	QPSK	12	13	21.64	21.98	21.68		
5	QPSK	25	0	21.68	21.93	21.82	22.5	1
5	16QAM	1	0	21.55	21.80	21.76		
5	16QAM	1	12	21.61	21.75	21.53		
5	16QAM	1	24	21.49	21.55	21.73	21.5	2
5	16QAM	12	0	20.71	20.81	20.82		
5	16QAM	12	7	20.65	20.78	20.66		
5	16QAM	12	13	20.48	20.72	20.48	21.5	2
5	16QAM	25	0	20.58	20.85	20.73		

Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.88	22.71	22.83	23.5	0
3	QPSK	1	8	22.89	22.72	22.67		
3	QPSK	1	14	22.54	22.89	22.85		
3	QPSK	8	0	21.79	21.84	21.90	22.5	1
3	QPSK	8	4	21.83	21.96	21.77		
3	QPSK	8	7	21.77	21.94	21.88		
3	QPSK	15	0	21.80	21.98	21.82	22.5	1
3	16QAM	1	0	21.75	21.99	21.95		
3	16QAM	1	8	21.64	21.97	21.93		
3	16QAM	1	14	21.53	21.70	21.89	21.5	2
3	16QAM	8	0	20.98	20.91	20.92		
3	16QAM	8	4	20.86	21.05	20.77		
3	16QAM	8	7	20.82	21.01	20.73	21.5	2
3	16QAM	15	0	20.89	20.76	20.73		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.59	22.66	22.59	23.5	0
1.4	QPSK	1	3	22.67	22.86	22.80		
1.4	QPSK	1	5	22.63	22.87	22.88		
1.4	QPSK	3	0	22.58	22.82	22.64		
1.4	QPSK	3	1	22.73	22.83	22.88		
1.4	QPSK	3	3	22.74	22.84	22.87	22.5	1
1.4	QPSK	6	0	21.68	21.87	21.90		
1.4	16QAM	1	0	21.58	21.74	21.74	22.5	1
1.4	16QAM	1	3	21.75	21.95	21.81		
1.4	16QAM	1	5	21.78	21.94	21.78		
1.4	16QAM	3	0	21.74	21.95	21.74		
1.4	16QAM	3	1	21.69	21.94	21.93		
1.4	16QAM	3	3	21.71	22.00	21.94	21.5	2
1.4	16QAM	6	0	20.59	20.76	20.61		

<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800	23.5	0
Frequency (MHz)				709	710	711		
10	QPSK	1	0	22.23	22.35	22.34	23.5	0
10	QPSK	1	25	22.36	22.46	22.32		
10	QPSK	1	49	22.31	22.44	22.25		
10	QPSK	25	0	21.73	21.60	21.64	22.5	1
10	QPSK	25	12	21.73	21.57	21.55		
10	QPSK	25	25	21.70	21.75	21.66		
10	QPSK	50	0	21.66	21.73	21.65	22.5	1
10	16QAM	1	0	21.37	21.38	21.71		
10	16QAM	1	25	21.30	21.39	21.44		
10	16QAM	1	49	21.54	21.55	21.31	21.5	2
10	16QAM	25	0	20.78	20.69	20.76		
10	16QAM	25	12	20.85	20.72	20.71		
10	16QAM	25	25	20.62	20.66	20.63	21.5	2
10	16QAM	50	0	20.59	20.58	20.69		
Channel				23755	23790	23825	23.5	0
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	22.42	22.32	22.27	23.5	0
5	QPSK	1	12	22.41	22.31	22.29		
5	QPSK	1	24	22.38	22.45	22.39		
5	QPSK	12	0	21.68	21.41	21.65	22.5	1
5	QPSK	12	7	21.75	21.60	21.59		
5	QPSK	12	13	21.77	21.54	21.56		
5	QPSK	25	0	21.73	21.54	21.55	22.5	1
5	16QAM	1	0	21.67	21.28	21.45		
5	16QAM	1	12	21.65	21.40	21.38		
5	16QAM	1	24	21.37	21.26	21.21	21.5	2
5	16QAM	12	0	20.52	20.23	20.66		
5	16QAM	12	7	20.57	20.63	20.47		
5	16QAM	12	13	20.63	20.58	20.45	21.5	2
5	16QAM	25	0	20.79	20.58	20.54		

<WLAN Conducted Power>**General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	15.60	17.00	98.98
		6	2437	15.80	17.00	
		11	2462	16.10	17.00	
	802.11g 6Mbps	1	2412	15.40	16.50	92.75
		6	2437	15.60	16.50	
		11	2462	15.90	16.50	
	802.11n-HT20 MCS0	1	2412	14.10	16.00	92.82
		6	2437	14.30	16.00	
		11	2462	14.60	16.00	

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	13.38	14.00	96.98
		40	5200	13.32	14.00	
		44	5220	13.19	14.00	
		48	5240	13.09	14.00	
	802.11n-HT20 MCS0	36	5180	13.10	13.50	96.79
		40	5200	12.91	13.50	
		44	5220	12.84	13.50	
		48	5240	12.75	13.50	
	802.11n-HT40 MCS0	38	5190	12.93	13.50	93.68
		46	5230	12.66	13.50	
	802.11ac-VHT20 MCS0	36	5180	13.06	13.50	97.33
		40	5200	12.90	13.50	
		44	5220	12.78	13.50	
		48	5240	12.69	13.50	
	802.11ac-VHT40 MCS0	38	5190	12.75	13.50	94.19
		46	5230	12.50	13.50	
	802.11ac-VHT80 MCS0	42	5210	11.11	12.50	88.54

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	12.95	14.00	96.98
		56	5280	12.92	14.00	
		60	5300	12.93	14.00	
		64	5320	12.86	14.00	
	802.11n-HT20 MCS0	52	5260	12.70	13.50	96.79
		56	5280	12.65	13.50	
		60	5300	12.61	13.50	
		64	5320	12.57	13.50	
	802.11n-HT40 MCS0	54	5270	12.46	13.50	93.68
		62	5310	12.36	13.50	
	802.11ac-VHT20 MCS0	52	5260	12.65	13.50	97.33
		56	5280	12.61	13.50	
		60	5300	12.58	13.50	
		64	5320	12.53	13.50	
	802.11ac-VHT40 MCS0	54	5270	12.32	13.50	94.19
		62	5310	12.27	13.50	
	802.11ac-VHT80 MCS0	58	5290	10.78	12.50	88.54


5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	13.31	15.00	96.98
		116	5580	13.73	15.00	
		132	5660	13.61	15.00	
		140	5700	13.43	15.00	
		144	5720	13.17	15.00	
	802.11n-HT20 MCS0	100	5500	12.90	14.00	96.79
		116	5580	13.52	14.00	
		132	5660	13.40	14.00	
		140	5700	13.09	14.00	
		144	5720	12.88	14.00	
	802.11n-HT40 MCS0	102	5510	12.93	14.00	93.68
		110	5550	13.29	14.00	
		134	5670	13.18	14.00	
		142	5710	12.88	14.00	
	802.11ac-VHT20 MCS0	100	5500	12.85	14.00	97.33
		116	5580	13.47	14.00	
		132	5660	13.38	14.00	
		140	5700	13.04	14.00	
		144	5720	12.86	14.00	
	802.11ac-VHT40 MCS0	102	5510	12.79	14.00	94.19
		110	5550	13.21	14.00	
		134	5670	13.07	14.00	
		142	5710	12.82	14.00	
	802.11ac-VHT80 MCS0	106	5530	12.64	14.00	88.54
		138	5690	12.51	14.00	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	149	5745	13.11	14.50	96.98
		157	5785	13.44	14.50	
		165	5825	13.80	14.50	
	802.11n-HT20 MCS0	149	5745	12.87	14.00	96.79
		157	5785	13.15	14.00	
		165	5825	13.36	14.00	
	802.11n-HT40 MCS0	151	5755	12.63	14.00	93.68
		159	5795	12.87	14.00	
	802.11ac-VHT20 MCS0	149	5745	12.81	14.00	97.33
		157	5785	13.10	14.00	
		165	5825	13.28	14.00	
	802.11ac-VHT40 MCS0	151	5755	12.52	14.00	94.19
		159	5795	12.78	14.00	
	802.11ac-VHT80 MCS0	155	5775	12.62	14.00	88.54

<2.4GHz Bluetooth>

General Note:


1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.99 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the theoretical duty cycle is 83.3%, therefore the actual duty cycle will be scaled up to the theoretical value of Bluetooth reported SAR calculation



Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up limit (dBm)
			1Mbps	
BR/EDR	CH 00	2402	8.50	10.00
	CH 39	2441	8.80	
	CH 78	2480	8.80	

Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up limit (dBm)
			GFSK	
LE	CH 00	2402	3.10	4.50
	CH 19	2440	3.70	
	CH 39	2480	3.20	

13. Antenna Location



Back View

General Note:

- The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
- Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
- Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

Exposure Position	Wireless Interface	WCDMA Band V	WCDMA Band II	LTE Band 12	LTE Band 17	LTE Band 5	LTE Band 4	LTE Band 2	BT	2.4GHz WLAN ANT 1	5GHz WLAN ANT 1
	Calculated Frequency	846MHz	1907MHz	715MHz	713MHz	848MHz	1754MHz	1909MHz	2480MHz	2462MHz	5825MHz
	Maximum power (dBm)	23.50	23.5	23.5	23.5	24	22.5	23	10	17	15
	Maximum rated power(mW)	224.0	224.0	224.0	224.0	251.0	178.0	200.0	10.0	50.0	32.0
	Separation distance(mm)	5.0							5.0	5.0	5.0
Bottom Face	exclusion threshold	41.2	61.9	37.9	37.8	46.2	47.2	55.3	3.2	15.7	15.5
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	5.0							5.0	5.0	5.0
	exclusion threshold	41.2	61.9	37.9	37.8	46.2	47.2	55.3	3.2	15.7	15.5
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Edge 2	Separation distance(mm)	127.0							5.0	5.0	5.0
	exclusion threshold	597.0	879.0	544.0	544.0	598.0	883.0	879.0	3.2	15.7	15.5
	Testing required?	No	No	No	No	No	No	No	Yes	Yes	Yes
Edge 3	Separation distance(mm)	129.0							129.0	129.0	129.0
	exclusion threshold	609.0	899.0	554.0	553.0	610.0	903.0	899.0	885.0	886.0	852.0
	Testing required?	No	No	No	No	No	No	No	No	No	No
Edge 4	Separation distance(mm)	5.0							140.0	140.0	140.0
	exclusion threshold	41.2	61.9	37.9	37.8	46.2	47.2	55.3	995.0	996.0	962.0
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is not required when the measured SAR is ≤ 0.8 W/kg.

WCDMA Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B5 / B12 / B17 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE B17 SAR test was covered by B12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. For head SAR testing, Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

14.1 Body SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Bottom Face	0	4182	836.4	23.04	23.50	1.112	-0.09	0.316	0.351
	WCDMA V	RMC 12.2Kbps	Edge 1	0	4182	836.4	23.04	23.50	1.112	0.06	0.177	0.197
	WCDMA V	RMC 12.2Kbps	Edge 2	0	4182	836.4	23.04	23.50	1.112	0.08	0.049	0.054
	WCDMA V	RMC 12.2Kbps	Edge 3	0	4182	836.4	23.04	23.50	1.112	0.03	0.022	0.025
	WCDMA V	RMC 12.2Kbps	Edge 4	0	4182	836.4	23.04	23.50	1.112	0.13	0.187	0.208
01	WCDMA V	RMC 12.2Kbps	Bottom Face	0	4132	826.4	23.00	23.50	1.122	-0.14	0.315	0.353
	WCDMA V	RMC 12.2Kbps	Bottom Face	0	4233	846.6	22.99	23.50	1.125	0.07	0.312	0.351
	WCDMA II	RMC 12.2Kbps	Bottom Face	0	9262	1852.4	22.77	23.50	1.183	-0.06	0.289	0.342
	WCDMA II	RMC 12.2Kbps	Edge 1	0	9262	1852.4	22.77	23.50	1.183	0.03	0.730	0.864
	WCDMA II	RMC 12.2Kbps	Edge 2	0	9262	1852.4	22.77	23.50	1.183	0.01	0.021	0.025
	WCDMA II	RMC 12.2Kbps	Edge 3	0	9262	1852.4	22.77	23.50	1.183	0.12	0.001	0.001
	WCDMA II	RMC 12.2Kbps	Edge 4	0	9262	1852.4	22.77	23.50	1.183	0.15	0.764	0.904
	WCDMA II	RMC 12.2Kbps	Edge 1	0	9400	1880	22.62	23.50	1.225	0.04	0.873	1.069
02	WCDMA II	RMC 12.2Kbps	Edge 1	0	9538	1907.6	22.53	23.50	1.250	0.09	1.090	1.363
	WCDMA II	RMC 12.2Kbps	Edge 4	0	9400	1880	22.62	23.50	1.225	0.08	0.836	1.024
	WCDMA II	RMC 12.2Kbps	Edge 4	0	9538	1907.6	22.53	23.50	1.250	-0.02	0.957	1.196



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	25	Bottom Face	0	23095	707.5	22.96	23.50	1.132	-0.12	0.263	0.298
	LTE Band 12	10M	QPSK	1	25	Edge 1	0	23095	707.5	22.96	23.50	1.132	0.08	0.145	0.164
	LTE Band 12	10M	QPSK	1	25	Edge 2	0	23095	707.5	22.96	23.50	1.132	0.03	0.011	0.013
	LTE Band 12	10M	QPSK	1	25	Edge 3	0	23095	707.5	22.96	23.50	1.132	0.01	0.007	0.008
03	LTE Band 12	10M	QPSK	1	25	Edge 4	0	23095	707.5	22.96	23.50	1.132	0.14	0.364	0.412
	LTE Band 12	10M	QPSK	25	25	Bottom Face	0	23095	707.5	21.99	22.50	1.125	0.15	0.206	0.232
	LTE Band 12	10M	QPSK	25	25	Edge 1	0	23095	707.5	21.99	22.50	1.125	0.06	0.102	0.115
	LTE Band 12	10M	QPSK	25	25	Edge 2	0	23095	707.5	21.99	22.50	1.125	0.03	0.008	0.009
	LTE Band 12	10M	QPSK	25	25	Edge 3	0	23095	707.5	21.99	22.50	1.125	0.06	0.007	0.008
	LTE Band 12	10M	QPSK	25	25	Edge 4	0	23095	707.5	21.99	22.50	1.125	0.09	0.222	0.250
04	LTE Band 5	10M	QPSK	1	25	Bottom Face	0	20525	836.5	23.17	24.00	1.211	-0.06	0.280	0.339
	LTE Band 5	10M	QPSK	1	25	Edge 1	0	20525	836.5	23.17	24.00	1.211	-0.12	0.193	0.234
	LTE Band 5	10M	QPSK	1	25	Edge 2	0	20525	836.5	23.17	24.00	1.211	0.01	0.049	0.059
	LTE Band 5	10M	QPSK	1	25	Edge 3	0	20525	836.5	23.17	24.00	1.211	0.09	0.026	0.032
	LTE Band 5	10M	QPSK	1	25	Edge 4	0	20525	836.5	23.17	24.00	1.211	0.02	0.225	0.272
	LTE Band 5	10M	QPSK	25	12	Bottom Face	0	20525	836.5	22.59	23.00	1.099	0.05	0.238	0.262
	LTE Band 5	10M	QPSK	25	12	Edge 1	0	20525	836.5	22.59	23.00	1.099	0.09	0.115	0.126
	LTE Band 5	10M	QPSK	25	12	Edge 2	0	20525	836.5	22.59	23.00	1.099	0.01	0.039	0.043
	LTE Band 5	10M	QPSK	25	12	Edge 3	0	20525	836.5	22.59	23.00	1.099	0.04	0.024	0.026
	LTE Band 5	10M	QPSK	25	12	Edge 4	0	20525	836.5	22.59	23.00	1.099	-0.04	0.137	0.151
	LTE Band 4	20M	QPSK	1	49	Bottom Face	0	20175	1732.5	21.89	22.50	1.151	0.15	0.307	0.353
	LTE Band 4	20M	QPSK	1	49	Edge 1	0	20175	1732.5	21.89	22.50	1.151	-0.03	0.312	0.359
	LTE Band 4	20M	QPSK	1	49	Edge 2	0	20175	1732.5	21.89	22.50	1.151	0.05	0.002	0.003
	LTE Band 4	20M	QPSK	1	49	Edge 3	0	20175	1732.5	21.89	22.50	1.151	0.09	0.001	0.001
05	LTE Band 4	20M	QPSK	1	49	Edge 4	0	20175	1732.5	21.89	22.50	1.151	0.05	0.474	0.545
	LTE Band 4	20M	QPSK	50	0	Bottom Face	0	20175	1732.5	20.87	21.50	1.156	0.05	0.241	0.279
	LTE Band 4	20M	QPSK	50	0	Edge 1	0	20175	1732.5	20.87	21.50	1.156	0.09	0.243	0.281
	LTE Band 4	20M	QPSK	50	0	Edge 2	0	20175	1732.5	20.87	21.50	1.156	0.04	0.002	0.002
	LTE Band 4	20M	QPSK	50	0	Edge 3	0	20175	1732.5	20.87	21.50	1.156	0.08	0.001	0.001
	LTE Band 4	20M	QPSK	50	0	Edge 4	0	20175	1732.5	20.87	21.50	1.156	0.03	0.305	0.353
	LTE Band 2	20M	QPSK	1	49	Bottom Face	0	18700	1860	22.07	23.00	1.239	0.18	0.304	0.377
	LTE Band 2	20M	QPSK	1	49	Edge 1	0	18700	1860	22.07	23.00	1.239	0.07	0.695	0.861
	LTE Band 2	20M	QPSK	1	49	Edge 2	0	18700	1860	22.07	23.00	1.239	0.01	0.009	0.011
	LTE Band 2	20M	QPSK	1	49	Edge 3	0	18700	1860	22.07	23.00	1.239	0.08	0.005	0.006
	LTE Band 2	20M	QPSK	1	49	Edge 4	0	18700	1860	22.07	23.00	1.239	0.03	0.694	0.860
	LTE Band 2	20M	QPSK	1	49	Edge 1	0	18900	1880	21.93	23.00	1.279	-0.06	0.809	1.035
06	LTE Band 2	20M	QPSK	1	49	Edge 1	0	19100	1900	22.03	23.00	1.250	0.13	0.880	1.100
	LTE Band 2	20M	QPSK	1	49	Edge 4	0	18900	1880	21.93	23.00	1.279	0.02	0.803	1.027
	LTE Band 2	20M	QPSK	1	49	Edge 4	0	19100	1900	22.03	23.00	1.250	0.03	0.778	0.973
	LTE Band 2	20M	QPSK	50	24	Bottom Face	0	18700	1860	21.27	22.00	1.183	0.06	0.268	0.317
	LTE Band 2	20M	QPSK	50	24	Edge 1	0	18700	1860	21.27	22.00	1.183	-0.09	0.452	0.535
	LTE Band 2	20M	QPSK	50	24	Edge 2	0	18700	1860	21.27	22.00	1.183	0.01	0.024	0.028
	LTE Band 2	20M	QPSK	50	24	Edge 3	0	18700	1860	21.27	22.00	1.183	0.09	0.010	0.012
	LTE Band 2	20M	QPSK	50	24	Edge 4	0	18700	1860	21.27	22.00	1.183	0.02	0.436	0.516
	LTE Band 2	20M	QPSK	100	0	Edge 1	0	18700	1860	21.23	22.00	1.194	0.07	0.455	0.543
	LTE Band 2	20M	QPSK	100	0	Edge 4	0	18700	1860	21.23	22.00	1.194	0.01	0.446	0.533

<WLAN2.4GHz SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0	11	2462	16.10	17.00	1.230	98.98	1.010	0.01	0.254	0.316
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0	11	2462	16.10	17.00	1.230	98.98	1.010	0.02	0.102	0.127
	WLAN2.4GHz	802.11b 1Mbps	Edge 2	0	11	2462	16.10	17.00	1.230	98.98	1.010	0.08	0.133	0.165
	WLAN2.4GHz	802.11b 1Mbps	Edge 3	0	11	2462	16.10	17.00	1.230	98.98	1.010	0.02	0.009	0.011
	WLAN2.4GHz	802.11b 1Mbps	Edge 4	0	11	2462	16.10	17.00	1.230	98.98	1.010	0.06	0.001	0.001
07	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0	1	2412	15.60	17.00	1.380	98.98	1.010	-0.13	0.303	0.422
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0	6	2437	15.80	17.00	1.318	98.98	1.010	0.03	0.270	0.359

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Bottom Face	0	78	2480	8.80	10.00	1.318	76.99	1.082	0.06	0.020	0.029
	Bluetooth	DH5 1Mbps	Edge 1	0	78	2480	8.80	10.00	1.318	76.99	1.082	0.05	0.007	0.011
	Bluetooth	DH5 1Mbps	Edge 2	0	78	2480	8.80	10.00	1.318	76.99	1.082	0.02	0.010	0.014
	Bluetooth	DH5 1Mbps	Edge 3	0	78	2480	8.80	10.00	1.318	76.99	1.082	0	0.001	0.001
	Bluetooth	DH5 1Mbps	Edge 4	0	78	2480	8.80	10.00	1.318	76.99	1.082	0	0.001	0.001
08	Bluetooth	DH5 1Mbps	Bottom Face	0	0	2402	8.50	10.00	1.413	76.99	1.082	0.13	0.026	0.040
	Bluetooth	DH5 1Mbps	Bottom Face	0	39	2441	8.80	10.00	1.318	76.99	1.082	0.05	0.025	0.036

<WLAN 5GHz SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 5.3GH	802.11a 6Mbps	Bottom Face	0	52	5260	12.95	14.00	1.274	96.98	1.031	0.11	0.329	0.432
	WLAN 5.3GH	802.11a 6Mbps	Edge 1	0	52	5260	12.95	14.00	1.274	96.98	1.031	-0.06	0.138	0.181
	WLAN 5.3GH	802.11a 6Mbps	Edge 2	0	52	5260	12.95	14.00	1.274	96.98	1.031	-0.03	0.060	0.079
	WLAN 5.3GH	802.11a 6Mbps	Edge 3	0	52	5260	12.95	14.00	1.274	96.98	1.031	0.09	0.016	0.021
	WLAN 5.3GH	802.11a 6Mbps	Edge 4	0	52	5260	12.95	14.00	1.274	96.98	1.031	0.04	0.017	0.023
09	WLAN 5.3GH	802.11a 6Mbps	Bottom Face	0	56	5280	12.92	14.00	1.282	96.98	1.031	0.02	0.352	0.465
	WLAN 5.3GH	802.11a 6Mbps	Bottom Face	0	60	5300	12.93	14.00	1.279	96.98	1.031	0.09	0.309	0.408
	WLAN 5.3GH	802.11a 6Mbps	Bottom Face	0	64	5320	12.86	14.00	1.300	96.98	1.031	0.07	0.295	0.395
	WLAN 5.5GH	802.11a 6Mbps	Bottom Face	0	116	5580	13.73	15.00	1.340	96.98	1.031	0.07	0.229	0.316
	WLAN 5.5GH	802.11a 6Mbps	Edge 1	0	116	5580	13.73	15.00	1.340	96.98	1.031	-0.05	0.087	0.120
	WLAN 5.5GH	802.11a 6Mbps	Edge 2	0	116	5580	13.73	15.00	1.340	96.98	1.031	0.06	0.054	0.075
	WLAN 5.5GH	802.11a 6Mbps	Edge 3	0	116	5580	13.73	15.00	1.340	96.98	1.031	0.01	0.008	0.011
	WLAN 5.5GH	802.11a 6Mbps	Edge 4	0	116	5580	13.73	15.00	1.340	96.98	1.031	0.05	0.002	0.002
10	WLAN 5.5GH	802.11a 6Mbps	Bottom Face	0	100	5500	13.31	15.00	1.476	96.98	1.031	-0.04	0.301	0.458
	WLAN 5.5GH	802.11a 6Mbps	Bottom Face	0	132	5660	13.61	15.00	1.377	96.98	1.031	0.03	0.177	0.251
	WLAN 5.5GH	802.11a 6Mbps	Bottom Face	0	140	5700	13.43	15.00	1.435	96.98	1.031	0.09	0.156	0.231
	WLAN 5.5GH	802.11a 6Mbps	Bottom Face	0	144	5720	13.17	15.00	1.524	96.98	1.031	0.04	0.290	0.456
11	WLAN 5.8GH	802.11a 6Mbps	Bottom Face	0	165	5825	13.80	14.50	1.175	96.98	1.031	0.11	0.236	0.286
	WLAN 5.8GH	802.11a 6Mbps	Edge 1	0	165	5825	13.80	14.50	1.175	96.98	1.031	0.04	0.026	0.031
	WLAN 5.8GH	802.11a 6Mbps	Edge 2	0	165	5825	13.80	14.50	1.175	96.98	1.031	0.08	0.036	0.044
	WLAN 5.8GH	802.11a 6Mbps	Edge 3	0	165	5825	13.80	14.50	1.175	96.98	1.031	0.06	0.002	0.003
	WLAN 5.8GH	802.11a 6Mbps	Edge 4	0	165	5825	13.80	14.50	1.175	96.98	1.031	0.01	0.001	0.001
	WLAN 5.8GH	802.11a 6Mbps	Bottom Face	0	149	5745	13.11	14.50	1.377	96.98	1.031	0.06	0.199	0.283
	WLAN 5.8GH	802.11a 6Mbps	Bottom Face	0	157	5785	13.44	14.50	1.276	96.98	1.031	-0.03	0.181	0.238

15. Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	Edge 1	0	9538	1907.6	22.53	23.50	1.250	0.09	1.090	1	1.363
2nd	WCDMA II	RMC 12.2Kbps	Edge 1	0	9538	1907.6	22.53	23.50	1.250	-0.01	1.010	1.079	1.263

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured* SAR.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WCDMA + WLAN2.4GHz	Yes
2.	LTE + WLAN2.4GHz	Yes
3.	WCDMA + WLAN5GHz	Yes
4.	LTE + WLAN5GHz	Yes
5.	WCDMA + Bluetooth	Yes
6.	LTE + Bluetooth	Yes

General Note:

- EUT will choose either WCDMA or LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment though they have independent antenna.
- WLAN 2.4GHz and Bluetooth share the same antenna, and cannot transmit simultaneously.
- According to the character of the EUT, WLAN 5GHz and Bluetooth cannot transmit simultaneously.
- The reported SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6\text{W/kg}$.
 - $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.

16.1 Body Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
WCDMA	WCDMA II	Bottom Face at 0mm	0.342	0.422	0.465	0.040	0.76	0.81	0.38
		Edge 1 at 0mm	1.363	0.127	0.181	0.011	1.49	1.54	1.37
		Edge 2 at 0mm	0.025	0.165	0.079	0.014	0.19	0.10	0.04
		Edge 3 at 0mm	0.001	0.011	0.021	0.001	0.01	0.02	< 0.01
		Edge 4 at 0mm	1.196	0.001	0.023	0.001	1.20	1.22	1.20
	WCDMA V	Bottom Face at 0mm	0.353	0.422	0.465	0.040	0.78	0.82	0.39
		Edge 1 at 0mm	0.197	0.127	0.181	0.011	0.32	0.38	0.21
		Edge 2 at 0mm	0.054	0.165	0.079	0.014	0.22	0.13	0.07
		Edge 3 at 0mm	0.025	0.011	0.021	0.001	0.04	0.05	0.03
		Edge 4 at 0mm	0.208	0.001	0.023	0.001	0.21	0.23	0.21
LTE	LTE Band 2	Bottom Face at 0mm	0.377	0.422	0.465	0.040	0.80	0.84	0.42
		Edge 1 at 0mm	1.100	0.127	0.181	0.011	1.23	1.28	1.11
		Edge 2 at 0mm	0.028	0.165	0.079	0.014	0.19	0.11	0.04
		Edge 3 at 0mm	0.012	0.011	0.021	0.001	0.02	0.03	0.01
		Edge 4 at 0mm	1.027	0.001	0.023	0.001	1.03	1.05	1.03
	LTE Band 4	Bottom Face at 0mm	0.353	0.422	0.465	0.040	0.78	0.82	0.39
		Edge 1 at 0mm	0.359	0.127	0.181	0.011	0.49	0.54	0.37
		Edge 2 at 0mm	0.003	0.165	0.079	0.014	0.17	0.08	0.02
		Edge 3 at 0mm	0.001	0.011	0.021	0.001	0.01	0.02	< 0.01
		Edge 4 at 0mm	0.545	0.001	0.023	0.001	0.55	0.57	0.55
	LTE Band 5	Bottom Face at 0mm	0.339	0.422	0.465	0.040	0.76	0.80	0.38
		Edge 1 at 0mm	0.234	0.127	0.181	0.011	0.36	0.42	0.25
		Edge 2 at 0mm	0.059	0.165	0.079	0.014	0.22	0.14	0.07
		Edge 3 at 0mm	0.032	0.011	0.021	0.001	0.04	0.05	0.03
		Edge 4 at 0mm	0.272	0.001	0.023	0.001	0.27	0.30	0.27
	LTE Band 12	Bottom Face at 0mm	0.298	0.422	0.465	0.040	0.72	0.76	0.34
		Edge 1 at 0mm	0.164	0.127	0.181	0.011	0.29	0.35	0.18
		Edge 2 at 0mm	0.013	0.165	0.079	0.014	0.18	0.09	0.03
		Edge 3 at 0mm	0.008	0.011	0.021	0.001	0.02	0.03	0.01
		Edge 4 at 0mm	0.412	0.001	0.023	0.001	0.41	0.44	0.41

Test Engineer : Changlin Huang, Bin He, Mengming Dai

17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [8] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [9] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [10] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [11] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.



Appendix A. Plots of System Performance Check

The plots are shown as follows.

System Check_Head_750MHz

DUT: D750V3-SN:1099

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium: HSL_750_190622 Medium parameters used: $f = 750$ MHz; $\sigma = 0.879$ S/m; $\epsilon_r = 40.957$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(10, 10, 10); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.52 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 53.89 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.89 W/kg

SAR(1 g) = 2.01 W/kg; SAR(10 g) = 1.36 W/kg

Maximum value of SAR (measured) = 2.50 W/kg



System Check_Head_835MHz

DUT: D835V2-SN:4d162

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL_835_190622 Medium parameters used: $f = 835$ MHz; $\sigma = 0.877$ S/m; $\epsilon_r = 41.373$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.57, 9.57, 9.57); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.97 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.87 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 2.4 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 3.00 W/kg



System Check_Head_1750MHz

DUT: D1750V2-SN:1137

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL_1750_190621 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.398$ S/m; $\epsilon_r = 41.384$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8.54, 8.54, 8.54); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 12.6 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.37 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 15.6 W/kg

SAR(1 g) = 8.76 W/kg; SAR(10 g) = 4.72 W/kg

Maximum value of SAR (measured) = 12.4 W/kg



System Check_Head_1900MHz

DUT: D1900V2-SN:5d182

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL_1900_190620 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.385$ S/m; $\epsilon_r = 39.053$;
 $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8.27, 8.27, 8.27); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 13.3 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.98 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 9.42 W/kg; SAR(10 g) = 4.83 W/kg

Maximum value of SAR (measured) = 13.3 W/kg



System Check_Head_2450MHz

DUT: D2450V2-SN:736

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL_2450_190619 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.872$ S/m; $\epsilon_r = 38.404$;
 $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(7.21, 7.21, 7.21); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 21.6 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.24 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 31.3 W/kg

SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.33 W/kg

Maximum value of SAR (measured) = 22.2 W/kg



System Check_Head_5250MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: HSL_5250_190616 Medium parameters used: $f = 5200$ MHz; $\sigma = 4.496$ S/m; $\epsilon_r = 37.058$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(5.07, 5.07, 5.07); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 18.1 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 56.20 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 31.4 W/kg

SAR(1 g) = 7.55 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 18.1 W/kg



System Check_Head_5600MHz

DUT: D5GHzV2-SN:1167

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL_5600_190617 Medium parameters used: $f = 5600$ MHz; $\sigma = 4.85$ S/m; $\epsilon_r = 36.497$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(4.7, 4.7, 4.7); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 19.0 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.71 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 34.4 W/kg

SAR(1 g) = 7.67 W/kg; SAR(10 g) = 2.18 W/kg

Maximum value of SAR (measured) = 19.7 W/kg



System Check_Head_5750MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: HSL_5750_190617 Medium parameters used: $f = 5750$ MHz; $\sigma = 5.013$ S/m; $\epsilon_r = 36.309$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(4.77, 4.77, 4.77); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 18.7 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 44.03 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 35.6 W/kg

SAR(1 g) = 7.52 W/kg; SAR(10 g) = 2.02 W/kg

Maximum value of SAR (measured) = 19.9 W/kg





Appendix B. Plots of High SAR Measurement

The plots are shown as follows.

01_WCDMA V_RMC 12.2Kbps_Bottom Face_0mm_Ch4132

Communication System: UID 0, UMTS (0); Frequency: 826.4 MHz; Duty Cycle: 1:1
Medium: HSL_835_190622 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.868$ S/m; $\epsilon_r = 41.478$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.57, 9.57, 9.57); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch4132/Area Scan (61x81x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.416 W/kg


Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.34 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.487 W/kg

SAR(1 g) = 0.315 W/kg; SAR(10 g) = 0.198 W/kg

Maximum value of SAR (measured) = 0.404 W/kg



02_WCDMA II_RMC 12.2Kbps_Edge 1_0mm_Ch9538

Communication System: UID 0, UMTS (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: HSL_1900_190620 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.392$ S/m; $\epsilon_r = 39.023$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8.27, 8.27, 8.27); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch9538/Area Scan (51x71x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.70 W/kg


Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.690 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.53 W/kg

SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.435 W/kg

Maximum value of SAR (measured) = 1.85 W/kg



03_LTE Band 12_10M_QPSK_1RB_25Offset_Edge 4_0mm_Ch23095

Communication System: UID 0, LTE (0); Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: HSL_750_190622 Medium parameters used: $f = 707.5$ MHz; $\sigma = 0.856$ S/m; $\epsilon_r = 41.885$;
 $\rho = 1000$ kg/m³

Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(10, 10, 10); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch23095/Area Scan (51x71x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.393 W/kg


Ch23095/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.71 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.364 W/kg; SAR(10 g) = 0.164 W/kg

Maximum value of SAR (measured) = 0.747 W/kg



04_LTE Band 5_10M_QPSK_1RB_25Offset_Bottom Face_0mm_Ch20525

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: HSL_835_190622 Medium parameters used: $f = 836.5$ MHz; $\sigma = 0.879$ S/m; $\epsilon_r = 41.352$;
 $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.57, 9.57, 9.57); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch20525/Area Scan (61x81x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.375 W/kg


Ch20525/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.431 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.431 W/kg

SAR(1 g) = 0.280 W/kg; SAR(10 g) = 0.177 W/kg

Maximum value of SAR (measured) = 0.359 W/kg



05_LTE Band 4_20M_QPSK_1RB_49Offset_Edge 4_0mm_Ch20175

Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1
Medium: HSL_1750_190621 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.378$ S/m; $\epsilon_r = 41.436$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8.54, 8.54, 8.54); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch20175/Area Scan (51x71x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.586 W/kg


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.75 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.474 W/kg; SAR(10 g) = 0.197 W/kg

Maximum value of SAR (measured) = 0.802 W/kg



06_LTE Band 2_20M_QPSK_1RB_49Offset_Edge 1_0mm_Ch19100

Communication System: UID 0, LTE (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL_1900_190620 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.385$ S/m; $\epsilon_r = 39.053$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8.27, 8.27, 8.27); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch19100/Area Scan (51x71x1): Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.47 W/kg


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.062 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 0.880 W/kg; SAR(10 g) = 0.358 W/kg

Maximum value of SAR (measured) = 1.41 W/kg



07_WLAN2.4GHz_802.11b 1Mbps_Bottom Face_0mm_Ch1

Communication System: UID 0, WIFI (0); Frequency: 2412 MHz; Duty Cycle: 1:1.01

Medium: HSL_2450_190619 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.825$ S/m; $\epsilon_r = 38.567$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(7.21, 7.21, 7.21); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1/Area Scan (81x91x1): Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.415 W/kg


Ch1/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.024 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.783 W/kg

SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.410 W/kg



08_Bluetooth_DH5 1Mbps_Bottom Face_0mm_Ch0

Communication System: UID 0, Bluetooth (0); Frequency: 2402 MHz; Duty Cycle: 1:1.299

Medium: HSL_2450_190619 Medium parameters used: $f = 2402$ MHz; $\sigma = 1.813$ S/m; $\epsilon_r = 38.615$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(7.21, 7.21, 7.21); Calibrated: 2019.03.01;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch0/Area Scan (81x91x1): Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.106 W/kg


Ch0/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.0580 W/kg

SAR(1 g) = 0.026 W/kg; SAR(10 g) = 0.011 W/kg

Maximum value of SAR (measured) = 0.0412 W/kg



09_WLAN5GHz_802.11a 6Mbps_Bottom Face_0mm_Ch56

Communication System: UID 0, WIFI (0); Frequency: 5280 MHz; Duty Cycle: 1:1.031
Medium: HSL_5250_190616 Medium parameters used: $f = 5280$ MHz; $\sigma = 4.584$ S/m; $\epsilon_r = 36.932$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(5.07, 5.07, 5.07); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch56/Area Scan (81x101x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.39 W/kg


Ch56/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.831 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.53 W/kg

SAR(1 g) = 0.352 W/kg; SAR(10 g) = 0.078 W/kg

Maximum value of SAR (measured) = 0.856 W/kg



10_WLAN5GHz_802.11a 6Mbps_Bottom Face_0mm_Ch100

Communication System: UID 0, WIFI (0); Frequency: 5500 MHz; Duty Cycle: 1:1.031
Medium: HSL_5600_190617 Medium parameters used: $f = 5500$ MHz; $\sigma = 4.747$ S/m; $\epsilon_r = 36.625$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(4.7, 4.7, 4.7); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch100/Area Scan (81x101x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.739 W/kg


Ch100/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 3.537 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.301 W/kg; SAR(10 g) = 0.086 W/kg

Maximum value of SAR (measured) = 0.777 W/kg



11_WLAN5GHz_802.11a 6Mbps_Bottom Face_0mm_Ch165

Communication System: UID 0, WIFI (0); Frequency: 5825 MHz; Duty Cycle: 1:1.031
Medium: HSL_5750_190617 Medium parameters used: $f = 5825$ MHz; $\sigma = 5.081$ S/m; $\epsilon_r = 36.176$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(4.77, 4.77, 4.77); Calibrated: 2019.03.01;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn715; Calibrated: 2019.01.23
- Phantom: ELI v5.0(Right); Type: QDOVA001BB; Serial: TP:1225
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch165/Area Scan (81x101x1): Interpolated grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.638 W/kg


Ch165/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0.9160 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.97 W/kg

SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.059 W/kg

Maximum value of SAR (measured) = 0.615 W/kg





Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client

Sporton

Certificate No: **Z18-60532**

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1099**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **December 6, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22 ± 3) $^{\circ}\text{C}$ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Power sensor NRV-Z5	100596	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Reference Probe EX3DV4	SN 7514	27-Aug-18(SPEAG,No.EX3-7514_Aug18)	Aug-19
DAE4	SN 1555	20-Aug-18(SPEAG,No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
NetworkAnalyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function
Calibrated by:	Zhao Jing	SAR Test Engineer
Reviewed by:	Lin Hao	SAR Test Engineer
Approved by:	Qi Dianyuan	SAR Project Leader

Signature

Issued: December 9, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



In Collaboration with

s p e a g**CALIBRATION LABORATORY**

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	43.1 $\pm$ 6 %	0.87 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.07 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	8.52 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.38 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	5.64 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.0 $\pm$ 6 %	0.95 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	8.61 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.44 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	5.77 mW / g $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.2 Ω - 1.12j Ω
Return Loss	- 27.7dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.8 Ω - 3.37j Ω
Return Loss	- 29.4dB

General Antenna Parameters and Design

Electrical Delay (one direction)	0.900 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 12.05.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1099

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.865$ S/m; $\epsilon_r = 43.13$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.47, 9.47, 9.47) @ 750 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.37 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.12 W/kg

SAR(1 g) = 2.07 W/kg; SAR(10 g) = 1.38 W/kg

Maximum value of SAR (measured) = 2.75 W/kg




0 dB = 2.75 W/kg = 4.39 dBW/kg



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 12.05.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1099

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.951 \text{ S/m}$; $\epsilon_r = 54.02$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.68, 9.68, 9.68) @ 750 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.51 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 3.29 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.44 W/kg

Maximum value of SAR (measured) = 2.88 W/kg



0 dB = 2.88 W/kg = 4.59 dBW/kg




In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **Sporton**

Certificate No: **Z18-60533**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d162**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **December 5, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Power sensor NRV-Z5	100596	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Reference Probe EX3DV4	SN 7514	27-Aug-18(SPEAG,No.EX3-7514_Aug18)	Aug-19
DAE4	SN 1555	20-Aug-18(SPEAG,No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
NetworkAnalyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function
Calibrated by:	Zhao Jing	SAR Test Engineer
Reviewed by:	Lin Hao	SAR Test Engineer
Approved by:	Qi Dianyuan	SAR Project Leader

Signature

Issued: December 8, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	42.7 $\pm$ 6 %	0.88 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.35 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	9.61 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.56 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	6.35 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.7 $\pm$ 6 %	0.99 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.47 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	9.70 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.64 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	6.47 mW / g $\pm$ 18.7 % (k=2)



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.6 Ω - 2.56j Ω
Return Loss	- 28.9dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.2 Ω - 6.92j Ω
Return Loss	- 22.3dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.306 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 12.04.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d162

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.881$ S/m; $\epsilon_r = 42.71$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.09, 9.09, 9.09) @ 835 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.75 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.50 W/kg

SAR(1 g) = 2.35 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 3.11 W/kg




0 dB = 3.11 W/kg = 4.93 dBW/kg



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 12.04.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d162

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.986$ S/m; $\epsilon_r = 53.72$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(9.47, 9.47, 9.47) @ 835 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 55.24 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.64 W/kg

Maximum value of SAR (measured) = 3.29 W/kg



0 dB = 3.29 W/kg = 5.17 dBW/kg