



# FCC RF Test Report

**APPLICANT** : PAX Technology Limited  
**EQUIPMENT** : Smart Tablet  
**BRAND NAME** : PAX  
**MODEL NAME** : Aries6  
**FCC ID** : V5PAR6LITE  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DX) Low Power Communication Device Transmitter

The product was received on Nov. 01, 2019 and testing was completed on Dec. 11, 2019. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

*Derreck Chen*

Reviewed by: Derreck Chen / Supervisor

*Eric Shih*

Approved by: Eric Shih / Manager



**Sporton International (ShenZhen) Inc.**

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055  
People's Republic of China



# TABLE OF CONTENTS

**TABLE OF CONTENTS** .....2

**REVISION HISTORY** .....3

**SUMMARY OF THE TEST RESULT** .....4

**1. GENERAL DESCRIPTION** .....5

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test ..... 5

    1.4 Product Specification of Equipment Under Test ..... 5

    1.5 Modification of EUT ..... 6

    1.6 Re-use of Measured Data ..... 6

    1.7 Testing Location ..... 8

    1.8 Test Software ..... 8

    1.9 Applicable Standards..... 8

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST** .....9

    2.1 Descriptions of Test Mode ..... 9

    2.2 Connection Diagram of Test System ..... 10

    2.3 Table for Supporting Units ..... 11

    2.4 EUT Operation Test Setup ..... 11

**3. TEST RESULTS**.....12

    3.1 AC Power Line Conducted Emissions Measurement ..... 12

    3.2 Field Strength of Fundamental Emissions and Mask Measurement..... 14

    3.3 Radiated Emissions Measurement ..... 16

    3.4 Antenna Requirements..... 19

**4. LIST OF MEASURING EQUIPMENT** .....20

**5. UNCERTAINTY OF EVALUATION** .....21

**APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST ITEMS**

    B1. Test Result of Field Strength of Fundamental Emissions

    B2. Results of Radiated Emissions (9 kHz~30MHz)

    B3. Results of Radiated Emissions (30MHz~1GHz)

**APPENDIX C. SETUP PHOTOGRAPHS**

**APPENDIX D. REFERENCE REPORT**





### SUMMARY OF THE TEST RESULT

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 11.43 dB at 13.560MHz
-	15.215(c)	20dB Spectrum Bandwidth	Pass	1
	-	99% OBW Spectrum Bandwidth	Pass	1
-	15.225(e)	Frequency Stability	Pass	1
3.2	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 73.84 dBμV/m at 13.560 MHz
3.3	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 2.87 dB at 40.670MHz for Quasi-Peak
3.4	15.203	Antenna Requirements	Complies	-
<b>Note 1:</b> Test items are performed on original report which can be referred to Sporton report number FR941109D.				



# 1. General Description

## 1.1 Applicant

**PAX Technology Limited**

Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

## 1.2 Manufacturer

**PAX Computer Technology (Shenzhen) Co., Ltd.**

4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Smart Tablet
<b>Brand Name</b>	PAX
<b>Model Name</b>	Aries6
<b>FCC ID</b>	V5PAR6LITE
<b>EUT supports Radios application</b>	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR / LE NFC
<b>IMEI Code</b>	Conduction/Radiation: N/A
<b>HW Version</b>	N/A
<b>SW Version</b>	N/A
<b>EUT Stage</b>	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	13.553 ~ 13.567MHz
<b>Channel Number</b>	1
<b>Antenna Type</b>	PCB Antenna
<b>Type of Modulation</b>	ASK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Re-use of Measured Data

#### 1.6.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: Aries6, FCC ID: V5PAR6LITE) is electrically identical to the reference device (Model: Aries6, FCC ID: V5PAR6) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

#### 1.6.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FR941109A for the reference device Model: Aries6, FCC ID: V5PAR6).

#### 1.6.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
DSS (BR/EDR)	V5PAR6	Part15C(FR941109A)	All sections applicable except AC Conducted Emission and RSE
DTS (BLE)	V5PAR6	Part15C(FR941109B)	All sections applicable except AC Conducted Emission and RSE
DTS (WLAN)	V5PAR6	Part15C(FR941109C)	All sections applicable except AC Conducted Emission and RSE
DXX(NFC)	V5PAR6	Part15C(FR941109D)	All sections applicable except AC Conducted Emission and RSE



1.6.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for the following test items, the test result were consistent with FCC ID: V5PAR6.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

Test Item	Mode	V5PAR6 Worst Result	V5PAR6LITE Worst Result	Difference (dB)
Peak Conducted Power (dBm)	Bluetooth BR	9.90	7.77	-2.13
	Bluetooth LE	3.70	3.50	-0.20
	WLAN 802.11b	16.10	15.50	-0.60
	WLAN 802.11a	13.80	13.42	-0.38
Radiated Spurious Emission (Band Edge. Harmonic) (dBuV/m)	NFC	36.99	37.13	0.14



### 1.7 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-SZ	CN1256	421272
<b>Test Engineer</b>	Liu DaLin		
<b>Temperature</b>	22~25°C		
<b>Relative Humidity</b>	50~55%		

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH04-SZ	CN1256	421272
<b>Test Engineer</b>	He Tao		
<b>Temperature</b>	24~25°C		
<b>Relative Humidity</b>	48~49%		

### 1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013





## 2. Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz


The EUT pre-scanned in four NFC type, A, B. The worst type (type A) was recorded in this report.

Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.


Test Cases	
<b>AC Conducted Emission</b>	Mode 1: Bluetooth Link + WLAN Link (2.4G) + NFC Tx + USB Cable(Charging from Adapter) + Earphone
<b>Remark:</b> For Radiated Test Cases, The tests were performed with Adapter, Earphone and USB Cable	

## 2.2 Connection Diagram of Test System

For Radiation



For Conducted Emission



## 2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
2.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2m DC O/P: Shielded, 1.8 m
3.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A
4.	Bluetooth Earphone	Samsung	EO-MG900	N/A	N/A	N/A
5.	NFC Card	N/A	N/A	N/A	N/A	N/A
6.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8m

## 2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.

### 3. Test Results

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test setup



### 3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



### 3.2 Field Strength of Fundamental Emissions and Mask Measurement

#### 3.2.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### 3.2.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.  
Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

### 3.2.4 Test Setup

For radiated emissions below 30MHz



### 3.2.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

### 3.3 Radiated Emissions Measurement

#### 3.3.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.






### **3.3.4 Test Procedures**


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

### 3.3.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



### 3.3.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

**Remark:** There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



## **3.4 Antenna Requirements**

### **3.4.1 Standard Applicable**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.4.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Apr. 18, 2019	Dec. 11, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 18, 2019	Dec. 11, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 29, 2018	Dec. 11, 2019	May 28, 2020	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Aug. 27, 2019	Dec. 11, 2019	Aug. 26, 2020	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 18, 2019	Dec. 11, 2019	Oct. 17, 2020	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Dec. 11, 2019	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Dec. 11, 2019	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Dec. 11, 2019	NCR	Radiation (03CH04-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Nov. 21, 2019~Nov. 26, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 17, 2019	Nov. 21, 2019~Nov. 26, 2019	Oct. 16, 2020	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	Nov. 21, 2019~Nov. 26, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 23, 2019	Nov. 21, 2019~Nov. 26, 2019	Jul. 22, 2020	Conduction (CO01-SZ)

NCR: No Calibration Required



### 5. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

**Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)**

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.6 dB
---	--------

**Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)**


Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

**Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)**

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------



## Appendix A. Test Results of Conducted Emission Test




(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Liu DaLin	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_20190719\_N NEUTRAL


	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.37	24.23	-24.20	48.43	14.20	0.02	10.01	Average
2	0.37	34.63	-23.80	58.43	24.60	0.02	10.01	QP
3	0.51	22.08	-23.92	46.00	12.00	0.02	10.06	Average
4	0.51	34.38	-21.62	56.00	24.30	0.02	10.06	QP
5	0.60	32.09	-13.91	46.00	22.00	0.02	10.07	Average
6	0.60	43.59	-12.41	56.00	33.50	0.02	10.07	QP
7	0.71	28.49	-17.51	46.00	18.40	0.02	10.07	Average
8	0.71	37.09	-18.91	56.00	27.00	0.02	10.07	QP
9	9.30	24.88	-25.12	50.00	14.50	0.14	10.24	Average
10	9.30	43.28	-16.72	60.00	32.90	0.14	10.24	QP
11	11.32	27.97	-22.03	50.00	17.50	0.21	10.26	Average
12	11.32	39.27	-20.73	60.00	28.80	0.21	10.26	QP
13 !	13.56	53.27	3.27	50.00	42.70	0.29	10.28	Average
14 *	13.56	68.17	8.17	60.00	57.60	0.29	10.28	QP

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Liu DaLin	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line



Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_20190719\_L LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	13.56	37.25	-12.75	50.00	26.50	0.47	10.28	Average
2	13.56	46.75	-13.25	60.00	36.00	0.47	10.28	QP


(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.





Test Engineer :	Liu DaLin	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ  
 Condition: FCC 15C\_QP LISN\_20190719\_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	13.56	38.57	-11.43	50.00	28.00	0.29	10.28	Average
2	13.56	45.77	-14.23	60.00	35.20	0.29	10.28	QP

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



## Appendix B. Test Results of Radiated Test Items

### B1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56																														
<p>Site : 03CH04-SZ Condition : 15.225 LIMIT 3m LOOP ANTENNA 1706 HORIZONTAL</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>ReadAntenna Level</th> <th>Antenna Factor</th> <th>Cable Loss</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>13.56</td> <td>73.84</td> <td>-50.16</td> <td>124.00</td> <td>53.92</td> <td>19.47</td> <td>0.45</td> <td>---</td> <td>--- QP</td> </tr> </tbody> </table>				Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	13.56	73.84	-50.16	124.00	53.92	19.47	0.45	---	--- QP
Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark																								
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																									
1	13.56	73.84	-50.16	124.00	53.92	19.47	0.45	---	--- QP																								
<p>Site : 03CH04-SZ Condition : 15.225 LIMIT 3m LOOP ANTENNA 1706 VERTICAL</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>ReadAntenna Level</th> <th>Antenna Factor</th> <th>Cable Loss</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>13.56</td> <td>72.73</td> <td>-51.27</td> <td>124.00</td> <td>52.81</td> <td>19.47</td> <td>0.45</td> <td>---</td> <td>--- QP</td> </tr> </tbody> </table>				Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	13.56	72.73	-51.27	124.00	52.81	19.47	0.45	---	--- QP
Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark																								
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																									
1	13.56	72.73	-51.27	124.00	52.81	19.47	0.45	---	--- QP																								

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



B2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx			Polarization :		Horizontal		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.04598	55.73	-58.62	114.35	35.17	20.5	0.06	-	-	Average
0.08766	51.3	-57.45	108.75	30.53	20.7	0.07	-	-	Average
0.09096	52.85	-55.58	108.43	32.08	20.7	0.07	-	-	QP
0.12897	44.67	-60.72	105.39	23.99	20.6	0.08	-	-	Average
1.016	42.18	-25.29	67.47	21.46	20.6	0.12	-	-	QP
2.252	36.2	-33.8	70	15.57	20.54	0.09	-	-	QP
13.032	40.06	-29.94	70	20.11	19.5	0.45	-	-	QP
16.27	36.07	-33.93	70	16.05	19.53	0.49	-	-	QP
29.975	34.82	-35.18	70	14.39	19.69	0.74	-	-	QP

Test Mode :		NFC Tx			Polarization :		Vertical		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.04608	55.52	-58.81	114.33	34.96	20.5	0.06	-	-	Average
0.08037	46.46	-63.04	109.5	25.89	20.5	0.07	-	-	Average
0.09219	45.24	-63.07	108.31	24.47	20.7	0.07	-	-	QP
0.13194	39.55	-65.65	105.2	18.87	20.6	0.08	-	-	Average
1.01	41.22	-26.3	67.52	20.5	20.6	0.12	-	-	QP
2.174	37.34	-32.66	70	16.7	20.54	0.1	-	-	QP
10.368	50.96	-19.04	70	30.22	20.33	0.41	-	-	QP
16.018	47.6	-22.4	70	27.62	19.5	0.48	-	-	QP
27.12	36.53	-33.47	70	16.32	19.49	0.72	-	-	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
3. Limit line = specific limits (dBμV) + distance extrapolation factor.



B3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :		NFC Tx			Polarization :		Horizontal			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
34.85	32.98	-7.02	40	41.21	21.8	0.57	30.6	-	-	Peak
108.57	22.91	-20.59	43.5	37.11	17.31	1.06	32.57	-	-	Peak
149.31	38.41	-5.09	43.5	52.77	16.79	1.25	32.4	142	90	Peak
190.05	32.64	-10.86	43.5	48.08	15.4	1.4	32.24	-	-	Peak
450.01	32.18	-13.82	46	39.38	22.5	2.2	31.9	-	-	Peak
749.74	38.28	-7.72	46	42.19	25.54	2.85	32.3	-	-	Peak

Test Mode :		NFC Tx			Polarization :		Vertical			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
40.67	37.13	-2.87	40	50.2	18.91	0.62	32.6	100	272	QP
57.16	36.69	-3.31	40	55.65	12.88	0.76	32.6	-	-	Peak
190.05	36.63	-6.87	43.5	52.02	15.45	1.4	32.24	-	-	Peak
379.2	28.02	-17.98	46	36.62	21.29	2.05	31.94	-	-	Peak
450.01	28.87	-17.13	46	35.82	22.75	2.2	31.9	-	-	Peak
749.74	32.71	-13.29	46	36.52	25.64	2.85	32.3	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.



## **Appendix D. Reference Report**

Please refer to Sporton report number FR941109D which is issued separately.