





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 1 of 14

TEST REPORT

Application No.: FYCR2301000009AT **Applicant:** PAX Technology Limited

Address of Applicant: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Hong Kong

Manufacturer: PAX Computer Technology (Shenzhen) Co., Ltd.

Address of Manufacturer: 401 and 402, Building 3, Shenzhen Software Park, Nanshan District,

Shenzhen City, Guangdong Province, P.R.C

Equipment Under Test (EUT):

EUT Name: UNATTENDED PAYMENT TERMINAL

Model No.: IM15 Trade Mark: PAX

FCC ID: V5PIM154GBW
Standard(s): 47 CFR Part 1.1307

47 CFR Part 1.1310

FCC Rules 47 CFR §2.1091

KDB 447498 D04 interim General RF Exposure Guidance v01

Date of Receipt: 2023-01-10

Date of Evaluation: 2023-01-16 to 2023-02-13

Date of Issue: 2023-03-06

Evaluation Result: Pass*

Winkey Wang EMC Technical Manager

WinkeyWang



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.sgx. Attention is drawn to the limitation of liability, indemnification and juryisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755)83071443

^{*} In the configuration evaluated, the EUT complied with the standards specified above.



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 2 of 14

	Revision Record									
Version	Version Chapter Date Modifier									
01		2023-03-06		Original						

Authorized for issue by:			
	Tree Zhan		
	Tree Zhan/Project Engineer	- _	
	WinkeyWang		
	Winkey Wang/Reviewer	_	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/T



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 3 of 14

2 Contents

			Fage
1	Co	over Page	1
2	Co	ontents	3
_			
3	Ge	eneral Information	4
	3.1	General Description of E.U.T.	4
	3.2	Details of E.U.T.	
	3.3	Separation Distance	
	3.4	Test Location	
	3.5	Test Facility	
	3.6	Deviation from Standards	6
	3.7	Abnormalities from Standard Conditions	6
4	FC	C Radiofrequency radiation exposure limits	7
	4.1	Blanket 1 mW Blanket Exemption	7
	4.2	MPE-based Exemption	
	4.3	SAR-based Exemption	
5	Me	easurement and Calculation	10
	5.1	Maximum transmit power	10
	5.2	RF Exposure Calculation	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemplification issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, remail: CARD Docebeck@ass.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 4 of 14

3 General Information

3.1	General	Description	of E.U.T.
-----	---------	--------------------	-----------

	☐ Portable device
Product Type:	⊠ Mobile device
	☐ Fixed device

3.2 Details of E.U.T.

Power supply:	DC5V from USB type C port			
	Or DC12-48V by DC Source			
	Or DC12V/1A by AC/DC adapter			
For BT:				
Operation Frequency:	2402MHz to 2480MHz			
Bluetooth Version:	V5.0 Dual mode			
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK			
Number of Channels:	79			
Channel Spacing:	1MHz			
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)			
Antenna Type:	PIFA Antenna			
Antenna Gain:	1.14dBi			

For BLE:	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0 Dual mode
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	1.14dBi
For 2.4G:	
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK)
Modulation Type.	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11
Channel Spacing:	5MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	1.14dBi
For 5G:	
Operation	U-NII-1: 5180-5240MHz (4 Channels)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Condi

| Fuyorg lab. Xinlong TechnoPark, Fargiang Road, Fuyong Subdistrid, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 5 of 14

Frequency/Number of channels (20MHz):	U-NII-2A: 5260-5320MHz (4 Channels)					
Charmers (20101112).	U-NII-2C: 5500-5700MHz (11 Channels)					
	U-NII-3: 5745-5825MHz (5 Channels)					
	U-NII-1: 5190-5230MHz (2 Channels)					
Operation Frequency/Number of	U-NII-2A: 5270-5310MHz (2 Channels)					
channels/(40MHz):	U-NII-2C: 5510-5670MHz (5 Channels)					
, ,	U-NII-3: 5755-5795MHz (2 Channels)					
	U-NII-1: 5210MHz (1 Channel)					
Operation Frequency/Number of	U-NII-2A: 5290MHz (1 Channels)					
channels (80MHz):	U-NII-2C: 5530-5610MHz (2 Channels)					
, ,	U-NII-3: 5775MHz (1 Channel)					
	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)					
Modulation Type:	802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)					
	802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)					
	802.11a/n(HT20)/ac(HT20): 20MHz					
Channel Spacing:	802.11n(HT40)/ac(HT40): 40MHz					
	802.11ac(HT80): 80MHz					
DFS Function:	Slave without Radar detection					
TPC Function:	Without TPC function					
Antenna Type:	PIFA Antenna					
Antenna Gain:	3.4dBi					
For NFC:						
Operation Frequency:	13.56MHz					
Modulation Type:	ASK					
Antenna Type:	Loop Antenna					
For LTE(contained FCC ID:X	MR2020BG95M1):					
LTE Operation Frequency Band:	LTE FDD Band 2,4,5,12,13,14,25,26,66,85					
Modulation Type:	QPSK, 16QAM					
LTE Power Class:	Level 3					
Antenna Type:	PIFA Antenna					
Antenna Gain:	B2: 2dBi; B4: 3dBi; B5: 1dBi; B12: 1dBi; B13: 1dBi; B14: 1dBi; B25: 2dBi; B26: 1dBi; B66: 3dBi; B85:1dBi					

Remark: The information in this section is provided by the applicant or manufacturer, CCS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

447498 D04 Interim General RF Exposure Guidance v01 is not accredited by A2LA



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate

| Fuyorg lab. Xinlong TechnoPark, Fargiang Road, Fuyong Subdistrid, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 6 of 14

3.3 Separation Distance

Minimum test separation distance:

20cm

Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China

Fax: +86 755 2671 0594 Tel: +86 755 8866 3988

No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

• FCC -Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

• Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.

3.6 Deviation from Standards

Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 7 of 14

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f∟ MHz		f₁ MHz	λ∟ / 2π	λ _L / 2π λ _H / 2π		W
0.3	_	1.34	159 m	_	35.6 m	1,920 R ²
1.34	_	30	35.6 m	_	1.6 m	3,450 R ² /f ²
30	_	300	1.6 m	_	159 mm	3.83 R ²
300	_	1,500	159 mm	_	31.8 mm	0.0128 R ² f
1,500	_	100,000	31.8 mm	_	0.5 mm	19.2R ²

Subscripts L and H are low and high; λ is wavelength.

From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 8 of 14

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than *ERP*_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation								
Frequency range	Frequency(MHz)	$R(\lambda 2\pi)(m)$	Threshold ERP(W)					
300~1500MHz	915	0.0522	0.032					
1500~100000MHz	2480	0.0193	0.007					

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 9 of 14

The SAR-based exemption formula of $\S1.1307(b)(3)(i)(B)$, repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B. 2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\,\mathrm{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency		Distance(mm)								
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation								
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)				
0.3~1.5	0.915	1.474	0.5	8.133				
1.5~6	2.48	1.905	0.5	2.717				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 10 of 14

5 Measurement and Calculation

5.1 Maximum transmit power

For BT:

Antenna Gain: 1.14dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum Conducted Power [dBm]	Maximum EIRP [dBm]	Maximum EIRP Power (mW)	
2441	7.80	8.94	7.83	

Note: Refer to report No. FYCR230100000902 for EUT test Max Power Value.

For BLE:

Antenna Gain: 1.14dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum Conducted Power [dBm]	Maximum EIRP [dBm]	Maximum EIRP Power (mW)
2440	3.99	5.13	3.26

Note: Refer to report No. FYCR230100000903 for EUT test Max Power Value.

For 2.4G:

Antenna gain:1.14dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum Conducted Power [dBm]	Maximum EIRP [dBm]	Maximum EIRP Power (mW)	
2437	14.50	15.64	36.64	

Note: Refer to report No. FYCR230100000904 for EUT test Max Power Value.

For 5G:

Antenna gain:3.4dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum Conducted Power [dBm]	Maximum EIRP [dBm]	Maximum EIRP Power (mW)	
5200	14.14	17.54	56.75	

Note: Refer to report No. FYCR230100000905 for EUT test Max Power Value.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and juryaidation issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Liness otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdishird, Bad'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 11 of 14

For NFC:

Mode	E-field strength(dBuV/m)			Limit(mW)	Verdict
NFC	67.25	0.0023	0.00159	1	Pass

$$EIRP = p_t \times g_t = (E \times d)^2 / 30$$

where

 $p_{\rm t}$ is the transmitter output power in watts

 g_t is the numeric gain of the transmitting antenna (dimensionless)

E is the electric field strength in V/m

d is the measurement distance in meters (m)

$$ERP = EIRP/1.64 = (E \times d)^2 / (30 \times 1.64) = (E \times d)^2 / 49.2$$

For LTE:

Antenna gain: B2: 2dBi; B4: 3dBi; B5: 1dBi; B12: 1dBi; B13: 1dBi; B14: 1dBi; B25: 2dBi; B26: 1dBi;

B66: 3dBi; B85:1dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Operating Band	Frequency	Frequency Maximum Conducted Maximum Power [dBm]		Maximum EIRP Power (mW)
2	1850.1	22	24	251.1886
4	1710.1	22	25	316.2278
5	824.1	22	23	199.5262
12	699.1	22	23	199.5262
13	777.1	22	23	199.5262
14	788.1	22	23	199.5262
25	1850.1	22	24	251.1886
26	814.1	22	23	199.5262
66	1710.1	22	25	316.2278
85	698.1	22	23	199.5262

Note: Refer to FCC ID:XMR2020BG95M1 for Max Power Value.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest settent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdishird, Bad'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 12 of 14

Remark: max conducted power including tune up, lowest frequency for Cat NB is selected to get worst limit evaluation.

5.2 RF Exposure Calculation

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

For BT:

The Max Power is 7.83mW. The best case gain of the antenna is 1.14dBi.

	Evaluation method	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
	Blanket 1 mW Blanket Exemption	/	1mW	0	N/A
	MPE-based Exemption(ERP)	/	7mW(ERP)	0	N/A
\boxtimes	SAR-based Exemption(Pth)	7.83	3060	0.0026	Pass

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For BLE:

The Max Power is 3.26mW. The best case gain of the antenna is 1.14dBi.

	Evaluation method	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
	Blanket 1 mW Blanket / Exemption		1mW	0	N/A
	MPE-based Exemption(ERP)	/	7mW(ERP)	0	N/A
\boxtimes	SAR-based Exemption(Pth)	3.26	3060	0.0011	Pass

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For 2.4G:

The Max Power is 36.64mW. The best case gain of the Ant:1.14dBi

	Evaluation method	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
	Blanket 1 mW Blanket Exemption	/	1mW	0	N/A
	MPE-based Exemption(ERP)	1	7mW(ERP)	0	N/A
\boxtimes	SAR-based Exemption(Pth)	36.64	3060	0.0120	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.and, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 13 of 14

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For 5G:

The Max Power is 56.75mW. The best case gain of the Ant:3.4dBi

	Evaluation method	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
	Blanket 1 mW Blanket Exemption	/	1mW	0	N/A
	MPE-based Exemption(ERP)	/	7mW(ERP)	0	N/A
\boxtimes	SAR-based Exemption(P th)	56.75	3060	0.0185	Pass

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For NFC:

The Max Power is 0.00159mW.

Evaluation method	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
Blanket 1 mW Blanket Exemption	0.00159	1mW	0.00159	Pass
MPE-based / Exemption(ERP)		7mW(ERP)	/	N/A
SAR-based Exemption(Pth)	/	3060	/	N/A

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For LTE:

The best case gain is B2: 2dBi; B4: 3dBi; B5: 1dBi; B12: 1dBi; B13: 1dBi; B14: 1dBi; B25: 2dBi; B26: 1dBi; B66: 3dBi; B85:1dBi

Evaluation method	Operating Band	RF Power(mW)	Exempt Limit(mW)	MPE ratio	Verdict
Blanket 1 mW Blanket Exemption	/	/	1mW	0	N/A
MPE-based Exemption(ERP)	/	/	7mW(ERP)	0	N/A
SAR-based Exemption(P_{th})	2	251.1886	3060	0.1301	Pass
SAR-based Exemption(<i>P</i> th)	4	316.2278	3060	0.2062	Pass
SAR-based Exemption(<i>P</i> th)	5	199.5262	1681.16	0.1494	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230100000907

Page: 14 of 14

	SAR-based Exemption(<i>P</i> th)	12	199.5262	1426.16	0.1761	Pass
\boxtimes	SAR-based Exemption(<i>P</i> th)	13	199.5262	1585.28	0.1585	Pass
	SAR-based Exemption(P_{th})	14	199.5262	1607.72	0.1562	Pass
	SAR-based Exemption(<i>P</i> th)	25	251.1886	3060	0.1301	Pass
	SAR-based Exemption(<i>P</i> th)	26	199.5262	1660.76	0.1512	Pass
\boxtimes	SAR-based Exemption(P_{th})	66	316.2278	3060	0.2062	Pass
	SAR-based Exemption(<i>P</i> th)	85	199.5262	1424.12	0.1764	Pass

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

For simultaneously transmitter:

Operating Mode	MPE ratio	MPE limit	Verdict
BT+LTE	0.2088	1	Pass
2.4GWIFI+LTE	0.2182	1	Pass
5GWIFI+LTE	0.2247	1	Pass

Remark: NFC didn't support simultaneously transmission with other transmitters.

KDB 447498 D04 is not accredited by A2LA.

-- End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or amalic CND Doccheck@ess.com.