

FCC RF Test Report

(NFC)

Applicant: PAX Technology Limited
Address of Applicant: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong Kong
Equipment Under Test (EUT)
Product Name: POS Terminal
Model No.: IM20
Trade Mark: PAX
FCC ID: V5PIM20BWL
Applicable Standards: FCC CFR Title 47 Part 15C (§15.225)
Date of Sample Receipt: 08 Aug., 2022
Date of Test: 09 Aug., to 17 Sep., 2022
Date of Report Issue: 19 Sep., 2022
Test Result: PASS

Tested by:	<u>Mike OU</u> Test Engineer	Date:	<u>19 Sep., 2022</u>
Reviewed by:	<u>Winnier Zhao</u> Project Engineer	Date:	<u>19 Sep., 2022</u>
Approved by:	<u>Winnier Zhao</u> Manager	Date:	<u>19 Sep., 2022</u>

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	19 Sep., 2022	Original
01	18 Oct., 2022	Updated page 5, page 15 and page 16

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents	3
3 General Information	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions From the Method.....	5
3.7 Laboratory Facility	5
3.8 Laboratory Location.....	5
3.9 Test Instruments List	7
4 Measurement Setup and Procedure	8
4.1 Test Setup	8
4.2 Test Procedure	9
5 Test Results	10
5.1 Summary	10
5.1.1 Clause and Data Summary.....	10
5.1.2 Test Limit.....	11
5.2 Antenna Requirement	12
5.3 AC Power Line Conducted Emission	13
5.4 20dB Bandwidth	17
5.5 Field Strength of Fundamental.....	18
5.6 Field Strength of Spurious Emissions	20
5.7 Frequency Tolerance	24

3 General Information

3.1 Client Information

Applicant:	PAX Technology Limited
Address:	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong Kong
Manufacturer:	PAX Computer Technology (Shenzhen) Co., Ltd.
Address:	401 and 402, Building 3, Shenzhen Software Park, Nanshan District, Shenzhen City, Guangdong Province, P.R.C

3.2 General Description of E.U.T.

Product Name:	POS Terminal
Model No.:	IM20
Operation Frequency:	13.56MHz
Channel Numbers:	1
Modulation Type:	ASK
Antenna Type:	Induction Coil Antenna
Power Supply:	12-48Vdc by MDB or 5Vdc by USB
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode and Environment

Test Mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation
Transmitting without NFC ANT mode	Keep the EUT in Transmitting without NFC ANT mode
<i>Remark: Pre-scan The EUT was placed on three different polar directions tested: i.e. X axis, Y axis, Z axis, and found Y axis was worse case, so the report only reflects the worse axis tested data.</i>	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar

3.4 Description of Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
N/A	N/A	N/A	N/A	N/A

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	±3.11 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.62 dB
Radiated Emission (9kHz ~ 30MHz) (3m SAC)	±3.13 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	±4.45 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	±5.34 dB

Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.6 Additions to, Deviations, or Exclusions From the Method

No

3.7 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC - Designation No.: CN1211 JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551. ● ISED – CAB identifier.: CN0021 The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1. ● CNAS - Registration No.: CNAS L15527 JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527. ● A2LA - Registration No.: 4346.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf
--

3.8 Laboratory Location

<p>JianYan Testing Group Shenzhen Co., Ltd. Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366 Email: info-JYTee@lets.com, Website: http://jyt.lets.com</p>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	03-07-2022	03-06-2023
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
Coaxial Cable (9kHz ~ 30MHz)	JYT	JYT3M-1G-BB-5M	WXG001-6	01-20-2022	01-19-2023
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-20-2022	01-19-2023
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		
EMI Test Software	AUDIX	E3	Version: 6.110919b		


Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	10-21-2021	10-20-2022
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI 3	WXJ003	01-19-2022	01-18-2023

4 Measurement Setup and Procedure

4.1 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.


2) Radiated emission measurement:

9kHz ~ 30 MHz (3m SAC)



30 MHz ~ 1GHz (3m SAC)





4.2 Test Procedure

Test method	Test step
Conducted emission	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Radiated emission	<ol style="list-style-type: none"> 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	<ol style="list-style-type: none"> 1. The antenna port of EUT was connected to the RF port of the spectrum analyzer through an RF cable. 2. The EUT is keeping in continuous transmission mode and tested in all modulation modes. 3. The test data is saved by the screenshot function of the spectrum analyzer.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203	See Section 6.2	Pass
AC Power Line Conducted Emission	15.207	See Section 6.3	Pass
20dB Bandwidth	15.215(c)	See Section 6.4	Pass
Field Strength of Fundamental	15.225 (a)	See Section 6.5	Pass
Field Strength of Spurious Emissions	15.209 15.225 (d)	See Section 6.6	Pass
Frequency Tolerance	15.225 (e)	See Section 6.7	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable.			
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013		

5.1.2 Test Limit


Items	Limit																								
AC Power Line Conducted Emission	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: center;">Frequency (MHz)</th> <th colspan="2" style="text-align: center;">Limit (dBμV)</th> </tr> <tr> <th style="text-align: center;">Quasi-Peak</th> <th style="text-align: center;">Average</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">0.15 – 0.5</td> <td style="text-align: center;">66 to 56 ^{Note 1}</td> <td style="text-align: center;">56 to 46 ^{Note 1}</td> </tr> <tr> <td style="text-align: center;">0.5 – 5</td> <td style="text-align: center;">56</td> <td style="text-align: center;">46</td> </tr> <tr> <td style="text-align: center;">5 – 30</td> <td style="text-align: center;">60</td> <td style="text-align: center;">50</td> </tr> </tbody> </table> <p>Note 1: The limit level in dBμV decreases linearly with the logarithm of frequency. Note 2: The more stringent limit applies at transition frequencies.</p>	Frequency (MHz)	Limit (dBμV)		Quasi-Peak	Average	0.15 – 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}	0.5 – 5	56	46	5 – 30	60	50										
Frequency (MHz)	Limit (dBμV)																								
	Quasi-Peak	Average																							
0.15 – 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}																							
0.5 – 5	56	46																							
5 – 30	60	50																							
20dB Bandwidth	N/A																								
Field Strength of Fundamental Field Strength of Spurious Emissions	<p>(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.</p> <p>(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Frequency (MHz)</th> <th style="text-align: center;">Field strength (microvolts/meter)</th> <th style="text-align: center;">Measurement distance (meters)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">0.009 – 0.490</td> <td style="text-align: center;">2400/F (kHz)</td> <td style="text-align: center;">300</td> </tr> <tr> <td style="text-align: center;">0.490 – 1.705</td> <td style="text-align: center;">24000/F (kHz)</td> <td style="text-align: center;">30</td> </tr> <tr> <td style="text-align: center;">1.705 – 30.0</td> <td style="text-align: center;">30</td> <td style="text-align: center;">30</td> </tr> <tr> <td style="text-align: center;">30 – 88</td> <td style="text-align: center;">100**</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">88 – 216</td> <td style="text-align: center;">150**</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">216 – 960</td> <td style="text-align: center;">200**</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">Above 960</td> <td style="text-align: center;">500</td> <td style="text-align: center;">3</td> </tr> </tbody> </table> <p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p>	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009 – 0.490	2400/F (kHz)	300	0.490 – 1.705	24000/F (kHz)	30	1.705 – 30.0	30	30	30 – 88	100**	3	88 – 216	150**	3	216 – 960	200**	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009 – 0.490	2400/F (kHz)	300																							
0.490 – 1.705	24000/F (kHz)	30																							
1.705 – 30.0	30	30																							
30 – 88	100**	3																							
88 – 216	150**	3																							
216 – 960	200**	3																							
Above 960	500	3																							
Frequency Tolerance	<p>The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of –20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.</p>																								

5.2 Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
E.U.T Antenna:	The EUT make use of an induction coil antenna.

5.3 AC Power Line Conducted Emission

Product name:	POS Terminal	Product model:	IM20
Test by:	Mike	Test mode:	NFC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




Trace: 44

	Freq	Read	LISN	Cable	Limit	Over	Remark
	MHz	Level	Factor	Loss	Line	Limit	
		dBuV	dB	dB	dBuV	dB	
1	0.170	34.75	0.04	0.01	34.80	54.94	-20.14 Average
2	0.206	47.10	0.05	0.04	47.19	63.36	-16.17 QP
3	0.322	46.61	0.06	0.03	46.70	59.66	-12.96 QP
4	0.354	39.76	0.06	0.02	39.84	48.87	-9.03 Average
5	0.701	40.43	0.07	0.03	40.53	56.00	-15.47 QP
6	0.705	32.87	0.07	0.03	32.97	46.00	-13.03 Average
7	1.082	30.68	0.07	0.07	30.82	46.00	-15.18 Average
8	2.133	36.26	0.08	0.19	36.53	56.00	-19.47 QP
9	2.513	27.89	0.09	0.13	28.11	46.00	-17.89 Average
10	10.072	40.09	0.22	0.13	40.44	60.00	-19.56 QP
11	27.127	24.21	0.39	0.20	24.80	50.00	-25.20 Average
12	27.127	31.89	0.39	0.20	32.48	60.00	-27.52 QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	POS Terminal	Product model:	IM20
Test by:	Mike	Test mode:	NFC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		




Trace: 42

	Read Freq	Read Level	LISN Factor	Cable Loss	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.162	47.45	0.06	0.01	47.52	65.34	-17.82	QP
2	0.170	33.41	0.06	0.01	33.48	54.94	-21.46	Average
3	0.350	49.17	0.05	0.02	49.24	58.96	-9.72	QP
4	0.354	42.14	0.05	0.02	42.21	48.87	-6.66	Average
5	0.705	28.32	0.06	0.03	28.41	46.00	-17.59	Average
6	0.796	37.60	0.06	0.03	37.69	56.00	-18.31	QP
7	1.388	25.85	0.06	0.13	26.04	46.00	-19.96	Average
8	1.829	25.60	0.07	0.19	25.86	46.00	-20.14	Average
9	2.487	33.87	0.08	0.13	34.08	56.00	-21.92	QP
10	10.288	39.93	0.21	0.13	40.27	60.00	-19.73	QP
11	27.127	19.85	0.43	0.20	20.48	50.00	-29.52	Average
12	27.127	30.18	0.43	0.20	30.81	60.00	-29.19	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	POS Terminal	Product model:	IM20
Test by:	Mike	Test mode:	Tx without NFC ANT mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Cable Loss	Aux2 Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.163	10.37	0.04	0.01	10.50	20.92	55.30	-34.38	Average
2	0.166	37.41	0.04	0.01	10.50	47.96	65.16	-17.20	QP
3	0.214	9.18	0.05	0.03	10.50	19.76	53.05	-33.29	Average
4	0.337	22.69	0.06	0.02	10.50	33.27	59.27	-26.00	QP
5	0.417	3.90	0.05	0.04	10.50	14.49	47.51	-33.02	Average
6	0.417	19.68	0.05	0.04	10.50	30.27	57.51	-27.24	QP
7	0.724	12.41	0.07	0.03	10.50	23.01	56.00	-32.99	QP
8	1.602	-2.79	0.08	0.16	10.50	7.95	46.00	-38.05	Average
9	2.273	12.69	0.08	0.17	10.50	23.44	56.00	-32.56	QP
10	3.565	18.05	0.10	0.08	10.50	28.73	56.00	-27.27	QP
11	3.623	1.24	0.10	0.08	10.50	11.92	46.00	-34.08	Average
12	28.755	-0.83	0.40	0.20	10.50	10.27	50.00	-39.73	Average

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	POS Terminal	Product model:	IM20
Test by:	Mike	Test mode:	Tx without NFC ANT mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



Trace: 61

	Freq	Read Level	LISN Factor	Cable Loss	Aux2 Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.158	5.54	0.06	0.01	10.50	16.11	55.56	-39.45	Average
2	0.158	32.31	0.06	0.01	10.50	42.88	65.56	-22.68	QP
3	0.190	29.68	0.05	0.03	10.50	40.26	64.02	-23.76	QP
4	0.249	0.91	0.05	0.01	10.50	11.47	51.78	-40.31	Average
5	0.282	24.51	0.05	0.02	10.50	35.08	60.76	-25.68	QP
6	0.747	14.48	0.06	0.03	10.50	25.07	56.00	-30.93	QP
7	0.963	-3.78	0.06	0.05	10.50	6.83	46.00	-39.17	Average
8	1.602	-1.78	0.07	0.16	10.50	8.95	46.00	-37.05	Average
9	3.509	1.53	0.10	0.08	10.50	12.21	46.00	-33.79	Average
10	3.661	16.10	0.10	0.08	10.50	26.78	56.00	-29.22	QP
11	27.562	13.41	0.43	0.19	10.50	24.53	60.00	-35.47	QP
12	28.755	-0.44	0.45	0.20	10.50	10.71	50.00	-39.29	Average

Remark:



1. Level = Read level + LISN Factor + Cable Loss.

5.4 20dB Bandwidth

20dB bandwidth (kHz)	Limit (kHz)	Results
0.86	11.2	Passed
99% bandwidth (kHz)	Limit (kHz)	Results
0.78	N/A	Passed


Note: For 13.56MHz, permitted Band is 14 kHz, so the Limit is 11.2 kHz.

Test plot as follows:



5.5 Field Strength of Fundamental

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Voltage:	DC 5V	Polarization:	Vertical




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	13.348	15.43	19.63	0.40	0.00	35.46	80.50	-45.04	Peak
2	13.422	16.59	19.61	0.41	0.00	36.61	90.50	-53.89	Peak
3	13.559	39.90	19.59	0.41	0.00	59.90	124.00	-64.10	Peak
4	13.633	17.87	19.57	0.42	0.00	37.86	90.50	-52.64	Peak
5	13.766	13.18	19.54	0.43	0.00	33.15	80.50	-47.35	Peak

Remark:

1. Level = Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Voltage:	DC 5V	Polarization:	Horizontal




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	13.347	15.15	19.63	0.40	0.00	35.18	80.50	-45.32	Peak
2	13.487	20.93	19.61	0.41	0.00	40.95	90.50	-49.55	Peak
3	13.559	40.29	19.59	0.41	0.00	60.29	124.00	-63.71	Peak
4	13.633	19.03	19.57	0.42	0.00	39.02	90.50	-51.48	Peak
5	13.770	19.56	19.54	0.43	0.00	39.53	80.50	-40.97	Peak

Remark:

1. Level = Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.

5.6 Field Strength of Spurious Emissions

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Frequency:	150 kHz – 30 MHz	Polarization:	Coxial
Test Voltage:	DC 5V		




	Read Freq	Antenna Level	Cable Factor	Preamp Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	0.165	36.24	20.25	0.03	0.00	56.52	103.27	-46.75	Peak
2	0.325	22.65	20.59	0.06	0.00	43.30	97.37	-54.07	Peak
3	0.579	15.35	20.74	0.09	0.00	36.18	72.35	-36.17	Peak
4	1.054	12.86	20.50	0.17	0.00	33.53	67.17	-33.64	Peak
5	1.848	11.79	20.44	0.17	0.00	32.40	69.50	-37.10	Peak
6	27.127	9.22	19.57	0.61	0.00	29.40	69.50	-40.10	Peak

Remark:

1. Level = Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of 9 kHz–150 kHz are background noise and very lower than the limit, so not show in test report.

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Frequency:	150 kHz – 30 MHz	Polarization:	Coplanar
Test Voltage:	DC 5V		




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	0.162	28.24	20.24	0.03	0.00	48.51	103.41	-54.90 Peak
2	0.176	27.48	20.28	0.04	0.00	47.80	102.72	-54.92 Peak
3	0.958	12.64	20.52	0.12	0.00	33.28	67.99	-34.71 Peak
4	1.269	10.75	20.48	0.17	0.00	31.40	65.56	-34.16 Peak
5	1.819	9.02	20.45	0.17	0.00	29.64	69.50	-39.86 Peak
6	10.905	8.09	20.20	0.40	0.00	28.69	69.50	-40.81 Peak

Remark:

1. Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of 9 kHz–150 kHz are background noise and very lower than the limit, so not show in test report.

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Frequency:	30 MHz – 1000 MHz	Polarization:	Vertical
Test Voltage:	DC 5V		




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	43.8710	45.71	32.69	-13.02	40.00	7.31	PK	Vertical
2	53.0375	46.04	33.01	-13.03	40.00	6.99	PK	Vertical
3	138.591	46.27	27.95	-18.32	43.50	15.55	PK	Vertical
4	195.627	47.08	31.69	-15.39	43.50	11.81	PK	Vertical
5	293.500	41.33	28.16	-13.17	46.00	17.84	PK	Vertical
6	358.684	35.39	23.98	-11.41	46.00	22.02	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	POS Terminal	Product Model:	IM20
Test By:	Mike	Test mode:	NFC Tx mode
Test Frequency:	30 MHz – 1000 MHz	Polarization:	Horizontal
Test Voltage:	DC 5V		



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	146.739	40.18	21.80	-18.38	43.50	21.70	PK	Horizontal
2	163.035	38.18	20.42	-17.76	43.50	23.08	PK	Horizontal
3	293.500	43.15	29.98	-13.17	46.00	16.02	PK	Horizontal
4	358.684	45.63	34.22	-11.41	46.00	11.78	PK	Horizontal
5	448.070	40.91	30.93	-9.98	46.00	15.07	PK	Horizontal
6	791.983	33.47	29.41	-4.06	46.00	16.59	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

5.7 Frequency Tolerance

Frequency Stability V.S. Temperature Measurement:

Voltage (Vdc)	Temperature (°C)	Frequency Tolerance (kHz)	Frequency Error (%)	Limit (%)	Results
5.0	-20	0.051	0.0004	±0.01	Pass
	-10	0.032	0.0002	±0.01	Pass
	0	0.059	0.0004	±0.01	Pass
	+10	0.060	0.0004	±0.01	Pass
	+20	0.030	0.0002	±0.01	Pass
	+30	0.032	0.0002	±0.01	Pass
	+40	0.035	0.0003	±0.01	Pass
	+50	0.380	0.0028	±0.01	Pass

Frequency Stability V.S. Voltage Measurement:

Temperature (°C)	Voltage (Vdc)	Frequency Tolerance (kHz)	Frequency Error (%)	Limit (%)	Results
25.0	4.25	0.062	0.0005	±0.01	Pass
	5.00	0.032	0.0002	±0.01	Pass
	5.75	0.051	0.0004	±0.01	Pass

-----End of report-----