

RF Exposure Evaluation Report

APPLICANT : PAX Technology Limited
EQUIPMENT : UNATTENDED PAYMENT TERMINAL
BRAND NAME : PAX
MODEL NAME : IM25
FCC ID : V5PIM25BW
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Jun. 27, 2024 and completed on Jun. 27, 2024. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8
5.2. Collocated Power Density Calculation.....	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA452701-01	Rev. 01	Initial issue of report.	Jul. 04, 2024



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	PAX Technology Limited
Address	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

Manufacturer	
Company Name	PAX Computer Technology (Shenzhen) Co., Ltd.
Address	Room 701, PAX Technology Building, Shanxia Community, Pinghu Sub-district, Longgang District, Shenzhen, China



2. Description of Equipment Under Test (EUT)

Table with 2 columns: Feature Name and Specification. Rows include EUT Type, Brand Name, Model Name, FCC ID, Wireless Technology and Frequency Range, Mode, Antenna Type, HW Version, SW Version, and EUT Stage.

Remark:

- 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a variant report for IM25, the change note please refer to the IM25_Operational Description of Product Equality Declaration exhibit submitted. and the differences do not affect the MPE analysis results, and all Bands leverage from original report which can be referred to Sporton Report Number FA452701.

Comments and Explanations:

- 1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

Antenna Gain:

Table with 2 columns: WIFI and Gain (dBi). Rows list various frequencies from Bluetooth to WLAN 5.8GHz with their corresponding gain values.



3. Maximum RF average output tune up power among production units

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	16.0
	802.11g	16.0
	802.11n-HT20	16.0

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	EDR	8.0
	LE	4.0

<5GHz WLAN >

Mode		Maximum Average Power (dBm)
5.2GHz	802.11a	15.5
	802.11n-HT20	15.5
	802.11n-HT40	14.0
	802.11ac-VHT20	15.5
	802.11ac-VHT40	14.0
	802.11ac-VHT80	11.0
5.3GHz	802.11a	15.5
	802.11n-HT20	15.5
	802.11n-HT40	14.0
	802.11ac-VHT20	15.5
	802.11ac-VHT40	14.0
	802.11ac-VHT80	12.0
5.5GHz	802.11a	15.5
	802.11n-HT20	15.5
	802.11n-HT40	14.0
	802.11ac-VHT20	15.5
	802.11ac-VHT40	14.0
	802.11ac-VHT80	11.0
5.8GHz	802.11a	15.5
	802.11n-HT20	16.0
	802.11n-HT40	15.0
	802.11ac-VHT20	16.0
	802.11ac-VHT40	15.0
	802.11ac-VHT80	12.0



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
Bluetooth	2402.0	-1.83	8.00	6.170	4.140	0.001	1.000	0.001
2.4GHz WLAN	2412.0	-1.83	16.00	14.170	26.122	0.005	1.000	0.005
5.2GHz WLAN	5180.0	3.06	15.50	18.560	71.779	0.014	1.000	0.014
5.3GHz WLAN	5260.0	3.19	15.50	18.690	73.961	0.015	1.000	0.015
5.5GHz WLAN	5500.0	2.87	15.50	18.370	68.707	0.014	1.000	0.014
5.8GHz WLAN	5745.0	2.68	16.00	18.680	73.790	0.015	1.000	0.015
NFC	13.6			-27.940	0.002	0.0000003	0.979	0.0000003

Note:

- For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
- Chose the maximum RF output tune up power of all antennas among same frequency WLAN bands and the maximum antenna gain to perform MPE calculation conservatively.
- NFC maximum EIRP power calculate from NFC E-Field level from RF test report which can be referred to Sproton No: 452701-01.
 - This device maximum E-Field level is 67.29dBuV/m at 3m, so the EIRP power is -27.94dBm(0.002mW).
 - Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

5.2. Collocated Power Density Calculation

Bluetooth Power Density / Limit	NFC Power Density / Limit	Σ(Power Density / Limit) of Bluetooth+NFC
0.001	0.0000003	0.001
WLAN 2.4GHz Power Density / Limit	NFC Power Density / Limit	Σ(Power Density / Limit) of WLAN 2.4GHz+NFC
0.005	0.0000003	0.005
WLAN 5GHz Power Density / Limit	NFC Power Density / Limit	Σ(Power Density / Limit) of WLAN 5GHz+NFC
0.015	0.0000003	0.015

Note:

- According to the EUT characteristic, NFC can transmit simultaneously with other Radios.
- According to the EUT characteristic, WLAN and Bluetooth cannot transmit simultaneously, WLAN 2.4GHz and WLAN 2.4GHz cannot transmit simultaneously
- Σ(Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for Bluetooth&WLAN 2.4GHz& WLAN 5GHz +NFC.
- Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----