

RF Exposure Evaluation Report

APPLICANT : PAX Technology Limited
EQUIPMENT : Encrypting PIN Pad
BRAND NAME : PAX
MODEL NAME : IM300
MARKETING NAME : IM300
FCC ID : V5PIM300BW
STANDARD : 47 CFR Part 2.1091

We, Sporton International (Shenzhen) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Mark Qu / Manager



Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA811505	Rev. 01	Initial issue of report	Jan. 25, 2018



1. Administration Data

1.1. Testing Laboratory

Testing Laboratory	
Test Site	Sporton International (Shenzhen) Inc.
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595

Applicant	
Company Name	PAX Technology Limited
Address	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

Manufacturer	
Company Name	PAX Computer Technology (Shenzhen) Co., Ltd.
Address	4/F, No.3 Building, Software Park, Second Central Science-Tech Road, High-Tech industrial Park, Shenzhen, Guangdong, P.R.C.



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Encrypting PIN Pad
Brand Name	PAX
Model Name	IM300
Marketing Name	IM300
FCC ID	V5PIM300BW
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	<ul style="list-style-type: none">• 802.11b/g/n HT20• Bluetooth v3.0+EDR, Bluetooth v4.0 LE
Antenna Type	WLAN: External Monopole Antenna Bluetooth: External Monopole Antenna
HW Version	IM300-XXX-XXX
SW Version	PED4.0
EUT Stage	Production Unit
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	



3. Maximum RF average output power among production units

Mode			Maximum Average Power (dBm)
2.4GHz	802.11b	CH1	16.50
		CH6	16.00
		CH11	16.00
	802.11g	CH1	14.50
		CH6	16.00
		CH11	12.50
	802.11n-HT20	CH1	14.00
		CH6	15.00
		CH11	12.00
Bluetooth v3.0+EDR			10.00
Bluetooth v4.0 LE			8.50

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum ERP/EIRP (dBm)	Maximum output power Limit (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
WLAN2.4GHz	2412.0	0	16.50	16.50	0.04	44.67	0.01	1.00
Bluetooth	2402.0	0	10.00	10.00	0.01	10.00	0.002	1.00

Note:

1. For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band
2. WLAN2.4GHz and Bluetooth can't transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.