

RF Exposure Evaluation Report

APPLICANT : PAX Technology Limited
EQUIPMENT : UNATTENDED PAYMENT TERMINAL
BRAND NAME : PAX
MODEL NAME : IM30
FCC ID : V5PIM304GBWL
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Sep. 18, 2023 and completed on Sep. 18, 2023. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	7
4. RF EXPOSURE LIMIT INTRODUCTION	9
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	10
5.1. Standalone Power Density Calculation	10
5.2. Collocated Power Density Calculation.....	11



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	PAX Technology Limited
Address	Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong

Manufacturer	
Company Name	PAX Computer Technology (Shenzhen) Co., Ltd.
Address	401 and 402, Building 3, Shenzhen Software Park, Nanshan District, Shenzhen City, Guangdong Province, P.R.C



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	UNATTENDED PAYMENT TERMINAL
Brand Name	PAX
Model Name	IM30
FCC ID	V5PIM304GBWL
Wireless Technology and Frequency Range	WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	RMC 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is not supported) LTE: QPSK, 16QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
Antenna Type	WWAN: Ant1/2: Dipole Antenna Ant3: Cable Antenna WLAN/Bluetooth: metal Antenna NFC: PCB Antenna
HW Version	NA
SW Version	NA
EUT Stage	Production Unit

Remark:

- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- There are three WWAN Antennas for optional, Ant.1 (SWA2241), Ant.2 (SWA2241C01) and Ant.3 (YJ086S.300294.S01), the detail gain value please refers to following gain table.

Comments and Explanations:

- The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
- The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



Antenna Gain:

WWAN Band	Ant1(SWA2241)	Ant2(SWA2241C01)	Ant3(YJ086S.300294.S01)
WCDMA Band II	2.01	-0.3	-0.77
WCDMA Band IV	3.61	0.85	-0.02
WCDMA Band V	1.33	0.82	0.7
LTE Band 2	2.01	-0.3	-0.77
LTE Band 4	3.61	0.85	-0.02
LTE Band 5	1.33	0.82	0.7
LTE Band 12	0.75	0.6	-2.23
LTE Band 13	0.7	0.5	-1.21
LTE Band 17	0.75	0.6	-2.23
LTE Band 66	3.61	0.85	-0.02
LTE Band 71	0.65	0.5	-2.75

WIFI	Gain
Bluetooth	1.7
WLAN 2.4GHz	1.7
WLAN 5.2GHz	2.3
WLAN 5.3GHz	2.3
WLAN 5.5GHz	2.3
WLAN 5.8GHz	2.3



3. Maximum RF average output tune up power among production units

<WCDMA>

Mode		Maximum Average power(dBm)
WCDMA	Band II	24.5
	Band IV	24.5
	Band V	24.5

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	24.0
	Band 4	24.0
	Band 5	24.0
	Band 12	24.0
	Band 13	24.0
	Band 17	24.0
	Band 66	24.0
	Band 71	24.0

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	16.5
	802.11g	16.0
	802.11n-HT20	16.0

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	EDR	9.0
	LE	5.0



<5GHz WLAN >

Mode		Maximum Average Power (dBm)
5.2GHz	802.11a	15.0
	802.11n-HT20	15.0
	802.11n-HT40	14.0
	802.11ac-VHT20	15.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	12.0
5.3GHz	802.11a	15.0
	802.11n-HT20	15.0
	802.11n-HT40	14.0
	802.11ac-VHT20	15.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	12.0
5.5GHz	802.11a	15.0
	802.11n-HT20	15.0
	802.11n-HT40	14.0
	802.11ac-VHT20	15.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	12.0
5.8GHz	802.11a	15.0
	802.11n-HT20	15.0
	802.11n-HT40	14.0
	802.11ac-VHT20	15.0
	802.11ac-VHT40	14.0
	802.11ac-VHT80	11.0

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
WCDMA Band 2	1852.4	2.01	24.50	26.510	447.713	0.089	1.000	0.089
WCDMA Band 4	1712.4	3.61	24.50	28.110	647.143	0.129	1.000	0.129
WCDMA Band 5	826.4	1.33	24.50	25.830	382.825	0.076	0.551	0.138
LTE Band 2	1850.7	2.01	24.00	26.010	399.025	0.079	1.000	0.079
LTE Band 4	1710.7	3.61	24.00	27.610	576.766	0.115	1.000	0.115
LTE Band 5	824.7	1.33	24.00	25.330	341.193	0.068	0.550	0.124
LTE Band 12	699.7	0.75	24.00	24.750	298.538	0.059	0.466	0.127
LTE Band 13	779.5	0.70	24.00	24.700	295.121	0.059	0.520	0.113
LTE Band 17	706.5	0.75	24.00	24.750	298.538	0.059	0.471	0.126
LTE Band 66	1710.7	3.61	24.00	27.610	576.766	0.115	1.000	0.115
LTE Band 71	706.5	0.65	24.00	24.650	291.743	0.058	0.471	0.123
Bluetooth	2402.0	1.70	9.00	10.700	11.749	0.002	1.000	0.002
2.4GHz WLAN	2412.0	1.70	16.50	18.200	66.069	0.013	1.000	0.013
5.2GHz WLAN	5180.0	2.30	15.00	17.300	53.703	0.011	1.000	0.011
5.3GHz WLAN	5260.0	2.30	15.00	17.300	53.703	0.011	1.000	0.011
5.5GHz WLAN	5500.0	2.30	15.00	17.300	53.703	0.011	1.000	0.011
5.8GHz WLAN	5745.0	2.30	15.00	17.300	53.703	0.011	1.000	0.011
NFC	13.6			-27.640	0.002	0.0000003	0.979	0.0000004

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum RF output tune up power of all antennas among same frequency WWAN/WLAN bands and the maximum antenna gain to perform MPE calculation conservatively.
3. NFC maximum EIRP power calculate from NFC E-Field level from RF test report which can be referred to Sproton No: FR380711D.
 - 1) This device maximum E-Field level is 67.59dBuV/m at 3m, so the EIRP power is -27.64dBm(0.002mW).
 - 2) Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

5.2. Collocated Power Density Calculation

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit) of WWAN + Bluetooth
0.138	0.002	0.140

WWAN Power Density / Limit	WLAN 2.4GHz Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 2.4GHz
0.138	0.013	0.151

WWAN Power Density / Limit	WLAN 5GHz Power Density / Limit	Σ (Power Density / Limit) of WWAN + WLAN 5GHz
0.138	0.011	0.149

Note:

1. For collocation analysis, WCDMA Band 4 is chosen for summation due to the highest (power density/limit) among all WWAN Band modes.
2. According to the EUT characteristic, NFC cannot transmit simultaneously with other Radios.
3. According to the EUT characteristic, WLAN and Bluetooth cannot transmit simultaneously, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously
4. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + Bluetooth&WLAN 2.4GHz& WLAN 5GHz.
5. Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----