



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

## RF Emissions Test Report

FCC Part 24

For

Kyocera Corporation  
c/o Kyocera Communication Inc.

Product:	CDMA Phone
Model:	C5155A1

Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

**TABLE OF CONTENTS**

1 SUMMARY OF TESTING ..... 4

2 EQUIPMENT UNDER TEST INFORMATION..... 4

3 TEST FACILITIES..... 5

4 TEST SETUP ..... 5

    4.1 Test Configuration ..... 6

5 EMI compliance ..... 7

6 Conducted RF OUTPUT POWER ..... 8

    6.1 Test Configuration ..... 8

    6.2 Test Results..... 8

7 RADIATED RF OUTPUT POWER ..... 8

    7.1 Test Configuration ..... 8

8 PEAK-AVERAGE RATIO ..... 9

    8.1 Test Configuration ..... 9

    8.2 Test Result ..... 9

9 OCCUPIED BANDWIDTH..... 11

    9.1 Test Configuration ..... 11

    9.2 Test Result ..... 11

10 Spurious Emissions At Antenna Terminals..... 14

    10.1 Test Configuration ..... 14

**10.2** Test Result ..... 14

11 Transmitter Radiated Spurious Emissions..... 18

    11.1 Test Configuration and Result..... 18

12 Receiver Spurious Emissions..... 18

    12.1 Receiver Spurious Emissions ..... 18

13 Transmitter RF Carrier Frequency Stability ..... 19

**13.1** Test Configuration ..... 19

**13.2** Test Result ..... 20

14 Exposure of Humans to RF Fields (SAR) ..... 21

**14.1** Test Configuration and Result..... 21

15 TEST EQUIPMENT..... 21



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

**ATTESTATION**

The tested device complies with the requirements in respect of all parameters subject to the test.

The test results and statements relate only to the items tested.

The test equipment used was suitable for the tests performed and within manufacturer's published specifications and operating parameters.

The test methods were consistent with the methods described in the relevant standards.

<b>Product:</b>	CDMA Cellular Phone with Bluetooth and WLAN
<b>Model #:</b>	C5155 A1
<b>FCC ID:</b>	V65C5155A1
<b>Tested in accordance with:</b>	FCC Part 24
<b>Test performed by:</b>	CompTest Services LLC
<b>Test Requested by:</b>	Kyocera Corporation c/o Kyocera Communication Inc 8611 Balboa Avenue San Diego, CA 92121 United States
<b>Date of Test:</b>	March 12 – 14, 2012

**Responsible Engineer**

*Benjamin Nguyen*

---

Benjamin Nguyen  
Test Engineer

**Reviewed and approved by:**

---

Tammy To  
Quality Manager

## 1 SUMMARY OF TESTING

Section #	Rule Part	Test Description	Verdict
6	FCC § 2.1046	Conducted Power	Pass
7	FCC § 22.913, 24.232	Radiated Power	Pass
8	FCC § 24.232(d)	Peak-to-Average Ratio	Pass
9	FCC § 2.1049, 22.917 (b)(d), 24.238	Occupied Bandwidth	Pass
10	FCC § 2.1051, 22.917(e)(f), 24.238	Spurious Emissions at Antenna Terminals	Pass
11	FCC § 2.1053, 22.91, 24.238	Transmitter Radiated Spurious Emissions	Pass
12	FCC § 15.109	Receiver Spurious Emissions	Pass
13	FCC § 2.1055, 22.355, 24.235	Transmitter RF Carrier Frequency Stability	Pass
14	FCC § 2.1093	Exposure of Humans to RF Fields	Pass

## 2 EQUIPMENT UNDER TEST INFORMATION


<b>EUT Serial Number:</b>	268435457816725951
<b>Type:</b>	[ ] Prototype, [X] Pre-Production, [ ] Production
<b>Equipment Category:</b>	Portable
<b>RF Exposure Environment:</b>	General Population / Uncontrolled
<b>Antenna:</b>	Internal Antenna
<b>Detachable Antenna:</b>	No
<b>External Input:</b>	Audio/Digital Data
<b>Quantity:</b>	Quantity production is planned
<b>Multiple Access Scheme:</b>	CDMA
<b>Emission Designators:</b>	1M25F9W
<b>FCC Rule Parts:</b>	§24E
<b>Modes:</b>	1900 CDMA
<b>TX Frequency (MHz):</b>	1850 - 1910
<b>Conducted Output Power (W):</b>	24.5

### 3 TEST FACILITIES

The test sites and measurement facilities used to collect data are located at 8611 Balboa Avenue, San Diego, CA 92123, USA

### 4 TEST SETUP

All CDMA measurements were conducted with a base station simulator to establish a CDMA link with the equipment under test (EUT). To investigate the response of the EUT the main antenna RF output port of the EUT was connected to the input of the spectrum analyzer with a RF cable. The amplitude of the spectrum analyzer is corrected for the cable insertion loss and any other applicable losses. A fully charged battery was used as a power supply voltage, except for the Transmitter RF Carrier Frequency Stability test a dummy battery connected to a power supply was used.



## 4.1 Test Configuration

To justify on the selection of applicable configurations, the EUT was pre-tested under all Radio Configuration and Service Option operation modes to determine the worst-case scenario.

The following configuration was determined and reported as worst-case for all measurements:

Radio Configuration:	<b>RC1</b>
Service Options:	<b>SO55</b>
Data Rate:	<b>Full Rate</b>

CONFIGURATION  Peak Power	CONDUCTED POWER (dBm)		
	CDMA 1900		
	Ch 25	Ch 600	Ch 1175
	Peak	Peak	Peak
SO2, RC1 Full Rate	29.97	30.51	29.98
SO2, RC3 Full Rate	29.52	29.70	29.54
SO55, RC1 Full Rate	<b>30.12</b>	<b>30.54</b>	<b>30.02</b>
SO55, RC3 Full Rate	29.55	29.86	29.61
TDSO SO32, RC3 (+F-SCH)	29.51	29.80	29.74
TDSO SO32, RC3 (SCH)	29.46	29.87	29.66
EvDo Rev0, RTAP	30.47	30.64	30.36
EvDo Rev0, FTAP 153.6kbps	30.63	30.87	30.18
EvDo RevA, RTAP 4096	30.86	31.00	30.39
EvDo RevA, FTAP 307.2kbps	30.59	31.01	30.47

Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

CONFIGURATION  Average Power	CONDUCTED POWER (dBm)		
	CDMA 1900		
	Ch 25	Ch 600	Ch 1175
	Avg	Avg	Avg
SO2, RC1 Full Rate	24.89	25.06	24.91
SO2, RC3 Full Rate	24.88	25.05	24.89
SO55, RC1 Full Rate	24.89	25.07	24.93
SO55, RC3 Full Rate	<b>24.90</b>	<b>25.08</b>	<b>24.95</b>
TDSO SO32, RC3 (F+SCH)	24.89	25.07	24.92
TDSO SO32, RC3 (SCH)	24.88	25.05	24.92
EvDo Rev0, RTAP	24.90	25.06	24.86
EvDo Rev0, FTAP 153.6kbps	24.86	25.07	24.82
EvDo RevA, RTAP 4096	24.87	25.05	24.91
EvDo RevA, FTAP 307.2kbps	24.89	25.07	24.82

## 5 TTY COMPLIANCE

**FCC: § 255 of the Telecom Act**

The EUT has been designed for TTY Compliance with Cellular Compatibility Standard.

## 6 CONDUCTED RF OUTPUT POWER

### 6.1 Test Configuration

**FCC:** § 2.1046

**IC:** RSS132 §4.4; RSS133 §6.4

The EUT was connected to a Universal Power Meter through a RF cable. The cable loss was taken into account for accurate power measurement. The EUT was set at low, mid, high channels and each frequency band to investigate the conducted power.

### 6.2 Test Results

Mode	Frequency (MHz)	Channel	Conducted Power (dBm)
CDMA 1900	1851.25	25	24.90
	1880	600	25.08
	1908.75	1175	24.95

## 7 RADIATED RF OUTPUT POWER

### 7.1 Test Configuration

**FCC:** § 22.913, § 24.232

**IC:** RSS132 §4.4; RSS133 §6.4

The test was performed in Compliance Certification Service using substitution method. See separated radiated emission report for details.



## 8 PEAK-AVERAGE RATIO

### 8.1 Test Configuration

**FCC:** § 24.232(d)

**IC:** RSS133 (6.4)

The RF output of the EUT was connected to the input of the spectrum analyzer (S.A.) with sufficient attenuation. The spectrum analyzer Complementary Cumulative Distribution Function (CCDF) function is utilized to determine the largest deviation between average and peak power of the EUT.

For Digital: Modulate with full rate and all up power control bit.

S.A. Setting	RBW	VBW
Power Stat CCDF	5MHz	auto

**Limits:** <13 dB

### 8.2 Test Result

Figure	Description	Mode	Result
8-1	CCDF @ Ch600	<b>CDMA 1900</b>	Pass

Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0



**Figure 8-1 CCDF @ CH 600**

## 9 OCCUPIED BANDWIDTH

### 9.1 Test Configuration

**FCC:** § 2.1049, § 22.917(b)(d), § 24.238, § 27.53(g)(1)

**IC:** RSS132 §4.5; RSS133 §6.5

The RF output of the EUT was connected to the input of the spectrum analyzer (S.A.) with sufficient attenuation. The spectrum with no modulation was recorded.

For Digital: Modulate with full rate all up power control bit.

S.A. Setting	RBW	VBW
Bandwidth Measurement	30KHz	300kHz
Band Edge Measurement	30KHz	100KHz

**Limits:** Bandwidth: N/A  
 Bandedge: -13dBm

### 9.2 Test Result

Figure	Description	Mode	Result
9-1	CDMA @ CH600	<b>CDMA 1900</b>	Pass
9-2	Lower Band Edge @ CH 25		Pass
9-3	Upper Band Edge @ CH 1175		Pass



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0




Figure 9-1 CDMA 1900 @ CH 600



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0




Figure 9-2 CDMA 1900 Lower Band Edge @ CH 25




Figure 9-3 CDMA 1900 Upper Band Edge @ CH 1175

## 10 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

### 10.1 Test Configuration

**FCC:** § 2.1051, § 22.917(e)(f), § 24.238

**IC:** RSS132 §4.5; RSS133 §6.5

**Measurement Procedures:**

Out of Band: The RF output of the EUT was connected to the input of the spectrum analyzer with sufficient attenuation. The modulating signal was applied accordingly. The frequency spectrum was investigated from the lowest frequency signal generated up to at least the tenth harmonic of the fundamental.

S.A. Setting	RBW	VBW
Spurious Emissions Measurement	1MHz	1MHz


**Limits:** -13dBm

### 10.2 Test Result


Figure	Channel	Plot Description	Result
10-1	25	CDMA 1900 Conducted spurious emissions 9kHz to 20GHz	Pass
10-2	600		Pass
10-3	1175		Pass



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0




**Figure 10-1a CDMA 1900 - Conducted Spurious Emission (CH 25)**




**Figure 10-1b CDMA 1900 - Conducted Spurious Emission (CH 25)**



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0



**Figure 10-2a CDMA 1900 - Conducted Spurious Emission (CH 600)**




**Figure 10-2b CDMA 1900 - Conducted Spurious Emission (CH 600)**






Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0



**Figure 10-3a CDMA 1900 - Conducted Spurious Emission (CH 1175)**



**Figure 10-3b CDMA 1900 - Conducted Spurious Emission (CH 1175)**

Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

## 11 TRANSMITTER RADIATED SPURIOUS EMISSIONS

<b>FCC:</b> § 2.1053, § 22.91, § 24.238, §27.53(g)
<b>IC:</b> RSS132 §4.5; RSS133 §6.5
The radiated spurious emission test was performed at Compliance Certification Service. The test report is attached in a separate attachment.

### 11.1 Test Configuration and Result

## 12 RECEIVER SPURIOUS EMISSIONS

### 12.1 Receiver Spurious Emissions

<b>FCC:</b> § 15.109
<b>IC:</b> RSS-GEN
The receiver radiated spurious emission test was performed at Compliance Certification Service. The test report is attached in a separate attachment.

## 13 TRANSMITTER RF CARRIER FREQUENCY STABILITY

### 13.1 Test Configuration

**FCC:** § 2.1055, § 22.355, § 24.235, § 27.54  
**IC:** RSS132 §4.3; RSS133 §6.3


The EUT was placed in an environmental chamber. The RF output of the EUT was connected to Agilent 8960 Series 10 E5515C. A power supplier was connected as primary voltage supply. Only the mid channel of each frequency band was investigated.

**Limits:**

Tx Frequency	Channel	Limit
1880 MHz	600	+/- 2.5 ppm (+/-4700 Hz)

### 13.2 Test Result

CDMA 1900						
Temperature (°C)	Deviation of Carrier (Hz)			Specification (Hz)		Result
	3.3V (Battery endpoint)	3.7V	4.2V (115%)	Lower limit	Upper limit	
-30		-7.68		-4700	4700	Pass
-20		-4.23		-4700	4700	
-10		6.63		-4700	4700	
0		3.71		-4700	4700	
10		4.67		-4700	4700	
20	-3.90	5.30	-6.46	-4700	4700	
30		-5.31		-4700	4700	
40		3.24		-4700	4700	
50		0.07		-4700	4700	
60		0.05		-4700	4700	



Applicant:	Kyocera
FCC ID:	V65C5155A1
Report #:	CT-C5155A1-24-0312-R0

## 14 EXPOSURE OF HUMANS TO RF FIELDS (SAR)

### 14.1 Test Configuration and Result

**FCC: § 2.1093**

**IC: RSS102**

The SAR test report is attached in a separate attachment.

## 15 TEST EQUIPMENT

The test equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

Description	Manufacturer	Model No.	Serial No.	Cal Due Date
Power Meter	Giga-tronics	8541C	1831306	09/08/12
Spectrum Analyzer	Agilent	E4440A	MY44303130	12/14/12
Wireless Communications Test Set	Agilent	8960	GB44052789	12/02/13
Temperature Chamber	Test Equity	ZH2-033-033-H/AC	ZZ9622421	06/24/12