

Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

RF Emissions Test Report

FCC Part 22 and 24

For

Kyocera Corporation
c/o Kyocera Communication Inc.

Product:	Tri-Band CDMA Phone
Model:	C5215

Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

TABLE OF CONTENTS

1 SUMMARY OF TESTING 4

2 EQUIPMENT UNDER TEST INFORMATION..... 4

3 TEST FACILITIES..... 5

4 TEST SETUP 5

5 Conducted RF OUTPUT POWER 6

 5.1 Test Configuration 6

 5.2 Test Results..... 6

6 RADIATED RF OUTPUT POWER 6

 6.1 Test Configuration 6

7 PEAK-AVERAGE RATIO 7

 7.1 Test Configuration 7

 7.2 Test Result 7

8 OCCUPIED BANDWIDTH..... 9

 8.1 Test Configuration 9

 8.2 Test Result 9

9 Spurious Emissions At Antenna Terminals..... 14

 9.1 Test Configuration 14

 9.2 Test Result 14

10 Transmitter Radiated Spurious Emissions..... 21

 10.1 Test Configuration and Result..... 21

11 Receiver Spurious Emissions..... 21

 11.1 Receiver Spurious Emissions 21

12 Transmitter RF Carrier Frequency Stability 22

 12.1 Test Configuration 22

 12.2 Test Result 23

13 Exposure of Humans to RF Fields (SAR) 25

 13.1 Test Configuration and Result..... 25

14 TEST EQUIPMENT..... 25

Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

ATTESTATION

The tested device complies with the requirements in respect of all parameters subject to the test.

The test results and statements relate only to the items tested.

The test equipment used was suitable for the tests performed and within manufacturer's published specifications and operating parameters.

The test methods were consistent with the methods described in the relevant standards.

Product:	CDMA Cellular Phone with Bluetooth and WiFi
Model #:	C5215
FCC ID:	V65C5215
Tested in accordance with:	FCC Part 22 & 24
Test performed by:	CompTest Services LLC
Test Requested by:	Kyocera Corporation c/o Kyocera Communication Inc 8611 Balboa Avenue San Diego, CA 92121 United States
Date of Test:	April 1 - 8, 2013

Responsible Engineer

Benjamin Nguyen

Benjamin Nguyen
Test Engineer

Reviewed and approved by:

Kelly Hill

Kelly Hill
Quality Manager

1 SUMMARY OF TESTING

Section #	Rule Part	Test Description	Verdict
4	FCC § 2.1046	Conducted Power	Pass
5	FCC § 22.913, 24.232	Radiated Power	Pass
6	FCC § 2.1049, 22.917 (b)(d), 24.238	Occupied Bandwidth	Pass
7	FCC § 2.1051, 22.917(e)(f), 24.238	Spurious Emissions at Antenna Terminals	Pass
8	FCC § 2.1053, 22.91, 24.238	Transmitter Radiated Spurious Emissions	Pass
9	FCC § 15.109	Receiver Spurious Emissions	Pass
10	FCC § 2.1055, 22.355, 24.235	Transmitter RF Carrier Frequency Stability	Pass
11	FCC § 2.1093	Exposure of Humans to RF Fields	Pass

2 EQUIPMENT UNDER TEST INFORMATION


EUT Serial Number:	268435457816731604	
Type:	[] Prototype, [X] Pre-Production, [] Production	
Equipment Category:	Portable	
RF Exposure Environment:	General Population / Uncontrolled	
Antenna:	Internal Antenna	
Detachable Antenna:	No	
External Input:	Audio/Digital Data	
Quantity:	Quantity production is planned	
Multiple Access Scheme:	CDMA	
Emission Designators:	1M25F9W	
FCC Rule Parts:	§22H	§24E
Modes:	800 CDMA	1900 CDMA
TX Frequency (MHz):	824 – 849	1850 - 1910
Conducted Output Power (dBm):	24.5	24.5

3 TEST FACILITIES

The test sites and measurement facilities used to collect data are located at 8611 Balboa Avenue, San Diego, CA 92123, USA

4 TEST SETUP

All CDMA measurements were conducted with a base station simulator to establish a CDMA link with the equipment under test (EUT). To investigate the response of the EUT the main antenna RF output port of the EUT was connected to the input of the spectrum analyzer with a RF cable. The amplitude of the spectrum analyzer is corrected for the cable insertion loss and any other applicable losses. A fully charged battery was used as a power supply voltage, except for the Transmitter RF Carrier Frequency Stability test a dummy battery connected to a power supply was used.



To justify on the selection of applicable configurations, the EUT was pre-tested under all Radio Configuration and Service Option operation modes to determine the worst-case scenario.

The following CDMA configuration was determined and reported as worst-case for all measurements:

Radio Configuration:	RC1
Service Options:	SO55
Data Rate:	Full Rate

5 CONDUCTED RF OUTPUT POWER

5.1 Test Configuration

FCC: § 2.1046

IC: RSS132 §4.4; RSS133 §6.4

The EUT was connected to a Universal Power Meter through a RF cable. The cable loss was taken into account for accurate power measurement. The EUT was set at low, mid, high channels and each frequency band to investigate the conducted power.

5.2 Test Results

Mode	Frequency (MHz)	Channel	Conducted Power (dBm)
CDMA 800	824.70	1013	24.53
	836.52	384	24.42
	848.31	777	24.45
CDMA 1900	1851.25	25	24.48
	1880	600	24.50
	1908.75	1175	24.60

6 RADIATED RF OUTPUT POWER

6.1 Test Configuration

FCC: § 22.913, § 24.232

IC: RSS132 §4.4; RSS133 §6.4

The test was performed in Compliance Certification Service using substitution method. See separated radiated emission report for details.

7 PEAK-AVERAGE RATIO

7.1 Test Configuration

FCC: § 24.232(d)

IC: RSS133 (6.4)

The RF output of the EUT was connected to the input of the spectrum analyzer (S.A.) with sufficient attenuation. The spectrum analyzer Complementary Cumulative Distribution Function (CCDF) function is utilized to determine the largest deviation between average and peak power of the EUT.

For Digital: Modulate with full rate and all up power control bit.

S.A. Setting	RBW	VBW
Power Stat CCDF	5MHz	auto

Limits: <13 dB

7.2 Test Result

Figure	Description	Mode	Result
8-1	CCDF @ Ch600	CDMA 1900	Pass



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 8-1 CCDF @ CH 600

8 OCCUPIED BANDWIDTH

8.1 Test Configuration

FCC:	§ 2.1049, § 22.917(b)(d), § 24.238, § 27.53(g)(1)	
IC:	RSS132 §4.5; RSS133 §6.5	
<p>The RF output of the EUT was connected to the input of the spectrum analyzer (S.A.) with sufficient attenuation. The spectrum with no modulation was recorded.</p> <p>For Digital: Modulate with full rate all up power control bit.</p>		
S.A. Setting	RBW	VBW
Bandwidth Measurement	30KHz	300kHz
Band Edge Measurement	13kHz	51kHz
<p>Limits: Bandwidth: N/A Bandedge: -13dBm</p>		

8.2 Test Result

Figure	Description	Mode	Result
9-1	CDMA @ Ch384	CDMA 800	Pass
9-2	Lower Band Edge @ Ch 1013		Pass
9-3	Upper Band Edge @ Ch 777		Pass
9-4	CDMA @ CH600	CDMA 1900	Pass
9-5	Lower Band Edge @ CH 25		Pass
9-6	Upper Band Edge @ CH 1175		Pass

Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 9-1 CDMA 800 @ CH 384



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 9-2 CDMA 800 Lower Band Edge @ CH 1013




Figure 9-3 CDMA 800 Lower Band Edge @ CH 777



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 9-4 CDMA 1900 @ CH 600



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 9-5 CDMA 1900 Lower Band Edge @ CH 25




Figure 9-6 CDMA 1900 Upper Band Edge @ CH 1175

9 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

9.1 Test Configuration

FCC: § 2.1051, § 22.917(e)(f), § 24.238

IC: RSS132 §4.5; RSS133 §6.5

Measurement Procedures:

Out of Band: The RF output of the EUT was connected to the input of the spectrum analyzer with sufficient attenuation. The modulating signal was applied accordingly. The frequency spectrum was investigated from the lowest frequency signal generated up to at least the tenth harmonic of the fundamental.

S.A. Setting	RBW	VBW
Spurious Emissions Measurement	1MHz	1MHz

Limits: -13dBm

9.2 Test Result

Figure	Channel	Plot Description	Result
10-1	1013	CDMA 800 Conducted spurious emissions 25MHz to 10GHz	Pass
10-2	384		Pass
10-3	777		Pass
10-4	25	CDMA 1900 Conducted spurious emissions 25MHz to 20GHz	Pass
10-5	600		Pass
10-6	1175		Pass



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-1a CDMA 800 – Conducted Spurious Emission (CH 1013)




Figure 10-1b CDMA 800 – Conducted Spurious Emission (CH 1013)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-2a CDMA 800 – Conducted Spurious Emission (CH 384)




Figure 10-2b CDMA 800 – Conducted Spurious Emission (CH 384)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-3a CDMA 800 – Conducted Spurious Emission (CH 777)




Figure 10-3b CDMA 800 – Conducted Spurious Emission (CH 777)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-4a CDMA 1900 - Conducted Spurious Emission (CH 25)




Figure 10-4b CDMA 1900 - Conducted Spurious Emission (CH 25)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-5a CDMA 1900 - Conducted Spurious Emission (CH 600)




Figure 10-5b CDMA 1900 - Conducted Spurious Emission (CH 600)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0




Figure 10-6a CDMA 1900 - Conducted Spurious Emission (CH 1175)




Figure 10-6b CDMA 1900 - Conducted Spurious Emission (CH 1175)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

10 TRANSMITTER RADIATED SPURIOUS EMISSIONS

10.1 Test Configuration and Result

FCC: § 2.1053, § 22.91, § 24.238, §27.53(g)
IC: RSS132 §4.5; RSS133 §6.5
The radiated spurious emission test was performed at Compliance Certification Service. The test report is attached in a separate attachment.

11 RECEIVER SPURIOUS EMISSIONS

11.1 Receiver Spurious Emissions

FCC: § 15.109
IC: RSS-GEN
The receiver radiated spurious emission test was performed at Compliance Certification Service. The test report is attached in a separate attachment.

12 TRANSMITTER RF CARRIER FREQUENCY STABILITY


12.1 Test Configuration		
FCC: § 2.1055, § 22.355, § 24.235, § 27.54		
IC: RSS132 §4.3; RSS133 §6.3		
<p>The EUT was placed in an environmental chamber. The RF output of the EUT was connected to Agilent 8960 Series 10 E5515C. A power supplier was connected as primary voltage supply. Only the mid channel of each frequency band was investigated.</p>		
<u>Limits:</u>		
Tx Frequency	Channel	Limit
836.49 MHz	384	+/- 2.5 ppm (+/- 2091 Hz)
1880 MHz	600	+/- 2.5 ppm (+/-4700 Hz)



Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

12.2 Test Result


CDMA 800						
Temperature (°C)	Deviation of Carrier (Hz)			Specification (Hz)		Result
	3.3V (Battery endpoint)	3.7V	4.2V (115%)	Lower limit	Upper limit	
-30	-8.50	-8.02	-8.31	-2091	2091	Pass
-20		-7.88		-2091	2091	
-10		-8.08		-2091	2091	
0		-7.59		-2091	2091	
10		-8.22		-2091	2091	
20	-9.20	-9.20	-2091	2091		
30	-8.50	-8.37	-8.31	-2091	2091	
40		-8.89		-2091	2091	
50		-8.40		-2091	2091	
60		-9.56		-2091	2091	





Applicant:	Kyocera
FCC ID:	V65C5215
Report #:	CT-C5215-22_24-0413-R0

CDMA 1900						
Temperature (°C)	Deviation of Carrier (Hz)			Specification (Hz)		Result
	3.3V (Battery endpoint)	3.7V	4.2V (115%)	Lower limit	Upper limit	
-30		7.81		-4700	4700	Pass
-20		6.92		-4700	4700	
-10		6.91		-4700	4700	
0		7.54		-4700	4700	
10		6.35		-4700	4700	
20	7.68	6.45	7.24	-4700	4700	
30		6.99		-4700	4700	
40		7.44		-4700	4700	
50		7.52		-4700	4700	
60		8.10		-4700	4700	



13 EXPOSURE OF HUMANS TO RF FIELDS (SAR)

13.1 Test Configuration and Result
FCC: § 2.1093
IC: RSS102
The SAR test report is attached in a separate attachment.

14 TEST EQUIPMENT

The test equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

Description	Manufacturer	Model No.	Serial No.	Cal Due Date
Power Meter	Giga-tronics	8541C	1831306	05/16/13
Spectrum Analyzer	Agilent	E4405B	US41441217	12/11/13
Wireless Communications Test Set	Agilent	8960	GB44052789	12/02/13
Temperature Chamber	Test Equity	ZH2-033-033-H/AC	ZZ9622421	08/03/13