




# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctestlab.com



## MEASUREMENT REPORT FCC PART 15.247 Bluetooth

**Applicant Name:**  
Kyocera Corporation  
9520 Towne Centre Drive, Suite 200  
San Diego, CA 92121  
United States


**Date of Testing:**  
June 23 - July 06, 2015  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1506221315.V65

<b>FCC ID:</b>	<b>V65E4281</b>
<b>APPLICANT:</b>	<b>Kyocera Corporation</b>



**Application Type:** Certification  
**Model(s):** E4281  
**EUT Type:** Portable Handset  
**Max. RF Output Power:** 2.181 mW (3.39 dBm) Peak Conducted  
**Frequency Range:** 2402 – 2480MHz (Bluetooth for US)  
**Type of Modulation:** GFSK,  $\pi/4$ -DQPSK, 8DPSK  
**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter (DSS)  
**FCC Rule Part(s):** Part 15 Subpart C (15.247)  
**Test Procedure(s):** ANSI C63.10-2009

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



  
 Randy Ortanez  
 President




FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 1 of 56	

# TABLE OF CONTENTS


FCC PART 15.247 MEASUREMENT REPORT .....		3
1.0 INTRODUCTION.....		4
1.1 SCOPE.....		4
1.2 PCTEST TEST LOCATION.....		4
2.0 PRODUCT INFORMATION .....		5
2.1 EQUIPMENT DESCRIPTION.....		5
2.2 DEVICE CAPABILITIES.....		5
2.3 TEST CONFIGURATION .....		5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....		5
3.0 DESCRIPTION OF TEST .....		6
3.1 EVALUATION PROCEDURE.....		6
3.2 AC LINE CONDUCTED EMISSIONS.....		6
3.3 RADIATED EMISSIONS .....		7
3.4 ENVIRONMENTAL CONDITIONS.....		7
4.0 ANTENNA REQUIREMENTS .....		8
5.0 TEST EQUIPMENT CALIBRATION DATA.....		9
6.0 TEST RESULTS .....		10
6.1 SUMMARY .....		10
6.2 20DB BANDWIDTH MEASUREMENT .....		11
6.3 OUTPUT POWER MEASUREMENT .....		17
6.4 BAND EDGE COMPLIANCE .....		28
6.5 CARRIER FREQUENCY SEPARATION.....		31
6.6 TIME OF OCCUPANCY.....		33
6.7 NUMBER OF HOPPING CHANNELS.....		35
6.8 CONDUCTED SPURIOUS EMISSIONS.....		37
6.9 RADIATED SPURIOUS EMISSION MEASUREMENTS – ABOVE 1GHZ.....		41
6.10 RADIATED RESTRICTED BAND EDGE MEASUREMENTS .....		49
6.11 RADIATED SPURIOUS EMISSIONS MEASUREMENTS – BELOW 1GHZ.....		51
6.12 LINE CONDUCTED MEASUREMENT DATA .....		54
7.0 CONCLUSION .....		56

FCC ID: V65E4281		<b>FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1506221315.V65	<b>Test Dates:</b> June 23 - July 06, 2015	<b>EUT Type:</b> Portable Handset	Page 2 of 56	



# MEASUREMENT REPORT

## FCC Part 15.247



### § 2.1033 General Information

**APPLICANT:** Kyocera Corporation  
**APPLICANT ADDRESS:** 9520 Towne Centre Drive, Suite 200  
 San Diego, CA 92121, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** Part 15 Subpart C (15.247)  
**BASE MODEL:** E4281  
**FCC ID:** V65E4281  
**FCC CLASSIFICATION:** FCC Part 15 Spread Spectrum Transmitter (DSS)  
**Test Device Serial No.:** 4281D033 & 4281D0337     Production     Pre-Production     Engineering  
**Method/System:** Frequency Hopping Spread Spectrum (FHSS)  
**DATE(S) OF TEST:** June 23 - July 06, 2015  
**TEST REPORT S/N:** 0Y1506221315.V65



### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



<b>FCC ID:</b> V65E4281	 <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b> <b>(CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1506221315.V65	<b>Test Dates:</b> June 23 - July 06, 2015	<b>EUT Type:</b> Portable Handset	Page 3 of 56

# 1.0 INTRODUCTION


## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.



## 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'tl (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 4 of 56	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Kyocera Portable Handset FCC ID: V65E4281**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

### 2.2 Device Capabilities

This device contains the following capabilities:


850/1900 CDMA/EvDO Rev0/A (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, Bluetooth (1x, EDR)

### 2.3 Test Configuration

The Kyocera Portable Handset FCC ID: V65E4281 was tested per the guidance of ANSI C63.10-2009. ANSI C63.10-2009 was also used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 6.2, 6.3, 6.4, 6.5, 6.6, 6.7, and 6.8 for antenna port conducted emissions test setups.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 5 of 56	

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) was used in the measurement of the **Kyocera Portable Handset FCC ID: V65E4281**.

Deviation from measurement procedure.....None



### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.12. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 9.15.0.

FCC ID: V65E4281		<b>FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)</b>		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 6 of 56	

### 3.3 Radiated Emissions


The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 7 of 56	

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”



- The antennas of the Kyocera Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The **Kyocera Portable Handset FCC ID: V65E4281** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

**Table 4-1. Frequency/ Channel Operations**

FCC ID: V65E4281		<b>FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1506221315.V65	<b>Test Dates:</b> June 23 - July 06, 2015	<b>EUT Type:</b> Portable Handset	Page 8 of 56	



## 5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	BT1	Bluetooth Cable Set	10/16/2014	Annual	10/16/2015	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	10/24/2014	Annual	10/24/2015	N/A
Agilent	8447D	Broadband Amplifier	6/12/2015	Annual	6/12/2016	1937A03348
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Agilent	N4010A	Wireless Connectivity Test Set	N/A			GB46170464
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	7/8/2014	Annual	7/8/2015	MY49432391
Com-Power	PAM-118A	Pre-Amplifier	4/10/2015	Annual	4/10/2016	551042
Emco	6502	Active Loop Antenna (10k - 30 MHz)	6/24/2014	Biennial	6/24/2016	267
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	11/11/2014	Biennial	11/11/2016	114451
K & L	11SH10-3075/U18000	High Pass Filter	12/1/2014	Annual	12/1/2015	3
Pasternack	NMLC-1	Line Conducted Emissions Cable (NM)	10/17/2014	Annual	10/17/2015	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	N/A			836536/0005
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	7/19/2013	Biennial	7/19/2015	A050307
VWR	62344-734	Thermometer with Clock	2/20/2014	Biennial	2/20/2016	140140336

**Table 5-1. Annual Test Equipment Calibration Schedule**

Note:

- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 9 of 56	

## 6.0 TEST RESULTS

### 6.1 Summary



Company Name: Kyocera Corporation  
 FCC ID: V65E4281  
 Method/System: Frequency Hopping Spread Spectrum (FHSS)  
 Number of Channels: 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (Tx)</b>					
15.247(a)(1)(iii)	20dB Bandwidth	< 1 MHz only if using less than 15 non-overlapping channels	CONDUCTED	PASS	Section 6.2
15.247(b)(1)	Peak Transmitter Output Power	< 1 Watt if $\geq$ 75 non-overlapping channels used		PASS	Section 6.3
15.247(a)(1)	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 6.5
15.247(a)(1)(iii)	Number of Channels	> 15 Channels		PASS	Section 6.7
15.247(a)(1)(iii)	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 6.6
15.247(d)	Band Edge / Out-of-Band Emissions	Conducted > 20dBc		PASS	Section 6.4, Section 6.8
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Section 6.9, Section 6.10, Section 6.11
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or	LINE CONDUCTED	PASS	Section 6.12

**Table 6-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "BT Auto," Version 2.9.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 10 of 56	

## 6.2 20dB Bandwidth Measurement

### §15.247 (a.1.iii)

#### Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

***The maximum permissible 20dB bandwidth is 1 MHz, unless more than 15 non-overlapping channels are employed.***

#### Test Procedure Used


ANSI C63.10-2009 – Section 6.9.1

#### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 20$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% OBW
3. VBW  $\geq 3 \times$  RBW
4. Span = 2x - 5x OBW
5. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
6. Detector = Peak
7. Trace mode = max hold
8. Sweep = auto couple
9. The trace was allowed to stabilize

#### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-1. Test Instrument & Measurement Setup**


#### Test Notes

None

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 11 of 56	


Frequency [MHz]	Data Rate [Mbps]	Channel No.	20dB Bandwidth Test Results	
			Measured Bandwidth [kHz]	Pass/Fail
2402	1.0	0	942.30	Pass
2441	1.0	39	950.90	Pass
2480	1.0	78	875.30	Pass
2402	2.0	0	1307.00	Pass
2441	2.0	39	1277.00	Pass
2480	2.0	78	1328.00	Pass
2402	3.0	0	1241.00	Pass
2441	3.0	39	1286.00	Pass
2480	3.0	78	1331.00	Pass

**Table 6-2. Conducted 20dB Bandwidth Measurements**




**Plot 6-1. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 0)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 12 of 56




Plot 6-2. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 39)




Plot 6-3. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 13 of 56




Plot 6-4. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 0)




Plot 6-5. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 39)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 14 of 56




Plot 6-6. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 78)




Plot 6-7. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 0)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 15 of 56



Plot 6-8. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 39)



Plot 6-9. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 16 of 56



## 6.3 Output Power Measurement

### §15.247 (b.1)

#### Test Overview and Limits

Measurement is made while the EUT is operating in non-hopping transmission mode. The powers shown below were measured using a spectrum analyzer with a Bluetooth signaling test set (Agilent Model: N4010A) used only to maintain a Bluetooth link with the EUT. Average power data is provided to determine the need for Bluetooth SAR testing according to KDB 447498 D01 v05r02. Average power measurements are performed using the analyzer's "burst power" function with RBW = 3MHz. The burst power function triggers on a single set burst set to maximum power and measures the maximum average power on the on-time.

***The maximum permissible output power is 1 Watt.***

#### Test Procedure Used

ANSI C63.10-2009 – Section 6.10.1


#### Test Settings

##### Peak Power Measurement

1. Span = approximately 5x 20dB bandwidth, centered on hopping channel
2. RBW > 20dB bandwidth of emission being measured
3. VBW ≥ RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-2. Test Instrument & Measurement Setup**

#### Note

This unit was tested with all possible data rates and the highest peak power is reported with the unit transmitting at 2Mbps.


Final results were obtained using calibrated couplers, attenuators and cables. The following formula was used:

Output Power (dBm) = Raw Analyzer Level (dBm) + Cable Loss (dB) + Loss in Directional Coupler/Insertion Loss (dB)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 17 of 56	


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Peak Conducted Power		Avg Conducted Power	
			[dBm]	[mW]	[dBm]	[mW]
2402	1.0	0	2.68	1.854	2.31	1.700
2441	1.0	39	2.39	1.732	1.93	1.560
2480	1.0	78	2.46	1.764	2.00	1.585
2402	2.0	0	3.39	2.181	0.33	1.080
2441	2.0	39	3.03	2.010	-0.04	0.990
2480	2.0	78	3.12	2.053	0.03	1.008
2402	3.0	0	2.50	1.778	-0.63	0.864
2441	3.0	39	2.13	1.633	-1.01	0.792
2480	3.0	78	2.24	1.675	-0.94	0.806

**Table 6-3. Conducted Output Power Measurements**




**Plot 6-10. Peak Conducted Power (1Mbps – Ch. 0)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 18 of 56




Plot 6-11. Peak Conducted Power (1Mbps – Ch. 39)




Plot 6-12. Peak Conducted Power (1Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 19 of 56



Plot 6-13. Peak Conducted Power (2Mbps – Ch. 0)




Plot 6-14. Peak Conducted Power (2Mbps – Ch. 39)



FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 20 of 56




Plot 6-15. Peak Conducted Power (2Mbps – Ch. 78)




Plot 6-16. Peak Conducted Power (3Mbps – Ch. 0)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 21 of 56




Plot 6-17. Peak Conducted Power (3Mbps – Ch. 39)




Plot 6-18. Peak Conducted Power (3Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 22 of 56




Plot 6-19. Average Conducted Power (1Mbps – Ch. 0)




Plot 6-20. Average Conducted Power (1Mbps – Ch. 39)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 23 of 56




Plot 6-21. Average Conducted Power (1Mbps – Ch. 78)




Plot 6-22. Average Conducted Power (2Mbps – Ch. 0)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 24 of 56






Plot 6-23. Average Conducted Power (2Mbps – Ch. 39)




Plot 6-24. Average Conducted Power (2Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 25 of 56




Plot 6-25. Average Conducted Power (3Mbps – Ch. 0)



Plot 6-26. Average Conducted Power (3Mbps – Ch. 39)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 26 of 56



Plot 6-27. Average Conducted Power (3Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 27 of 56

## 6.4 Band Edge Compliance

### §15.247 (d)

#### Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. **The maximum permissible out-of-band emission level is 20 dBc.**

#### Test Procedure Used


ANSI C63.10-2009 – Section 7.7.9

#### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of spectrum analyzer display span
4. VBW  $\geq$  RBW
5. Detector = Peak
6. Trace mode = max hold
7. Sweep time = auto couple
8. The trace was allowed to stabilize
9. Marker-delta function used to determine the amplitude difference between the peak of the in-band emission and the highest out-of-band emission

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-3. Test Instrument & Measurement Setup**


#### Test Notes

Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.


FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 28 of 56	




Plot 6-28. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0)




Plot 6-29. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 29 of 56	



Plot 6-30. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps)



Plot 6-31. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 30 of 56

## 6.5 Carrier Frequency Separation

### §15.247 (a.1)

#### Test Overview and Limit

Measurement is made with EUT operating in hopping mode. **The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.**

#### Test Procedure Used


ANSI C63.10-2009 – Section 7.7.2

#### Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW  $\geq$  1% of span
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-4. Test Instrument & Measurement Setup**


#### Test Notes

The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels and when operating in AFH mode using 20 channels.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 31 of 56	

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.628
2441	1.0	39	0.634
2480	1.0	78	0.584
2402	2.0	0	0.871
2441	2.0	39	0.851
2480	2.0	78	0.885
2402	3.0	0	0.827
2441	3.0	39	0.857
2480	3.0	78	0.858

**Table 6-4. Minimum Channel Separation**



**Plot 6-32. Channel Spacing Plot (Bluetooth)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 32 of 56



## 6.6 Time of Occupancy

**§15.247 (a.1.iii)**

### Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. **The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.**

### Test Procedure Used


ANSI C63.10-2009 – Section 7.7.4

### Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW = 1MHz
3. VBW  $\geq$  RBW
4. Sweep = as necessary to capture entire dwell time per hopping channel
5. Detector = peak
6. Trace mode = max hold
7. Marker-delta function used to determine transmit time per hop

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-5. Test Instrument & Measurement Setup**

### Test Notes

None

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 33 of 56	



Plot 6-33. Time of Occupancy Plot (Bluetooth)

### Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of  $1600 / 6 = 266.67$  hops/s/slot

- $400\text{ms} \times 79$  hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79$  channels = 3.38 hops/second (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6$  seconds = 106.67 hops (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.905 \text{ ms/channel} = 309.87 \text{ ms}$  (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of  $800 / 6 = 133.3$  hops/s/slot

- $400\text{ms} \times 20$  hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20$  channels = 6.67 hops/second (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8$  seconds = 53.34 hops (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.905 \text{ ms/channel} = 154.95 \text{ ms}$  (worst case dwell time for one channel in AFH mode)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 34 of 56	

## 6.7 Number of Hopping Channels

### §15.247 (a.1.iii)

#### Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

#### Test Procedure Used


ANSI C63.10-2009 – Section 7.7.3

#### Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW  $\geq$  1% of the span
3. VBW  $\geq$  RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

#### Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-6. Test Instrument & Measurement Setup**


#### Test Notes

The frequency spectrum was broken up into two sub-ranges to clearly show all of the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 35 of 56	



Plot 6-34. Low End Spectrum Channel Hopping Plot (Bluetooth)



Plot 6-35. High End Spectrum Channel Hopping Plot (Bluetooth)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 36 of 56

## 6.8 Conducted Spurious Emissions §15.247 (d)

### Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10<sup>th</sup> harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

### Test Procedure Used


ANSI C63.10-2009 – Section 7.7.10

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz\* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 6-7. Test Instrument & Measurement Setup**


### Test Notes

Out-of-band conducted spurious emissions were investigated for all data rates and the worst case emissions were found with the EUT transmitting at 2Mbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 37 of 56	




Plot 6-36. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 0)




Plot 6-37. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 0)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 38 of 56




Plot 6-38. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 39)




Plot 6-39. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 39)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 39 of 56



Plot 6-40. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 78)



Plot 6-41. Conducted Spurious Plot (Bluetooth, 2Mbps – Ch. 78)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 40 of 56



## 6.9 Radiated Spurious Emission Measurements – Above 1GHz

§15.205 §15.209 §15.247 (d)

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-5 per Section 15.209.***

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
Above 960.0 MHz	500	3

**Table 6-5. Radiated Limits**

### Test Procedure Used

ANSI C63.10-2009 – Section 6.6.4.2



### Test Settings

#### Average Field Strength Measurements per Section 4.2.3.2.3 of ANSI C63.10-2009

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

#### Peak Field Strength Measurements per Section 4.2.3.2.2 of ANSI C63.10-2009

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 6-6 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 41 of 56	

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

**Table 6-6. RBW as a Function of Frequency**

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-8. Test Instrument & Measurement Setup**

**Test Notes**

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-5.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
6. The duty cycle correction factor was not applied to noise floor measurements.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.



FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 42 of 56	

**Sample Calculation**

- Field Strength Level  $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]} + \text{Duty Cycle Correction }_{[dB]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


**Duty Cycle Correction Factor Calculation**

- Channel hop rate = 800 hops/second (AFH Mode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop =  $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- Time to cycle through all channels =  $7.50 \times 20 \text{ channels} = 150 \text{ ms}$
- Number of times transmitter hits on one channel =  $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- Worst case dwell time = 7.5 ms
- Duty cycle correction factor =  $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$


FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 43 of 56

# Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d)



**Plot 6-42. Radiated Spurious Plot above 1GHz (BT – Ch. 0, Ant. Pol. H)**




**Plot 6-43. Radiated Spurious Plot above 1GHz (BT – Ch. 0, Ant. Pol. V)**




**Plot 6-44. Radiated Spurious Plot above 1GHz (BT – Ch. 39, Ant. Pol. H)**


FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 44 of 56



**Plot 6-45. Radiated Spurious Plot above 1GHz (BT – Ch. 39, Ant. Pol. V)**




**Plot 6-46. Radiated Spurious Plot above 1GHz (BT – Ch. 78, Ant. Pol. H)**




**Plot 6-47. Radiated Spurious Plot above 1GHz (BT – Ch. 78, Ant. Pol. V)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 45 of 56	

## Radiated Spurious Emissions Measurements (Above 18GHz) §15.209



**Plot 6-48. Radiated Spurious Plot above 18GHz (Pol. H)**



**Plot 6-49. Radiated Spurious Plot above 18GHz (Pol. V)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 46 of 56

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d)

Worst Case Mode: Bluetooth  
 Worst Case Data Rate: 1 Mbps  
 Measurement Distance: 3 Meters  
 Operating Frequency: 2402MHz  
 Channel: 0



Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	-98.05	Avg	H	42.80	-22.50	29.25	53.98	-24.73
4804.00	-94.13	Peak	H	42.80	0.00	55.67	73.98	-18.31
12010.00	-119.32	Avg	H	54.45	0.00	42.13	53.98	-11.85
12010.00	-110.42	Peak	H	54.45	0.00	51.03	73.98	-22.95

**Table 6-7. Radiated Measurements**

Worst Case Mode: Bluetooth  
 Worst Case Data Rate: 1 Mbps  
 Measurement Distance: 3 Meters  
 Operating Frequency: 2441MHz  
 Channel: 39

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4882.00	-93.31	Avg	H	44.08	-22.50	35.27	53.98	-18.71
4882.00	-97.57	Peak	H	44.08	0.00	53.51	73.98	-20.47
7323.00	-119.85	Avg	H	47.72	0.00	34.88	53.98	-19.10
7323.00	-110.72	Peak	H	47.72	0.00	44.01	73.98	-29.97
12205.00	-119.23	Avg	H	54.67	0.00	42.44	53.98	-11.54
12205.00	-110.26	Peak	H	54.67	0.00	51.41	73.98	-22.57

**Table 6-8. Radiated Measurements**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 47 of 56	



## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d)

Worst Case Mode: Bluetooth  
 Worst Case Data Rate: 1 Mbps  
 Measurement Distance: 3 Meters  
 Operating Frequency: 2480MHz  
 Channel: 78

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	AFCL [dB]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	-98.37	Avg	H	44.49	-22.50	30.63	53.98	-23.35
4960.00	-94.78	Peak	H	44.49	0.00	56.72	73.98	-17.26
7440.00	-119.91	Avg	H	47.65	0.00	34.74	53.98	-19.24
7440.00	-110.10	Peak	H	47.65	0.00	44.55	73.98	-29.43
12400.00	-119.82	Avg	H	54.57	0.00	41.75	53.98	-12.23
12400.00	-109.77	Peak	H	54.57	0.00	51.80	73.98	-22.18

Table 6-9. Radiated Measurements

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 48 of 56	



## 6.10 Radiated Restricted Band Edge Measurements

§15.205 §15.209 §15.247 (d)

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$


Worst Case Mode: Bluetooth

Worst Case Data Rate: 1 Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78



Date: 3.JUL.2015 14:00:28


**Plot 6-50. Radiated Restricted Upper Band Edge Measurement (Average)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 49 of 56

## Radiated Restricted Band Edge Measurements §15.205 §15.209 §15.247 (d)

The amplitude offset shown in the following plots for peak measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Pre-amplifier Gain}$$



Date: 3 JUL 2015 14:06:52

Plot 6-51. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 50 of 56

## 6.11 Radiated Spurious Emissions Measurements – Below 1GHz

### §15.209

#### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-10 per Section 15.209.***

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 6-10. Radiated Limits**



#### Test Procedures Used

ANSI C63.4-2009

#### Test Settings


##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 51 of 56	

### Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 6-9. Test Instrument & Measurement Setup**


### Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 52 of 56	

## Radiated Spurious Emissions Measurements (Below 1GHz)

### §15.209



**Plot 6-52. Radiated Spurious Plot below 1GHz (Pol. H)**




**Plot 6-53. Radiated Spurious Plot below 1GHz (Pol. V)**

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 53 of 56	

## 6.12 Line Conducted Measurement Data

### §15.207



**Plot 6-54. Line-Conducted Test Plot (L1)**

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.168	L1	0.2	37.70	65.06	27.36	18.93	55.06	36.13
0.373	L1	0.1	23.37	58.44	35.07	9.15	48.44	39.29
0.429	L1	0.1	21.71	57.27	35.56	9.45	47.27	37.82
0.458	L1	0.1	24.58	56.72	32.14	12.55	46.72	34.17
5.415	L1	0.2	35.78	60.00	24.22	20.61	50.00	29.39
23.384	L1	0.7	29.71	60.00	30.29	14.28	50.00	35.72

**Table 6-11. Line-Conducted Test Data (L1)**


#### Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in BT BDR mode using 1Mbps on Channel 39. The emissions found were not affected by the choice of channel used during testing.
- The limit for an intentional radiator from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset		Page 54 of 56

# Line Conducted Measurement Data

## §15.207



**Plot 6-55. Line-Conducted Test Plot (N)**

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.152	N	0.3	39.56	65.88	26.32	19.40	55.88	36.48
0.384	N	0.1	32.86	58.19	25.33	26.51	48.19	21.68
0.409	N	0.1	28.59	57.67	29.08	16.79	47.67	30.88
1.784	N	0.2	17.42	56.00	38.58	6.82	46.00	39.18
5.197	N	0.2	35.52	60.00	24.48	24.21	50.00	25.79
22.837	N	0.8	24.56	60.00	35.44	14.90	50.00	35.10

**Table 6-12. Line-Conducted Test Data (N)**


**Notes:**

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in BT BDR mode using 1Mbps on Channel 39. The emissions found were not affected by the choice of channel used during testing.
- The limit for an intentional radiator from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: V65E4281		FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1506221315.V65	Test Dates: June 23 - July 06, 2015	EUT Type: Portable Handset	Page 55 of 56	

## 7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Kyocera Portable Handset FCC ID: V65E4281** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: V65E4281		<b>FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0Y1506221315.V65	<b>Test Dates:</b> June 23 - July 06, 2015	<b>EUT Type:</b> Portable Handset		Page 56 of 56