

FCC Test Report

(PART 27)

Report No.: RF170328C23-7

FCC ID: V65E4750

Test Model: E4750

Received Date: Mar. 28, 2017

Test Date: Apr. 12, 2017 ~ Apr. 24, 2017

Issued Date: May 02, 2017

Applicant: Kyocera Corporation c/o Kyocera International, Inc.

Address: 8611 Balboa Avenue, San Diego, CA 92123

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments	6
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units.....	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	11
3.5 General Description of Applied Standards.....	11
4 Test Types and Results	12
4.1 Output Power Measurement	12
4.1.1 Limits of Output Power Measurement.....	12
4.1.2 Test Procedures.....	12
4.1.3 Test Setup.....	13
4.1.4 Test Results	14
4.2 Frequency Stability Measurement	17
4.2.1 Limits of Frequency Stability Measurement.....	17
4.2.2 Test Procedure	17
4.2.3 Test Setup.....	17
4.2.4 Test Results	18
4.3 Occupied Bandwidth Measurement.....	22
4.3.1 Limits of Occupied Bandwidth Measurement	22
4.3.2 Test Procedure	22
4.3.3 Test Setup.....	22
4.3.4 Test Result	23
4.4 Band Edge Measurement	25
4.4.1 Limits of Band Edge Measurement	25
4.4.2 Test Setup.....	25
4.4.3 Test Procedures.....	25
4.4.4 Test Results	26
4.5 Peak to Average Ratio	34
4.5.1 Limits of Peak to Average Ratio Measurement	34
4.5.2 Test Setup.....	34
4.5.3 Test Procedures.....	34
4.5.4 Test Results	35
4.6 Conducted Spurious Emissions	37
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	37
4.6.2 Test Setup.....	37
4.6.3 Test Procedure	37
4.6.4 Test Results	38
4.7 Radiated Emission Measurement.....	42
4.7.1 Limits of Radiated Emission Measurement	42
4.7.2 Test Procedure	42
4.7.3 Deviation from Test Standard	42
4.7.4 Test Setup.....	42
4.7.5 Test Results	43
5 Pictures of Test Arrangements.....	49
Appendix – Information on the Testing Laboratories	50

Release Control Record

Issue No.	Description	Date Issued
RF170328C23-7	Original Release	May 02, 2017

1 Certificate of Conformity

Product: Feature Phone

Brand: KYOCERA

Test Model: E4750

Sample Status: Identical Prototype

Applicant: Kyocera Corporation c/o Kyocera International, Inc.

Test Date: Apr. 12, 2017 ~ Apr. 24, 2017

Standards: FCC Part 27, Subpart C, M

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Evonne Lin, **Date:** May 02, 2017

Evonne Liu / Specialist

Approved by : David Huang, **Date:** May 02, 2017

David Huang / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(h)	Equivalent Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
--	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(l)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(m)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(m)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.37 dB at 8040 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jun. 21, 2016	Jun. 20, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 16, 2016	Dec. 15, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Dec. 29, 2016	Dec. 28, 2017
Double Ridge Guide Horn Antenna EMCO	3115	5619	Dec. 27, 2016	Dec. 26, 2017
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 13, 2016	Dec. 12, 2017
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2016	Jul. 07, 2017
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 19, 2016	Oct. 18, 2017
Preamplifier Agilent	310N	187226	Jun. 24, 2016	Jun. 23, 2017
Preamplifier Agilent	83017A	MY39501357	Jun. 24, 2016	Jun. 23, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 08, 2016	Sep. 07, 2017
Power Sensor Anritsu	MA2411B	1207325	Sep. 08, 2016	Sep. 07, 2017
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 24, 2016	Jun. 23, 2017
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 24, 2016	Jun. 23, 2017
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 10, 2015	Aug. 09, 2017
Temperature & Humidity Chamber	GTH-120-40-CP-A R	MAA1306-019	Sep. 02, 2016	Sep. 01, 2017
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jul. 01, 2016	Jun. 30, 2017

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The FCC Site Registration No. is 149147.
 5. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Feature Phone	
Brand	KYOCERA	
Test Model	E4750	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0 Vdc (adapter) 3.8 Vdc (Li-ion battery)	
Modulation Type	QPSK, 16QAM	
Frequency Range	LTE Band 41 (Channel Bandwidth: 5 MHz)	2498.5 ~ 2687.5 MHz
	LTE Band 41 (Channel Bandwidth: 10 MHz)	2501.0 ~ 2685.0 MHz
	LTE Band 41 (Channel Bandwidth: 15 MHz)	2503.5 ~ 2682.5 MHz
	LTE Band 41 (Channel Bandwidth: 20 MHz)	2506.0 ~ 2680.0 MHz
Max. EIRP Power	LTE Band 41 (Channel Bandwidth: 5 MHz)	360.33 mW
	LTE Band 41 (Channel Bandwidth: 10 MHz)	362.83 mW
	LTE Band 41 (Channel Bandwidth: 15 MHz)	362.83 mW
	LTE Band 41 (Channel Bandwidth: 20 MHz)	360.33 mW
Emission Designator	LTE Band 41 (Channel Bandwidth: 5 MHz)	4M49G7D
	LTE Band 41 (Channel Bandwidth: 10 MHz)	8M96W7D
	LTE Band 41 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 41 (Channel Bandwidth: 20 MHz)	17M9G7D
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	KYOCERA	SCP-50ADT	I/P: 100-240 Vac, 50/60 Hz, 0.25 A O/P: 5 Vdc, 1.5 A
Battery	KYOCERA	SCP-71LBPS	3.8 Vdc, 11.02 Wh
USB Cable	KYOCERA	SCP-22SDC	1 m shielded cable w/o core


2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	EIRP	Radiated Emission
LTE Band 41	X-plane	Z-axis

LTE Band 41

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	39675 to 41565	39675, 40620, 41565	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		39700 to 41540	39700, 40620, 41540	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset
		39725 to 41515	39725, 40620, 41515	15 MHz	QPSK, 16QAM	1 RB / 37 RB Offset
		39750 to 41490	39750, 40620, 41490	20 MHz	QPSK, 16QAM	1 RB / 50 RB Offset
-	Frequency Stability	39675 to 41565	39675, 41565	5 MHz	QPSK	1 RB / 12 RB Offset
		39700 to 41540	39700, 41540	10 MHz	QPSK	1 RB / 24 RB Offset
		39725 to 41515	39725, 41515	15 MHz	QPSK	1 RB / 37 RB Offset
		39750 to 41490	39750, 41490	20 MHz	QPSK	1 RB / 50 RB Offset
-	Occupied Bandwidth	39675 to 41565	39675, 40620, 41565	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		39700 to 41540	39700, 40620, 41540	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		39725 to 41515	39725, 40620, 41515	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		39750 to 41490	39750, 40620, 41490	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	39675 to 41565	39675, 40620, 41565	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		39700 to 41540	39700, 40620, 41540	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		39725 to 41515	39725, 40620, 41515	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		39750 to 41490	39750, 40620, 41490	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	39675 to 41565	39675, 41565	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		39700 to 41540	39700, 41540	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		39725 to 41515	39725, 41515	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		39750 to 41490	39750, 41490	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Conducted Emission	39675 to 41565	39675, 40620, 41565	5 MHz	QPSK	1 RB / 12 RB Offset
		39700 to 41540	39700, 40620, 41540	10 MHz	QPSK	1 RB / 24 RB Offset
		39725 to 41515	39725, 40620, 41515	15 MHz	QPSK	1 RB / 37 RB Offset
		39750 to 41490	39750, 40620, 41490	20 MHz	QPSK	1 RB / 50 RB Offset
-	Radiated Emission	39750 to 41490	39750, 40620, 41490	20 MHz	QPSK	1 RB / 50 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Frequency Stability	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Occupied Bandwidth	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Band Edge	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Peak to Average Ratio	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Conducted Emission	25 deg. C, 65 % RH	3.8 Vdc	Anson Lin
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao / Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-D 2010

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “User stations are limited to 2 watts” and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

4.1.2 Test Procedures

EIRP Measurement:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$

Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 39675	Mid Ch 40620	High Ch 41565		Low Ch 39675	Mid Ch 40620	High Ch 41565	
			2498.5 MHz	2593.0 MHz	2687.5 MHz		2498.5 MHz	2593.0 MHz	2687.5 MHz	
41 / 5M	1	0	22.54	24.02	23.99	0	21.51	23.06	23.02	1
	1	12	22.35	23.77	23.67	0	21.31	22.78	22.68	1
	1	24	22.47	23.91	23.86	0	21.43	22.94	22.88	1
	12	0	21.53	22.90	22.85	1	20.49	21.90	21.85	2
	12	6	21.41	22.72	22.63	1	20.36	21.69	21.60	2
	12	13	21.49	22.83	22.76	1	20.45	21.82	21.74	2
	25	0	21.44	22.79	22.69	1	20.39	21.78	21.66	2
41 / 10M	1	0	22.68	24.08	24.05	0	21.65	23.13	23.09	1
	1	24	22.49	23.85	23.77	0	21.45	22.87	22.79	1
	1	49	22.61	23.97	23.94	0	21.57	23.01	22.97	1
	25	0	21.68	23.00	22.96	1	20.64	22.01	21.97	2
	25	12	21.56	22.85	22.76	1	20.51	21.84	21.74	2
	25	25	21.64	22.94	22.89	1	20.60	21.95	21.89	2
	50	0	21.59	22.91	22.82	1	20.54	21.92	21.80	2
41 / 15M	1	0	22.82	24.14	24.11	0	21.78	23.19	23.16	1
	1	37	22.63	23.94	23.86	0	21.59	22.97	22.88	1
	1	74	22.75	24.04	24.02	0	21.71	23.08	23.05	1
	36	0	21.82	23.10	23.07	1	20.78	22.11	22.06	2
	36	19	21.71	22.97	22.89	1	20.66	21.94	21.86	2
	36	39	21.78	23.05	23.01	1	20.73	22.04	21.99	2
	75	0	21.74	23.02	22.95	1	20.69	22.00	21.92	2
41 / 20M	1	0	22.95	24.19	24.17	0	21.89	23.24	23.21	1
	1	50	22.80	24.01	23.97	0	21.73	23.04	22.96	1
	1	99	22.86	24.11	24.07	0	21.84	23.15	23.13	1
	50	0	22.01	23.18	23.13	1	20.88	22.20	22.17	2
	50	25	21.85	23.08	23.00	1	20.81	22.06	21.99	2
	50	50	21.96	23.14	23.12	1	20.86	22.15	22.11	2
	100	0	21.89	23.13	23.06	1	20.84	22.13	22.05	2

EIRP Power (dBm)

LTE Band 41							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	39675	2498.5	-18.71	44.24	25.53	357.11	H
	40620	2593.0	-18.63	44.20	25.57	360.33	
	41565	2687.5	-19.24	44.80	25.56	359.83	
	39675	2498.5	-21.66	44.19	22.53	179.10	V
	40620	2593.0	-21.58	44.09	22.51	178.16	
	41565	2687.5	-21.90	44.50	22.60	181.93	

Channel Bandwidth: 5 MHz / 16QAM

X	39675	2498.5	-19.68	44.24	24.56	285.63	H
	40620	2593.0	-19.64	44.20	24.56	285.56	
	41565	2687.5	-20.23	44.80	24.57	286.48	
	39675	2498.5	-22.68	44.19	21.51	141.61	V
	40620	2593.0	-22.52	44.09	21.57	143.48	
	41565	2687.5	-22.94	44.50	21.56	143.19	

LTE Band 41
Channel Bandwidth: 10 MHz / QPSK

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	39700	2501.0	-18.79	44.34	25.55	359.00	H
	40620	2593.0	-18.60	44.20	25.60	362.83	
	41540	2685.0	-19.23	44.72	25.49	354.24	
	39700	2501.0	-21.69	44.23	22.54	179.31	V
	40620	2593.0	-21.54	44.09	22.55	179.80	
	41540	2685.0	-21.89	44.41	22.52	178.48	

Channel Bandwidth: 10 MHz / 16QAM

X	39700	2501.0	-19.74	44.34	24.60	288.47	H
	40620	2593.0	-19.72	44.20	24.48	280.35	
	41540	2685.0	-20.13	44.72	24.59	287.94	
	39700	2501.0	-22.69	44.23	21.54	142.43	V
	40620	2593.0	-22.54	44.09	21.55	142.82	
	41540	2685.0	-22.93	44.41	21.48	140.48	

LTE Band 41								
Channel Bandwidth: 15 MHz / QPSK								
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)	
X	39725	2503.5	-18.76	44.32	25.56	359.58	H	
	40620	2593.0	-18.60	44.20	25.60	362.83		
	41515	2682.5	-19.34	44.85	25.51	355.47		
	39725	2503.5	-21.46	43.99	22.53	179.14	V	
	40620	2593.0	-21.58	44.09	22.51	178.16		
	41515	2682.5	-21.90	44.51	22.61	182.39		
Channel Bandwidth: 15 MHz / 16QAM								
X	39725	2503.5	-19.74	44.32	24.58	286.95	H	
	40620	2593.0	-19.65	44.20	24.55	284.90		
	41515	2682.5	-20.41	44.85	24.44	277.84		
	39725	2503.5	-22.48	43.99	21.51	141.64	V	
	40620	2593.0	-22.56	44.09	21.53	142.17		
	41515	2682.5	-22.93	44.51	21.58	143.88		
LTE Band 41								
Channel Bandwidth: 20 MHz / QPSK								
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)	
X	39750	2506.0	-18.66	44.16	25.50	354.81	H	
	40620	2593.0	-18.68	44.20	25.52	356.20		
	41490	2680.0	-19.24	44.81	25.57	360.33		
	39750	2506.0	-22.16	44.78	22.62	182.81	V	
	40620	2593.0	-21.58	44.09	22.51	178.16		
	41490	2680.0	-22.24	44.72	22.48	177.01		
Channel Bandwidth: 20 MHz / 16QAM								
X	39750	2506.0	-19.66	44.16	24.50	281.84	H	
	40620	2593.0	-19.76	44.20	24.44	277.78		
	41490	2680.0	-20.33	44.81	24.48	280.35		
	39750	2506.0	-23.14	44.78	21.64	145.88	V	
	40620	2593.0	-22.58	44.09	21.51	141.51		
	41490	2680.0	-23.21	44.72	21.51	141.58		

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 5 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
3.8	2498.500001	0.000	2687.500002	0.001	2.5	
3.3	2498.500001	0.000	2687.500004	0.001	2.5	
4.35	2498.500004	0.002	2687.500001	0.000	2.5	

Note: The applicant defined the normal working voltage of the battery is from 3.3 Vdc to 4.35 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 5 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
-30	2498.500003	0.001	2687.500002	0.001	2.5	
-20	2498.500002	0.001	2687.500003	0.001	2.5	
-10	2498.500003	0.001	2687.500002	0.001	2.5	
0	2498.500001	0.001	2687.500003	0.001	2.5	
10	2498.500004	0.001	2687.500002	0.001	2.5	
20	2498.499997	-0.001	2687.499997	-0.001	2.5	
30	2498.499997	-0.001	2687.499997	-0.001	2.5	
40	2498.499997	-0.001	2687.499998	-0.001	2.5	
50	2498.499998	-0.001	2687.499997	-0.001	2.5	
60	2498.499996	-0.002	2687.499998	-0.001	2.5	

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 10 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
3.8	2501.000004	0.001	2685.000003	0.001	2.5	
3.3	2501.000002	0.001	2685.000001	0.000	2.5	
4.35	2501.000001	0.001	2685.000002	0.001	2.5	

Note: The applicant defined the normal working voltage of the battery is from 3.3 Vdc to 4.35 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 10 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
-30	2501.000002	0.001	2685.000002	0.001	2.5	
-20	2501.000002	0.001	2685.000001	0.000	2.5	
-10	2501.000004	0.001	2685.000003	0.001	2.5	
0	2501.000004	0.001	2685.000003	0.001	2.5	
10	2501.000004	0.002	2685.000003	0.001	2.5	
20	2500.999998	-0.001	2684.999997	-0.001	2.5	
30	2500.999999	-0.001	2684.999999	0.000	2.5	
40	2500.999998	-0.001	2684.999997	-0.001	2.5	
50	2500.999998	-0.001	2684.999998	-0.001	2.5	
60	2500.999997	-0.001	2684.999997	-0.001	2.5	

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 15 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
3.8	2503.500001	0.000	2682.500002	0.001	2.5	
3.3	2503.500004	0.002	2682.500003	0.001	2.5	
4.35	2503.500002	0.001	2682.500003	0.001	2.5	

Note: The applicant defined the normal working voltage of the battery is from 3.3 Vdc to 4.35 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 15 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
-30	2503.500003	0.001	2682.500004	0.001	2.5	
-20	2503.500001	0.001	2682.500002	0.001	2.5	
-10	2503.500002	0.001	2682.500002	0.001	2.5	
0	2503.500004	0.001	2682.500003	0.001	2.5	
10	2503.500003	0.001	2682.500004	0.001	2.5	
20	2503.499997	-0.001	2682.499996	-0.001	2.5	
30	2503.499999	-0.001	2682.499997	-0.001	2.5	
40	2503.499998	-0.001	2682.499996	-0.001	2.5	
50	2503.499997	-0.001	2682.499999	-0.001	2.5	
60	2503.499997	-0.001	2682.499997	-0.001	2.5	

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 20 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
3.8	2506.000001	0.001	2680.000002	0.001	2.5	
3.3	2506.000001	0.000	2680.000003	0.001	2.5	
4.35	2506.000003	0.001	2680.000002	0.001	2.5	

Note: The applicant defined the normal working voltage of the battery is from 3.3 Vdc to 4.35 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 41				Limit (ppm)	
	Channel Bandwidth: 20 MHz					
	Low Channel		High Channel			
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)		
-30	2506.000002	0.001	2680.000002	0.001	2.5	
-20	2506.000001	0.001	2680.000003	0.001	2.5	
-10	2506.000003	0.001	2680.000002	0.001	2.5	
0	2506.000001	0.001	2680.000002	0.001	2.5	
10	2506.000001	0.001	2680.000001	0.000	2.5	
20	2505.999997	-0.001	2679.999996	-0.001	2.5	
30	2505.999996	-0.002	2679.999997	-0.001	2.5	
40	2505.999999	0.000	2679.999998	-0.001	2.5	
50	2505.999996	-0.002	2679.999998	-0.001	2.5	
60	2505.999996	-0.002	2679.999997	-0.001	2.5	

4.3 Occupied Bandwidth Measurement


4.3.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result

LTE Band 41							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
39675	2498.5	4.4972	4.4928	39700	2501.0	8.9448	8.9620
40620	2593.0	4.4982	4.4944	40620	2593.0	8.9581	8.9611
41565	2687.5	4.4969	4.4955	41540	2685.0	8.9516	8.9557




LTE Band 41


Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
39725	2503.5	13.4460	13.4380	39750	2506.0	17.9070	17.9040
40620	2593.0	13.4620	13.4510	40620	2593.0	17.9230	17.9170
41515	2682.5	13.4580	13.4430	41490	2680.0	17.9210	17.9110

Spectrum Plot of Worst Value


15 MHz / QPSK




15 MHz / 16QAM



20 MHz / QPSK



20 MHz / 16QAM




4.4 Band Edge Measurement

4.4.1 Limits of Band Edge Measurement

According to FCC 27.53(l)(4) specified that power of any emission outside of the channel edge must be attenuated below the transmitting power (P) by a factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495-2496 MHz, in which case a resolution bandwidth of at least one percent may be employed.


4.4.2 Test Setup



4.4.3 Test Procedures

- The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- The center frequency of spectrum is the band edge frequency and span is 20 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (Channel bandwidth 5 MHz).
- The center frequency of spectrum is the band edge frequency and span is 40 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (Channel bandwidth 10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 60 MHz. RB of the spectrum is 200 kHz and VB of the spectrum is 1 MHz (Channel bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 80 MHz. RB of the spectrum is 200 kHz and VB of the spectrum is 1 MHz (Channel bandwidth 20 MHz).
- Record the max trace plot into the test report.

4.4.4 Test Results



LTE Band 41

Channel Bandwidth: 5 MHz / 16QAM

<Adjacent Channel Band Edge>

Channel 39675

1 RB

Channel 41565

1 RB




Date: 24/APR/2017 13:01:46


Channel 39675

25 RB

25 RB



Date: 24/APR/2017 11:59:07



Date: 24/APR/2017 13:05:24

<Channel Band Edge>

Channel 39675



25 RB

25 RB

Channel 41565

41565

25 RB



LTE Band 41



Channel Bandwidth: 10 MHz / QPSK
 <Adjacent Channel Band Edge>

Channel 39700

1 RB

Channel 41540


1 RB



Channel 39700

50 RB

50 RB



<Channel Band Edge>

Channel 39700



50 RB

50 RB

Channel 41540

41540

50 RB



LTE Band 41



Channel Bandwidth: 10 MHz / 16QAM
 <Adjacent Channel Band Edge>

Channel 39700

1 RB

Channel 41540

1 RB





Channel 39700

50 RB

Channel 41540

50 RB




<Channel Band Edge>

Channel 39700

50 RB

Channel 41540

50 RB



LTE Band 41



Channel Bandwidth: 15 MHz / QPSK
 <Adjacent Channel Band Edge>

Channel 39725

1 RB

Channel 41515

1 RB



Channel 39725

75 RB

Channel 41515

75 RB




<Channel Band Edge>

Channel 39725

75 RB

Channel 41515

75 RB



LTE Band 41



Channel Bandwidth: 15 MHz / 16QAM
 <Adjacent Channel Band Edge>

Channel 39725

1 RB

Channel 41515

1 RB




Channel 39725

75 RB

Channel 41515

75 RB





<Channel Band Edge>

Channel 39725

75 RB

Channel 41515

75 RB




LTE Band 41

Channel Bandwidth: 20 MHz / QPSK




<Adjacent Channel Band Edge>

Summary	Range Up:	RBW:	Frequency:	Power dBm:	Alimit:
1000 Hz	2.450 GHz	500.000 kHz	2.44810 GHz	-49.71 dBm	-24.71 dB
1000 Hz	2.451 GHz	500.000 kHz	2.44949 GHz	-43.98 dBm	-30.98 dB
1000 Hz	2.452 GHz	500.000 kHz	2.44989 GHz	-37.84 dBm	-24.84 dB
1000 Hz	2.453 GHz	500.000 kHz	2.45020 GHz	-31.70 dBm	-24.70 dB
1000 Hz	2.454 GHz	500.000 kHz	2.45060 GHz	-25.56 dBm	-24.56 dB
1000 Hz	2.507 GHz	200.000 kHz	2.49708 GHz	17.95 dBm	-12.05 dB




Channel 39750 100 RB

Range Up:	RBW:	Frequency:	Power Abs:	Min:
495 GHz	2,450 kHz	2.49046 GHz	-43.22 dBm	-18.22 dB
499 GHz	2,465 kHz	2.49486 GHz	-40.32 dBm	-27.32 dB
503 GHz	2,480 kHz	2.49926 GHz	-41.42 dBm	-28.42 dB
506 GHz	2,500 kHz	2.50060 GHz	-37.57 dBm	-67.52 dB
		2.50498 GHz	-1.84 dBm	-31.84 dB




<Channel Band Edge>

The figure shows a screenshot of a spectrum analysis software interface. The top header displays "Channel 39750" and "100 F". Below the header, a status bar shows "Time Spectrum Analysis - Sweep 001" and "0115:19 AM Apr 21, 2017". The main window features a graph with a black trace representing a signal. A vertical red line at approximately 2.495992 GHz is labeled "Mkr1 2.495 992 GHz -34.80 dBm". A horizontal blue line at approximately 2.496000 GHz is labeled "Mkr2 2.496 000 GHz -38.00 dBm". On the left side, there are several status parameters: "Ref Offset 15 dB", "Ref 35.00 dBm", "PNO: Wide", "IFGain: Low", "Trig: Free Run", and "#Atten: 30 dB". The bottom of the screen has a menu bar with "File", "Edit", "View", "Analysis", "Tools", "Help", and "About". The footer contains frequency labels "2.496000 GHz", "BW 180 kHz", "VBW 560 kHz", "Span 8.000 MHz", and "Sweep 1.000 s (1001 pts.)".







The screenshot shows a spectrum analysis software interface. The top header includes 'Channel' (1), '41490', '100 RB', and 'Peak Search'. Below the header, the frequency is set to '2.690000000000000 GHz'. The 'Avg Type' is 'Log-Pwr'. The time range is '0117-02 AM April 21, 2017'. The plot area displays a signal with markers. A red marker at the top left is labeled 'Mkr1 2.690 000 GHz -34.25 dBm'. A black marker at the bottom is labeled 'Mkr--Ref L'. Other markers include '1' and '2'. The x-axis is labeled '#VBW 560 kHz' and 'Span 8.000 MHz'. The y-axis is labeled 'Ref Offset 15 dB' and 'Ref 35.00 dBm'. The bottom right corner shows 'Mon 1 of 1'.



LTE Band 41

Channel Bandwidth: 20 MHz / 16QAM

<Adjacent Channel Band Edge>


Channel **39750**
1 RB
Channel
41490
1 RB

Channel **39750**
100 RB
Channel
41490
100 RB

Channel **39750**
100 RB
Channel
41490
100 RB


4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results

LTE Band 41							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
39675	2498.5	7.67	9.18	39700	2501.0	7.70	9.05
40620	2593.0	7.38	8.17	40620	2593.0	7.36	7.59
41565	2687.5	7.95	9.20	41540	2685.0	7.77	8.83




LTE Band 41


Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
39725	2503.5	9.97	8.49	39750	2506.0	8.12	8.46
40620	2593.0	7.81	8.25	40620	2593.0	7.83	8.41
41515	2682.5	8.25	8.54	41490	2680.0	8.24	10.62

Spectrum Plot of Worst Value


15 MHz / QPSK




15 MHz / 16QAM



20 MHz / QPSK



20 MHz / 16QAM




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25 dBm.


4.6.2 Test Setup




4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 27 GHz for LTE Band 41. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.4 Test Results






LTE Band 41


Channel Bandwidth: 15 MHz

Channel 39725

Frequency Range : 30 MHz ~ 3 GHz




Frequency Range : 3 GHz ~ 27 GHz




Channel 40620

Frequency Range : 30 MHz ~ 3 GHz




Frequency Range : 3 GHz ~ 27 GHz





Channel 41515

Frequency Range : 30 MHz ~ 3 GHz



Frequency Range : 3 GHz ~ 27 GHz





4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25 dBm.

4.7.2 Test Procedure


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dBi.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

LTE Band 41

Channel Bandwidth: 20 MHz / QPSK


Low Channel



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B7/B41) Horizontal

Remark : LTE_Band 41_Link_CH39750

Tested by: Karl Lee


	Freq	Read Level	Limit Level	Over Line	Limit Factor	Remark
	MHz	dBm	dBm	dBm	dB	
1	5012.00	-38.77	-57.85	-25.00	-13.77	19.08 Peak
2 pp	7518.00	-37.98	-60.66	-25.00	-12.98	22.68 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1

Condition: PART 27(B7/B41) Vertical

Remark : LTE_Band 41_Link_CH39750

Tested by: Karl Lee

	Freq	Read Level	Limit Level	Over Line	Limit Factor	Remark
	MHz	dBm	dBm	dBm	dB	
1	5012.00	-37.80	-56.88	-25.00	-12.80	19.08 Peak
2 pp	7518.00	-34.68	-57.36	-25.00	-9.68	22.68 Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B7/B41) Horizontal

Remark : LTE_Band 41_Link_CH40620

Tested by: Charles Hsiao


	Freq	Read Level	Limit Level	Over Line	Limit Factor	Remark
	MHz	dBm	dBm	dBm	dB	
1	5186.00	-40.78	-60.90	-25.00	-15.78	20.12 Peak
2 pp	7779.00	-36.10	-59.43	-25.00	-11.10	23.33 Peak



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
 Condition: PART 27(B7/B41) Vertical
 Remark : LTE_Band 41_Link_CH40620
 Tested by: Charles Hsiao

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	
1	5186.00	-41.26	-61.38	-25.00	-16.26	20.12 Peak
2 pp	7779.00	-37.52	-60.85	-25.00	-12.52	23.33 Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1

Condition: PART 27(B7/B41) Horizontal

Remark : LTE_Band 41_Link_CH41490

Tested by: Karl Lee


Freq	Read Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm	dBm	dBm	dB		
1	83.73	-63.42	-51.98	-25.00	-38.42	-11.44 Peak
2	167.97	-73.12	-66.22	-25.00	-48.12	-6.90 Peak
3	202.26	-71.64	-65.50	-25.00	-46.64	-6.14 Peak
4	481.30	-73.01	-68.28	-25.00	-48.01	-4.73 Peak
5	651.40	-68.53	-68.39	-25.00	-43.53	-0.14 Peak
6	743.10	-69.58	-68.40	-25.00	-44.58	-1.18 Peak
7	5360.00	-38.94	-59.24	-25.00	-13.94	20.30 Peak
8 pp	8040.00	-33.20	-56.95	-25.00	-8.20	23.75 Peak



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1
 Condition: PART 27(B7/B41) Vertical
 Remark : LTE_Band 41_Link_CH41490
 Tested by: Karl Lee

	Read Freq	Limit Level	Over Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	
1	53.49	-58.49	-44.43	-25.00	-33.49	-14.06 Peak
2	106.95	-69.43	-60.13	-25.00	-44.43	-9.30 Peak
3	240.06	-72.52	-66.88	-25.00	-47.52	-5.64 Peak
4	440.70	-71.54	-67.91	-25.00	-46.54	-3.63 Peak
5	630.40	-68.60	-68.69	-25.00	-43.60	0.09 Peak
6	741.70	-70.17	-69.01	-25.00	-45.17	-1.16 Peak
7	5360.00	-41.38	-61.68	-25.00	-16.38	20.30 Peak
8 pp	8040.00	-31.37	-55.12	-25.00	-6.37	23.75 Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---