

Appendix B1:
SAR Distribution Plots (Head)

Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-800 Ch777 Left Cheek

Communication System: CDMA-800, Frequency: 848.31 MHz, Duty Cycle: 1:1

Medium: HSL900, Medium parameters used (interpolated): $f = 848.31 \text{ MHz}$; $\sigma = 0.908 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Left Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(6.47, 6.47, 6.47), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch777 LC/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 14.3 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 1.22 mW/g; SAR(10 g) = 0.904 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.28 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-800 Ch383 Left Tilt

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1

Medium: HSL900, Medium parameters used (interpolated): $f = 836.49$ MHz; $\sigma = 0.908$ mho/m; $\epsilon_r = 42.1$; $\rho = 1000$ kg/m³

Phantom: SAM 12, Phantom section: Left Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(6.47, 6.47, 6.47), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 LT/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 17.7 V/m; Power Drift = -0.178 dB

Peak SAR (extrapolated) = 0.685 W/kg

SAR(1 g) = 0.594 mW/g; SAR(10 g) = 0.456 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.624 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-800 Ch777 Right Cheek

Communication System: CDMA-800, Frequency: 848.31 MHz, Duty Cycle: 1:1

Medium: HSL900, Medium parameters used (interpolated): $f = 848.31 \text{ MHz}$; $\sigma = 0.908 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Right Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(6.47, 6.47, 6.47), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch777 RC/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 15.4 V/m; Power Drift = 0.081 dB


Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 1.25 mW/g; SAR(10 g) = 0.940 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.32 mW/g





Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-800 Ch383 Right Tilt

Communication System: CDMA-800, Frequency: 836.49 MHz, Duty Cycle: 1:1

Medium: HSL900, Medium parameters used (interpolated): $f = 836.49 \text{ MHz}$; $\sigma = 0.908 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Right Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(6.47, 6.47, 6.47), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-800 Ch383 RT/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 19.0 V/m; Power Drift = 0.142 dB

Peak SAR (extrapolated) = 0.729 W/kg

SAR(1 g) = 0.627 mW/g; SAR(10 g) = 0.485 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.661 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-1900 Ch1175 Left Cheek

Communication System: CDMA-1900, Frequency: 1908.75 MHz, Duty Cycle: 1:1

Medium: HSL1900, Medium parameters used (interpolated): $f = 1908.75 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 39.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Left Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(5.08, 5.08, 5.08), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900 Ch1175 LC/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.7 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.652 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

CDMA-1900 Ch1175 LC/Zoom Scan (7x7x7)/Cube 1:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 12.7 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.923 mW/g; SAR(10 g) = 0.572 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.996 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-1900 Ch600 Left Tilt

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1

Medium: HSL1900, Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³

Phantom: SAM 12, Phantom section: Left Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(5.08, 5.08, 5.08), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900 Ch600 LT/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = -0.007 dB

Peak SAR (extrapolated) = 0.652 W/kg

SAR(1 g) = 0.428 mW/g; SAR(10 g) = 0.273 mW/g

Maximum value of SAR (measured) = 0.464 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-1900 Ch1175 Right Cheek

Communication System: CDMA-1900, Frequency: 1908.75 MHz, Duty Cycle: 1:1

Medium: HSL1900, Medium parameters used (interpolated): $f = 1908.75 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 39.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Right Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(5.08, 5.08, 5.08), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900 Ch1175 RC/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 14.6 V/m; Power Drift = -0.083 dB


Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 1.16 mW/g; SAR(10 g) = 0.729 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.26 mW/g





Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-1900 Ch600 Right Tilt

Communication System: CDMA-1900, Frequency: 1880 MHz, Duty Cycle: 1:1

Medium: HSL1900, Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 39.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Right Section

DASY4 Configuration:

Probe: ET3DV6 - SN1664, ConvF(5.08, 5.08, 5.08), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-1900 Ch600 RT/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.5 V/m; Power Drift = 0.080 dB

Peak SAR (extrapolated) = 0.490 W/kg

SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.218 mW/g

Maximum value of SAR (measured) = 0.353 mW/g



Test Laboratory: Kyocera-Wireless Corp.

SCP-2700 #0449 CDMA-2450 Ch 0 Right Cheek

Communication System: Bluetooth 2450Mhz, Frequency: 2402 MHz, Duty Cycle: 1:1

Medium: HSL2450, Medium parameters used (interpolated): $f = 2402 \text{ MHz}$; $\sigma = 1.84 \text{ mho/m}$; $\epsilon_r = 39.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom: SAM 12, Phantom section: Right Section

DASY4 Configuration:

Probe: ES3DV3 - SN3078, ConvF(4.46, 4.46, 4.46), Calibrated: 6/23/2008

Sensor-Surface: 4mm (Mechanical Surface Detection),

Electronics: DAE4 Sn602, Calibrated: 6/25/2008

Measurement SW: DASY4, V4.7 Build 71

Postprocessing SW: SEMCAD, V1.8 Build 176

Temperature:

Room T = 21.8 +/- 1 deg C, Liquid T = 22.0 +/- 1 deg C

CDMA-2450 CH 0 RC/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.448 V/m; Power Drift = -0.153 dB

Peak SAR (extrapolated) = 0.824 W/kg

SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.00423 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.397 mW/g

