



Bundesnetzagentur

Test report

AIN19a04

BNetzA-CAB-02/21-01

Product / EUT: RFID reader
Type designation: ARE H9 – FullIso/A/U/C/B/H/Li
URH 1LL - x/U/C/B/H/Li/CS2
Tested type: ARE H9 – FullIso/A/U/C/B/H/Li
EUT authorization: Certification Declaration of Conformity
 Verification
Production level: 03/2016
S/N: 3651
Manufacturer: AEG Identifikationssysteme GmbH
Hörvelsinger Weg 47
89081 Ulm / Germany

Test remit: FCC Rules 47 CFR Part 15 – Subpart C – Intentional radiators
in accordance with the procedures given in
§15.207; 15.209

The standards were: kept*
 not kept*

***Remark:** Validation covered by the accredited scope
 Validation not covered by the accredited scope
according: _____
 Validation of the EMC-requirements partly proceeded

Applicant: AEG Identifikationssysteme GmbH
Hörvelsinger Weg 47
89081 Ulm / Germany

EUT-
Date of arrival: 2016-03-21
Test ID: PRN12_04
Date(s) of test: 2016-03-23 – 2016-04-25

Burgrieden, 2016-07-08

Released by:

Principal engineer - Christian Vogelmann

Test laboratory: EMCE GmbH
Ingenieurbüro für EMV-Prüfungen und Schaltungsentwicklung
Untere Wiesen 1 / 88483 Burgrieden / Germany

DAkkS-Registration No.: D-PL-12122-01-01
CAB-Registration No.: BnetzA-CAB-02/21-01/1
FCC-Registration No.: 219415

Test procedure: ANSI C63.10-2013

Responsible inspector: Mr. Hauser
EMCE GmbH
Ingenieurbüro für EMV-Prüfungen und Schaltungsentwicklung

Contact person: Mr. Kössler / AEG Identifikationssysteme GmbH

EUT-

Description: Handheld LF-RFID reader.
A = AEG ID 3D-front-label
x = no front-label
U = USB interface
H = HID interface
B = Bluetooth interface
CSx = customer specific software, sequential number x
C = real time clock
Li = lithium-ion battery
FullISO = all ISO 11784 & 11785 transponders supported

Voltage supply: 7.4VDC

Fundamental frequency: 134kHz,
Frequency list: 32.768kHz; 17.1776MHz; 20MHz; 48MHz

Temperature range: 0°C to 55°C

Approximate size: LxWxH / cm - 13.5x7.0x2.5

**Supplied /
used equipment:**

Designation	Type	Manufacturer	S/N
Laptop	Inspiron 5150	Dell	CN-0W0941-1296136J-2083
AC Adapter (Inspiron 5150)	PA-1131-02D	Dell	CN-9Y819-48010-360-0954
Bluetooth – USB Stick	USB Bluetooth Nano Stick	CSL Computer	Mod.No. - BSN23996
Transponder (tag)	Tier ISO, 20mm disc	AEG ID	9990000000000000
Battery (2x)	3.7V / 800mAh	XTAR	n/a
Bluetooth module (EUT)	WT12	bluegiga	FCC ID: QOQWT12

Configuration:



As-delivered condition*
Modified*

- A ferrite core (type WE 742 711 11) was attached on the USB cable, see image below



Cable designation	Type	Length	Remarks
USB cable	Shielded	0.8m	Ferrite core WE 742 711 11, 3cm off the EUT

Remarks: n/a

State of revision:

Source document	New Document	Date / Reviser	Modifications
AIN19_04	AIN19a04	2016-06-24 Chr. Vogelmann	List of valid equipment shrink to used equipment. Test conditions supplemented. Note for the use of RFID and Bluetooth at the same time. Environmental conditions recorded.

Test equipment list of EMCE GmbH:

Inv.- No.	Designation	Type	Manufacturer	S/N	Calibration: Interval /valid until
001	Test receiver	ESS 5Hz - 1000MHz	Rohde & Schwarz	833776/008 Firmware: Main: 1.21 OTP: 02.01 GRA: 02.03	1 Year(s)/ 2016-10-05
003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007	1 Year(s)/ 2016-08-31
004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003	1 Year(s)/ 2016-11-30
008	Loop antenna 9kHz-30MHz	HFH2-Z2	Rohde & Schwarz	835776/0002	3 Year(s)/ 2016-11-22
009	Antenna 30-300MHz	VHBA9123 / BBA9106	Schwarzbeck	435	3 Year(s)/ 2018-10-27
010	Antenna 250-1200MHz	UHALP 9108A	Schwarzbeck	108	2 Year(s)/ 2016-09-05
011	Antenna 30-300MHz	VHBA9123 / BBA9106	Schwarzbeck	0403/94	2 Year(s)/ 2016-09-05
012	Antenna 250-1200MHz	UHALP 9108A	Schwarzbeck	166	3 Year(s)/ 2018-11-10
014	OATS	3m	EMCE GmbH		3 Year(s)/ 2017-10-31
015	OATS	10m	EMCE GmbH		3 Year(s)/ 2017-10-31
042	AC-Source/ Analyser/ Norm impedance	EMV D 5000/PAS	Spitzenberger+ Spies	A2747 00/0 0501 A2747 07/00501 (ARS16/3)	2 Year(s)/ 2017-08-31
058	Receiver	ESIB 40	Rohde & Schwarz	100200/ Firmware 4.35	1 Year(s)/ 2017-04-07
062	Semi anechoic chamber #2	13.0m x 7.0m x 5.0m	EMC-Technik & Consulting GmbH		1 Year(s)/ 2016-07-31
067	LISN	ESH2-Z5	Rohde&Schwarz	872460/043	1 Year(s)/ 2016-08-31
068	LISN	ESH2-Z5	Rohde&Schwarz	872460/042	1 Year(s)/ 2016-08-31
070	Pulse limiter + 10dB Attenuator	ESH3-Z2	Rohde&Schwarz	n/a	1 Year(s)/ 2016-08-31
175	EMI Test receiver	ESR7	Rohde & Schwarz	101108 Firmware:	1 Year(s)/ 2016-07-14

Inv.- No.	Designation	Type	Manufacturer	S/N	Calibration: Interval /valid until
				FW V2.26	
997	EMC Software	EMC32 Vers. 8.53.0	Rohde& Schwarz	n/a	

Scope:

1	EMC-Test(s).....	8
1.1	Emission according 47 CFR Part 15 Subpart C - 04/2016	8
1.1.1	Terminal voltage according 47 CFR Part 15 Subpart C - 04/2016	8
1.1.1.1	Test set up	9
1.1.1.2	Test.....	11
1.1.2	Radio disturbances according 47 CFR Part 15 Subpart C - 04/2016	17
1.1.2.1	Test set up	18
1.1.2.2	Test – Radiated emission fundamental.....	23
1.1.2.3	Test – Spurious emissions.....	25
1.1.2.4	Restricted bands of operation	41
1.1.2.5	Antenna requirement	44
2	Summary	45

1 EMC-Test(s)

1.1 Emission according 47 CFR Part 15 Subpart C - 04/2016

1.1.1 Terminal voltage according 47 CFR Part 15 Subpart C - 04/2016

- Full compliance
 Precompliance
 Test not requested*
 Test not carried out*

*

Test location

<input checked="" type="checkbox"/>	Inv.-No.	Designation	Type (LxWxH)	Manufacturer	Location
<input checked="" type="checkbox"/>	588	Shielded room #2	8.3/5.8 x 5.5/2.9 x 3.4m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	584	Shielded room #3	3.6 x 3.6 x 2.5m	Siemens AG	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	678	Shielded room #4	4.0 x 4.0 x 3.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	062	Semi anechoic chamber #2	13.5 x 6.1 x 5.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	679	Full anechoic chamber #3	8.8 x 4.6 x 4.2m	Albatross Projects GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	014	Open area test site	10m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	015	Open area test site	3m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	042	Voltage- / current source test site	0-382VDC 0-270VAC 1x10kW / 3x5kW	Spitzenberger + Spies	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input type="checkbox"/>	n/a	Alternative test site	n/a	n/a	n/a

1.1.1.1 Test set up

According ANSI C63.10-2013



Used test equipment

<input checked="" type="checkbox"/>	Inv.-No.	Designation	Type	Manufacturer	S/N
<input checked="" type="checkbox"/>	001	Test receiver	ESS 5Hz - 1000 MHz	Rohde & Schwarz	833776/008
	002	Probe	ESH2-Z3	Rohde & Schwarz	
	003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007
	004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003
	005	LISN 3	NNB 4/32T	Rolf Heine HF-Technik	4/32T-96015
	006	LISN	NNBM 8125	Schwarzbeck	8125371
	007	Absorbing clamp	MDS 21	Schwarzbeck	942436
	025	Current clamp BCI	F-120-2	FCC	47
	026	Coupling device network	CDN 801-M3-25	FCC	92
	030	Coupling device network	CDN-S9	EMCE GmbH	
	031	Coupling device network	CDN-S9	EMCE GmbH	
	036	Coupling device network	CDN-M5-25	EMCE GmbH	
	037	Coupling device network	CDN-S1	EMCE GmbH	
<input checked="" type="checkbox"/>	042	AC-Source / Analyser / Norm impedance	EMV D5000/PAS	Spitzenberger + Spies	A274700/ 0 0501
	058	Test receiver	ESIB 40	Rohde & Schwarz	100200
	060	HF-coupling clamp	KEMA 801	Schaffner	20808
<input checked="" type="checkbox"/>	067	LISN 5	ESH2-Z5	Rohde & Schwarz	0872460/043
	068	LISN 4	ESH2-Z5	Rohde & Schwarz	0872460/042
	073	Absorbing clamp	MDS 21	Schwarzbeck	881757

All used test equipment are checked resp. calibrated periodically.

Test equipment was checked and complied to the requirements

Test / Measurement uncertainty

The measurement uncertainty in the test met the guideline of CISPR16-4-2 or better.

Measurement uncertainty of the terminal voltage with an extended coverage factor of $k=2$:

Frequency	Measurement uncertainty
9kHz – 150kHz	4.0dB
150kHz – 30MHz	3.6dB

1.1.1.2 Test

Regulation

47 CFR Part 15 Subpart C - 04/2016

9kHz - 30MHz

150kHz - 30MHz

Mains supply

Limits:

Section 15.207

__

Operation mode

EUT arrangement:

Tabletop

Floor standing

Power supply:

120V/60Hz

240V/60Hz

Rated voltage variation:

85%

115%

Port #	Designation	Remarks
#1	AC power line - Laptop	L1/N/PE
#2		
#3		

Continuous operation of the RFID reader, supplied with the internal battery and connected to the laptop USB-port.

RFID tag placed at approx. of the half reading distance. The Bluetooth module was configured as "Master" and active. During the test the remote station was removed from the laptop and the Bluetooth module was polling for a BT device. RFID and Bluetooth module were active at the same time.

Environmental conditions

Temperature [10 - 40°C]:

24°C

Relative humidity [10 - 90%]:

41%

Environmental conditions during the test:

kept

not kept

Test - / Measurement procedure

Measurements are made with a receiver according CISPR 16 guidelines. A pulse limiter and a 10dB attenuator at the receiver input is used to protect the receiver. The required frequency range is scanned in an automatically operation. When the EUT is arranged the frequency range is monitored. The setup of the equipment and the cables are manipulated within the range to produce the highest emission. Frequency steps of $<0.5 \times$ receiver bandwidth and peak / average detectors are used. If the conducted emission is closer than 20dB to the limits or exceeds, the receiver will retest the emission with quasipeak or average detector. The identified frequency and amplitude of the six highest conducted emissions relative to the limit lines are listed for each current-carrying conductor. If less than six emission frequencies are within the 20dB of the limit, the noise level of the measuring instrument at representative frequencies are reported.

The reported test results are calculated with the following formula:

$$\text{Result (dB}\mu\text{V)} = \text{Reading (dB}\mu\text{V)} + \text{ATF (dB)} + \text{CF (dB)}$$

ATF = Correction factor for the pulse limiter / 10dB attenuator

CF = Correction factor for the cable loss

Test result

Limits for continuous disturbances:

kept
 not kept

Remarks: n/a

Protocol scope

- Readings - continuous emanation
- Diagram - continuous emanation

EMCE GmbH Ing_buero fuer EMV_Pruefungen

Terminal voltage

23. Mar 16 16:05


EUT: ARE H9 LF
 Manuf: AEG ID GmbH
 Op Cond: Reading tag, half reading distance
 Operator: P. Hauser
 Test Spec: 47 CFR Part 15 Subpart C
 Comment: Test_ID PRN12_05
 AIN12_11, Phase L1 - laptop

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement: x QP / + AV
 Meas Time: 1 s
 Subranges: 50
 Acc Margin: 6dB

Transducer No.	Start	Stop	Name
3	2	1Hz	1000M Ca_#1006
20	9k	30M	Lim_#070



EMCE GmbH Ing_buero fuer EMV_Pruefungen Terminal voltage

23. Mar 16 16:05

EUT: ARE H9 LF
Manuf: AEG ID GmbH
Op Cond: Reading tag, half reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN12_05
AIN12_11, Phase L1 - laptop

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

no Results

EMCE GmbH Ing_buero fuer EMV_Pruefungen

Terminal voltage

23. Mar 16 16:16


EUT: ARE H9 LF
 Manuf: AEG ID GmbH
 Op Cond: Reading tag, half reading distance
 Operator: P. Hauser
 Test Spec: 47 CFR Part 15 Subpart C
 Comment: Test_ID PRN12_05
 AIN12_12, Phase N - laptop

Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN OFF 60dB

Final Measurement: x QP / + AV
 Meas Time: 1 s
 Subranges: 50
 Acc Margin: 6dB

Transducer No.	Start	Stop	Name
3	2 1Hz	1000M	Ca_#1006
20	9k	30M	Lim_#070



EMCE GmbH Ing_buero fuer EMV_Pruefungen Terminal voltage

23. Mar 16 16:16

EUT: ARE H9 LF
Manuf: AEG ID GmbH
Op Cond: Reading tag, half reading distance
Operator: P. Hauser
Test Spec: 47 CFR Part 15 Subpart C
Comment: Test_ID PRN12_05
AIN12_12, Phase N - laptop

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	30M	5k	10k	PK+AV	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

no Results

1.1.2 Radio disturbances according 47 CFR Part 15 Subpart C - 04/2016

- Full compliance
- Precompliance
- Test not requested*
- Test not carried out*

* _____


Test location

<input checked="" type="checkbox"/>	Inv.-No.	Designation	Type (LxWxH)	Manufacturer	Location
	588	Shielded room #2	8.3/5.8 x 5.5/2.9 x 3.4m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	584	Shielded room #3	3.6 x 3.6 x 2.5m	Siemens AG	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	678	Shielded room #4	4.0 x 4.0 x 3.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input checked="" type="checkbox"/>	062	Semi anechoic chamber #2	13.5 x 6.1 x 5.5m	EMC-Technik & Consulting GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	679	Full anechoic chamber #3	8.8 x 4.6 x 4.2m	Albatross Projects GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input checked="" type="checkbox"/>	014	Open area test site	10m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
<input checked="" type="checkbox"/>	015	Open area test site	3m	EMCE GmbH	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	042	Voltage- / current source test site	0-382VDC 0-270VAC 1x10kW / 3x5kW	Spitzenberger + Spies	EMCE GmbH Untere Wiesen 1 88483 Burgrieden
	n/a	Alternative test site	n/a	n/a	n/a

1.1.2.1 Test set up

According ANSI C63.10-2013







Used test equipment

<input type="checkbox"/>	Inv.-No.	Designation	Type	Manufacturer	S/N
<input checked="" type="checkbox"/>	001	Test receiver	ESS 5Hz - 1000 MHz	Rohde & Schwarz	833776/008
	003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007
	004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003
	005	LISN 3	NNB 4/32T	Rolf Heine HF-Technik	4/32T-96015
	006	LISN	NNBM 8125	Schwarzbeck	8125371
	007	Absorbing clamp	MDS 21	Schwarzbeck	942436
<input checked="" type="checkbox"/>	008	Antenna 9kHz – 30MHz	HFH2-Z2	Rohde & Schwarz	835776/0002
<input checked="" type="checkbox"/>	009	Antenna 30 – 300MHz	VHBA9123 / BBA9106	Schwarzbeck	435
<input checked="" type="checkbox"/>	010	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	108
<input checked="" type="checkbox"/>	011	Antenna 30 – 300MHz	VHBA9123 / BBA9106	Schwarzbeck	0408/94
<input checked="" type="checkbox"/>	012	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	166
	013	Antenna 9kHz – 30 MHz	Loop antenna 1.5m Ø	EMCE GmbH	
	025	Current clamp BCI	F-120-2	FCC	47
	041	HZ-10	Shielded coil	Rohde & Schwarz	849788/020
	042	AC-Source / Analyser / Norm impedance	EMV D5000/PAS	Spitzenberger + Spies	A274700/ 0 0501
<input checked="" type="checkbox"/>	058	Test receiver	ESIB 40	Rohde & Schwarz	100200
	059	Logper. Antenna	HL050	Rohde & Schwarz	100006
	060	HF coupling clamp	KEMA 801	Schaffner	20808
	063	Logper. Antenna	HL023 A2	Rohde & Schwarz	
	067	LISN 5	ESH2-Z5	Rohde & Schwarz	0872460/043
	068	LISN 4	ESH2-Z5	Rohde & Schwarz	0872460/042
	073	Absorbing clamp	MDS 21	Schwarzbeck	881757
	116	Vertical rod antenna	VAMP 9243	Schwarzbeck	9243-205

All used test equipment are checked resp. calibrated periodically.

Test equipment was checked and complied to the requirements

Test / Measurement uncertainty

The measurement uncertainty in the test met the guideline of CISPR16-4-2 or better.

Measurement uncertainty of the radiated emission with an extended coverage factor of $k=2$:

Frequency	Measurement uncertainty
9kHz – 30MHz	on request
30MHz – 300MHz	4.4dB
300MHz – 1GHz	3.4dB
1GHz – 18GHz	on request

1.1.2.2 Test – Radiated emission fundamental

Regulation

47 CFR Part 15 Subpart C - 04/2016

- | | |
|--|--|
| <input checked="" type="checkbox"/> 9kHz - 30MHz | <input type="checkbox"/> 150kHz – 1GHz |
| <input type="checkbox"/> 30MHz - 1000MHz | <input type="checkbox"/> 1 – 18GHz |

Limits: Section 15.209* Section 15.225*

* The limits for frequencies below 30MHz were corrected for a closer measuring distance by using an extrapolation factor of 40 dB/decade..

Test distance: 3m 5m
 10m 30m

Operation mode

EUT arrangement:	<input checked="" type="checkbox"/> Tabletop	<input type="checkbox"/> Floor standing
Power supply:	<input checked="" type="checkbox"/> 7.2VDC	<input type="checkbox"/> 240V/60Hz
Rated voltage variation:	<input type="checkbox"/> 85%	<input type="checkbox"/> 115%

Continuous operation of the RFID reader supplied by the internal battery and connected to the laptop USB-port.

The Bluetooth module was configured as “Master” and active. During the test the remote station was removed from the laptop and the Bluetooth module was polling for a BT device. RFID and Bluetooth module were active at the same time.

The emanation was maximized while placing the RFID tag inside the field or without tag.

Environmental conditions

Temperature [10 - 40°C]:	21°C
Relative humidity [10 - 90%]:	48%

Environmental conditions during the test: kept
 not kept

Test - / Measurement procedure

The test was performed at an antenna to EUT distance of 10m in the frequency range $\leq 30\text{MHz}$ and at 3m distance for frequencies $\geq 30\text{MHz}$. Measurements were made with a CISPR receiver with quasi-peak. The average detector is used in the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. For pulse modulated devices with a pulse repetition frequency of 20Hz or less, peak detector is used (15.35a Note). The frequency, the measured value, antenna information and the limit will be printed out.

The reported test results are calculated with the following formula:

$$\text{Field strength (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)}$$

AF = Correction factor for the antenna
CF = Correction factor for the cable loss

$$\text{Limit}_{10\text{m}} \text{ (dB}\mu\text{V/m)} = \text{Limit (dB}\mu\text{V/m)} + \text{LCF}_{10\text{m}} \text{ (dB)}$$

Limit_{10m} Limit calculated for 10m test distance
LCF_{10m} = Limit Correction factor for 10m test distance
LCF_{10m} for 30m antenna distance = 20dB
LCF_{10m} for 100m antenna distance = 40dB
LCF_{10m} for 300m antenna distance = 60dB

Test result

Frequency	Field strength	Limit _{10m}	Margin	Ant.-	Ant.-	Detector	Receiver	Supply voltage	Remarks
				Distance	Polar.	Peak /	6dB BW		
MHz	dB μ V/m	dB μ V/m	dB	m	H/V	QP / AV	kHz		
0.13422	59.2	85.0	25.8	10.0	V	AV	0.2	7.2VDC	Full charged battery

Limit_{10m} Limit calculated for 10m test distance

Limits for radiated disturbances:

kept
 not kept

Remarks: n/a

1.1.2.3 Test – Spurious emissions

Regulation

47 CFR Part 15 Subpart C - 04/2016

- | | |
|---|--|
| <input checked="" type="checkbox"/> 9kHz - 30MHz | <input type="checkbox"/> 150kHz – 1GHz |
| <input checked="" type="checkbox"/> 30MHz - 1000MHz | <input type="checkbox"/> 1 – 18GHz |

Limits: Section 15.209 __

Test distance: 3m 5m
 10m 30m

Operation mode

EUT arrangement:	<input checked="" type="checkbox"/> Tabletop	<input type="checkbox"/> Floor standing
Power supply:	<input checked="" type="checkbox"/> 7.2VDC	<input type="checkbox"/> 240V/60Hz
Rated voltage variation:	<input type="checkbox"/> 85%	<input type="checkbox"/> 115%

Continuous operation of the RFID reader supplied by the internal battery and connected to the laptop USB-port.

RFID tag placed at approx. of the half reading distance. The Bluetooth module was configured as "Master" and active. During the test the remote station was removed from the laptop and the Bluetooth module was polling for a BT device. RFID and Bluetooth module were active at the same time.

Environmental conditions

Temperature [10 - 40°C]: 21°C
Relative humidity [10 - 90%]: 48%

Environmental conditions during the test: kept
 not kept

Test - / Measurement procedure

The test was performed at an antenna to EUT distance of 10m in the frequency range ≤ 30 MHz and at 3m distance for frequencies ≥ 30 MHz. Measurements were made with a CISPR receiver with quasi-peak. The average detector is used in the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. For pulse modulated devices with a pulse repetition frequency of 20Hz or less, peak detector is used (15.35a Note). The frequency, the measured value, antenna information and the limit will be printed out.

The reported test results are calculated with the following formula:

$$\text{Field strength (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{AF (dB/m)} + \text{CF (dB)}$$

AF = Correction factor for the antenna
CF = Correction factor for the cable loss

$$\text{Limit}_{10\text{m}} \text{ (dB}\mu\text{V/m)} = \text{Limit (dB}\mu\text{V/m)} + \text{LCF}_{10\text{m}} \text{ (dB)}$$

Limit_{10m} Limit calculated for 10m test distance
LCF_{10m} = Limit Correction factor for 10m test distance
LCF_{10m} for 30m antenna distance = 20dB
LCF_{10m} for 100m antenna distance = 40dB
LCF_{10m} for 300m antenna distance = 60dB

Test result

Limits for intentional radiators: kept
 not kept

Level of the fundamental > unwanted emission: kept
 not kept

Remarks: Radio disturbances below the limit line with a margin > 10dB to the limit are generally not listed.

Protocol scope

- Readings - Antenna horizontal polarized.
- Diagram - Antenna horizontal polarized.
- Readings - Antenna vertical polarized.
- Diagram - Antenna vertical polarized.
- Bandwidth plot – Frequency response vs. supply voltage
- Precompliance measurement(s) – 3 axis.

Readings - Antenna vertical polarized, Antenna loop lowest height 1 m


Frequency	Field strength	Limit _{10m}	Margin	Ant.-	Ant.-	Detector	Receiver	Remarks
				Distance	Polar.	Peak /	6dB BW	
MHz	dB μ V/m	dB μ V/m	dB	m	H/V	QP / AV	kHz	
0.26844	42.0	79.0	37.0	10.0	V	AV	10	Increased ambient noise
0.40266	41.0	75.5	34.5	10.0	V	AV	10	Increased ambient noise
0.53688	31.1	53.0	21.9	10.0	V	QP	10	
0.67110	26.5	51.1	24.6	10.0	V	QP	10	
0.80532	26.5	49.5	23.0	10.0	V	QP	10	
0.93954	26.1	48.1	22.0	10.0	V	QP	10	
1.07376	25.8	47.0	21.2	10.0	V	QP	10	
1.20798	26.0	46.0	20.0	10.0	V	QP	10	
1.34220	25.8	45.0	19.2	10.0	V	QP	10	

Limit_{10m} Limit calculated for 10m test distance

Diagram - Antenna vertical polarized

Limits according FCC Rules CFR 47 Part 15 – Subpart C


☒ Section 15.209 – Corrected to 10m distance EUT-Antenna



EUT Information

EUT Name: ARE H9 – FullIso/A/U/C/B/H/Li
 Test_ID: / SN: PRN12_04
 Customer: AEG ID GmbH
 Operational condition: Field on, no tag in field
 Test specification: 47 CFR §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: V / Ant.Height: 1.0m
 Operator: P. Hauser
 File #: AIN18_06

Magnetic Field Strength dBµV with Sweep_SAC2




— 15_209_3m [..EMI radiated] — Preview Result 1V-PK+ [Preview Result 1V.Result:2]
 — MaxPeak-MaxHold [Preview Result 1V.Result:2]

Readings - Antenna horizontal polarized

Frequency	Readings	+ AF Antenna correction factor	+ KF Cable correction factor	Field strength	Limit	Margin	Antenna- Height	Antenna- Polarization	Turntable position
MHz	dB μ V	dB/m	dB	dB μ V/m	dB μ V/m	dB	m	hor./ver.	deg.
68.710	20.4	8.5	1.3	30.2	40.0	9.8	2.8	H	70
96.000	15.1	9.1	1.5	25.8	43.5	17.7	2.2	H	95
138.550	13.1	11.7	1.9	26.6	43.5	16.9	2.0	H	200
154.750	5.4	12.4	2.0	19.7	43.5	23.8	2.0	H	190
163.330	4.9	12.7	2.0	19.7	43.5	23.8	1.8	H	190
166.570	8.0	12.9	2.1	23.0	43.5	20.5	1.9	H	190
192.000	16.6	14.7	2.2	33.5	43.5	10.0	1.7	H	178
279.100	11.9	14.3	2.7	28.9	46.0	17.1	1.5	H	210
316.570	16.1	13.9	2.9	32.9	46.0	13.1	1.5	H	210
357.920	6.5	15.0	3.1	24.6	46.0	21.4	1.5	H	210

Diagram radio disturbances – Antenna horizontal polarized

Limits: Section 15.209* __




Readings - Antenna vertical polarized

Frequency	Readings	+ AF Antenna correction factor	+ KF Cable correction factor	Field strength	Limit	Margin	Antenna- Height	Antenna- Polarization	Turntable position
MHz	$\text{dB}\mu\text{V}$	dB/m	dB	$\text{dB}\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	dB	m	hor./ver.	deg.
68.710	21.6	8.5	1.3	31.4	40.0	8.6	1.0	V	60
96.000	10.6	9.1	1.5	21.3	43.5	22.2	1.0	V	60
192.000	4.2	14.7	2.2	21.1	43.5	22.4	1.0	V	185
279.400	6.5	14.3	2.7	23.5	46.0	22.5	1.0	V	190
316.570	11.3	13.9	2.9	28.1	46.0	17.9	1.0	V	190


Diagram radio disturbances – Antenna vertical polarized

Limits: Section 15.209 _



EUT Information

EUT Name: ARE H9 - FullIso/A/U/C/B/H/Li
 Test_ID: / SN: PRN12_04
 Customer: AEG ID GmbH
 Operational condition: Reading tag, half reading distance
 Test specification: FCC §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: H/V / Ant.Height: 1.0-4.0m
 Operator: P. Hauser
 File #: AIN19_21
 Comment #1: X-axis




— FCC Part 15 subpart C [.\EMI radiated]
— Preview Result 1V-PK+ [Preview Result 1V.Result:2]
— Preview Result 1H-PK+ [Preview Result 1H.Result:2]
◆ Final Result 1-QPK [Final Result 1.Result:1]

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
59.887776	24.5	120.000	212.0	H	346.0	8.7	15.5	40.0
192.000000	34.2	120.000	168.0	H	61.0	15.2	9.3	43.5
497.074148	28.9	120.000	122.0	V	194.0	18.4	17.1	46.0
630.096192	37.4	120.000	166.0	H	290.0	20.5	8.6	46.0
696.236473	37.6	120.000	124.0	H	258.0	21.8	8.4	46.0
948.132265	35.6	120.000	124.0	H	47.0	23.6	10.4	46.0

EUT Information

EUT Name: ARE H9 - FullIso/A/U/C/B/H/Li
 Test_ID: / SN: PRN12_04
 Customer: AEG ID GmbH
 Operational condition: Reading tag, half reading distance
 Test specification: FCC §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: H/V / Ant.Height: 1.0-4.0m
 Operator: P. Hauser
 File #: AIN19_22
 Comment #1: Y-axis




— FCC Part 15 subpart C [..EMI radiated]
— Preview Result 1V-PK+ [Preview Result 1V.Result:2]
◆ Preview Result 1H-PK+ [Preview Result 1H.Result:2]
◆ Final Result 1-QPK [Final Result 1.Result:1]

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
60.016032	28.0	120.000	118.0	V	286.0	8.7	12.0	40.0
138.549098	26.6	120.000	161.0	H	301.0	12.2	16.9	43.5
192.008016	33.7	120.000	161.0	H	261.0	15.2	9.8	43.5
632.765531	37.1	120.000	167.0	H	290.0	20.6	8.9	46.0
663.867735	34.1	120.000	167.0	H	320.0	21.1	11.9	46.0
936.172345	34.6	120.000	209.0	H	77.0	23.6	11.4	46.0

EUT Information

EUT Name: ARE H9 - Full Iso/A/U/C/B/H/Li
 Test_ID: / SN: PRN12_04
 Customer: AEG ID GmbH
 Operational condition: Reading tag, half reading distance
 Test specification: FCC §15.209
 Antenna information: Distance EUT-Ant.: 3.0m / Polarisation: H/V / Ant.Height: 1.0-4.0m
 Operator: P. Hauser
 File #: AIN19_23
 Comment #1: Z-axis



— FCC Part 15 subpart C [.\EMI radiated]
— Preview Result 1V-PK+ [Preview Result 1V.Result:2]
— Preview Result 1H-PK+ [Preview Result 1H.Result:2]
◆ Final Result 1-QPK [Final Result 1.Result:1]

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
68.713427	29.6	120.000	214.0	V	101.0	8.9	10.4	40.0
139.342685	26.6	120.000	116.0	H	323.0	12.3	16.9	43.5
191.991984	31.0	120.000	158.0	H	268.0	15.2	12.5	43.5
632.496994	38.6	120.000	165.0	H	297.0	20.6	7.4	46.0
663.014028	34.7	120.000	121.0	V	178.0	21.1	11.3	46.0
699.114229	37.1	120.000	123.0	H	258.0	21.8	8.9	46.0

1.1.2.4 Restricted bands of operation

Regulation

47 CFR Part 15 Subpart C - 04/2016

Requirement: Section 15.205(a)

Limit spurious emission: Section 15.209
 CISPR quasi peak detector ($f \leq 1\text{GHz}$)
 Average detector ($f > 1\text{GHz}$)

Operation mode

EUT arrangement: Tabletop Floor standing
Power supply: 7.2VDC 240V/60Hz
Rated voltage variation: 85% 115%

Continuous operation of the RFID reader supplied by the internal battery and connected to the laptop USB-port.

RFID tag placed at approx. of the half reading distance. The Bluetooth module was configured as "Master" and active. During the test the remote station was removed from the laptop and the Bluetooth module was polling for a BT device. RFID and Bluetooth module were active at the same time.

Environmental conditions

Temperature [10 - 40°C]: 24°C
Relative humidity [10 - 90%]: 40%

Environmental conditions during the test: kept
 not kept

Test - / Measurement procedure

Position the EUT in front of the measuring antenna. The analyzer is set to peak detector and the trace mode to max. hold. Set the analyzer to the identified fundamental and the sweep is continued until the trace is stabilized. The frequencies of the maximum of the envelope and the outermost points attenuated by 20dB to the maximum are noted.

Test result

Measured fundamental: 0.13422MHz
20dB-Emission Bandwidth: 0.688kHz

Fundamental out
of restricted bands: kept
 not kept


Limit spurious emission: kept
 not kept

Remarks: n/a

Protocol scope

Diagram – 20dB-Emission bandwidth.

Occupied bandwidth



PRN12_04, ARE H9 - FullIso/A/U/C/B/H/Li

Date: 22.MAR.2016 18:20:19

Occupied bandwidth BW = D1 - D2 = 0.349kHz - -0.339kHz=0.688kHz

1.1.2.5 Antenna requirement

Regulation

47 CFR Part 15 Subpart C - 04/2016

Requirement: Section 15.203
 Permanent attached
 Unique coupling to the intentional radiator

Test result

Requirement: kept
 not kept

Authorized antenna: Print antenna
 Internal antenna
 External antenna

Remarks: n/a

2 Summary

Regulation	Class / Test level	Result	Remark(s)
FCC Rules 47 CFR Part 15 Subpart C			
Terminal voltage 0.15-30MHz	Section 15.207	Limits kept	
Radiated emissions 0.009-30MHz	Section 15.209	Limits kept	
Radiated emissions 30-1000MHz	Section 15.209	Limits kept	
Occupied bandwidth	Section 15.215(c)	n. r.	
Restricted bands	Section 15.205(a)	Requirement kept	
Antenna requirement	Section 15.203	Requirement kept	

n. r. – not relevant

Burgrieden, 2016-07-08

Report generated by:



Acceptance inspector – Peter Hauser