



FCC PART 15.247  
TEST REPORT

For

**SHENZHEN TENDA TECHNOLOGY CO.,LTD.**

Tenda Industrial Park, No. 34-1, Shilong Rd., Shiyan Town, Bao'an District, Shenzhen, P.R.China

**FCC ID: V7TA3**

<b>Report Type:</b> Original Report	<b>Product Type:</b> 150Mbps Wireless Range Extender
<b>Test Engineer:</b> Ares Liu	<i>Ares Liu</i>
<b>Report Number:</b> R1DG120710003-00A	
<b>Report Date:</b> 2012-07-25	
<b>Reviewed By:</b> Ivan Cao EMC Engineer	<i>Ivan Cao</i>
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

    OBJECTIVE .....4

    RELATED SUBMITTAL(S)/GRANT(S).....4

    TEST METHODOLOGY .....4

    TEST FACILITY .....5

**SYSTEM TEST CONFIGURATION.....6**

    DESCRIPTION OF TEST CONFIGURATION .....6

    EUT EXERCISE SOFTWARE .....6

    EQUIPMENT MODIFICATIONS .....6

    SUPPORT EQUIPMENT.....7

    EXTERNAL CABLE.....7

    PRINTER .....7

    BLOCK DIAGRAM OF TEST SETUP .....8

**SUMMARY OF TEST RESULTS .....9**

**FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....10**

    APPLICABLE STANDARD .....10

**FCC §15.203 - ANTENNA REQUIREMENT.....11**

    APPLICABLE STANDARD .....11

    ANTENNA CONNECTOR CONSTRUCTION .....11

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....12**

    APPLICABLE STANDARD .....12

    MEASUREMENT UNCERTAINTY .....12

    EUT SETUP .....12

    EMI TEST RECEIVER SETUP.....13

    TEST PROCEDURE .....13

    TEST EQUIPMENT LIST AND DETAILS.....13

    TEST RESULTS SUMMARY .....13

    TEST DATA .....13

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....16**

    APPLICABLE STANDARD .....16

    MEASUREMENT UNCERTAINTY.....16

    EUT SETUP .....16

    EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....17

    TEST PROCEDURE .....17

    CORRECTED AMPLITUDE & MARGIN CALCULATION .....17

    TEST EQUIPMENT LIST AND DETAILS.....18

    TEST RESULTS SUMMARY .....18

    TEST DATA .....18

**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....33**

    APPLICABLE STANDARD .....33

    TEST PROCEDURE .....33

    TEST EQUIPMENT LIST AND DETAILS.....33

    TEST DATA .....33

**FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....41**

APPLICABLE STANDARD .....41  
TEST PROCEDURE .....41  
TEST EQUIPMENT LIST AND DETAILS.....41  
TEST DATA .....41

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....49**  
APPLICABLE STANDARD .....49  
TEST PROCEDURE .....49  
TEST EQUIPMENT LIST AND DETAILS.....49  
TEST DATA .....49

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....54**  
APPLICABLE STANDARD .....54  
TEST PROCEDURE .....54  
TEST EQUIPMENT LIST AND DETAILS.....54  
TEST DATA .....54

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *SHENZHEN TENDA TECHNOLOGY CO.,LTD.*'s product, model number: A3 (FCC ID: V7TA3) or ("EUT") in this report is a 150Mbps Wireless Range Extender, which was measured approximately:28.0 cm (L) x9.5cm (W) x2.0cm (H), rated input voltage: DC 9V from adapter.

#### Adapter information:

Model: TEA09U-09060

Input: 100-240V, 50/60Hz,0.3A

Output: 9V, 0.6A

#### Frequency Range:

802.11b/g/n20: 2412-2462MHz

802.11n40: 2422-2452MHz

*\* All measurement and test data in this report was gathered from production sample serial number:120710003 (Assigned by BAACL,Dongguan). The EUT was received on 2012-07-11.*

### Objective

This report is prepared on behalf of *SHENZHEN TENDA TECHNOLOGY CO.,LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: V7TA30.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is  $\pm 0.96$  dB, the uncertainty of any radiation on emissions measurement is  $\pm 4.0$  dB

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b and 802.11g, 802.11n20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

EUT for 802.11b, 802.11g and 802.11 n20 modes were tested with Channel 1, 6 and 11.

For 802.11n40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### EUT Exercise Software

The test was performed under “*Duck 1.1.9*” which was provided by the manufacturer.

### Equipment Modifications

No modification was made to the EUT tested.


**Support Equipment**

Manufacturer	Description	Model	Serial Number
Dell	Notebook	PP11L	N/A
DELL	Keyboard	SK-8115	CN-ODJ313-716716-05A-0DS0
HP	Printer	C3941A	JPTVO13237
SAST	Modem	AEM-2100	090200213

**External Cable**

Cable Description	Length (m)	From Port	To
Shielded Detachable Printer Cable	1.2	Parallel Port of PC	Printer
Shielded Detachable Serial Cable	1.2	Serial Port of PC	Modem
RJ45 cable	1.5	RJ45 port of PC	EUT
Shielded Detachable Keyboard Cable	1.5	Keyboard Port of PC	Keyboard

### Block Diagram of Test Setup





**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

**FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculated Formulary:**

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412	5	3.16	15.59	36.22	20	0.0228	1.0
802.11g	2412	5	3.16	12.39	17.34	20	0.0109	1.0
802.11n ht20	2462	5	3.16	11.93	15.60	20	0.0098	1.0
802.11n ht40	2452	5	3.16	12.76	18.88	20	0.0119	1.0

**Result:** The device meet FCC MPE at 20cm distance

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has a dipole antennas permanently attached to the EUT, which complied with 15.203, the maximum gain is 5.0dBi, please refer to the internal photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard


FCC§15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Dongguan) is  $\pm 2.4$  dB ( $k=2$ , 95% level of confidence).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	830245/006	2011-10-08	2012-10-07
Rohde & Schwarz	LISN	ESH3-Z5	843331/015	2011-10-08	2012-10-07
Rohde & Schwarz	LISN	ESH3-Z5	100113	2011-10-08	2012-10-07

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**8.14 dB at 0.510 MHz** in the **Neutral** conducted mode

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Ares Liu on 2012-07-20.*


*Test Mode: Transmitting*

120 V, 60 Hz, Line:



Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK /QP/Ave.)
0.490	44.23	0.42	56.29	12.06	QP
0.490	32.52	0.42	46.29	13.77	Ave.
0.730	41.75	0.44	56.00	14.25	QP
0.730	30.91	0.44	46.00	15.09	Ave.
0.870	40.73	0.45	56.00	15.27	QP
1.280	40.47	0.46	56.00	15.53	QP
1.790	39.58	0.47	56.00	16.42	QP
1.275	28.63	0.46	46.00	17.37	Ave.
2.360	38.62	0.48	56.00	17.38	QP
1.800	27.07	0.47	46.00	18.93	Ave.
0.865	26.60	0.45	46.00	19.40	Ave.
2.360	24.89	0.48	46.00	21.11	Ave.

**120V, 60 Hz, Neutral:**



Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/QP/Ave.)
0.510	37.86	0.42	46.00	8.14	Ave.
0.510	47.12	0.42	56.00	8.88	QP
0.705	34.44	0.44	46.00	11.56	Ave.
1.670	34.41	0.47	46.00	11.59	Ave.
0.700	44.29	0.44	56.00	11.71	QP
1.170	34.13	0.46	46.00	11.87	Ave.
2.185	32.89	0.48	46.00	13.11	Ave.
2.535	32.35	0.49	46.00	13.65	Ave.
1.665	42.15	0.47	56.00	13.85	QP
1.170	41.99	0.46	56.00	14.01	QP
2.185	41.38	0.48	56.00	14.62	QP
2.535	38.53	0.49	56.00	17.47	QP

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Dongguan) is 4.0 dB(k=2, 95% level of confidence) .

### EUT Setup

Below 1GHz:



Above 1GHz:





The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

### EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

### Test Procedure

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	1166.5950.03	2011-10-08	2012-10-07
Sunol Sciences	Hybrid Antennas	JB3	A060611-1	2011-09-06	2012-09-05
HP	Pre-amplifier	8447E	2434A02181	2011-10-08	2012-10-07
R&S	Spectrum Analyzer	FSEM	1079 8500	2011-10-09	2012-10-08
Dayang	Horn Antenna	OMCDH10180	10279001B	2010-07-30	2015-07-29
Mini-Circuits	Wideband Amplifier	ZVA-183-S+	96901149	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**1.56 dB at 3217.31 MHz in the Vertical polarization (802.11n20 mode)**

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Ares Liu on 2012-07-18.*

Mode: Transmitting

1) 30MHz-25GHz

802.11b Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel:2412(MHz)									
2412	50.76	AV	H	31.11	3.93	0.00	85.79	N/A	N/A
2412	55.41	PK	H	31.11	3.93	0.00	90.44	N/A	N/A
2412	69.6	AV	V	31.11	3.93	0.00	104.63	N/A	N/A
2412	74.38	PK	V	31.11	3.93	0.00	109.41	N/A	N/A
4824	40.87	AV	V	33.21	4.73	27.19	51.62	54.00	2.38 *
2390	14.32	AV	V	30.98	3.84	0.00	49.15	54.00	4.85
2390	31.24	PK	V	30.98	3.84	0.00	66.07	74.00	7.93
613.2	33.67	QP	V	19.42	3.03	22.28	33.85	46.00	12.15
3217.31	35.09	AV	V	31.25	4.98	27.42	43.90	54.00	10.10
7236	36.49	PK	V	38.72	6.56	26.58	55.20	74.00	18.80
9648	14.07	AV	V	38.60	8.70	26.43	34.94	54.00	19.06
3217.31	50.37	PK	V	31.25	4.98	27.42	59.18	74.00	14.82
7236	14.56	AV	V	38.72	6.56	26.58	33.27	54.00	20.73
4824	42.32	PK	V	33.21	4.73	27.19	53.07	74.00	20.93
9648	30.28	PK	V	38.60	8.70	26.43	51.15	74.00	22.85
Middle Channel: 2437(MHz)									
2437	50.74	AV	H	31.25	3.98	0.00	85.97	N/A	N/A
2437	55.45	PK	H	31.25	3.98	0.00	90.68	N/A	N/A
2437	69.66	AV	V	31.25	3.98	0.00	104.89	N/A	N/A
2437	74.47	PK	V	31.25	3.98	0.00	109.70	N/A	N/A
4874	40.1	AV	V	33.32	4.76	27.03	51.16	54.00	2.84 *
9748	14.21	AV	V	38.80	8.60	26.53	35.08	54.00	18.92
403.21	29.76	QP	V	16.30	2.44	21.78	26.71	46.00	19.29
7311	15.72	AV	V	38.86	6.70	26.65	34.63	54.00	19.37
4874	42.85	PK	V	33.32	4.76	27.03	53.91	74.00	20.09
7311	34.18	PK	V	38.86	6.70	26.65	53.09	74.00	20.91
9748	31.51	PK	V	38.80	8.60	26.53	52.38	74.00	21.62

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
High Channel: 2462(MHz)									
2462	50.26	AV	H	31.39	3.93	0.00	85.58	N/A	N/A
2462	55.14	PK	H	31.39	3.93	0.00	90.46	N/A	N/A
2462	69.5	AV	V	31.39	3.93	0.00	104.82	N/A	N/A
2462	73.94	PK	V	31.39	3.93	0.00	109.26	N/A	N/A
4924	40.05	AV	V	33.43	4.70	27.17	51.02	54.00	2.98 *
2483.5	14.21	AV	V	31.51	3.80	0.00	49.51	54.00	4.49
2483.5	30.89	PK	V	31.51	3.80	0.00	66.19	74.00	7.81
9848	14.59	AV	V	39.00	8.49	26.63	35.45	54.00	18.55
7386	15.95	AV	V	38.99	6.84	26.73	35.06	54.00	18.94
241.24	31.72	PK	V	12.23	1.86	21.48	24.32	46	21.68
4924	41.24	PK	V	33.43	4.70	27.17	52.21	74.00	21.79
7386	32.92	PK	V	38.99	6.84	26.73	52.03	74.00	21.97
9848	29.59	PK	V	39.00	8.49	26.63	50.45	74.00	23.55

\* Within measurement uncertainty.

802.11g Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2412(MHz)									
2412	48.63	AV	H	31.11	3.93	0.00	83.66	N/A	N/A
2412	53.21	PK	H	31.11	3.93	0.00	88.24	N/A	N/A
2412	67.6	AV	V	31.11	3.93	0.00	102.63	N/A	N/A
2412	72.46	PK	V	31.11	3.93	0.00	107.49	N/A	N/A
3217.31	43.21	AV	V	31.25	4.98	27.42	52.02	54.00	1.98 *
4824	39.28	AV	V	33.21	4.73	27.19	50.03	54.00	3.97 *
2390	14.11	AV	V	30.98	3.84	0.00	48.94	54.00	5.06
2390	30.22	PK	V	30.98	3.84	0.00	65.05	74.00	8.95
613.2	32.55	QP	V	19.42	3.03	22.28	32.73	46.00	13.27
9648	14.09	PK	V	38.60	8.70	26.43	34.96	54.00	19.04
7236	15.76	AV	V	38.72	6.56	26.58	34.47	54.00	19.53
3217.31	44.21	PK	V	31.25	4.98	27.42	53.02	74.00	20.98
7236	32.43	PK	V	38.72	6.56	26.58	51.14	74.00	22.86
4824	40.27	PK	V	33.21	4.73	27.19	51.02	74.00	22.98
9648	29.35	PK	V	38.60	8.70	26.43	50.22	74.00	23.78
Middle Channel: 2437(MHz)									
2437	48.69	AV	H	31.25	3.98	0.00	83.92	N/A	N/A
2437	53.3	PK	H	31.25	3.98	0.00	88.53	N/A	N/A
2437	67.34	AV	V	31.25	3.98	0.00	102.57	N/A	N/A
2437	72.33	PK	V	31.25	3.98	0.00	107.56	N/A	N/A
4874	38.24	AV	V	33.32	4.76	27.03	49.30	54.00	4.70
9748	14.11	AV	V	38.80	8.60	26.53	34.98	54.00	19.02
7311	14.58	AV	V	38.86	6.70	26.65	33.49	54.00	20.51
403.21	27.65	QP	V	16.30	2.44	21.78	24.60	46.00	21.40
7311	32.39	PK	V	38.86	6.70	26.65	51.30	74.00	22.70
4874	40.12	PK	V	33.32	4.76	27.03	51.18	74.00	22.82
9748	29.43	PK	V	38.80	8.60	26.53	50.30	74.00	23.70

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
High Channel: 2462(MHz)									
2462	48.24	AV	H	31.39	3.93	0.00	83.56	N/A	N/A
2462	52.83	PK	H	31.39	3.93	0.00	88.15	N/A	N/A
2462	67.39	AV	V	31.39	3.93	0.00	102.71	N/A	N/A
2462	71.36	PK	V	31.39	3.93	0.00	106.68	N/A	N/A
2483.5	14.08	AV	V	31.51	3.80	0.00	49.38	54.00	4.62
4924	38.19	AV	V	33.43	4.70	27.17	49.16	54.00	4.84
2483.5	29.62	PK	V	31.51	3.80	0.00	64.92	74.00	9.08
9848	14.52	AV	V	39.00	8.49	26.63	35.38	54.00	18.62
7386	14.53	AV	V	38.99	6.84	26.73	33.64	54.00	20.36
7386	31.79	PK	V	38.99	6.84	26.73	50.90	74.00	23.10
4924	39.89	PK	V	33.43	4.70	27.17	50.86	74.00	23.14
9848	29.41	PK	V	39.00	8.49	26.63	50.27	74.00	23.73
241.24	28.79	QP	V	12.23	1.86	21.48	21.39	46	24.61

\* Within measurement uncertainty.

802.11n20 Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel:2412(MHz)									
2412	49.41	AV	H	31.11	3.93	0.00	84.44	N/A	N/A
2412	53.89	PK	H	31.11	3.93	0.00	88.92	N/A	N/A
2412	68.21	AV	V	31.11	3.93	0.00	103.24	N/A	N/A
2412	72.83	PK	V	31.11	3.93	0.00	107.86	N/A	N/A
3217.31	43.63	AV	V	31.25	4.98	27.42	52.44	54.00	1.56 *
4824	38.66	AV	V	33.21	4.73	27.19	49.41	54.00	4.59
2390	14.54	AV	V	30.98	3.84	0.00	49.37	54.00	4.63
2390	28.72	PK	V	30.98	3.84	0.00	63.55	74.00	10.45
613.2	32.67	QP	V	19.42	3.03	22.28	32.85	46.00	13.15
9648	14.21	AV	V	38.60	8.70	26.43	35.08	54.00	18.92
7236	15.01	AV	V	38.72	6.56	26.58	33.72	54.00	20.28
3217.31	44.25	PK	V	31.25	4.98	27.42	53.06	74.00	20.94
7236	32.74	PK	V	38.72	6.56	26.58	51.45	74.00	22.55
9648	29.89	PK	V	38.60	8.70	26.43	50.76	74.00	23.24
4824	39.02	PK	V	33.21	4.73	27.19	49.77	74.00	24.23
Middle Channel: 2437(MHz)									
2437	49.23	AV	H	31.25	3.98	0.00	84.46	N/A	N/A
2437	53.72	PK	H	31.25	3.98	0.00	88.95	N/A	N/A
2437	67.6	AV	V	31.25	3.98	0.00	102.83	N/A	N/A
2437	72.69	PK	V	31.25	3.98	0.00	107.92	N/A	N/A
4874	38.51	AV	V	33.32	4.76	27.03	49.57	54.00	4.43
9748	13.99	AV	V	38.80	8.60	26.53	34.86	54.00	19.14
403.21	29.36	QP	V	16.30	2.44	21.78	26.31	46.00	19.69
7311	14.32	AV	V	38.86	6.70	26.65	33.23	54.00	20.77
7311	32.42	PK	V	38.86	6.70	26.65	51.33	74.00	22.67
4874	40.05	PK	V	33.32	4.76	27.03	51.11	74.00	22.89
9748	29.38	PK	V	38.80	8.60	26.53	50.25	74.00	23.75

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
High Channel: 2462(MHz)									
2462	48.53	AV	H	31.39	3.93	0.00	83.85	N/A	N/A
2462	53.3	PK	H	31.39	3.93	0.00	88.62	N/A	N/A
2462	67.81	AV	V	31.39	3.93	0.00	103.13	N/A	N/A
2462	72.35	PK	V	31.39	3.93	0.00	107.67	N/A	N/A
2483.5	14.08	AV	V	31.51	3.80	0.00	49.38	54.00	4.62
2483.5	29.51	PK	V	31.51	3.80	0.00	64.81	74.00	9.19
4924	38.61	AV	V	33.43	4.70	27.17	49.58	54.00	4.42
4924	39.96	PK	V	33.43	4.70	27.17	50.93	74.00	23.07
7386	15.02	AV	V	38.99	6.84	26.73	34.13	54.00	19.87
7386	32.19	PK	V	38.99	6.84	26.73	51.30	74.00	22.70
9848	14.79	AV	V	39.00	8.49	26.63	35.65	54.00	18.35
9848	29.68	PK	V	39.00	8.49	26.63	50.54	74.00	23.46
241.24	31.28	PK	V	12.23	1.86	21.48	23.88	46	22.12

\* Within measurement uncertainty.



802.11n40 Mode:


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel:2422(MHz)									
2422	46.19	AV	H	31.16	3.95	0.00	81.30	N/A	N/A
2422	50.89	PK	H	31.16	3.95	0.00	86.00	N/A	N/A
2422	65.26	AV	V	31.16	3.95	0.00	100.37	N/A	N/A
2422	70.07	PK	V	31.16	3.95	0.00	105.18	N/A	N/A
3217.31	40.91	AV	V	31.25	4.98	27.42	49.72	54.00	4.28
2390	14.23	AV	V	30.98	3.84	0.00	49.06	54.00	4.94
2390	14.23	AV	V	30.98	3.84	0.00	49.06	54.00	4.94
4844	34.85	AV	V	33.26	4.78	27.04	45.85	54.00	8.15
613.2	32.21	QP	V	19.42	3.03	22.28	32.39	46.00	13.61
9688	14.27	AV	V	38.68	8.66	26.47	35.14	54.00	18.86
3217.31	42.33	PK	V	31.25	4.98	27.42	51.14	74.00	22.86
9688	29.37	PK	V	38.68	8.66	26.47	50.24	74.00	23.76
7266	30.83	PK	V	38.78	6.62	26.61	49.62	74.00	24.38
4844	34.85	PK	V	33.26	4.78	27.04	45.85	74.00	28.15
7266	15.16	AV	V	38.78	6.62	26.61	33.95	74.00	40.05
Middle Channel: 2437(MHz)									
2437	46.21	AV	H	31.25	3.98	0.00	81.44	N/A	N/A
2437	50.81	PK	H	31.25	3.98	0.00	86.04	N/A	N/A
2437	65.04	AV	V	31.25	3.98	0.00	100.27	N/A	N/A
2437	69.85	PK	V	31.25	3.98	0.00	105.08	N/A	N/A
4874	40.11	AV	V	33.32	4.76	27.03	51.17	54.00	2.83*
9748	14.27	AV	V	38.80	8.60	26.53	35.14	54.00	18.86
403.21	29.52	QP	V	16.30	2.44	21.78	26.47	46.00	19.53
7311	15.07	AV	V	38.86	6.70	26.65	33.98	54.00	20.02
4874	42.37	PK	V	33.32	4.76	27.03	53.43	74.00	20.57
7311	33.16	PK	V	38.86	6.70	26.65	52.07	74.00	21.93
9748	29.62	PK	V	38.80	8.60	26.53	50.49	74.00	23.51

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	(FCC 15.247)	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
High Channel: 2452(MHz)									
2452	45.61	AV	H	31.33	4.00	0.00	80.94	N/A	N/A
2452	50.66	PK	H	31.33	4.00	0.00	85.99	N/A	N/A
2452	65.41	AV	V	31.33	4.00	0.00	100.74	N/A	N/A
2452	70.46	PK	V	31.33	4.00	0.00	105.79	N/A	N/A
2483.5	14.29	AV	V	31.51	3.80	0.00	49.59	54.00	4.41
2483.5	30.24	PK	V	31.51	3.80	0.00	65.54	74.00	8.46
9808	14.13	AV	V	38.92	8.53	26.59	34.99	54.00	19.01
7356	14.02	AV	V	38.94	6.79	26.70	33.05	54.00	20.95
9808	29.59	PK	V	38.92	8.53	26.59	50.45	74.00	23.55
241.24	29.15	QP	V	12.23	1.86	21.48	21.75	46	24.25
7356	29.64	PK	V	38.94	6.79	26.70	48.67	74.00	25.33
4904	36.09	PK	V	33.39	4.72	27.08	47.12	74.00	26.88
4904	14.02	AV	V	33.39	4.72	27.08	25.05	54.00	28.95

\* Within measurement uncertainty.


### Conducted Spurious Emissions at Antenna Port

#### 802.11b Low Channel




Date: 18.JUL.2012 11:01:45

#### 802.11b Middle Channel




Date: 18.JUL.2012 11:10:21


### 802.11b High Channel




### 802.11g Low Channel




### 802.11g Middle Channel




### 802.11g High Channel




### 802.11n20 Low Channel




### 802.11n20 Middle Channel




### Chain 0: 802.11n20 High Channel




### 802.11n40 Low Channel



### 802.11n40 Middle Channel



### 802.11n40 High Channel






## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-05-27	2013-05-26

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0kPa


*The testing was performed by Ares Liu from 2012-07-17 to 2012-07-18.*

**Test Result:** Pass.

Please refer to the following tables and plots.


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (KHz)
802.11b mode			
Low	2412	8.24	>500
Middle	2437	8.24	>500
High	2462	8.24	>500
802.11g mode			
Low	2412	15.84	>500
Middle	2437	15.92	>500
High	2462	15.76	>500
802.11n20 mode			
Low	2412	17.36	>500
Middle	2437	17.28	>500
High	2462	17.12	>500
802.11n40 mode			
Low	2422	36.96	>500
Middle	2437	36.96	>500
High	2452	36.96	>500

### 802.11b Low Channel




Date: 17.JUL.2012 15:20:45

### 802.11b Middle Channel




Date: 17.JUL.2012 15:24:12

### 802.11b High Channel




Date: 17.JUL.2012 15:26:47

### 802.11g Low Channel




Date: 17.JUL.2012 15:30:52

### 802.11g Middle Channel




Date: 17.JUL.2012 15:35:08

### 802.11g High Channel




Date: 17.JUL.2012 15:41:56

### 802.11n20 Low Channel




Date: 18.JUL.2012 12:33:11

### 802.11n20 Middle Channel




Date: 18.JUL.2012 12:37:14

### 802.11n20 High Channel




Date: 18.JUL.2012 12:39:37

### 802.11n40 Low Channel




Date: 18.JUL.2012 12:43:16

### 802.11n40 Middle Channel



Date: 18.JUL.2012 12:46:24

### 802.11n40 High Channel



Date: 18.JUL.2012 12:48:59




## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-05-27	2013-05-26

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

*The testing was performed by Ares Liu from 2012-07-17 to 2012-07-18.*

*Test Mode: Transmitting*


Channel	Frequency (MHz)	Reading Power (dBm)	Limit (dBm)	Result
802.11b				
Low	2412 MHz	15.59	30	pass
Middle	2437 MHz	15.07	30	pass
High	2462 MHz	15.26	30	pass
802.11g				
Low	2412 MHz	12.39	30	pass
Middle	2437 MHz	11.91	30	pass
High	2462 MHz	11.81	30	pass
802.11n20				
Low	2412 MHz	11.82	30	pass
Middle	2437 MHz	11.81	30	pass
High	2462 MHz	11.93	30	pass
802.11n40				
Low	2422 MHz	11.53	30	pass
Middle	2437 MHz	12.7	30	pass
High	2452 MHz	12.76	30	pass

Note:

The antenna gain is 5.0 dBi.


Please refer to the following plots

### 802.11b RF Output Power, Low Channel




Date: 17.JUL.2012 15:21:14

### 802.11b RF Output Power, Middle Channel




Date: 17.JUL.2012 15:24:38

### 802.11b RF Output Power, High Channel




Date: 17.JUL.2012 15:27:21

### 802.11g RF Output Power, Low Channel




Date: 17.JUL.2012 15:31:48

### 802.11g RF Output Power, Middle Channel




Date: 17.JUL.2012 15:35:53

### 802.11g RF Output Power, High Channel




Date: 18.JUL.2012 12:27:25

### 802.11n20 RF Output Power, Low Channel




Date: 18.JUL.2012 12:34:29

### 802.11n20 RF Output Power, Middle Channel




Date: 18.JUL.2012 12:38:00

### 802.11n20 RF Output Power, High Channel




Date: 18.JUL.2012 12:40:26

### 802.11n40 RF Output Power, Low Channel




Date: 18.JUL.2012 12:43:58

### 802.11n40 RF Output Power, Middle Channel



Date: 18.JUL.2012 12:47:31

### 802.11n40 RF Output Power, High Channel



Date: 18.JUL.2012 12:49:24



## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-05-27	2013-05-26

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Ares Liu from 2012-07-17 to 2012-07-18.*

#### **Test Result: Compliance**


Please refer to following plots.

**802.11b: Band Edge, Left Side**




Date: 17.JUL.2012 15:22:16

**802.11b: Band Edge, Right Side**




Date: 17.JUL.2012 15:29:01

### 802.11g: Band Edge, Left Side




Date: 17.JUL.2012 15:33:10

### 802.11g: Band Edge, Right Side




Date: 18.JUL.2012 12:31:14

### 802.11n20: Band Edge, Left Side




Date: 18.JUL.2012 12:35:54

### 802.11n20: Band Edge, Right Side




Date: 18.JUL.2012 12:41:37

### 802.11n40: Band Edge, Left Side



Date: 18.JUL.2012 12:45:13

### 802.11n40: Band Edge, Right Side



Date: 18.JUL.2012 12:50:30

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. According to KDB 558074 D01 DTS Meas Guidance v01, set the RBW = 100 kHz, VBW  $\geq$  300 kHz, set the span to 5-30 % greater than the EBW.
4. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
5. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(3\text{ kHz}/100\text{ kHz} = -15.2\text{ dB})$ .

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-05-27	2013-05-26

\* **Statement of Traceability:** Bay Area Compliance Lab Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

*The testing was performed by Ares Liu from 2012-07-17 to 2012-07-18.*

*Test Mode: Transmitting*


**Test Result:** Pass

Channel	Reading Level (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11b				
Low	4.77	-10.43	8	pass
Middle	3.81	-11.39	8	pass
High	4.41	-10.79	8	pass
802.11g				
Low	-6.2	-21.4	8	pass
Middle	-6.34	-21.54	8	pass
High	-6.88	-22.08	8	pass
802.11n20				
Low	-6.51	-21.71	8	pass
Middle	-6.47	-21.67	8	pass
High	-6.56	-21.76	8	pass
802.11n40				
Low	-9.98	-25.18	8	pass
Middle	-8.81	-24.01	8	pass
High	-8.84	-24.04	8	pass

**Note:** the antenna gain is 5.0 dBi.


Please refer to the following plots

### Power Spectral Density, 802.11b Low Channel



Date: 17.JUL.2012 15:21:36


### Power Spectral Density, 802.11b Middle Channel



Date: 17.JUL.2012 15:25:02




### Power Spectral Density, 802.11b High Channel




Date: 17.JUL.2012 15:27:41

### Power Spectral Density, 802.11g Low Channel




Date: 17.JUL.2012 15:32:21

### Power Spectral Density, 802.11g Middle Channel




Date: 17.JUL.2012 15:36:26

### Power Spectral Density, 802.11g High Channel




Date: 18.JUL.2012 12:28:18

### Power Spectral Density, 802.11n20 Low Channel




Date: 18.JUL.2012 12:34:57

### Power Spectral Density, 802.11n20 Middle Channel




Date: 18.JUL.2012 12:38:24

### Power Spectral Density, 802.11n20 High Channel




Date: 18.JUL.2012 12:40:55

### Power Spectral Density, 802.11n40 Low Channel




Date: 18.JUL.2012 12:44:22

**Power Spectral Density, 802.11n40 Middle Channel**



Date: 18.JUL.2012 12:47:53

**Power Spectral Density, 802.11n40 High Channel**



Date: 18.JUL.2012 12:49:49

**\*\*\*\*\* END OF REPORT \*\*\*\*\***