



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: V7TA301

Project No. : 1404C109
Equipment : Wireless N300 Universal Range Extender
Model : A301
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD
**Address : 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan
Road, Nanshan District, Shenzhen, China. 518052**

According: : FCC Guidelines for Human Exposure IEEE C95.1

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



Neutron Engineering Inc.

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	Tenda	NA	Dipole	N/A	2.25	TX/RX
1	Tenda	NA	Dipole	N/A	2.25	TX/RX



Neutron Engineering Inc.

TEST RESULTS

EUT:	Wireless N300 Universal Range Extender	Model Name :	A301
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX B MODE /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.25	1.6788	21.3	134.8963	0.04507652	1	Complies
2.25	1.6788	20.8	120.2264	0.04017449	1	Complies
2.25	1.6788	20.6	114.8154	0.03836634	1	Complies

EUT:	Wireless N300 Universal Range Extender	Model Name :	A301
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX G MODE /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.25	1.6788	21.2	131.8257	0.04405045	1	Complies
2.25	1.6788	22.2	165.9587	0.05545623	1	Complies
2.25	1.6788	21.3	134.8963	0.04507652	1	Complies



Neutron Engineering Inc.

EUT:	Wireless N300 Universal Range Extender	Model Name :	A301
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-20M MODE_ Total /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.25	1.6788	24.46	279.2544	0.09331477	1	Complies
2.25	1.6788	25.36	343.5579	0.11480224	1	Complies
2.25	1.6788	24.36	272.8978	0.09119066	1	Complies

EUT:	Wireless N300 Universal Range Extender	Model Name :	A301
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-40M MODE_ Total /CH03, CH06, CH09		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.25	1.6788	22.81	190.9853	2.25	1	Complies
2.25	1.6788	22.76	188.7991	2.25	1	Complies
2.25	1.6788	22.66	184.5015	2.25	1	Complies

The calculated distance is 20 cm