

FCC RF EXPOSURE REPORT

FCC ID: V7TA9

Project No. : 1606C194
Equipment : Wireless N300 Universal Range Extender
Model : A9
Applicant : SHENZHEN TENDA TECHNOLOGY CO.,LTD.
**Address : 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan
Road, Nanshan District, Shenzhen, China.
518052**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Tenda	N/A	Dipole	N/A	3
2	Tenda	N/A	Dipole	N/A	3

Note:

- (1) The EUT incorporates a MIMO function. Physically, the EUT provides two completed two transmitters and two receivers (2T2R). All transmit signals are completely uncorrelated, then, Directional gain= G_{ANT} , that is Directional gain=3.

Operating Mode TX Mode	1TX	2TX
	802.11b	V (ANT 1 or ANT 2)
802.11g	V (ANT 1 or ANT 2)	-
802.11n(20MHz)	-	V (ANT 1 + ANT 2)
802.11n(40MHz)	-	V (ANT 1 + ANT 2)

TEST RESULTS

EUT :	Wireless N300 Universal Range Extender	Model Name :	A9
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX B MODE_Ant 2 /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	15.71	37.2392	0.01479	1	Complies
3	1.9953	17.24	52.9663	0.02104	1	Complies
3	1.9953	18.66	73.4514	0.02917	1	Complies

EUT :	Wireless N300 Universal Range Extender	Model Name :	A9
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX G MODE_Ant 2 /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	25.87	386.3670	0.15344	1	Complies
3	1.9953	25.82	381.9443	0.15169	1	Complies
3	1.9953	25.69	370.6807	0.14721	1	Complies

EUT :	Wireless N300 Universal Range Extender	Model Name :	A9
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-20M MODE_ Total /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	28.12	648.6344	0.25760	1	Complies
3	1.9953	29.27	845.2788	0.33570	1	Complies
3	1.9953	27.53	566.2393	0.22488	1	Complies

EUT :	Wireless N300 Universal Range Extender	Model Name :	A9
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N-40M MODE_ Total /CH03, CH06, CH09		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	26.76	474.2420	0.18834	1	Complies
3	1.9953	27.37	545.7579	0.21675	1	Complies
3	1.9953	22.88	194.0886	0.07708	1	Complies

Note: the calculated distance is 20 cm.