



**中认信通**  
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



# TEST REPORT

**Applicant:** SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Address: 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

**FCC ID:** V7TCP3P

**Product Name:** Security Pan/Tilt Camera 3MP

**Standard(s):** 47 CFR Part 15, Subpart C(15.247)  
ANSI C63.10-2013

**KDB 558074 D01 15.247 Meas Guidance v05r02**

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number:** CR230741646-00A

**Date Of Issue:** 2023/8/15

**Reviewed By:** Julie Tan

*Julie Tan*

Title: RF Engineer

**Approved By:** Sun Zhong

*Sun Zhong*

Title: Manager

**Test Laboratory:** China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China  
Tel: +86-769-82016888

## Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

## Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

# CONTENTS

<b>TEST FACILITY .....</b>	<b>2</b>
<b>DECLARATIONS.....</b>	<b>2</b>
<b>DOCUMENT REVISION HISTORY .....</b>	<b>5</b>
<b>1. GENERAL INFORMATION .....</b>	<b>6</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>6</b>
<b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>	<b>8</b>
1.2.1 EUT Operation Condition: .....	8
1.2.2 Support Equipment List and Details .....	8
1.2.3 Support Cable List and Details .....	8
1.2.4 Block Diagram of Test Setup.....	9
<b>1.3 MEASUREMENT UNCERTAINTY .....</b>	<b>10</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>11</b>
<b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>12</b>
<b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>12</b>
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup .....	13
3.1.4 Test Procedure .....	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
<b>3.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>15</b>
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....	16
3.2.4 Test Procedure .....	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
<b>3.3 MINIMUM 6 DB BANDWIDTH: .....</b>	<b>17</b>
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure .....	17
<b>3.4 99% OCCUPIED BANDWIDTH: .....</b>	<b>18</b>
3.4.1 EUT Setup.....	18
3.4.2 Test Procedure .....	18
<b>3.5 MAXIMUM CONDUCTED OUTPUT POWER: .....</b>	<b>19</b>
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure .....	19
<b>3.6 MAXIMUM POWER SPECTRAL DENSITY: .....</b>	<b>20</b>
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure .....	20
<b>3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: .....</b>	<b>21</b>

3.7.1 Applicable Standard.....	21
3.7.2 EUT Setup.....	21
3.7.3 Test Procedure .....	21
<b>3.8 DUTY CYCLE:.....</b>	<b>22</b>
3.8.1 EUT Setup.....	22
3.8.2 Test Procedure .....	22
<b>3.9 ANTENNA REQUIREMENT.....</b>	<b>22</b>
3.9.1 Applicable Standard.....	22
3.9.2 Judgment.....	22
<b>4. Test DATA AND RESULTS .....</b>	<b>23</b>
<b>4.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>23</b>
<b>4.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>26</b>
<b>4.3 MINIMUM 6 dB EMISSION BANDWIDTH:.....</b>	<b>37</b>
<b>4.4 99% OCCUPIED BANDWIDTH: .....</b>	<b>44</b>
<b>4.5 MAXIMUM CONDUCTED OUTPUT POWER: .....</b>	<b>51</b>
<b>4.6 MAXIMUM POWER SPECTRAL DENSITY: .....</b>	<b>52</b>
<b>4.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: .....</b>	<b>59</b>
<b>4.8 DUTY CYCLE:.....</b>	<b>66</b>
<b>5. RF EXPOSURE EVALUATION- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>69</b>
<b>5.1 APPLICABLE STANDARD.....</b>	<b>69</b>
<b>5.2 CALCULATION FORMULA:.....</b>	<b>69</b>
<b>5.3 CALCULATED DATA: .....</b>	<b>69</b>

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230741646-00A	Original Report	2023/8/15

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Security Pan/Tilt Camera 3MP
<b>EUT Model:</b>	CP3 Pro
<b>Multiple Model:</b>	RP3 Pro
<b>Operation Frequency:</b>	2412-2462 MHz(802.11b/g/n ht20/ax he20) 2422-2452 MHz(802.11n ht40/ax he40)
<b>Maximum Average Output Power (Conducted):</b>	17.47dBm
<b>Modulation Type:</b>	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n/ax: OFDM-BPSK, QPSK, 16QAM, 64QAM
<b>Rated Input Voltage:</b>	DC 9.0V from Adapter
<b>Serial Number:</b>	28HG-1 (for AC line conducted emissions test) 28HG-2(for RF Conducted and Radiated Spurious Emissions test)
<b>EUT Received Date:</b>	2023/7/19
<b>EUT Received Status:</b>	Good
Note: The Multiple model is electrically identical with test model, please refer to the declaration letter for more detail, which was provided by manufacturer.	

#### Operation Frequency Detail: For 802.11b/g/n/ ht20/ax he20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2412	
Middle		2437	
Highest		2462	

#### For 802.11n ht40/ax he40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2422	
Middle		2437	
Highest		2452	

**Antenna Information Detail ▲:**

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
SHENZHEN TENDA TECHNOLOGY CO.,LTD	PCB	50	2.4~2.5GHz	1.94 dBi
The Method of §15.203 Compliance: <input checked="" type="checkbox"/> Antenna must be permanently attached to the unit. <input type="checkbox"/> Antenna must use a unique type of connector to attach to the EUT. <input type="checkbox"/> Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

**Accessory Information:**

Accessory Description	Manufacturer	Model	Information
Adapter	SHENZHEN HEWEISHUN NETWORK TECHNOLOGY CO.,LTD.	BN073-A09009U	Input:100-240V 50/60Hz 0.4A Output:9V 1A

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

<b>EUT Operation Mode:</b>	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
<b>Equipment Modifications:</b>	No
<b>EUT Exercise Software:</b>	accessMtool_3.1.0.6

The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:

Mode	Channel	Frequency (MHz)	Data Rate	Power Level Setting
802.11b	Lowest	2412	1Mbps	18
	Middle	2437	1Mbps	18
	Highest	2462	1Mbps	18
802.11g	Lowest	2412	6Mbps	18
	Middle	2437	6Mbps	18
	Highest	2462	6Mbps	18
802.11n ht20	Lowest	2412	MCS0	16
	Middle	2437	MCS0	16
	Highest	2462	MCS0	16
802.11n ht40	Lowest	2422	MCS0	16
	Middle	2437	MCS0	16
	Highest	2452	MCS0	16
802.11ax he20	Lowest	2412	MCS0	18
	Middle	2437	MCS0	18
	Highest	2462	MCS0	18
802.11ax he40	Lowest	2422	MCS0	16
	Middle	2437	MCS0	16
	Highest	2452	MCS0	16

Note:

The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

The device 802.11ax mode supports full RU only.

### 1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
SanDisk	TF Card	16 GB	1183DRECV11N


### 1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	2.9	Adapter	EUT




### 1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

## 2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1310 & §2.1091	RF Exposure Evaluation	Compliant

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions


### 3.2.1 Applicable Standard

FCC §15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 3.2.2 EUT Setup

**Below 1GHz:**



**Above 1GHz:**



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result




### 3.3 Minimum 6 dB Bandwidth:

#### 3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.3.2 EUT Setup




#### 3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 3.4 99% Occupied Bandwidth:

#### 3.4.1 EUT Setup



#### 3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


### 3.5 Maximum Conducted Output Power:

#### 3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### 3.5.2 EUT Setup



#### 3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


### 3.6 Maximum Power Spectral Density:

#### 3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### 3.6.2 EUT Setup



#### 3.6.3 Test Procedure

**Duty cycle  $\geq 98\%$**

According to ANSI C63.10-2013 Section 11.10.3

**Duty cycle  $< 98\%$ , duty cycle variations are less than  $\pm 2\%$**

According to ANSI C63.10-2013 Section 11.10.5

**Duty cycle  $< 98\%$ , duty cycle variations exceed  $\pm 2\%$**

According to ANSI C63.10-2013 Section 11.10.7


### 3.7 100 kHz Bandwidth of Frequency Band Edge:

#### 3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 3.7.2 EUT Setup



#### 3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 3.8 Duty Cycle:

#### 3.8.1 EUT Setup



#### 3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 3.9 Antenna Requirement

#### 3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 3.9.2 Judgment

**Compliant.** Please refer to the Antenna Information detail in Section 1.

## 4. Test DATA AND RESULTS

### 4.1 AC Line Conducted Emissions

Serial Number:	28HG-1	Test Date:	2023/08/09
Test Site:	CE	Test Mode:	Transmitting (802.11b Middle channel was tested)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	26.1	Relative Humidity: (%)	57	ATM Pressure: (kPa)	100.6

### Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2023/03/31	2024/03/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/08/06	2024/08/05
Audix	Test Software	E3	190306 (V9)	N/A	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data:

Test Mode: Transmitting  
 Port: Line  
 Note:

Date: 2023-08-09




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	17.47	9.61	27.08	55.95	28.87	Average
2	0.151	32.47	9.61	42.08	65.95	23.87	QP
3	0.448	20.78	9.61	30.39	46.91	16.52	Average
4	0.448	27.32	9.61	36.93	56.91	19.98	QP
5	1.230	18.11	9.62	27.73	46.00	18.27	Average
6	1.230	25.26	9.62	34.88	56.00	21.12	QP
7	3.563	16.36	9.65	26.01	46.00	19.99	Average
8	3.563	25.56	9.65	35.21	56.00	20.79	QP
9	12.168	11.22	9.67	20.89	50.00	29.11	Average
10	12.168	21.41	9.67	31.08	60.00	28.92	QP
11	29.900	16.47	9.82	26.29	50.00	23.71	Average
12	29.900	27.48	9.82	37.30	60.00	22.70	QP



Test Mode: Transmitting  
 Port: neutral  
 Note:

Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	16.38	9.61	25.99	55.95	29.96	Average
2	0.151	32.69	9.61	42.30	65.95	23.65	QP
3	0.468	16.34	9.61	25.95	46.56	20.61	Average
4	0.468	21.45	9.61	31.06	56.56	25.50	QP
5	1.216	21.26	9.62	30.88	46.00	15.12	Average
6	1.216	29.13	9.62	38.75	56.00	17.25	QP
7	1.753	14.92	9.63	24.55	46.00	21.45	Average
8	1.753	24.79	9.63	34.42	56.00	21.58	QP
9	3.821	12.63	9.65	22.28	46.00	23.72	Average
10	3.821	22.97	9.65	32.62	56.00	23.38	QP
11	29.847	15.81	9.82	25.63	50.00	24.37	Average
12	29.847	24.67	9.82	34.49	60.00	25.51	QP

## 4.2 Radiation Spurious Emissions

Serial Number:	28HG-2	Test Date:	2023/8/10
Test Site:	966-2, 966-1	Test Mode:	Transmitting
Tester:	Vic Du, Tao Zhu	Test Result:	Pass

### Environmental Conditions:

Temperature: (°C)	26.2~26.8	Relative Humidity: (%)	43~61	ATM Pressure: (kPa)	99.9
----------------------	-----------	---------------------------	-------	------------------------	------

### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2022/9/16	2023/9/15
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data:


Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.10 Figure 8, the worst orientation was photographed and it's data was recorded.

1) 30MHz-1GHz(802.11b Low channel was tested)


Test Mode: Transmitting  
 Polarization: horizontal  
 Note:

Date: 2023-08-10



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.979	30.17	-5.90	24.27	40.00	15.73	Peak
2	99.528	47.14	-14.43	32.71	43.50	10.79	Peak
3	142.824	38.73	-11.91	26.82	43.50	16.68	Peak
4	200.688	37.42	-12.23	25.19	43.50	18.31	Peak
5	383.932	34.38	-9.03	25.35	46.00	20.65	Peak
6	919.287	27.88	-0.69	27.19	46.00	18.81	Peak

Test Mode: Transmitting  
 Polarization: vertical  
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	34.057	40.70	-6.71	33.99	40.00	6.01	QP
2	43.812	39.64	-13.56	26.08	40.00	13.92	Peak
3	80.081	45.83	-17.46	28.37	40.00	11.63	Peak
4	84.702	43.96	-17.20	26.76	40.00	13.24	Peak
5	98.487	40.06	-14.66	25.40	43.50	18.10	Peak
6	145.861	32.58	-11.97	20.61	43.50	22.89	Peak

2) 1-25GHz:  
802.11b Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2412 MHz							
2412.000	69.94	PK	H	31.53	101.47	N/A	N/A
2412.000	66.82	AV	H	31.53	98.35	N/A	N/A
2412.000	71.81	PK	V	31.53	103.34	N/A	N/A
2412.000	68.76	AV	V	31.53	100.29	N/A	N/A
2390.000	27.10	PK	V	31.46	58.56	74.00	15.44
2390.000	14.42	AV	V	31.46	45.88	54.00	8.12
4824.000	42.67	PK	V	10.94	53.61	74.00	20.39
4824.000	37.95	AV	V	10.94	48.89	54.00	5.11
7236.000	34.36	PK	V	14.44	48.80	74.00	25.20
7236.000	21.55	AV	V	14.44	35.99	54.00	18.01
Middle Channel: 2437 MHz							
2437.000	69.52	PK	H	31.60	101.12	N/A	N/A
2437.000	66.20	AV	H	31.60	97.80	N/A	N/A
2437.000	71.55	PK	V	31.60	103.15	N/A	N/A
2437.000	68.47	AV	V	31.60	100.07	N/A	N/A
4874.000	43.25	PK	V	11.05	54.30	74.00	19.70
4874.000	38.14	AV	V	11.05	49.19	54.00	4.81
7311.000	34.63	PK	V	14.80	49.43	74.00	24.57
7311.000	21.40	AV	V	14.80	36.20	54.00	17.80
High Channel: 2462MHz							
2462.000	69.12	PK	H	31.63	100.75	N/A	N/A
2462.000	66.83	AV	H	31.63	98.46	N/A	N/A
2462.000	71.59	PK	V	31.63	103.22	N/A	N/A
2462.000	68.47	AV	V	31.63	100.10	N/A	N/A
2483.500	27.42	PK	V	31.64	59.06	74.00	14.94
2483.500	14.23	AV	V	31.64	45.87	54.00	8.13
4924.000	43.27	PK	V	11.18	54.45	74.00	19.55
4924.000	38.62	AV	V	11.18	49.80	54.00	<b>4.20</b>
7386.000	34.25	PK	V	14.89	49.14	74.00	24.86
7386.000	21.41	AV	V	14.89	36.30	54.00	17.70

**802.11g Mode:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2412 MHz							
2412.000	71.88	PK	H	31.53	103.41	N/A	N/A
2412.000	61.78	AV	H	31.53	93.31	N/A	N/A
2412.000	73.91	PK	V	31.53	105.44	N/A	N/A
2412.000	63.12	AV	V	31.53	94.65	N/A	N/A
2390.000	32.46	PK	V	31.46	63.92	74.00	10.09
2390.000	14.12	AV	V	31.46	45.58	54.00	8.42
4824.000	35.28	PK	V	10.94	46.22	74.00	27.78
4824.000	22.56	AV	V	10.94	33.50	54.00	20.50
7236.000	34.36	PK	V	14.44	48.80	74.00	25.20
7236.000	21.34	AV	V	14.44	35.78	54.00	18.22
Middle Channel: 2437 MHz							
2437.000	72.33	PK	H	31.60	103.93	N/A	N/A
2437.000	62.28	AV	H	31.60	93.88	N/A	N/A
2437.000	74.48	PK	V	31.60	106.08	N/A	N/A
2437.000	64.55	AV	V	31.60	96.15	N/A	N/A
4874.000	35.63	PK	V	11.05	46.68	74.00	27.32
4874.000	22.86	AV	V	11.05	33.91	54.00	20.09
7311.000	34.28	PK	V	14.80	49.08	74.00	24.92
7311.000	21.48	AV	V	14.80	36.28	54.00	17.72
High Channel: 2462MHz							
2462.000	72.32	PK	H	31.63	103.95	N/A	N/A
2462.000	62.48	AV	H	31.63	94.11	N/A	N/A
2462.000	74.87	PK	V	31.63	106.50	N/A	N/A
2462.000	64.33	AV	V	31.63	95.96	N/A	N/A
2483.500	32.04	PK	V	31.64	63.68	74.00	10.32
2483.500	15.34	AV	V	31.64	46.98	54.00	7.02
4924.000	35.68	PK	V	11.18	46.86	74.00	27.14
4924.000	22.63	AV	V	11.18	33.81	54.00	20.19
7386.000	34.42	PK	V	14.89	49.31	74.00	24.69
7386.000	21.40	AV	V	14.89	36.29	54.00	17.71

**802.11n ht20 Mode:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2412 MHz							
2412.000	72.36	PK	H	31.53	103.89	N/A	N/A
2412.000	58.66	AV	H	31.53	90.19	N/A	N/A
2412.000	75.23	PK	V	31.53	106.76	N/A	N/A
2412.000	61.37	AV	V	31.53	92.90	N/A	N/A
2390.000	41.33	PK	V	31.46	72.79	74.00	1.21
2390.000	16.31	AV	V	31.46	47.77	54.00	6.23
4824.000	37.66	PK	V	10.94	48.60	74.00	25.40
4824.000	24.70	AV	V	10.94	35.64	54.00	18.36
7236.000	36.67	PK	V	14.44	51.11	74.00	22.90
7236.000	23.57	AV	V	14.44	38.01	54.00	15.99
Middle Channel: 2437 MHz							
2437.000	73.58	PK	H	31.60	105.18	N/A	N/A
2437.000	59.64	AV	H	31.60	91.24	N/A	N/A
2437.000	75.36	PK	V	31.60	106.96	N/A	N/A
2437.000	61.47	AV	V	31.60	93.07	N/A	N/A
4874.000	37.85	PK	V	11.05	48.90	74.00	25.10
4874.000	24.74	AV	V	11.05	35.79	54.00	18.21
7311.000	36.58	PK	V	14.80	51.38	74.00	22.62
7311.000	23.36	AV	V	14.80	38.16	54.00	15.84
High Channel: 2462MHz							
2462.000	71.69	PK	H	31.63	103.32	N/A	N/A
2462.000	57.82	AV	H	31.63	89.45	N/A	N/A
2462.000	74.45	PK	V	31.63	106.08	N/A	N/A
2462.000	60.65	AV	V	31.63	92.28	N/A	N/A
2483.500	41.12	PK	V	31.64	72.76	74.00	1.24
2483.500	16.49	AV	V	31.64	48.13	54.00	5.87
4924.000	37.15	PK	V	11.18	48.33	74.00	25.67
4924.000	24.69	AV	V	11.18	35.87	54.00	18.13
7386.000	36.41	PK	V	14.89	51.30	74.00	22.70
7386.000	23.41	AV	V	14.89	38.30	54.00	15.70

**802.11n ht40 Mode:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2422 MHz							
2422.000	70.36	PK	H	31.56	101.92	N/A	N/A
2422.000	56.47	AV	H	31.56	88.03	N/A	N/A
2422.000	72.30	PK	V	31.56	103.86	N/A	N/A
2422.000	58.71	AV	V	31.56	90.27	N/A	N/A
2390.000	41.52	PK	V	31.46	72.98	74.00	1.02
2390.000	20.88	AV	V	31.46	52.34	54.00	1.66
4844.000	34.87	PK	V	10.96	45.83	74.00	28.17
4844.000	21.42	AV	V	10.96	32.38	54.00	21.62
7266.000	35.66	PK	V	14.63	50.29	74.00	23.71
7266.000	22.30	AV	V	14.63	36.93	54.00	17.07
Middle Channel: 2437 MHz							
2437.000	68.72	PK	H	31.60	100.32	N/A	N/A
2437.000	55.40	AV	H	31.60	87.00	N/A	N/A
2437.000	71.47	PK	V	31.60	103.07	N/A	N/A
2437.000	57.32	AV	V	31.60	88.92	N/A	N/A
4874.000	34.75	PK	V	11.05	45.80	74.00	28.20
4874.000	21.46	AV	V	11.05	32.51	54.00	21.49
7311.000	35.89	PK	V	14.80	50.69	74.00	23.31
7311.000	22.58	AV	V	14.80	37.38	54.00	16.62
High Channel: 2452MHz							
2452.000	69.50	PK	H	31.63	101.13	N/A	N/A
2452.000	55.74	AV	H	31.63	87.37	N/A	N/A
2452.000	71.41	PK	V	31.63	103.04	N/A	N/A
2452.000	57.52	AV	V	31.63	89.15	N/A	N/A
2483.500	40.82	PK	V	31.64	72.46	74.00	1.54
2483.500	20.55	AV	V	31.64	52.19	54.00	1.81
4904.000	34.52	PK	V	11.14	45.66	74.00	28.34
4904.000	21.63	AV	V	11.14	32.77	54.00	21.23
7356.000	35.63	PK	V	14.80	50.43	74.00	23.57
7356.000	22.47	AV	V	14.80	37.27	54.00	16.73



**802.11ax he20 Mode:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2412 MHz							
2412.000	74.45	PK	H	31.53	105.98	N/A	N/A
2412.000	60.58	AV	H	31.53	92.11	N/A	N/A
2412.000	76.43	PK	V	31.53	107.96	N/A	N/A
2412.000	62.25	AV	V	31.53	93.78	N/A	N/A
2390.000	30.76	PK	V	31.46	62.22	74.00	11.78
2390.000	15.32	AV	V	31.46	46.78	54.00	7.22
4824.000	34.58	PK	V	10.94	45.52	74.00	28.48
4824.000	21.74	AV	V	10.94	32.68	54.00	21.32
7236.000	34.69	PK	V	14.44	49.13	74.00	24.87
7236.000	21.68	AV	V	14.44	36.12	54.00	17.88
Middle Channel: 2437 MHz							
2437.000	73.72	PK	H	31.60	105.32	N/A	N/A
2437.000	60.53	AV	H	31.60	92.13	N/A	N/A
2437.000	75.38	PK	V	31.60	106.98	N/A	N/A
2437.000	61.65	AV	V	31.60	93.25	N/A	N/A
4874.000	34.39	PK	V	11.05	45.44	74.00	28.56
4874.000	21.36	AV	V	11.05	32.41	54.00	21.59
7311.000	34.17	PK	V	14.80	48.97	74.00	25.03
7311.000	21.45	AV	V	14.80	36.25	54.00	17.75
High Channel: 2462MHz							
2462.000	74.42	PK	H	31.63	106.05	N/A	N/A
2462.000	60.16	AV	H	31.63	91.79	N/A	N/A
2462.000	76.09	PK	V	31.63	107.72	N/A	N/A
2462.000	61.84	AV	V	31.63	93.47	N/A	N/A
2483.500	28.64	PK	V	31.64	60.28	74.00	13.72
2483.500	15.34	AV	V	31.64	46.98	54.00	7.02
4924.000	35.68	PK	V	11.18	46.86	74.00	27.14
4924.000	22.56	AV	V	11.18	33.74	54.00	20.26
7386.000	35.79	PK	V	14.89	50.68	74.00	23.32
7386.000	22.21	AV	V	14.89	37.10	54.00	16.90


**802.11 ax he40 Mode:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 2422 MHz							
2422.000	68.46	PK	H	31.56	100.02	N/A	N/A
2422.000	54.08	AV	H	31.56	85.64	N/A	N/A
2422.000	69.93	PK	V	31.56	101.49	N/A	N/A
2422.000	55.59	AV	V	31.56	87.15	N/A	N/A
2390.000	38.21	PK	V	31.46	69.67	74.00	4.33
2390.000	15.44	AV	V	31.46	46.90	54.00	7.10
4844.000	35.69	PK	V	10.96	46.65	74.00	27.35
4844.000	21.86	AV	V	10.96	32.82	54.00	21.18
7266.000	35.43	PK	V	14.63	50.06	74.00	23.94
7266.000	21.82	AV	V	14.63	36.45	54.00	17.55
Middle Channel: 2437 MHz							
2437.000	68.52	PK	H	31.60	100.12	N/A	N/A
2437.000	54.33	AV	H	31.60	85.93	N/A	N/A
2437.000	69.30	PK	V	31.60	100.90	N/A	N/A
2437.000	55.21	AV	V	31.60	86.81	N/A	N/A
4874.000	35.66	PK	V	11.05	46.71	74.00	27.29
4874.000	22.36	AV	V	11.05	33.41	54.00	20.59
7311.000	35.78	PK	V	14.80	50.58	74.00	23.42
7311.000	22.47	AV	V	14.80	37.27	54.00	16.73
High Channel: 2452 MHz							
2452.000	69.55	PK	H	31.63	101.18	N/A	N/A
2452.000	55.42	AV	H	31.63	87.05	N/A	N/A
2452.000	70.70	PK	V	31.63	102.33	N/A	N/A
2452.000	56.37	AV	V	31.63	88.00	N/A	N/A
2483.500	38.48	PK	V	31.64	70.12	74.00	3.88
2483.500	16.00	AV	V	31.64	47.64	54.00	6.36
4904.000	35.69	PK	V	11.14	46.83	74.00	27.17
4904.000	22.30	AV	V	11.14	33.44	54.00	20.56
7356.000	35.63	PK	V	14.80	50.43	74.00	23.57
7356.000	22.42	AV	V	14.80	37.22	54.00	16.78

**Worst Test plots(802.11b High channel was tested):**



**Vertical**



**4.3 Minimum 6 dB Emission Bandwidth:**

Serial Number:	28HG-2	Test Date:	2023/8/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.8	Relative Humidity: (%)	42	ATM Pressure: (kPa)	99.9

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200445	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Frequency (MHz)	Minimum 6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	7.66	0.5
	2437	7.20	0.5
	2462	7.15	0.5
802.11g	2412	15.59	0.5
	2437	15.36	0.5
	2462	15.62	0.5
802.11n ht20	2412	15.88	0.5
	2437	15.33	0.5
	2462	15.33	0.5
802.11n ht40	2422	35.79	0.5
	2437	35.84	0.5
	2452	35.59	0.5
802.11n ax20	2412	18.39	0.5
	2437	18.56	0.5
	2462	18.21	0.5
802.11n ax40	2422	37.22	0.5
	2437	36.62	0.5
	2452	36.62	0.5


### 6dB Emission Bandwidth

802.11b  
Lowest Channel




Date: 14.AUG.2023 10:25:16

802.11b  
Middle Channel



Date: 14.AUG.2023 10:27:27


802.11b  
Highest Channel



Date: 14.AUG.2023 10:29:14


### 6dB Emission Bandwidth

802.11g  
Lowest Channel




Date: 14.AUG.2023 10:35:03

802.11g  
Middle Channel



Date: 14.AUG.2023 10:41:05


802.11g  
Highest Channel



Date: 14.AUG.2023 10:44:16


### 6dB Emission Bandwidth

802.11n ht20  
Lowest Channel




Date: 14.AUG.2023 10:49:51

802.11n ht20  
Middle Channel



Date: 14.AUG.2023 10:52:27

802.11n ht20  
Highest Channel




Date: 14.AUG.2023 10:55:54




### 6dB Emission Bandwidth

802.11n ht40  
Lowest Channel




Date: 14.AUG.2023 10:58:40

802.11n ht40  
Middle Channel



Date: 14.AUG.2023 11:02:58


802.11n ht40  
Highest Channel



Date: 14.AUG.2023 11:08:54


### 6dB Emission Bandwidth

802.11ax he20  
Lowest Channel




Date: 14.AUG.2023 11:12:55

802.11ax he20  
Middle Channel



Date: 14.AUG.2023 11:15:40


802.11ax he20  
Highest Channel



Date: 14.AUG.2023 11:18:22


### 6dB Emission Bandwidth

802.11ax he40  
Lowest Channel




Date: 14.AUG.2023 11:21:42

802.11ax he40  
Middle Channel



Date: 14.AUG.2023 11:23:50

802.11ax he40  
Highest Channel



Date: 14.AUG.2023 11:25:57

**4.4 99% Occupied Bandwidth:**

Serial Number:	28HG-2	Test Date:	2023/8/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	N/A

**Environmental Conditions:**

Temperature: (°C)	25.8	Relative Humidity: (%)	52	ATM Pressure: (kPa)	99.7
----------------------	------	------------------------------	----	------------------------	------

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200445	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	10.88
	Middle	2437	10.64
	Highest	2462	10.64
802.11g	Lowest	2412	17.12
	Middle	2437	17.28
	Highest	2462	17.28
802.11n ht20	Lowest	2412	18.40
	Middle	2437	18.40
	Highest	2462	18.40
802.11n ht40	Lowest	2422	37.12
	Middle	2437	37.12
	Highest	2452	37.12
802.11n ax20	Lowest	2412	19.28
	Middle	2437	19.28
	Highest	2462	19.44
802.11n ax40	Lowest	2422	38.08
	Middle	2437	38.08
	Highest	2452	38.08


### 99% Occupied Bandwidth

802.11b  
Lowest Channel




Date: 11.AUG.2023 14:52:32

802.11b  
Middle Channel



Date: 11.AUG.2023 14:58:45


802.11b  
Highest Channel



Date: 11.AUG.2023 14:59:58


### 99% Occupied Bandwidth

802.11g  
Lowest Channel




Date: 11.AUG.2023 16:09:36

802.11g  
Middle Channel



Date: 11.AUG.2023 16:13:40


802.11g  
Highest Channel



Date: 11.AUG.2023 16:15:36


### 99% Occupied Bandwidth

802.11n ht20  
Lowest Channel




Date: 11.AUG.2023 16:22:46

802.11n ht20  
Middle Channel



Date: 11.AUG.2023 16:25:13


802.11n ht20  
Highest Channel



Date: 11.AUG.2023 16:27:52


### 99% Occupied Bandwidth

802.11n ht40  
Lowest Channel




Date: 11.AUG.2023 16:30:46

802.11n ht40  
Middle Channel



Date: 11.AUG.2023 16:33:22

802.11n ht40  
Highest Channel




Date: 11.AUG.2023 16:35:25




### 99% Occupied Bandwidth

802.11ax he20  
Lowest Channel




Date: 11.AUG.2023 16:42:18

802.11ax he20  
Middle Channel



Date: 11.AUG.2023 16:45:05


802.11ax he20  
Highest Channel



Date: 11.AUG.2023 16:48:22


### 99% Occupied Bandwidth

802.11ax he40  
Lowest Channel




Date: 11.AUG.2023 16:52:10

802.11ax he40  
Middle Channel



Date: 11.AUG.2023 16:56:02

802.11ax he40  
Highest Channel



Date: 11.AUG.2023 17:00:20

**4.5 Maximum Conducted Output Power:**

Serial Number:	28HG-2	Test Date:	2023/8/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	25.8	Relative Humidity: (%)	52	ATM Pressure: (kPa)	99.7
----------------------	------	------------------------------	----	------------------------	------

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY54080014	2022/11/22	2023/11/21

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Frequency (MHz)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	<b>17.47</b>	30
	2437	16.54	30
	2462	16.41	30
802.11g	2412	17.39	30
	2437	16.32	30
	2462	16.23	30
802.11n ht20	2412	15.24	30
	2437	14.22	30
	2462	14.04	30
802.11n ht40	2422	15.12	30
	2437	14.23	30
	2452	14.01	30
802.11n ax20	2412	17.04	30
	2437	16.21	30
	2462	16.01	30
802.11n ax40	2422	15.08	30
	2437	14.18	30
	2452	14.02	30

**4.6 Maximum power spectral density:**

Serial Number:	28HG-2	Test Date:	2023/8/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	26.4	Relative Humidity: (%)	59	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200445	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Frequency (MHz)	Reading (dBm/10kHz)	Duty Factor (dB)	Maximum Power Spectral Density (dBm/10kHz)	Limit (dBm/3kHz)
802.11b	2412	-6.82	/	-6.82	8.00
	2437	-7.84	/	-7.84	8.00
	2462	-8.04	/	-8.04	8.00
802.11g	2412	-8.70	/	-8.70	8.00
	2437	-10.18	/	-10.18	8.00
	2462	-10.01	/	-10.01	8.00
802.11n ht20	2412	-11.80	/	-11.80	8.00
	2437	-12.91	/	-12.91	8.00
	2462	-13.31	/	-13.31	8.00
802.11n ht40	2422	-15.53	/	-15.53	8.00
	2437	-16.40	/	-16.40	8.00
	2452	-16.75	/	-16.75	8.00
802.11n ax20	2412	-10.93	/	-10.93	8.00
	2437	-12.22	/	-12.22	8.00
	2462	-14.30	/	-14.30	8.00
802.11n ax40	2422	-16.54	/	-16.54	8.00
	2437	-17.64	/	-17.64	8.00
	2452	-18.13	/	-18.13	8.00


### Maximum power spectral density

802.11b  
Lowest Channel




Date: 12.AUG.2023 13:25:20

802.11b  
Middle Channel



Date: 12.AUG.2023 13:29:52


802.11b  
Highest Channel



Date: 12.AUG.2023 13:33:53


Maximum power spectral density

802.11g  
Lowest Channel




Date: 12.AUG.2023 13:16:13

802.11g  
Middle Channel



Date: 12.AUG.2023 13:17:33


802.11g  
Highest Channel



Date: 12.AUG.2023 13:19:08


**Maximum power spectral density**

802.11n ht20  
Lowest Channel




Date: 12.AUG.2023 13:37:57

802.11n ht20  
Middle Channel



Date: 12.AUG.2023 13:40:55


802.11n ht20  
Highest Channel



Date: 12.AUG.2023 13:43:57


### Maximum power spectral density

802.11n ht40  
Lowest Channel




Date: 12.AUG.2023 13:48:26

802.11n ht40  
Middle Channel



Date: 12.AUG.2023 13:51:24

802.11n ht40  
Highest Channel




Date: 12.AUG.2023 13:54:21




### Maximum power spectral density

802.11ax he20  
Lowest Channel




Date: 12.AUG.2023 13:58:42

802.11ax he20  
Middle Channel



Date: 12.AUG.2023 14:02:23


802.11ax he20  
Highest Channel



Date: 12.AUG.2023 14:06:03


**Maximum power spectral density**

802.11ax he40  
Lowest Channel




Date: 12.AUG.2023 14:10:01

802.11ax he40  
Middle Channel



Date: 12.AUG.2023 14:14:00

802.11ax he40  
Highest Channel



Date: 12.AUG.2023 14:17:20

**4.7 100 kHz Bandwidth of Frequency Band Edge:**

Serial Number:	28HG-2	Test Date:	2023/8/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	26.4	Relative Humidity: (%)	59	ATM Pressure: (kPa)	99.9

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200445	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:**




### 100 kHz Bandwidth of Frequency Band Edge

802.11g  
Lowest Band edge



Date: 12.AUG.2023 15:04:18


802.11g  
Highest Band edge



Date: 12.AUG.2023 15:36:25


### 100 kHz Bandwidth of Frequency Band Edge

802.11n ht20  
Lowest Band edge



Date: 12.AUG.2023 15:39:01


802.11n ht20  
Highest Band edge



Date: 12.AUG.2023 15:46:26


### 100 kHz Bandwidth of Frequency Band Edge

802.11n ht40  
Lowest Band edge



Date: 12.AUG.2023 15:43:57


802.11n ht40  
Highest Band edge



Date: 12.AUG.2023 15:54:31


### 100 kHz Bandwidth of Frequency Band Edge

802.11ax he20  
Lowest Band edge



Date: 12.AUG.2023 15:08:26

802.11ax he20  
Highest Band edge




Date: 12.AUG.2023 15:59:52




### 100 kHz Bandwidth of Frequency Band Edge

802.11ax he40  
Lowest Band edge



Date: 12.AUG.2023 15:14:56

802.11ax he40  
Highest Band edge



Date: 12.AUG.2023 15:31:37

**4.8 Duty Cycle:**

Serial Number:	28HG-2	Test Date:	2023/8/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	N/A

**Environmental Conditions:**

Temperature: (°C)	26.4	Relative Humidity: (%)	59	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200445	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	Duty Factor (dB)
802.11b	8.29	/	Not constant	121	/
802.11g	1.48	/	Not constant	676	/
802.11n ht20	5.30	/	Not constant	189	/
802.11n ht40	5.02	/	Not constant	199	/
802.11n ax20	3.94	/	Not constant	254	/
802.11n ax40	4.10	/	Not constant	244	/


### Duty Cycle

802.11b




Date: 12.AUG.2023 11:38:48

802.11g




Date: 12.AUG.2023 11:07:56

802.11n ht20



Date: 12.AUG.2023 11:13:28



## 5. RF EXPOSURE EVALUATION- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 5.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### 5.2 Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### 5.3 Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	1.94	1.56	18	63.1	20.00	0.02	1.0

The Conducted output power including Tune-up Tolerance provided by manufacturer

**Result:** The device meet FCC MPE at 20 cm distance

===== END OF REPORT =====