



FCC PART 15.247  
TEST REPORT

For

**SHENZHEN TENDA TECHNOLOGY CO.,LTD**

6-8 Floor, Tower E3, No.1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

**FCC ID: V7TCT6**

<b>Report Type:</b> Original Report	<b>Product Name:</b> Outdoor Wi-Fi Camera 2K
<b>Report Number:</b>	<u>RDG210409040-00A</u>
<b>Report Date:</b>	<u>2021-05-20</u>
<b>Reviewed By:</b>	Ivan Cao Assistant Manager 
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 <sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
DECLARATIONS.....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	9
SUPPORT EQUIPMENT LIST AND DETAILS .....	9
SUPPORT CABLE LIST AND DETAILS .....	9
BLOCK DIAGRAM OF TEST SETUP .....	9
<b>SUMMARY OF TEST RESULTS.....</b>	<b>10</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
ANTENNA CONNECTOR CONSTRUCTION .....	12
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
EUT SETUP .....	13
EMI TEST RECEIVER SETUP .....	13
TEST PROCEDURE .....	14
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA .....	15
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP.....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	18
TEST PROCEDURE .....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA .....	19
<b>FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....</b>	<b>30</b>
APPLICABLE STANDARD .....	30
TEST PROCEDURE .....	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA .....	30
<b>FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....</b>	<b>38</b>
APPLICABLE STANDARD .....	38
TEST PROCEDURE .....	38
TEST EQUIPMENT LIST AND DETAILS.....	38

---

TEST DATA .....	38
<b>FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>40</b>
APPLICABLE STANDARD .....	40
TEST PROCEDURE .....	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA .....	41
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>50</b>
APPLICABLE STANDARD .....	50
TEST PROCEDURE .....	50
TEST EQUIPMENT LIST AND DETAILS.....	50
TEST DATA .....	50

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>		Outdoor Wi-Fi Camera 2K
<b>EUT Model:</b>		CT6
<b>Multiple Models:</b>		CT6-N, CT6-L, CT6-H, KCT6
<b>Operation Frequency:</b>		2412-2462 MHz(802.11b/g/n ht20), 2422-2452 MHz(802.11n ht40)
<b>Maximum Peak Output Power (Conducted):</b>		28.49 dBm(802.11b/g/n)
<b>Modulation Type:</b>		DSSS, OFDM
<b>Antenna Gain▲:</b>		2.8 dBi
<b>Rated Input Voltage:</b>		DC 12V from adapter
<b>Adapter Information:</b>	<b>Model:</b>	BN073-A12012U
	<b>Input:</b>	100-240V 50/60Hz 0.4A
	<b>Output:</b>	12V 1A
<b>Serial Number:</b>		RDG210409040-RF-S1
<b>EUT Received Date:</b>		2021.04.12
<b>EUT Received Status:</b>		Good

*Note: The series product, models CT6, CT6-N, CT6-L, CT6-H, KCT6 are electrically identical, the model CT6 was fully tested. The differences between them please refer to the declaration letter for details.*

### Objective

This report is prepared on behalf of **SHENZHEN TENDA TECHNOLOGY CO.,LTD** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 DTS Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

## Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

*Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

## Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1, 6, 11.

For 802.11n ht40 modes were test with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The device supports SISO in all modes, and MIMO 2T2R in 802.11n modes, per pretest, 2TX mode was the worst mode and reported for 802.11n modes.

### EUT Exercise Software

The software “SecureCRT” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer ▲:

Mode	Channel	Frequency (MHz)	Data Rate	Power level Setting	
				Chain 0	Chain 1
802.11 b	Low	2412	1Mbps	21	45
	Middle	2437	1Mbps	21	45
	High	2462	1Mbps	22	46
802.11 g	Low	2412	6Mbps	49	43
	Middle	2437	6Mbps	49	43
	High	2462	6Mbps	50	46
802.11n ht20	Low	2412	MCS8	40	40
	Middle	2437	MCS8	40	40
	High	2462	MCS8	40	40
802.11n ht40	Low	2422	MCS8	40	40
	Middle	2437	MCS8	40	40
	High	2452	MCS8	40	40

The maximum duty cycle as following table:


Test mode	T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	2.087	2.304	90.58
802.11n ht20	1.009	1.223	82.50
802.11n ht40	0.503	0.733	68.62

802.11b




Date: 21.APR.2021 11:15:51

802.11g




Date: 21.APR.2021 10:46:25

802.11n ht20



Date: 21.APR.2021 11:07:16

802.11n ht40



Date: 21.APR.2021 11:11:27



### Equipment Modifications

No modification was made to the EUT.


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Tenda	Wireless N300 Universal Range Extender	A9	RDG210409037-RF-S1
Tenda	Wi-Fi Network Video Recorder	N3W-4H	DG2210427-14137E-S1

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	Yes	Yes	1.5	Adapter	EUT
RJ45 Cable	Yes	No	1.0	EUT	Extender
RJ45 Cable	Yes	No	10	EUT	Recorder

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

## FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	2.8	1.91	29	794.33	20.00	0.30	1.0

**Result:** The device meet FCC MPE at 20 cm distance

## FCC §15.203 - ANTENNA REQUIREMENT

### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### Antenna Connector Construction

The EUT has two Dipole antenna permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Dipole	50	2.8 dBi/2.4~2.5GHz


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

## Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_c$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2020-09-12	2021-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2020-09-05	2021-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data


#### Environmental Conditions

Temperature:	25.4°C
Relative Humidity:	56%
ATM Pressure:	100.9kPa
Tester:	Walker Chen
Test Date:	2021-04-28

Test Result: Compliance

Test Mode: Transmitting(802.11b mode high channel was the worst)


#### AC120 V, 60 Hz, Line:



### Final Result

Frequency (MHz)	QuasiPeak (dB μV)	Average (dB μV)	Limit (dB μV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.431814	---	24.82	47.22	22.40	9.000	L1	9.6
0.431814	29.58	---	57.22	27.64	9.000	L1	9.6
0.486723	38.18	---	56.22	18.04	9.000	L1	9.6
0.489157	---	33.77	46.18	12.41	9.000	L1	9.6
0.978432	29.98	---	56.00	26.02	9.000	L1	9.7
1.043973	---	24.53	46.00	21.47	9.000	L1	9.7
1.495016	25.98	---	56.00	30.02	9.000	L1	9.7
1.908898	---	19.76	46.00	26.24	9.000	L1	9.7
2.173203	26.85	---	56.00	29.15	9.000	L1	9.7
2.511402	---	20.66	46.00	25.34	9.000	L1	9.7
3.668908	---	18.64	46.00	27.36	9.000	L1	9.7
3.668908	27.05	---	56.00	28.95	9.000	L1	9.7

**AC120 V, 60 Hz, Neutral:**



**Final Result**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.412859	28.88	---	57.59	28.71	9.000	N	9.6
0.431814	---	26.65	47.22	20.57	9.000	N	9.6
0.477109	---	33.23	46.39	13.16	9.000	N	9.6
0.484301	38.47	---	56.26	17.79	9.000	N	9.6
0.944861	29.62	---	56.00	26.38	9.000	N	9.6
1.070335	---	27.58	46.00	18.42	9.000	N	9.6
1.532767	29.57	---	56.00	26.43	9.000	N	9.6
1.918443	---	24.67	46.00	21.33	9.000	N	9.6
2.536578	31.58	---	56.00	24.42	9.000	N	9.6
2.536578	---	24.42	46.00	21.58	9.000	N	9.6
4.303788	---	22.86	46.00	23.14	9.000	N	9.6
4.684615	29.94	---	56.00	26.06	9.000	N	9.6




## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

#### Below 1GHz:



#### Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2020-08-25	2023-08-25
R&S	EMI Test Receiver	ESCI	100224	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2020-09-24	2021-09-24
Sonoma	Amplifier	310N	185914	2020-10-13	2021-10-13
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
HUBER+SUHNER	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26E A	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Mini Circuits	High Pass Filter	VHF-6010+	31118	2020-06-16	2021-06-16

*\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data****Environmental Conditions**

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
<b>Temperature:</b>	26.4 °C	26.3°C
<b>Relative Humidity:</b>	54.1 %	53 %
<b>ATM Pressure:</b>	100.4kPa	100.9kPa
<b>Tester:</b>	Burt Hu	Joker Chen
<b>Test Date:</b>	2021-05-18	2021-04-29


*Test Result: Compliance, please Refer to the following data*

*Test Mode: Transmitting*

1) 30MHz-1GHz(802.11b Chain 1 High channel was the worst)

Horizontal:


90.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
359.8000	38.79	peak	-5.95	32.84	46.00	13.16
127.0000	44.08	peak	-10.68	33.40	43.50	10.10
33.8800	34.02	peak	-6.11	27.91	40.00	12.09
879.7200	34.54	peak	2.88	37.42	46.00	8.58
515.0000	36.13	peak	-2.82	33.31	46.00	12.69
600.3600	33.44	peak	-1.39	32.05	46.00	13.95

**Vertical:**

90.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
34.8500	41.23	QP	-6.63	34.60	40.00	5.40
48.4300	46.52	peak	-15.12	31.40	40.00	8.60
127.9700	44.36	peak	-10.37	33.99	43.50	9.51
323.9100	32.14	peak	-7.04	25.10	46.00	20.90
524.7000	41.42	peak	-2.51	38.91	46.00	7.09
675.0500	39.11	peak	-0.06	39.05	46.00	6.95

**2) 1-25GHz:  
802.11b Mode(Chain 0):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	69.45	PK	H	28.12	2.50	0.00	100.07	N/A	N/A
2412.00	65.78	AV	H	28.12	2.50	0.00	96.40	N/A	N/A
2412.00	70.65	PK	V	28.12	2.50	0.00	101.27	N/A	N/A
2412.00	66.93	AV	V	28.12	2.50	0.00	97.55	N/A	N/A
2390.00	27.05	PK	V	28.08	2.50	0.00	57.63	74.00	16.37
2390.00	14.15	AV	V	28.08	2.50	0.00	44.73	54.00	9.27
4824.00	46.43	PK	V	32.92	3.59	27.41	55.53	74.00	18.47
4824.00	42.35	AV	V	32.92	3.59	27.41	51.45	54.00	2.55
7236.00	36.28	PK	V	35.62	4.67	27.22	49.35	74.00	24.65
7236.00	24.58	AV	V	35.62	4.67	27.22	37.65	54.00	16.35
3585.00	46.00	PK	V	31.42	3.07	26.69	53.80	74.00	20.20
3585.00	33.23	AV	V	31.42	3.07	26.69	41.03	54.00	12.97
Middle Channel: 2437 MHz									
2437.00	68.49	PK	H	28.17	2.51	0.00	99.17	N/A	N/A
2437.00	64.84	AV	H	28.17	2.51	0.00	95.52	N/A	N/A
2437.00	69.57	PK	V	28.17	2.51	0.00	100.25	N/A	N/A
2437.00	65.78	AV	V	28.17	2.51	0.00	96.46	N/A	N/A
4874.00	43.55	PK	V	33.00	3.58	27.54	52.59	74.00	21.41
4874.00	39.69	AV	V	33.00	3.58	27.54	48.73	54.00	5.27
7311.00	36.45	PK	V	35.78	4.65	27.28	49.60	74.00	24.40
7311.00	25.11	AV	V	35.78	4.65	27.28	38.26	54.00	15.74
3585.00	44.90	PK	V	31.42	3.07	26.69	52.70	74.00	21.30
3585.00	31.68	AV	V	31.42	3.07	26.69	39.48	54.00	14.52
High Channel: 2462 MHz									
2462.00	69.89	PK	H	28.22	2.52	0.00	100.63	N/A	N/A
2462.00	64.63	AV	H	28.22	2.52	0.00	95.37	N/A	N/A
2462.00	71.11	PK	V	28.22	2.52	0.00	101.85	N/A	N/A
2462.00	65.76	AV	V	28.22	2.52	0.00	96.50	N/A	N/A
2483.50	27.59	PK	V	28.27	2.53	0.00	58.39	74.00	15.61
2483.50	15.20	AV	V	28.27	2.53	0.00	46.00	54.00	8.00
4924.00	43.41	PK	V	33.08	3.58	27.51	52.56	74.00	21.44
4924.00	40.24	AV	V	33.08	3.58	27.51	49.39	54.00	4.61
7386.00	36.59	PK	V	35.95	4.62	27.18	49.98	74.00	24.02
7386.00	24.94	AV	V	35.95	4.62	27.18	38.33	54.00	15.67
3585.00	43.70	PK	V	31.42	3.07	26.69	51.50	74.00	22.50
3585.00	30.93	AV	V	31.42	3.07	26.69	38.73	54.00	15.27

**802.11b Mode(Chain 1):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	79.24	PK	H	28.12	2.50	0.00	109.86	N/A	N/A
2412.00	75.74	AV	H	28.12	2.50	0.00	106.36	N/A	N/A
2412.00	82.01	PK	V	28.12	2.50	0.00	112.63	N/A	N/A
2412.00	78.31	AV	V	28.12	2.50	0.00	108.93	N/A	N/A
2387.20	35.12	PK	V	28.07	2.50	0.00	65.69	74.00	8.31
2387.20	21.20	AV	V	28.07	2.50	0.00	51.77	54.00	2.23
4824.00	46.07	PK	V	32.92	3.59	27.41	55.17	74.00	18.83
4824.00	43.13	AV	V	32.92	3.59	27.41	52.23	54.00	1.77
7236.00	39.25	PK	V	35.62	4.67	27.22	52.32	74.00	21.68
7236.00	31.04	AV	V	35.62	4.67	27.22	44.11	54.00	9.89
3585.00	43.30	PK	V	31.42	3.07	26.69	51.10	74.00	22.90
3585.00	30.11	AV	V	31.42	3.07	26.69	37.91	54.00	16.09
Middle Channel: 2437 MHz									
2437.00	76.94	PK	H	28.17	2.51	0.00	107.62	N/A	N/A
2437.00	73.19	AV	H	28.17	2.51	0.00	103.87	N/A	N/A
2437.00	79.72	PK	V	28.17	2.51	0.00	110.40	N/A	N/A
2437.00	76.26	AV	V	28.17	2.51	0.00	106.94	N/A	N/A
4874.00	45.96	PK	V	33.00	3.58	27.54	55.00	74.00	19.00
4874.00	43.03	AV	V	33.00	3.58	27.54	52.07	54.00	1.93
7311.00	38.27	PK	V	35.78	4.65	27.28	51.42	74.00	22.58
7311.00	29.87	AV	V	35.78	4.65	27.28	43.02	54.00	10.98
3585.00	45.20	PK	V	31.42	3.07	26.69	53.00	74.00	21.00
3585.00	32.38	AV	V	31.42	3.07	26.69	40.18	54.00	13.82
High Channel: 2462 MHz									
2462.00	78.21	PK	H	28.22	2.52	0.00	108.95	N/A	N/A
2462.00	74.24	AV	H	28.22	2.52	0.00	104.98	N/A	N/A
2462.00	80.61	PK	V	28.22	2.52	0.00	111.35	N/A	N/A
2462.00	76.90	AV	V	28.22	2.52	0.00	107.64	N/A	N/A
2483.50	28.35	PK	V	28.27	2.53	0.00	59.15	74.00	14.85
2483.50	16.23	AV	V	28.27	2.53	0.00	47.03	54.00	6.97
4924.00	45.41	PK	V	33.08	3.58	27.51	54.56	74.00	19.44
4924.00	42.18	AV	V	33.08	3.58	27.51	51.33	54.00	2.67
7386.00	38.86	PK	V	35.95	4.62	27.18	52.25	74.00	21.75
7386.00	30.47	AV	V	35.95	4.62	27.18	43.86	54.00	10.14
3585.00	45.50	PK	V	31.42	3.07	26.69	53.30	74.00	20.70
3585.00	32.45	AV	V	31.42	3.07	26.69	40.25	54.00	13.75

**802.11g Mode(Chain 0):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	77.59	PK	H	28.12	2.50	0.00	108.21	N/A	N/A
2412.00	69.32	AV	H	28.12	2.50	0.00	99.94	N/A	N/A
2412.00	78.68	PK	V	28.12	2.50	0.00	109.30	N/A	N/A
2412.00	70.21	AV	V	28.12	2.50	0.00	100.83	N/A	N/A
2390.00	38.52	PK	V	28.08	2.50	0.00	69.10	74.00	4.90
2390.00	21.65	AV	V	28.08	2.50	0.00	52.23	54.00	1.77
4824.00	52.58	PK	V	32.92	3.59	27.41	61.68	74.00	12.32
4824.00	40.08	AV	V	32.92	3.59	27.41	49.18	54.00	4.82
7236.00	37.33	PK	V	35.62	4.67	27.22	50.40	74.00	23.60
7236.00	25.58	AV	V	35.62	4.67	27.22	38.65	54.00	15.35
3585.00	45.90	PK	V	31.42	3.07	26.69	53.70	74.00	20.30
3585.00	33.15	AV	V	31.42	3.07	26.69	40.95	54.00	13.05
Middle Channel: 2437 MHz									
2437.00	75.39	PK	H	28.17	2.51	0.00	106.07	N/A	N/A
2437.00	66.79	AV	H	28.17	2.51	0.00	97.47	N/A	N/A
2437.00	76.48	PK	V	28.17	2.51	0.00	107.16	N/A	N/A
2437.00	67.94	AV	V	28.17	2.51	0.00	98.62	N/A	N/A
4874.00	50.07	PK	V	33.00	3.58	27.54	59.11	74.00	14.89
4874.00	37.78	AV	V	33.00	3.58	27.54	46.82	54.00	7.18
7311.00	37.20	PK	V	35.78	4.65	27.28	50.35	74.00	23.65
7311.00	25.44	AV	V	35.78	4.65	27.28	38.59	54.00	15.41
3585.00	42.60	PK	V	31.42	3.07	26.69	50.40	74.00	23.60
3585.00	29.52	AV	V	31.42	3.07	26.69	37.32	54.00	16.68
High Channel: 2462 MHz									
2462.00	74.11	PK	H	28.22	2.52	0.00	104.85	N/A	N/A
2462.00	65.43	AV	H	28.22	2.52	0.00	96.17	N/A	N/A
2462.00	75.42	PK	V	28.22	2.52	0.00	106.16	N/A	N/A
2462.00	66.58	AV	V	28.22	2.52	0.00	97.32	N/A	N/A
2483.50	37.74	PK	V	28.27	2.53	0.00	68.54	74.00	5.46
2483.50	20.59	AV	V	28.27	2.53	0.00	51.39	54.00	2.61
4924.00	47.21	PK	V	33.08	3.58	27.51	56.36	74.00	17.64
4924.00	34.99	AV	V	33.08	3.58	27.51	44.14	54.00	9.86
7386.00	37.22	PK	V	35.95	4.62	27.18	50.61	74.00	23.39
7386.00	25.94	AV	V	35.95	4.62	27.18	39.33	54.00	14.67
3585.00	43.60	PK	V	31.42	3.07	26.69	51.40	74.00	22.60
3585.00	30.80	AV	V	31.42	3.07	26.69	38.60	54.00	15.40



**802.11g Mode(Chain 1):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	77.11	PK	H	28.12	2.50	0.00	107.73	N/A	N/A
2412.00	67.79	AV	H	28.12	2.50	0.00	98.41	N/A	N/A
2412.00	79.72	PK	V	28.12	2.50	0.00	110.34	N/A	N/A
2412.00	70.56	AV	V	28.12	2.50	0.00	101.18	N/A	N/A
2390.00	38.15	PK	V	28.08	2.50	0.00	68.73	74.00	5.27
2390.00	20.01	AV	V	28.08	2.50	0.00	50.59	54.00	3.41
4824.00	43.13	PK	V	32.92	3.59	27.41	52.23	74.00	21.77
4824.00	32.71	AV	V	32.92	3.59	27.41	41.81	54.00	12.19
7236.00	37.11	PK	V	35.62	4.67	27.22	50.18	74.00	23.82
7236.00	25.61	AV	V	35.62	4.67	27.22	38.68	54.00	15.32
3585.00	43.00	PK	V	31.42	3.07	26.69	50.80	74.00	23.20
3585.00	30.07	AV	V	31.42	3.07	26.69	37.87	54.00	16.13
Middle Channel: 2437 MHz									
2437.00	74.99	PK	H	28.17	2.51	0.00	105.67	N/A	N/A
2437.00	65.85	AV	H	28.17	2.51	0.00	96.53	N/A	N/A
2437.00	77.61	PK	V	28.17	2.51	0.00	108.29	N/A	N/A
2437.00	68.67	AV	V	28.17	2.51	0.00	99.35	N/A	N/A
4874.00	42.49	PK	V	33.00	3.58	27.54	51.53	74.00	22.47
4874.00	31.77	AV	V	33.00	3.58	27.54	40.81	54.00	13.19
7311.00	37.05	PK	V	35.78	4.65	27.28	50.20	74.00	23.80
7311.00	25.60	AV	V	35.78	4.65	27.28	38.75	54.00	15.25
3585.00	44.80	PK	V	31.42	3.07	26.69	52.60	74.00	21.40
3585.00	31.82	AV	V	31.42	3.07	26.69	39.62	54.00	14.38
High Channel: 2462 MHz									
2462.00	77.23	PK	H	28.22	2.52	0.00	107.97	N/A	N/A
2462.00	68.09	AV	H	28.22	2.52	0.00	98.83	N/A	N/A
2462.00	79.81	PK	V	28.22	2.52	0.00	110.55	N/A	N/A
2462.00	70.78	AV	V	28.22	2.52	0.00	101.52	N/A	N/A
2483.50	38.75	PK	V	28.27	2.53	0.00	69.55	74.00	4.45
2483.50	20.63	AV	V	28.27	2.53	0.00	51.43	54.00	2.57
4924.00	41.22	PK	V	33.08	3.58	27.51	50.37	74.00	23.63
4924.00	30.93	AV	V	33.08	3.58	27.51	40.08	54.00	13.92
7386.00	37.17	PK	V	35.95	4.62	27.18	50.56	74.00	23.44
7386.00	25.46	AV	V	35.95	4.62	27.18	38.85	54.00	15.15
3585.00	43.90	PK	V	31.42	3.07	26.69	51.70	74.00	22.30
3585.00	30.68	AV	V	31.42	3.07	26.69	38.48	54.00	15.52

**802.11n ht20(2Tx mode was the worst):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	79.16	PK	H	28.12	2.50	0.00	109.78	N/A	N/A
2412.00	67.47	AV	H	28.12	2.50	0.00	98.09	N/A	N/A
2412.00	81.26	PK	V	28.12	2.50	0.00	111.88	N/A	N/A
2412.00	69.69	AV	V	28.12	2.50	0.00	100.31	N/A	N/A
2390.00	32.30	PK	V	28.08	2.50	0.00	62.88	74.00	11.12
2390.00	17.85	AV	V	28.08	2.50	0.00	48.43	54.00	5.57
4824.00	48.23	PK	V	32.92	3.59	27.41	57.33	74.00	16.67
4824.00	36.86	AV	V	32.92	3.59	27.41	45.96	54.00	8.04
7236.00	37.06	PK	V	35.62	4.67	27.22	50.13	74.00	23.87
7236.00	25.29	AV	V	35.62	4.67	27.22	38.36	54.00	15.64
3585.00	42.90	PK	V	31.42	3.07	26.69	50.70	74.00	23.30
3585.00	30.13	AV	V	31.42	3.07	26.69	37.93	54.00	16.07
Middle Channel: 2437 MHz									
2437.00	77.59	PK	H	28.17	2.51	0.00	108.27	N/A	N/A
2437.00	65.82	AV	H	28.17	2.51	0.00	96.50	N/A	N/A
2437.00	80.02	PK	V	28.17	2.51	0.00	110.70	N/A	N/A
2437.00	68.38	AV	V	28.17	2.51	0.00	99.06	N/A	N/A
4874.00	42.58	PK	V	33.00	3.58	27.54	51.62	74.00	22.38
4874.00	31.26	AV	V	33.00	3.58	27.54	40.30	54.00	13.70
7311.00	36.81	PK	V	35.78	4.65	27.28	49.96	74.00	24.04
7311.00	25.45	AV	V	35.78	4.65	27.28	38.60	54.00	15.40
3585.00	44.40	PK	V	31.42	3.07	26.69	52.20	74.00	21.80
3585.00	31.55	AV	V	31.42	3.07	26.69	39.35	54.00	14.65
High Channel: 2462 MHz									
2462.00	78.32	PK	H	28.22	2.52	0.00	109.06	N/A	N/A
2462.00	66.78	AV	H	28.22	2.52	0.00	97.52	N/A	N/A
2462.00	80.53	PK	V	28.22	2.52	0.00	111.27	N/A	N/A
2462.00	69.20	AV	V	28.22	2.52	0.00	99.94	N/A	N/A
2483.50	30.95	PK	V	28.27	2.53	0.00	61.75	74.00	12.25
2483.50	18.34	AV	V	28.27	2.53	0.00	49.14	54.00	4.86
4924.00	41.10	PK	V	33.08	3.58	27.51	50.25	74.00	23.75
4924.00	29.75	AV	V	33.08	3.58	27.51	38.90	54.00	15.10
7386.00	36.52	PK	V	35.95	4.62	27.18	49.91	74.00	24.09
7386.00	24.83	AV	V	35.95	4.62	27.18	38.22	54.00	15.78
3585.00	44.70	PK	V	31.42	3.07	26.69	52.50	74.00	21.50
3585.00	31.98	AV	V	31.42	3.07	26.69	39.78	54.00	14.22




**802.11n ht40(2Tx mode was the worst):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	77.26	PK	H	28.14	2.51	0.00	107.91	N/A	N/A
2422.00	65.17	AV	H	28.14	2.51	0.00	95.82	N/A	N/A
2422.00	79.29	PK	V	28.14	2.51	0.00	109.94	N/A	N/A
2422.00	67.38	AV	V	28.14	2.51	0.00	98.03	N/A	N/A
2390.00	38.52	PK	V	28.08	2.50	0.00	69.10	74.00	4.90
2390.00	21.23	AV	V	28.08	2.50	0.00	51.81	54.00	2.19
4844.00	44.52	PK	V	32.95	3.59	27.46	53.60	74.00	20.40
4844.00	32.06	AV	V	32.95	3.59	27.46	41.14	54.00	12.86
7266.00	36.89	PK	V	35.69	4.66	27.25	49.99	74.00	24.01
7266.00	25.33	AV	V	35.69	4.66	27.25	38.43	54.00	15.57
3585.00	45.20	PK	V	31.42	3.07	26.69	53.00	74.00	21.00
3585.00	31.91	AV	V	31.42	3.07	26.69	39.71	54.00	14.29
Middle Channel: 2437 MHz									
2437.00	76.93	PK	H	28.17	2.51	0.00	107.61	N/A	N/A
2437.00	64.83	AV	H	28.17	2.51	0.00	95.51	N/A	N/A
2437.00	78.89	PK	V	28.17	2.51	0.00	109.57	N/A	N/A
2437.00	66.76	AV	V	28.17	2.51	0.00	97.44	N/A	N/A
4874.00	40.30	PK	V	33.00	3.58	27.54	49.34	74.00	24.66
4874.00	28.57	AV	V	33.00	3.58	27.54	37.61	54.00	16.39
7311.00	36.57	PK	V	35.78	4.65	27.28	49.72	74.00	24.28
7311.00	24.85	AV	V	35.78	4.65	27.28	38.00	54.00	16.00
3585.00	42.90	PK	V	31.42	3.07	26.69	50.70	74.00	23.30
3585.00	29.94	AV	V	31.42	3.07	26.69	37.74	54.00	16.26
High Channel: 2452 MHz									
2452.00	76.08	PK	H	28.20	2.52	0.00	106.80	N/A	N/A
2452.00	64.07	AV	H	28.20	2.52	0.00	94.79	N/A	N/A
2452.00	78.11	PK	V	28.20	2.52	0.00	108.83	N/A	N/A
2452.00	66.63	AV	V	28.20	2.52	0.00	97.35	N/A	N/A
2483.50	32.39	PK	V	28.27	2.53	0.00	63.19	74.00	10.81
2483.50	21.25	AV	V	28.27	2.53	0.00	52.05	54.00	1.95
4904.00	38.95	PK	V	33.05	3.58	27.58	48.00	74.00	26.00
4904.00	27.51	AV	V	33.05	3.58	27.58	36.56	54.00	17.44
7356.00	36.85	PK	V	35.88	4.63	27.22	50.14	74.00	23.86
7356.00	25.14	AV	V	35.88	4.63	27.22	38.43	54.00	15.57
3585.00	45.00	PK	V	31.42	3.07	26.69	52.80	74.00	21.20
3585.00	31.96	AV	V	31.42	3.07	26.69	39.76	54.00	14.24

Test plots(802.11b Chain 1 Low channel was the worst)




Horizontal:

Fundamental Test with Band Rejection Filter



**Vertical:**

Fundamental  
Test with Band  
Rejection Filter



## FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


### Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101591	2020-06-29	2021-06-28
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	100.9kPa
<b>Tester:</b>	Tiger Mo
<b>Test Date:</b>	2021-05-07

*Test Mode: Transmitting*

*Test Result: Compliance. Test only was performed at chain 0, please refer to the following table and plots.*

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.000	$\geq 0.5$
	Middle	2437	10.000	$\geq 0.5$
	High	2462	10.000	$\geq 0.5$
802.11g	Low	2412	16.400	$\geq 0.5$
	Middle	2437	16.400	$\geq 0.5$
	High	2462	16.400	$\geq 0.5$
802.11n ht20	Low	2412	17.360	$\geq 0.5$
	Middle	2437	17.440	$\geq 0.5$
	High	2462	17.200	$\geq 0.5$
802.11n ht40	Low	2422	35.520	$\geq 0.5$
	Middle	2437	35.520	$\geq 0.5$
	High	2452	35.680	$\geq 0.5$


6dB Emission Bandwidth:

802.11b Low Channel



Date: 7.MAY.2021 08:09:36

802.11b Middle Channel



Date: 7.MAY.2021 08:11:47




### 802.11b High Channel




Date: 7.MAY.2021 08:13:10

### 802.11g Low Channel




Date: 7.MAY.2021 08:16:29

### 802.11g Middle Channel




Date: 7.MAY.2021 08:18:25

### 802.11g High Channel




Date: 7.MAY.2021 08:19:59

### 802.11n ht20 Low Channel




Date: 7.MAY.2021 08:21:34

### 802.11n ht20 Middle Channel




Date: 7.MAY.2021 08:23:12

### 802.11n ht20 High Channel




Date: 7.MAY.2021 08:24:38

### 802.11n ht40 Low Channel




Date: 7.MAY.2021 08:26:22

### 802.11n ht40 Middle Channel



Date: 7.MAY.2021 08:28:03

### 802.11n ht40 High Channel



Date: 7.MAY.2021 08:33:28


## FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2020-09-12	2021-09-12

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	100.9kPa
<b>Tester:</b>	Tiger Mo
<b>Test Date:</b>	2021-05-07

*Test Mode: Transmitting*

Test Result: Compliance. Please refer to the following table.

Mode	Channel	Frequency (MHz)	Conducted Peak Output Power (dBm)			Limits (dBm)
			Chain 0	Chain 1	Total	
802.11 b	Low	2412	13.67	25.27	/	30
	Middle	2437	13.57	25.13	/	30
	High	2462	14.52	25.31	/	30
802.11 g	Low	2412	28.49	25.04	/	30
	Middle	2437	27.66	24.85	/	30
	High	2462	27.81	25.33	/	30
802.11n ht20	Low	2412	25.35	24.4	27.91	30
	Middle	2437	25.28	23.47	27.48	30
	High	2462	25.22	23.34	27.39	30
802.11n ht40	Low	2422	25.52	24.99	28.27	30
	Middle	2437	25.41	24.82	28.14	30
	High	2452	25.13	24.28	27.74	30

Note:

The maximum antenna gain is 2.8dBi in 2.4GHz band. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

So:

Directional gain = 2.8dBi

## **FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
R&S	Spectrum Analyzer	FSV40	101591	2020-06-29	2021-06-28
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




**Test Data****Environmental Conditions**

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	100.9kPa
<b>Tester:</b>	Tiger Mo
<b>Test Date:</b>	2021-05-07


*Test mode: Transmitting*

*Test Result: Compliance. Please refer to following plots.*


### Chain 0, 802.11b: Band Edge, Left Side



### Chain 0,802.11b: Band Edge, Right Side




### Chain 0,802.11g: Band Edge, Left Side




### Chain 0,802.11g: Band Edge, Right Side




Chain 0,802.11n ht20 Band Edge, Left Side




Chain 0,802.11n ht20 Band Edge, Right Side




Chain 0,802.11n ht40 Band Edge, Left Side




Chain 0,802.11n ht40 Band Edge, Right Side




### Chain 1, 802.11b: Band Edge, Left Side




### Chain 1,802.11b: Band Edge, Right Side



### Chain 1,802.11g: Band Edge, Left Side




### Chain 1,802.11g: Band Edge, Right Side






### Chain 1,802.11n ht20 Band Edge, Left Side




### Chain 1,802.11n ht20 Band Edge, Right Side






### Chain 1,802.11n ht40 Band Edge, Left Side



### Chain 1,802.11n ht40 Band Edge, Right Side



## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101591	2020-06-29	2021-06-28
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24.1 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	100.9kPa
<b>Tester:</b>	Tiger Mo
<b>Test Date:</b>	2021-05-07

**Test Result:** Compliance. Please refer to the following table and plots

Test Mode: Transmitting

Test mode	Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	-12.91	-2.63	/	≤8
	Middle	2437	-13.07	-2.42	/	≤8
	High	2462	-12.05	-2.23	/	≤8
802.11g	Low	2412	-5.88	-10.84	/	≤8
	Middle	2437	-6.45	-10.84	/	≤8
	High	2462	-6.84	-9.24	/	≤8
802.11n ht20	Low	2412	-12.81	-12.23	-9.5	≤8
	Middle	2437	-12.96	-12.12	-9.51	≤8
	High	2462	-12.80	-12.50	-9.64	≤8
802.11n ht40	Low	2422	-13.78	-14.86	-11.28	≤8
	Middle	2437	-14.68	-14.50	-11.58	≤8
	High	2452	-15.01	-14.43	-11.7	≤8


Note 1: The maximum antenna gain is 2.8 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{SS}}) \text{ dB.}$$

So:


$$\text{Directional gain} = G_{\text{ANT}} + \text{Array Gain} = 2.8 + 10 \cdot \log(2/1) = 5.8 \text{ dBi}$$

**Chain 0, Power Spectral Density, 802.11b Low Channel**




Date: 7.MAY.2021 08:10:31

### Chain 0,Power Spectral Density, 802.11b Middle Channel




Date: 7.MAY.2021 08:12:36

### Chain 0,Power Spectral Density, 802.11b High Channel




Date: 7.MAY.2021 08:13:59

### Chain 0, Power Spectral Density, 802.11g Low Channel




Date: 7.MAY.2021 08:17:05

### Chain 0, Power Spectral Density, 802.11g Middle Channel




Date: 7.MAY.2021 08:19:04

### Chain 0, Power Spectral Density, 802.11g High Channel




Date: 7.MAY.2021 08:20:32

### Chain 0, Power Spectral Density, 802.11n ht20 Low Channel




Date: 7.MAY.2021 09:26:06

### Chain 0, Power Spectral Density, 802.11n ht20 Middle Channel




Date: 7.MAY.2021 09:20:35

### Chain 0, Power Spectral Density, 802.11n ht20 High Channel




Date: 7.MAY.2021 08:25:14

### Chain 0, Power Spectral Density, 802.11n ht40 Low Channel



Date: 7.MAY.2021 08:27:07


### Chain 0, Power Spectral Density, 802.11n ht40 Middle Channel



Date: 7.MAY.2021 09:21:14




### Chain 0, Power Spectral Density, 802.11n ht40 High Channel




Date: 7.MAY.2021 08:34:16

### Chain 1, Power Spectral Density, 802.11b Low Channel




Date: 7.MAY.2021 08:38:03

### Chain 1,Power Spectral Density, 802.11b Middle Channel




Date: 7.MAY.2021 08:40:06

### Chain 1,Power Spectral Density, 802.11b High Channel




Date: 7.MAY.2021 08:42:22

### Chain1,Power Spectral Density, 802.11g Low Channel




Date: 7.MAY.2021 08:44:16

### Chain 1,Power Spectral Density, 802.11g Middle Channel




Date: 7.MAY.2021 08:45:31


### Chain1,Power Spectral Density, 802.11g High Channel



### Chain1,Power Spectral Density, 802.11n ht20 Low Channel




### Chain 1, Power Spectral Density, 802.11n ht20 Middle Channel




Date: 7.MAY.2021 08:50:13

### Chain 1, Power Spectral Density, 802.11n ht20 High Channel




Date: 7.MAY.2021 09:23:42

### Chain 1, Power Spectral Density, 802.11n ht40 Low Channel




Date: 7.MAY.2021 08:52:57

### Chain 1, Power Spectral Density, 802.11n ht40 Middle Channel



Date: 7.MAY.2021 08:54:21

### Chain 1, Power Spectral Density, 802.11n ht40 High Channel



Date: 7.MAY.2021 08:55:33

\*\*\*\*\* END OF REPORT \*\*\*\*\*