



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO.,LTD

6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China.
518052

FCC ID: V7TF3V5

Report Type: Original Report	Product Name: Wireless N300 Easy Setup Router
Report Number: DG2210531-20261E-00A	
Report Date: 2021-06-23	
Reviewed By: Test Laboratory:	Ivan Cao Assistant Manager Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY.....	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	11
APPLICABLE STANDARD	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA	19
FCC §15.247(a) (2)-6 dB EMISSION BANDWIDTH.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA	30
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38

TEST DATA	38
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	40
FCC §15.247(e) - POWER SPECTRAL DENSITY	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST EQUIPMENT LIST AND DETAILS.....	49
TEST DATA	49

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	Wireless N300 Easy Setup Router
EUT Model:	F3
Multiple Models:	F3v5
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20), 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	25.99 dBm(802.11b/g/n)
Modulation Type:	DSSS, OFDM
Antenna Gain :	5 dBi
Rated Input Voltage:	DC 9 V from Adapter
Adapter Information	Model: BN003-A05009U
	Input: 100-240V~50/60Hz 0.3A
	Output: 9Vdc/0.6A
Serial Number:	DG2210531-20261E-RF-S_7VS
EUT Received Date:	2021.06.01
EUT Received Status:	Good

Note: The series product, models F3, F3v5 are electrically identical, the model F3 was fully tested. The difference between them please refer to the declaration letter for details.

Objective

This report is prepared on behalf of **SHENZHEN TENDA TECHNOLOGY CO.,LTD** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 DTS Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1, 6, 11.

For 802.11n ht40 modes were test with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The device supports SISO in all modes, and MIMO 2T3R in 802.11n modes, per pretest, 2TX mode was the worst mode and reported for 802.11n modes.


EUT Exercise Software

The software “MP v3.6” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer▲:


Mode	Channel	Frequency (MHz)	Data Rate	Power level Setting	
				Chain 0	Chain 1
802.11 b	Low	2412	1Mbps	58	56
	Middle	2437	1Mbps	58	56
	High	2462	1Mbps	58	56
802.11 g	Low	2412	6Mbps	56	56
	Middle	2437	6Mbps	56	56
	High	2462	6Mbps	56	56
802.11n ht20	Low	2412	MCS8	54	54
	Middle	2437	MCS8	54	54
	High	2462	MCS8	54	54
802.11n ht40	Low	2422	MCS8	54	54
	Middle	2437	MCS8	54	54
	High	2452	MCS8	51	51

The maximum duty cycle as following table:

Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100.00
802.11g	1.453	1.485	97.85
802.11n ht20	0.696	0.841	82.76
802.11n ht40	0.361	0.478	75.52


802.11b

Date: 15.JUN.2021 07:15:40

802.11g


Date: 15.JUN.2021 07:14:55

802.11n ht20



Date: 15.JUN.2021 07:13:09

802.11n ht40



Date: 15.JUN.2021 07:17:03

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ThinkPad	Laptop	E450	PF-0MR8KV 16/08
DELL	Laptop	PP11L	QDS-BRCM1017
Un-known	RJ45 Load	Un-known	RJ45 Load-1

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	No	No	10	EUT	Laptop
Power Cable	No	No	1.2	Adapter	EUT
RJ45 Cable	No	No	10	EUT	Laptop
RJ45 Cable	No	No	10	EUT	RJ45 Load
RJ45 Cable	No	No	10	EUT	RJ45 Load

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	5	3.16	26	398.11	20.00	0.25	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has 3 Dipole antennas permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Dipole	50	5dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2020-09-12	2021-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2020-09-05	2021-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.7°C
Relative Humidity:	66%
ATM Pressure:	100.2kPa
Tester:	Mia Huang
Test Date:	2021-06-17

Test Result: Compliance


Test Mode: Transmitting(802.11b mode high channel was the worst)

AC120 V, 60 Hz, Line:



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.412859	---	32.17	47.59	15.42	9.000	L1	9.6
0.416998	36.49	---	57.51	21.02	9.000	L1	9.6
0.444931	30.66	---	56.97	26.31	9.000	L1	9.6
0.707516	---	26.58	46.00	19.42	9.000	L1	9.7
0.809506	32.20	---	56.00	23.80	9.000	L1	9.7
1.043973	---	27.67	46.00	18.33	9.000	L1	9.7
4.303788	---	24.81	46.00	21.19	9.000	L1	9.7
4.412464	32.10	---	56.00	23.90	9.000	L1	9.7
13.418776	39.94	---	60.00	20.06	9.000	L1	10.1
13.418776	---	32.07	50.00	17.93	9.000	L1	10.1
21.659819	42.02	---	60.00	17.98	9.000	L1	10.0
22.881343	---	31.68	50.00	18.32	9.000	L1	10.0

AC120 V, 60 Hz, Neutral:**Final_Result**

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.679842	29.57	---	56.00	26.43	9.000	N	9.6
0.732654	---	23.79	46.00	22.21	9.000	N	9.6
1.043973	---	25.91	46.00	20.09	9.000	N	9.6
1.091902	32.07	---	56.00	23.93	9.000	N	9.6
3.081234	30.39	---	56.00	25.61	9.000	N	9.6
3.973689	33.30	---	56.00	23.70	9.000	N	9.6
4.412464	---	19.26	46.00	26.74	9.000	N	9.6
9.511623	---	21.85	50.00	28.15	9.000	N	9.7
13.418776	40.57	---	60.00	19.43	9.000	N	9.8
13.418776	---	31.34	50.00	18.66	9.000	N	9.8
21.659819	---	34.41	50.00	15.59	9.000	N	9.9
22.881343	43.08	---	60.00	16.92	9.000	N	9.9


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-1	2020-11-10	2023-11-10
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2021-05-06	2022-05-05
HP	Amplifier	8447D	2727A05902	2020-09-05	2021-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
Agilent	Spectrum Analyzer	E4440A	MY44303352	2021-04-25	2022-04-24
HUBER+SUHNE R	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26E A	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Mini Circuits	High Pass Filter	VHF-6010+	31118	2020-06-16	2021-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	28.4 °C	25.9°C
Relative Humidity:	56 %	49 %
ATM Pressure:	100.2kPa	100.3kPa
Tester:	Alex Hu	Alex Hu
Test Date:	2021-06-18	2021-06-14

Test Result: Compliance, please Refer to the following data


Test Mode: Transmitting

1) 30MHz-1GHz(802.11b Middle channel chain 0 was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
249.2200	31.36	peak	-5.93	25.43	46.00	20.57
274.4400	33.20	peak	-4.08	29.12	46.00	16.88
362.7100	31.24	peak	-2.75	28.49	46.00	17.51
399.5700	34.27	peak	-2.11	32.16	46.00	13.84
544.1000	29.90	peak	0.08	29.98	46.00	16.02
898.1500	34.26	peak	-0.76	33.50	46.00	12.50

Vertical:80.0 dB_{uV/m}

Frequency (MHz)	Receiver Reading (dB _{uV})	Detector	Correction Factor (dB/m)	Cord. Amp. (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)
30.9700	27.59	peak	0.74	28.33	40.00	11.67
64.9200	38.11	peak	-11.81	26.30	40.00	13.70
197.8100	33.36	peak	-6.15	27.21	43.50	16.29
399.5700	33.01	peak	-2.11	30.90	46.00	15.10
499.4800	29.69	peak	-0.39	29.30	46.00	16.70
544.1000	31.83	peak	0.08	31.91	46.00	14.09

**2) 1-25GHz:
802.11b Mode(Chain 0):**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	76.50	PK	H	28.12	2.50	0.00	107.12	N/A	N/A
2412.00	72.77	AV	H	28.12	2.50	0.00	103.39	N/A	N/A
2412.00	83.38	PK	V	28.12	2.50	0.00	114.00	N/A	N/A
2412.00	79.50	AV	V	28.12	2.50	0.00	110.12	N/A	N/A
2390.00	31.17	PK	V	28.08	2.50	0.00	61.75	74.00	12.25
2390.00	20.03	AV	V	28.08	2.50	0.00	50.61	54.00	3.39
4824.00	47.30	PK	V	32.92	3.59	27.41	56.40	74.00	17.60
4824.00	44.02	AV	V	32.92	3.59	27.41	53.12	54.00	0.88
7236.00	36.86	PK	V	35.62	4.67	27.22	49.93	74.00	24.07
7236.00	24.02	AV	V	35.62	4.67	27.22	37.09	54.00	16.91
Middle Channel: 2437 MHz									
2437.00	75.88	PK	H	28.17	2.51	0.00	106.56	N/A	N/A
2437.00	71.98	AV	H	28.17	2.51	0.00	102.66	N/A	N/A
2437.00	83.10	PK	V	28.17	2.51	0.00	113.78	N/A	N/A
2437.00	79.13	AV	V	28.17	2.51	0.00	109.81	N/A	N/A
4874.00	42.03	PK	V	33.00	3.58	27.54	51.07	74.00	22.93
4874.00	37.92	AV	V	33.00	3.58	27.54	46.96	54.00	7.04
7311.00	36.82	PK	V	35.78	4.65	27.28	49.97	74.00	24.03
7311.00	24.01	AV	V	35.78	4.65	27.28	37.16	54.00	16.84
High Channel: 2462 MHz									
2462.00	74.59	PK	H	28.22	2.52	0.00	105.33	N/A	N/A
2462.00	70.65	AV	H	28.22	2.52	0.00	101.39	N/A	N/A
2462.00	83.88	PK	V	28.22	2.52	0.00	114.62	N/A	N/A
2462.00	79.80	AV	V	28.22	2.52	0.00	110.54	N/A	N/A
2483.50	32.20	PK	V	28.27	2.53	0.00	63.00	74.00	11.00
2483.50	19.31	AV	V	28.27	2.53	0.00	50.11	54.00	3.89
4924.00	43.85	PK	V	33.08	3.58	27.51	53.00	74.00	21.00
4924.00	40.66	AV	V	33.08	3.58	27.51	49.81	54.00	4.19
7386.00	36.84	PK	V	35.95	4.62	27.18	50.23	74.00	23.77
7386.00	24.03	AV	V	35.95	4.62	27.18	37.42	54.00	16.58

802.11b Mode(Chain 1):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	69.98	PK	H	28.12	2.50	0.00	100.60	N/A	N/A
2412.00	66.02	AV	H	28.12	2.50	0.00	96.64	N/A	N/A
2412.00	82.57	PK	V	28.12	2.50	0.00	113.19	N/A	N/A
2412.00	78.74	AV	V	28.12	2.50	0.00	109.36	N/A	N/A
2390.00	29.30	PK	V	28.08	2.50	0.00	59.88	74.00	14.12
2390.00	19.24	AV	V	28.08	2.50	0.00	49.82	54.00	4.18
4824.00	42.61	PK	V	32.92	3.59	27.41	51.71	74.00	22.29
4824.00	39.18	AV	V	32.92	3.59	27.41	48.28	54.00	5.72
7236.00	37.20	PK	V	35.62	4.67	27.22	50.27	74.00	23.73
7236.00	24.16	AV	V	35.62	4.67	27.22	37.23	54.00	16.77
Middle Channel: 2437 MHz									
2437.00	69.85	PK	H	28.17	2.51	0.00	100.53	N/A	N/A
2437.00	65.84	AV	H	28.17	2.51	0.00	96.52	N/A	N/A
2437.00	83.58	PK	V	28.17	2.51	0.00	114.26	N/A	N/A
2437.00	79.69	AV	V	28.17	2.51	0.00	110.37	N/A	N/A
4874.00	44.35	PK	V	33.00	3.58	27.54	53.39	74.00	20.61
4874.00	41.48	AV	V	33.00	3.58	27.54	50.52	54.00	3.48
7311.00	37.26	PK	V	35.78	4.65	27.28	50.41	74.00	23.59
7311.00	24.20	AV	V	35.78	4.65	27.28	37.35	54.00	16.65
High Channel: 2462 MHz									
2462.00	69.58	PK	H	28.22	2.52	0.00	100.32	N/A	N/A
2462.00	65.80	AV	H	28.22	2.52	0.00	96.54	N/A	N/A
2462.00	84.80	PK	V	28.22	2.52	0.00	115.54	N/A	N/A
2462.00	80.90	AV	V	28.22	2.52	0.00	111.64	N/A	N/A
2483.50	30.25	PK	V	28.27	2.53	0.00	61.05	74.00	12.95
2483.50	19.77	AV	V	28.27	2.53	0.00	50.57	54.00	3.43
4924.00	42.36	PK	V	33.08	3.58	27.51	51.51	74.00	22.49
4924.00	38.63	AV	V	33.08	3.58	27.51	47.78	54.00	6.22
7386.00	37.21	PK	V	35.95	4.62	27.18	50.60	74.00	23.40
7386.00	24.16	AV	V	35.95	4.62	27.18	37.55	54.00	16.45

802.11g Mode(Chain 0):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	75.30	PK	H	28.12	2.50	0.00	105.92	N/A	N/A
2412.00	66.27	AV	H	28.12	2.50	0.00	96.89	N/A	N/A
2412.00	81.60	PK	V	28.12	2.50	0.00	112.22	N/A	N/A
2412.00	72.13	AV	V	28.12	2.50	0.00	102.75	N/A	N/A
2390.00	38.47	PK	V	28.08	2.50	0.00	69.05	74.00	4.95
2390.00	22.80	AV	V	28.08	2.50	0.00	53.38	54.00	0.62
4824.00	41.02	PK	V	32.92	3.59	27.41	50.12	74.00	23.88
4824.00	29.57	AV	V	32.92	3.59	27.41	38.67	54.00	15.33
7236.00	37.02	PK	V	35.62	4.67	27.22	50.09	74.00	23.91
7236.00	24.16	AV	V	35.62	4.67	27.22	37.23	54.00	16.77
Middle Channel: 2437 MHz									
2437.00	73.90	PK	H	28.17	2.51	0.00	104.58	N/A	N/A
2437.00	64.82	AV	H	28.17	2.51	0.00	95.50	N/A	N/A
2437.00	81.58	PK	V	28.17	2.51	0.00	112.26	N/A	N/A
2437.00	72.81	AV	V	28.17	2.51	0.00	103.49	N/A	N/A
4874.00	38.35	PK	V	33.00	3.58	27.54	47.39	74.00	26.61
4874.00	26.30	AV	V	33.00	3.58	27.54	35.34	54.00	18.66
7311.00	36.41	PK	V	35.78	4.65	27.28	49.56	74.00	24.44
7311.00	23.83	AV	V	35.78	4.65	27.28	36.98	54.00	17.02
High Channel: 2462 MHz									
2462.00	73.89	PK	H	28.22	2.52	0.00	104.63	N/A	N/A
2462.00	64.38	AV	H	28.22	2.52	0.00	95.12	N/A	N/A
2462.00	82.67	PK	V	28.22	2.52	0.00	113.41	N/A	N/A
2462.00	73.03	AV	V	28.22	2.52	0.00	103.77	N/A	N/A
2483.50	38.56	PK	V	28.27	2.53	0.00	69.36	74.00	4.64
2483.50	21.96	AV	V	28.27	2.53	0.00	52.76	54.00	1.24
4924.00	38.33	PK	V	33.08	3.58	27.51	47.48	74.00	26.52
4924.00	26.29	AV	V	33.08	3.58	27.51	35.44	54.00	18.56
7386.00	36.55	PK	V	35.95	4.62	27.18	49.94	74.00	24.06
7386.00	23.87	AV	V	35.95	4.62	27.18	37.26	54.00	16.74

802.11g Mode(Chain 1):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	68.92	PK	H	28.12	2.50	0.00	99.54	N/A	N/A
2412.00	60.03	AV	H	28.12	2.50	0.00	90.65	N/A	N/A
2412.00	81.85	PK	V	28.12	2.50	0.00	112.47	N/A	N/A
2412.00	72.95	AV	V	28.12	2.50	0.00	103.57	N/A	N/A
2390.00	35.41	PK	V	28.08	2.50	0.00	65.99	74.00	8.01
2390.00	20.90	AV	V	28.08	2.50	0.00	51.48	54.00	2.52
4824.00	41.58	PK	V	32.92	3.59	27.41	50.68	74.00	23.32
4824.00	30.14	AV	V	32.92	3.59	27.41	39.24	54.00	14.76
7236.00	37.53	PK	V	35.62	4.67	27.22	50.60	74.00	23.40
7236.00	24.24	AV	V	35.62	4.67	27.22	37.31	54.00	16.69
Middle Channel: 2437 MHz									
2437.00	69.23	PK	H	28.17	2.51	0.00	99.91	N/A	N/A
2437.00	60.11	AV	H	28.17	2.51	0.00	90.79	N/A	N/A
2437.00	82.71	PK	V	28.17	2.51	0.00	113.39	N/A	N/A
2437.00	73.46	AV	V	28.17	2.51	0.00	104.14	N/A	N/A
4874.00	38.26	PK	V	33.00	3.58	27.54	47.30	74.00	26.70
4874.00	26.25	AV	V	33.00	3.58	27.54	35.29	54.00	18.71
7311.00	37.43	PK	V	35.78	4.65	27.28	50.58	74.00	23.42
7311.00	24.21	AV	V	35.78	4.65	27.28	37.36	54.00	16.64
High Channel: 2462 MHz									
2462.00	68.73	PK	H	28.22	2.52	0.00	99.47	N/A	N/A
2462.00	60.03	AV	H	28.22	2.52	0.00	90.77	N/A	N/A
2462.00	83.27	PK	V	28.22	2.52	0.00	114.01	N/A	N/A
2462.00	74.37	AV	V	28.22	2.52	0.00	105.11	N/A	N/A
2483.50	35.15	PK	V	28.27	2.53	0.00	65.95	74.00	8.05
2483.50	20.70	AV	V	28.27	2.53	0.00	51.50	54.00	2.50
4924.00	38.02	PK	V	33.08	3.58	27.51	47.17	74.00	26.83
4924.00	26.19	AV	V	33.08	3.58	27.51	35.34	54.00	18.66
7386.00	37.39	PK	V	35.95	4.62	27.18	50.78	74.00	23.22
7386.00	24.18	AV	V	35.95	4.62	27.18	37.57	54.00	16.43

802.11n ht20(2Tx mode was the worst):




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	72.89	PK	H	28.12	2.50	0.00	103.51	N/A	N/A
2412.00	62.60	AV	H	28.12	2.50	0.00	93.22	N/A	N/A
2412.00	82.38	PK	V	28.12	2.50	0.00	113.00	N/A	N/A
2412.00	71.23	AV	V	28.12	2.50	0.00	101.85	N/A	N/A
2390.00	32.89	PK	V	28.08	2.50	0.00	63.47	74.00	10.53
2390.00	18.77	AV	V	28.08	2.50	0.00	49.35	54.00	4.65
4824.00	40.70	PK	V	32.92	3.59	27.41	49.80	74.00	24.20
4824.00	28.17	AV	V	32.92	3.59	27.41	37.27	54.00	16.73
7236.00	37.18	PK	V	35.62	4.67	27.22	50.25	74.00	23.75
7236.00	24.01	AV	V	35.62	4.67	27.22	37.08	54.00	16.92
Middle Channel: 2437 MHz									
2437.00	71.76	PK	H	28.17	2.51	0.00	102.44	N/A	N/A
2437.00	61.80	AV	H	28.17	2.51	0.00	92.48	N/A	N/A
2437.00	82.78	PK	V	28.17	2.51	0.00	113.46	N/A	N/A
2437.00	72.14	AV	V	28.17	2.51	0.00	102.82	N/A	N/A
4874.00	37.43	PK	V	33.00	3.58	27.54	46.47	74.00	27.53
4874.00	25.36	AV	V	33.00	3.58	27.54	34.40	54.00	19.60
7311.00	37.12	PK	V	35.78	4.65	27.28	50.27	74.00	23.73
7311.00	23.92	AV	V	35.78	4.65	27.28	37.07	54.00	16.93
High Channel: 2462 MHz									
2462.00	71.40	PK	H	28.22	2.52	0.00	102.14	N/A	N/A
2462.00	61.66	AV	H	28.22	2.52	0.00	92.40	N/A	N/A
2462.00	83.46	PK	V	28.22	2.52	0.00	114.20	N/A	N/A
2462.00	72.42	AV	V	28.22	2.52	0.00	103.16	N/A	N/A
2483.50	31.99	PK	V	28.27	2.53	0.00	62.79	74.00	11.21
2483.50	19.80	AV	V	28.27	2.53	0.00	50.60	54.00	3.40
4924.00	37.56	PK	V	33.08	3.58	27.51	46.71	74.00	27.29
4924.00	25.43	AV	V	33.08	3.58	27.51	34.58	54.00	19.42
7386.00	37.09	PK	V	35.95	4.62	27.18	50.48	74.00	23.52
7386.00	23.90	AV	V	35.95	4.62	27.18	37.29	54.00	16.71

802.11n ht40(2Tx mode was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	68.60	PK	H	28.14	2.51	0.00	99.25	N/A	N/A
2422.00	57.95	AV	H	28.14	2.51	0.00	88.60	N/A	N/A
2422.00	80.34	PK	V	28.14	2.51	0.00	110.99	N/A	N/A
2422.00	69.24	AV	V	28.14	2.51	0.00	99.89	N/A	N/A
2390.00	32.22	PK	V	28.08	2.50	0.00	62.80	74.00	11.20
2390.00	20.80	AV	V	28.08	2.50	0.00	51.38	54.00	2.62
4844.00	39.63	PK	V	32.95	3.59	27.46	48.71	74.00	25.29
4844.00	26.47	AV	V	32.95	3.59	27.46	35.55	54.00	18.45
7266.00	36.82	PK	V	35.69	4.66	27.25	49.92	74.00	24.08
7266.00	23.81	AV	V	35.69	4.66	27.25	36.91	54.00	17.09
Middle Channel: 2437 MHz									
2437.00	70.15	PK	H	28.17	2.51	0.00	100.83	N/A	N/A
2437.00	58.91	AV	H	28.17	2.51	0.00	89.59	N/A	N/A
2437.00	80.29	PK	V	28.17	2.51	0.00	110.97	N/A	N/A
2437.00	68.94	AV	V	28.17	2.51	0.00	99.62	N/A	N/A
4874.00	37.63	PK	V	33.00	3.58	27.54	46.67	74.00	27.33
4874.00	25.41	AV	V	33.00	3.58	27.54	34.45	54.00	19.55
7311.00	36.79	PK	V	35.78	4.65	27.28	49.94	74.00	24.06
7311.00	23.76	AV	V	35.78	4.65	27.28	36.91	54.00	17.09
High Channel: 2452 MHz									
2452.00	68.14	PK	H	28.20	2.52	0.00	98.86	N/A	N/A
2452.00	57.09	AV	H	28.20	2.52	0.00	87.81	N/A	N/A
2452.00	79.75	PK	V	28.20	2.52	0.00	110.47	N/A	N/A
2452.00	68.05	AV	V	28.20	2.52	0.00	98.77	N/A	N/A
2483.50	35.35	PK	V	28.27	2.53	0.00	66.15	74.00	7.85
2483.50	21.75	AV	V	28.27	2.53	0.00	52.55	54.00	1.45
4904.00	37.52	PK	V	33.05	3.58	27.58	46.57	74.00	27.43
4904.00	25.33	AV	V	33.05	3.58	27.58	34.38	54.00	19.62
7356.00	36.75	PK	V	35.88	4.63	27.22	50.04	74.00	23.96
7356.00	23.68	AV	V	35.88	4.63	27.22	36.97	54.00	17.03




Test plots(802.11b low channel chain 0 was the worst)**Horizontal:**

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental Test with Band Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101591	2020-06-29	2021-06-28
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.8 °C
Relative Humidity:	47%
ATM Pressure:	100.1kPa
Tester:	Tiger Mo
Test Date:	2021-06-15


Test Mode: Transmitting

Test Result: Compliance. Test only was performed at chain 0, please refer to the following table and plots.



Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.000	≥0.5
	Middle	2437	10.000	≥0.5
	High	2462	9.920	≥0.5
802.11g	Low	2412	16.080	≥0.5
	Middle	2437	16.000	≥0.5
	High	2462	16.160	≥0.5
802.11n ht20	Low	2412	17.360	≥0.5
	Middle	2437	17.360	≥0.5
	High	2462	17.280	≥0.5
802.11n ht40	Low	2422	35.520	≥0.5
	Middle	2437	35.520	≥0.5
	High	2452	35.680	≥0.5


6dB Emission Bandwidth:**802.11b Low Channel**

Date: 15.JUN.2021 04:53:23


802.11b Middle Channel

Date: 15.JUN.2021 04:55:18



802.11b High Channel**802.11g Low Channel**


802.11g Middle Channel

Date: 15.JUN.2021 05:00:34


802.11g High Channel

Date: 15.JUN.2021 05:01:47


802.11n ht20 Low Channel**802.11n ht20 Middle Channel**

802.11n ht20 High Channel


Date: 15.JUN.2021 05:06:57

802.11n ht40 Low Channel

Date: 15.JUN.2021 05:08:38

802.11n ht40 Middle Channel

Date: 15.JUN.2021 05:10:02

802.11n ht40 High Channel

Date: 15.JUN.2021 05:11:22