

FCC RF EXPOSURE REPORT

FCC ID: V7TSS9V1

Project No.	:	2010C044
Equipment	:	Smart Wi-Fi Dimmer Switch
Brand Name	:	Tenda
Test Model	:	SS9
Series Model	:	N/A
Applicant	:	SHENZHEN TENDA TECHNOLOGY CO., LTD
Address	:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan
		District, Shenzhen, China. 518052
Manufacturer	:	SHENZHEN TENDA TECHNOLOGY CO., LTD
Address	:	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan
		District, Shenzhen, China. 518052
Date of Receipt	:	Oct. 14, 2020
Date of Test	:	Oct. 15, 2020 ~ Oct. 29, 2020
Issued Date	:	Nov. 11, 2020
Report Version	:	R00
Test Sample	:	Engineering Sample No.: DG202010167
Standard(s)	:	FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091 FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Peggy-Zhu

Prepared by : Peggy Zhu

Chan Ma

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town,Dongguan, Guangdong, China. Tel: +86-769-8318-3000 Web: www.newbtl.com



REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Nov. 11, 2020





1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China. BTL's Test Firm Registration Number for FCC: 357015 BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Internal	N/A	0

3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0	1	27.21	526.0173	0.10470	1	Complies

Note: The calculated distance is 20 cm.

End of Test Report