

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Wireless N Broadband Router

MODEL No.: W308R

FCC ID: V7TW308R

REPORT NO: ES110530147F-1

ISSUE DATE: September 8, 2011

Prepared for

**SHENZHEN TENDA TECHNOLOGY CO., LTD.
Tenda Industrial Park, No. 34-1, Shilong Rd., Shiyan Town, Bao'an District,
Shenzhen, P.R.China 518108**

Prepared by

SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE


Applicant:	SHENZHEN TENDA TECHNOLOGY CO., LTD. Tenda Industrial Park, No. 34-1, Shilong Rd., Shiyan Town, Bao'an District, Shenzhen, P.R.China 518108
Manufacturer:	SHENZHEN TENDA TECHNOLOGY CO., LTD. Tenda Industrial Park, No. 34-1, Shilong Rd., Shiyan Town, Bao'an District, Shenzhen, P.R.China 518108
Trademark:	Tenda
Product Description:	Wireless N Broadband Router
Model Number:	W308R
File Number:	ES110530147F-1
Date of Test:	May 30, 2011 to June 16, 2011


We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : May 30, 2011 to June 16, 2011

Prepared by : 
(Engineer)

Reviewer : 
(Quality Manager)


Approve & Authorized Signer : 
(Manager)

Table of Contents

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION.....	5
1.2 RELATED SUBMITTAL(S) / GRANT(S).....	5
1.3 TEST METHODOLOGY.....	6
1.4 SPECIAL ACCESSORIES	6
1.5 EQUIPMENT MODIFICATIONS.....	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE.....	7
2.3 TEST PROCEDURE.....	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES.....	9
4. SUMMARY OF TEST RESULTS	10
5. CONDUCTED EMISSIONS TEST.....	11
5.1 MEASUREMENT PROCEDURE.....	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	11
5.3 MEASUREMENT EQUIPMENT USED.....	11
5.4 CONDUCTED EMISSION LIMIT	12
5.5 MEASUREMENT RESULT	12
5.6 CONDUCTED MEASUREMENT PHOTO	13
6. RADIATED EMISSION TEST.....	14
6.1 MEASUREMENT PROCEDURE.....	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3 MEASUREMENT EQUIPMENT USED.....	15
6.4 RADIATED EMISSION LIMIT.....	15
6.5 MEASUREMENT RESULT	16
6.6 RADIATED MEASUREMENT PHOTOS	34
7. OCCUPIED BANDWIDTH TEST.....	35
7.1 MEASUREMENT PROCEDURE.....	35
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	35
7.3 MEASUREMENT EQUIPMENT USED.....	35
7.4 MEASUREMENT RESULTS	35
8. MAXIMUM PEAK OUTPUT POWER TEST	44
8.1 MEASUREMENT PROCEDURE.....	44
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	44
8.3 MEASUREMENT EQUIPMENT USED.....	44
8.4 PEAK POWER OUTPUT LIMIT	44
8.5 MEASUREMENT RESULTS	44

9. BAND EDGE TEST	46
9.1 MEASUREMENT PROCEDURE	46
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	46
9.3 MEASUREMENT EQUIPMENT USED	46
9.4 MEASUREMENT RESULTS	46
10. POWER DENSITY	47
10.1 TEST EQUIPMENT	47
10.2 MEASURING INSTRUMENTS AND SETTING	47
10.3 TEST PROCEDURES	47
10.4 BLOCK DIAGRAM OF TEST SETUP	47
10.5 LIMIT	47
10.6 TEST RESULT	48
11. ANTENNA PORT EMISSION	60
11.1 TEST EQUIPMENT	60
11.2 MEASURING INSTRUMENTS AND SETTING	60
11.3 TEST PROCEDURES	60
11.4 BLOCK DIAGRAM OF TEST SETUP	60
11.5 TEST RESULT	60
12. ANTENNA APPLICATION	64
12.1 ANTENNA REQUIREMENT	64
12.2 RESULT	64

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Standards: IEEE802.11b/g/n
- B). Operation Frequency: 802.11b /g, 802.11n (HT 20): 2412-2462MHz;
802.11n (HT 40): 2422-2452MHz;
- C). Modulation: OFDM, DSSS
DBPSK, DQPSK, CCK, 16QAM, 64QAM
- D). Number of Channel: 802.11b /g /n(HT 20): 11 Channels; 802.11n(HT 40): 7Channels
- E). Data Rate (Max): 802.11b: 11 Mbps
802.11g: 54 Mbps
802.11n: 72.2MHz(HT 20), 150Mbps(HT 40)
- F). Conducted Power: 12.27dBm(802.11b), 15.0dBm(802.11g),
18.45dBm(802.11n, HT20) 18.11dBm(802.11n, HT40)
- G) Antenna Gain: 5dBi
- H). Antenna Assembly: MIMO 2X2 welding Antenna
- I). Power Supply: DC 9V with AC Adapter
- J). Adapter: Input: AC 100-240V, 50/60Hz
Output: DC 9V, 1A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is a Wireless N Broadband Router included 802.11b, 802.11g and 802.11n 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in highest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: V7TW308R filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2009). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description
EMC Lab.

: Accredited by CNAS, 2010.10.29
The certificate is valid until 2013.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm
Site Location

: SHENZHEN EMTEK CO., LTD.
: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Wireless N Broadband Router	N/A	W308R	V7TW308R	N/A	EUT
2.	PC	LENOVO	9702	N/A	L3C4410	
3.	LCD Monitor	LENOVO	9227-AE6	N/A	4M0293084302824	
4.	Keyboard	LENOVO	KU-0225	N/A	0585494	
5.	Mouse	LENOVO	MO28UOL	N/A	44G7862 068	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is a Wireless N Broadband Router and powered by host equipment. The max data rates of this Digital Transmission system (DTS) are 11Mbps (802.11b), 54Mbps(802.11g) &72.2Mbps(802.11n, HT20) 150Mbps(802.11n, HT40).

The equipment enables high-speed access without wires to network assets. This EUT uses the IEEE 802.11b/g/n protocol.

802.11b/g/n(HT20)

1. For lowest channel : 2412MHz (Channel 1)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2462MHz (Channel 11)

802.11n(HT40)

1. For lowest channel : 2422MHz (Channel 3)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2452MHz (Channel 9)

EUT operating conditions:

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to typical use, The exercise sequence is listed as below:

1. Setup the EUT and simulators as shown on 2.4.
2. Turn on the power of all equipments.
3. The EUT Ping with the wireless router.
4. Repeat the above steps.

4. Summary of Test Results


FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Compliant
§15.247(b)(3)	Max Peak output Power test	Compliant
§15.247(e)	Power density	Compliant
§15.247(d)	Band edge test	Compliant
§15.207	AC Power Conducted Emission	Compliant
§15.247(d), §15.209	Radiated Emission	Compliant
§15.203	Antenna Port Emission	Compliant
§15.109	Antenna Application	Compliant

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2011	05/29/2012
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2011	05/29/2012
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2011	05/29/2012
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2011	05/29/2012
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2011	05/29/2012

5.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

- Note:** 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

Date of Test: June 7, 2011 Temperature: 22
 Frequency Detector: 0.15~30MHz Humidity: 50%
 Test Result: PASS Test Mode: WIFI Mode

Test Line	Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Over QP dB(μV)	Over AV dB(μV)
Neutral	0.19	49.60	35.77	64.26	54.26	-14.66	-18.49
	0.57	42.30	30.93	56.00	46.00	-13.70	-15.07
	0.67	43.70	28.99	56.00	46.00	-12.30	-17.01
	0.87	44.60	25.49	56.00	46.00	-11.40	-20.51
	1.58	42.30	25.87	56.00	46.00	-13.70	-20.13
	2.38	45.80	29.73	56.00	46.00	-10.20	-16.27
Line	0.19	53.40	34.31	64.26	54.26	-10.86	-19.95
	0.41	46.70	25.76	57.75	47.75	-11.05	-21.99
	0.56	43.80	25.87	56.00	46.00	-12.20	-20.13
	1.20	45.70	22.56	56.00	46.00	-10.30	-23.44
	1.61	44.60	22.75	56.00	46.00	-11.40	-23.25
	6.73	49.31	24.23	60.00	50.00	-10.69	-25.77

5.6 Conducted Measurement Photo




6. Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Pre-Amplifier	HP	8447D	2944A07999	05/29/2011	05/29/2012
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2011	05/29/2012
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2011	05/29/2012
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/29/2011	05/29/2012
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2011	05/29/2012
Cable	Rosenberger	N/A	FP2RX2	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2011	05/29/2012
Pre-Amplifier	HP	8447D	2944A07999	05/29/2011	05/29/2012

6.4 Radiated Emission Limit

FCC Class B Limit at 3m:

Frequency MHz	Distance Meter	Field Strength uV/m	Field Strength dBuV/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
Above 960	3	500	54.0

Note: The frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above maximum permitted average limit.

6.5 Measurement Result

Operation Mode: 802.11b TX Channel 1 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.65	V	34.97	40	-5.03	PK
37.77	V	34.77	40	-5.23	PK
57.98	V	33.78	40	-6.22	PK
101.51	V	36.64	43.5	-6.86	PK
183.89	V	35.64	43.5	-7.86	PK
499.46	V	35.11	46	-10.89	PK
54.87	H	27.24	40	-12.76	PK
101.51	H	33.01	43.5	-10.49	PK
183.89	H	37.01	43.5	-6.49	PK
249.18	H	39.53	46	-6.47	PK
399.97	H	30.56	46	-15.44	PK
499.46	H	38.07	46	-7.93	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 6 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
31.69	V	34.41	40	-5.59	PK
37.67	V	34.23	40	-5.77	PK
61.55	V	33.54	40	-6.46	PK
97.51	V	36.00	43.5	-7.50	PK
180.93	V	36.17	43.5	-7.33	PK
498.41	V	34.84	46	-11.16	PK
52.60	H	26.71	40	-13.29	PK
98.57	H	33.79	43.5	-9.71	PK
186.29	H	37.51	43.5	-5.99	PK
248.11	H	39.02	46	-6.98	PK
396.00	H	30.73	46	-15.27	PK
496.42	H	37.80	46	-8.20	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 11 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.75	V	33.41	40	-6.59	PK
36.70	V	33.74	40	-6.26	PK
56.73	V	32.73	40	-7.27	PK
103.96	V	34.96	43.5	-8.54	PK
183.84	V	31.8	43.5	-11.70	PK
499.44	V	31.4	46	-14.60	PK
51.44	H	24.58	40	-15.42	PK
102.72	H	34.04	43.5	-9.46	PK
180.26	H	34.4	43.5	-9.10	PK
252.42	H	42.01	46	-3.99	PK
401.39	H	28.68	46	-17.32	PK
522.51	H	37.73	46	-8.27	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 1 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.00	V	35.23	40	-4.77	PK
36.22	V	36.22	40	-3.78	PK
59.54	V	33.23	40	-6.77	PK
101.51	V	36.46	43.5	-7.04	PK
183.89	V	35.84	43.5	-7.66	PK
499.46	V	35.74	46	-10.26	PK
101.51	H	33.34	43.5	-10.16	PK
183.89	H	37.5	43.5	-6	PK
249.18	H	40.45	46	-5.55	PK
298.93	H	29.31	46	-16.69	PK
499.46	H	38.05	46	-7.95	PK
623.81	H	33.21	46	-12.79	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 6 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65%
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.25	V	34.72	40	-5.28	PK
35.87	V	35.17	40	-4.83	PK
63.05	V	33.02	40	-6.98	PK
98.46	V	35.91	43.5	-7.59	PK
181.43	V	35.72	43.5	-7.78	PK
498.41	V	35.66	46	-10.34	PK
99.40	H	32.91	43.5	-10.59	PK
181.41	H	38.16	43.5	-5.34	PK
250.63	H	41.47	46	-4.53	PK
296.88	H	28.26	46	-17.74	PK
495.82	H	38.20	46	-7.80	PK
619.45	H	32.76	46	-13.24	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 11 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.61	V	33.87	40	-6.13	PK
35.17	V	35.1	40	-4.90	PK
57.18	V	31.18	40	-8.82	PK
103.86	V	34.24	43.5	-9.26	PK
183.77	V	32	43.5	-11.50	PK
499.02	V	32.3	46	-13.70	PK
102.87	H	30.68	43.5	-12.82	PK
185.37	H	37.12	43.5	-6.38	PK
245.45	H	37.4	46	-8.60	PK
300.99	H	28.19	46	-17.81	PK
500.21	H	36.69	46	-9.31	PK
639.44	H	32.44	46	-13.56	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

We took 802.11n HT20, HT 40 to test, and the worst operation mode is 802.11n HT20. Test data as the next pages.

Operation Mode: 802.11n TX Channel 1 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.64	V	38.67	40	-1.33	PK
37.77	V	36.57	40	-3.43	PK
98.40	V	41.34	43.5	-2.16	PK
124.82	V	37.57	43.5	-5.93	PK
191.67	V	38.62	43.5	-4.88	PK
499.46	V	39.66	46	-6.34	PK
73.53	H	33.6	40	-6.4	PK
98.40	H	40.44	43.5	-3.06	PK
124.82	H	36.61	43.5	-6.89	PK
191.67	H	38.8	43.5	-4.7	PK
249.18	H	40.04	46	-5.96	PK
499.46	H	41.13	46	-4.87	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX Channel 6 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.00	V	38.20	40	-1.80	PK
36.72	V	35.34	40	-4.66	PK
100.43	V	41.16	43.5	-2.34	PK
121.37	V	37.01	43.5	-6.49	PK
189.56	V	38.26	43.5	-5.24	PK
497.43	V	39.44	46	-6.56	PK
71.08	H	32.86	40	-7.14	PK
95.77	H	41.06	43.5	-2.44	PK
126.26	H	37.62	43.5	-5.88	PK
189.66	H	37.36	43.5	-6.14	PK
245.93	H	40.40	46	-5.60	PK
498.41	H	40.72	46	-5.28	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX Channel 11 Test Date : June 16, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
34.25	V	37.31	40	-2.69	PK
36.72	V	35.32	40	-4.68	PK
96.04	V	39.65	43.5	-3.85	PK
127.17	V	35.35	43.5	-8.15	PK
191.55	V	34.85	43.5	-8.65	PK
499.02	V	36.45	46	-9.55	PK
74.89	H	31.15	40	-8.85	PK
99.88	H	40.22	43.5	-3.28	PK
121.09	H	34.48	43.5	-9.02	PK
193.73	H	37.02	43.5	-6.48	PK
249.93	H	38.5	46	-7.50	PK
515.09	H	40.08	46	-5.92	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX Channel 1 Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3750	V	51.16	34.29	74	54	-22.84	-19.71
5153.84	V	46.62	33.9	74	54	-27.38	-20.1
5250	V	49.09	35.44	74	54	-24.91	-18.56
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3750	H	49.78	33.97	74	54	-24.22	-20.03
4576.92	H	44.52	32.92	74	54	-29.48	-21.08
5250	H	49.46	35.37	74	54	-24.54	-18.63

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX (Channel 6) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3770	V	49.36	33.09	74	54	-24.64	-20.91
5164.19	V	49.07	34.57	74	54	-24.93	-19.43
5228.85	V	52.32	37.24	74	54	-21.68	-16.76
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3760.67	H	53.28	34.83	74	54	-20.72	-19.17
4592.6	H	45.3	30.27	74	54	-28.7	-23.73
5238.77	H	50.69	35.61	74	54	-23.31	-18.39

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11b TX (Channel 11) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3762.35	V	49.66	31.89	74	54	-24.34	-22.11
5162.84	V	46.17	32	74	54	-27.83	-22
5238.66	V	51.43	36	74	54	-22.57	-18
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3758.45	H	54.34	35.43	74	54	-19.66	-18.57
4587.7	H	46.86	33.5	74	54	-27.14	-20.5
5228.66	H	46.43	33.39	74	54	-27.57	-20.61

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX Channel 1 Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3750	V	50.58	33.91	74	54	-23.42	-20.09
5250	V	48.97	35.04	74	54	-25.03	-18.96
6750	V	50.81	37.54	74	54	-23.19	-16.46
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3750	H	49.58	33.7	74	54	-24.42	-20.3
5250	H	49.95	35.21	74	54	-24.05	-18.79
6557.69	H	50.65	37.11	74	54	-23.35	-16.89

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX (Channel 6) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3760.5	V	49.13	32.89	74	54	-24.87	-21.11
5260.05	V	51.09	35.71	74	54	-22.91	-18.29
6729.79	V	54.27	38.99	74	54	-19.73	-15.01
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3752.5	H	51.68	34.54	74	54	-22.32	-19.46
5265.46	H	50.7	32.58	74	54	-23.3	-21.42
6546.51	H	51.86	37.23	74	54	-22.14	-16.77

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11g TX (Channel 11) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3760.05	V	48.93	31.76	74	54	-25.07	-22.24
5255.36	V	48.56	33.2	74	54	-25.44	-20.8
6739.64	V	53.14	38.11	74	54	-20.86	-15.89
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
3758.05	H	54.11	35.13	74	54	-19.89	-18.87
5259.63	H	52.26	35.26	74	54	-21.74	-18.74
6547.46	H	47.6	35.64	74	54	-26.4	-18.36

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

**We took 802.11n HT20, HT 40 to test, and the worst operation mode is 802.11n HT20.
 Test data as the next pages.**

Operation Mode: 802.11n TX Channel 1 Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3750	V	51.03	34.14	74	54	-22.97	-19.86
5250	V	50.82	35.55	74	54	-23.18	-18.45
6519.23	V	49.58	36.87	74	54	-24.42	-17.13
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5250	H	49.06	35.05	74	54	-24.94	-18.95
6519.23	H	49.28	37.16	74	54	-24.72	-16.84
7230.76	H	52.13	39.15	74	54	-21.87	-14.85

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX (Channel 6) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3765.36	V	49.29	32.79	74	54	-24.71	-21.21
5267.26	V	51.84	35.91	74	54	-22.16	-18.09
6498.98	V	51.63	38.64	74	54	-22.37	-15.36
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5262.03	H	52.08	35.79	74	54	-21.92	-18.21
6523.25	H	49.99	36.13	74	54	-24.01	-17.87
7229.71	H	53.45	39.6	74	54	-20.55	-14.4

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

Operation Mode: 802.11n TX (Channel 11) Test Date : June 16, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3755.02	V	49.62	33.12	74	54	-24.38	-20.88
5253.05	V	50.46	33.15	74	54	-23.54	-20.85
6509.16	V	51.68	37.32	74	54	-22.32	-16.68
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5258.11	H	52.11	36.3	74	54	-21.89	-17.7
6528.59	H	50.4	37.67	74	54	-23.6	-16.33
7222.41	H	51.11	37.7	74	54	-22.89	-16.3

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 - (4) EUT lying on the table position is the worst case result in the report.

6.6 Radiated Measurement Photos




7. Occupied Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g/n mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2011	05/29/2012



7.4 Measurement Results

6 Bandwidth Test Data Chart:
Refer to attached data chart.

Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11b

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	9.25	>500
6	2437	9.37	>500
11	2462	9.12	>500







Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 g


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	16.00	>500
6	2437	16.50	>500
11	2462	16.00	>500







Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n (H20)


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	17.00	>500
6	2437	16.88	>500
11	2462	17.00	>500







Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n (H40)

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2423	36.25	>500
6	2447	36.00	>500
11	2452	36.63	>500





Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11g

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	15.00	1W(30dBm)	PASS
6	2437.00	14.78	1W(30dBm)	PASS
11	2462.00	14.70	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11n(HT20)

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)			Peak Power Limit(W)	Pass/Fail
		Chain 0	Chain 1	total		
1	2412.00	14.96	15.87	18.45	1W(30dBm)	PASS
6	2437.00	14.67	15.63	18.19	1W(30dBm)	PASS
11	2462.00	14.73	15.91	18.37	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11n(HT40)

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)			Peak Power Limit(W)	Pass/Fail
		Chain 0	Chain 1	total		
3	2422.00	14.23	15.34	17.83	1W(30dBm)	PASS
6	2437.00	14.57	15.48	18.06	1W(30dBm)	PASS
9	2452.00	14.45	15.67	18.11	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Spectrum Detector: PK/AV Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test channel: 01 Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2395.89	H	49.37	38.01	74	54
2394.56	V	48.22	38.56	74	54

Spectrum Detector: PK/AV Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test channel: 11 Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2484.54	H	49.38	39.45	74	54
2483.75	V	48.25	39.16	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2011	05/29/2012

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	300kHz
RB	3kHz
VB	30kHz
Detector	Peak
Trace	Max hold
Sweep Time	100s

10.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 3 kHz and VBW to 30 kHz, Set Detector to Peak, Trace to Max Hold.
- Mark the frequency with maximum peak power as the center of the display of the spectrum.
- Set the span to 300 kHz and the sweep time to 100s and record the maximum peak value.

10.4 Block Diagram of Test Setup



10.5 Limit


The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.



For IEEE802.11n mode, it's MIMO technology, so account total power density by add each chain's power density.

10.6 Test Result

Spectrum Detector:	PK	Test Date :	June 7, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11 b		


Channel number	Measurement Level (dBm)	Required Limit (dBm)	Result
1	-11.96	<8dBm	PASS
6	-12.88	<8dBm	PASS
11	-12.32	<8dBm	PASS







Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 g

Channel number	Measurement Level (dBm)	Required Limit (dBm)	Result
1	-15.15	<8dBm	PASS
6	-14.46	<8dBm	PASS
11	-15.19	<8dBm	PASS








Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n (HT20)


Channel number	Measurement Level (dBm)			Required Limit (dBm)	Result
	Chain 0	Chain 1	Total		
1	-15.72	-12.10	-10.53	<8dBm	PASS
6	-15.00	-12.21	-10.37	<8dBm	PASS
11	-15.10	-12.23	-10.42	<8dBm	PASS

Chain 0 test plots:





Chain 1 test plots:









Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 n(HT40)

Channel number	Measurement Level (dBm)			Required Limit (dBm)	Result
	Chain 0	Chain 1	Total		
3	-18.26	-16.50	-14.28	<8dBm	PASS
6	-22.61	-14.73	-14.07	<8dBm	PASS
9	-18.66	-16.10	-14.18	<8dBm	PASS


Chain 0 test plots:









Chain 1 test plots:





11. Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/29/2011	05/29/2012

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Wireless N Broadband Router, and hi channels, The limit was determined by attenuation 20dB of the RF peak power output.

11.4 Block Diagram of Test setup



11.5 Test Result



PASS.

All the modes have been tested , the worst test data 802.11b was recorded in the next pages.



802.11b Low Channel 1



802.11b Mid Channel 6



802.11g High Channel 11



12. Antenna Application

12.1 Antenna Requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

12.2 Result

The EUT'S antenna is welding Antenna. If user remove the antenna, can cause damage to the EUT!
The antenna's gain is 5dBi and meets the requirement.

