



A D T

# FCC TEST REPORT

**REPORT NO.:** RF110922C37

**MODEL NO.:** W326U

**FCC ID:** V7TW326U

**RECEIVED:** Sep. 22, 2011

**TESTED:** Oct. 03 to 27, 2011

**ISSUED:** Nov. 10, 2011

**APPLICANT:** SHENZHEN TENDA TECHNOLOGY  
CO.,LTD.

**ADDRESS:** Tenda Industrial Park, No. 34-1, Shilong  
Rd., Shiyan Town, Bao'an District,  
Shenzhen, P.R.China 518108

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS :** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

**TEST LOCATION (1):** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

**TEST LOCATION (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 79 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

## Table of Contents

RELEASE CONTROL RECORD .....	4
1. CERTIFICATION .....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY .....	7
3. GENERAL INFORMATION .....	8
3.1 GENERAL DESCRIPTION OF EUT .....	8
3.2 DESCRIPTION OF TEST MODES .....	9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	10
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
3.4 DESCRIPTION OF SUPPORT UNITS.....	13
3.5 CONFIGURATION OF SYSTEM UNDER TEST .....	13
4. TEST TYPES AND RESULTS .....	14
4.1 CONDUCTED EMISSION MEASUREMENT .....	14
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	14
4.1.2 TEST INSTRUMENTS.....	14
4.1.3 TEST PROCEDURES .....	15
4.1.4 DEVIATION FROM TEST STANDARD .....	15
4.1.5 TEST SETUP .....	16
4.1.6 EUT OPERATING CONDITIONS .....	16
4.1.7 TEST RESULTS .....	17
4.2 RADIATED EMISSION MEASUREMENT .....	19
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	19
4.2.2 TEST INSTRUMENTS.....	19
4.2.3 TEST PROCEDURES .....	22
4.2.4 DEVIATION FROM TEST STANDARD .....	22
4.2.5 TEST SETUP .....	23
4.2.6 EUT OPERATING CONDITIONS .....	23
4.2.7 TEST RESULTS .....	24
4.3 6dB BANDWIDTH MEASUREMENT .....	53
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	53
4.3.2 TEST INSTRUMENTS.....	53
4.3.3 TEST PROCEDURE.....	53
4.3.4 DEVIATION FROM TEST STANDARD .....	53
4.3.5 TEST SETUP .....	53
4.3.6 EUT OPERATING CONDITIONS .....	53
4.3.7 TEST RESULTS .....	54
4.4 MAXIMUM PEAK OUTPUT POWER.....	58
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	58
4.4.2 INSTRUMENTS.....	58
4.4.3 TEST PROCEDURES .....	58



A D T

4.4.4	DEVIATION FROM TEST STANDARD .....	58
4.4.5	TEST SETUP .....	58
4.4.6	EUT OPERATING CONDITIONS .....	58
4.4.7	TEST RESULTS .....	59
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	60
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	60
4.5.2	TEST INSTRUMENTS.....	60
4.5.3	TEST PROCEDURE.....	60
4.5.4	DEVIATION FROM TEST STANDARD .....	60
4.5.5	TEST SETUP .....	60
4.5.6	EUT OPERATING CONDITION.....	60
4.5.7	TEST RESULTS .....	61
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT .....	65
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	65
4.6.2	TEST INSTRUMENTS.....	65
4.6.3	TEST PROCEDURE.....	65
4.6.4	DEVIATION FROM TEST STANDARD .....	65
4.6.5	EUT OPERATING CONDITION .....	65
4.6.6	TEST RESULTS .....	65
5.	INFORMATION ON THE TESTING LABORATORIES .....	78
6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	79



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF110922C37	Original release	Nov. 10, 2011



A D T

## 1. CERTIFICATION

**PRODUCT:** 300M Mbps Wireless USB Adapter  
**BRAND NAME:** Tenda  
**MODEL NO.:** W326U  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**APPLICANT:** SHENZHEN TENDA TECHNOLOGY CO.,LTD.  
**TESTED:** Oct. 03 to 27, 2011  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.4-2003  
ANSI C63.10-2009

The above equipment (Model: W326U) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** :  , **DATE:** Nov. 10, 2011  
( Lori Chung, Specialist )

**APPROVED BY** :  , **DATE:** Nov. 10, 2011  
( May Chen, Deputy Manager )

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: FCC Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>Remark</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -24.26dB at 0.357MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -0.9dB at 4824.00MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.81 dB
Radiated emissions (1GHz -18GHz)	2.19 dB
Radiated emissions (18GHz -40GHz)	2.56 dB



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	300M Mbps Wireless USB Adapter
<b>MODEL NO.</b>	W326U
<b>FCC ID</b>	V7TW326U
<b>POWER SUPPLY</b>	DC 5V from host equipment
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: up to 11Mbps. 802.11g: up to 54Mbps. 802.11n: up to 300Mbps.
<b>OPERATING FREQUENCY</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	For 802.11b, 802.11g, 802.11n (20MHz) : 11 For 802.11n (40MHz) : 7
<b>MAXIMUM OUTPUT POWER</b>	802.11b: 11.0mW 802.11g: 7.9mW 802.11n (20MHz): 8.8mW 802.11n (40MHz): 6.9mW
<b>ANTENNA TYPE</b>	Chip antenna with 1dBi antenna gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT is 2 \* 2 spatial MIMO (2Tx & 2Rx) without beam forming function.
2. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.





A D T

### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



A D T

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
	√	√	√	√	√	

Where **PLC**: Power Line Conducted Emission      **RE < 1G**: Radiated Emission below 1GHz  
**RE ≥ 1G**: Radiated Emission above 1GHz      **APCM**: Antenna Port Conducted Measurement  
**OB**: Conducted Out-Band Emission Measurement

### ANTENNA COMBINATION MODE:

COMBINATION MODE	OPERATION MODE	TX CHAIN(0)	TX CHAIN(1)
A	802.11 b	√	
B	802.11 g	√	
C	802.11n(20MHz)	√	
D	802.11n(20MHz)	√	√
E	802.11n(40MHz)	√	
F	802.11n(40MHz)	√	√

Note:  
The above information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.  
2. Mode A, B, D, F the worst modes, were selected as representative mode for the report.

### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1	DSSS	DBPSK	6	A



A D T

#### **RADIATED EMISSION TEST (BELOW 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1	DSSS	DBPSK	6	A

#### **RADIATED EMISSION TEST (ABOVE 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	D
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	F

#### **ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	D
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	F



A D T

**CONDUCTED OUT-BAND EMISSION MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	B
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	D
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	F

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
PLC	25deg. C, 67%RH	120Vac, 60Hz	Frank Liu
RE <sup>3</sup> 1G	25deg. C, 69%RH	120Vac, 60Hz	Amos Chuang
RE<1G	24deg. C, 66%RH	120Vac, 60Hz	Nelson Teng
APCM	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu
OB	25deg. C, 60%RH	120Vac, 60Hz	Frank Liu

**3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4-2003**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

### 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	I-Pod	Apple	MC749TA/A	CC4DMFJUDFDM	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	0.1m USB cable

**NOTE:** All power cords of the above support units are non shielded (1.8m).

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST



## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

Test date: Oct. 27, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 09, 2011	Mar. 08, 2012
Line-Impedance Stabilization Network (for EUT)	ENV216	100072	June 10, 2011	June 09, 2012
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Nov. 03, 2010	Nov. 02, 2011
RF Cable (JYEBAO)	5DFB	COCCAB-002	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	3	Nov. 03, 2010	Nov. 02, 2011
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.



A D T


#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of all equipment.
2. The notebook computer ran test program "RT3x7xQA.exe" to enable EUT under transmission/receiving condition continuously at specific channel frequency.




### 4.1.7 TEST RESULTS

<b>PHASE</b>	Line (L)	<b>6dB BANDWIDTH</b>	9 kHz
--------------	----------	----------------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.09	28.35	22.12	28.44	22.21	66.00	56.00	-37.56	-33.79
2	0.209	0.10	27.02	22.29	27.12	22.39	63.26	53.26	-36.14	-30.87
<b>3</b>	<b>0.357</b>	<b>0.11</b>	<b>31.02</b>	<b>24.43</b>	<b>31.13</b>	<b>24.54</b>	<b>58.80</b>	<b>48.80</b>	<b>-27.67</b>	<b>-24.26</b>
4	2.195	0.21	28.59	20.48	28.80	20.69	56.00	46.00	-27.20	-25.31
5	3.348	0.28	26.74	17.58	27.02	17.86	56.00	46.00	-28.98	-28.14
6	17.852	0.73	24.05	17.65	24.78	18.38	60.00	50.00	-35.22	-31.62


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Emission level - Limit value
  4. Correction factor = Insertion loss + Cable loss
  5. Emission Level = Correction Factor + Reading Value.



<b>PHASE</b>	Neutral (N)	<b>6dB BANDWIDTH</b>	9 kHz
--------------	-------------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.07	26.66	19.82	26.73	19.89	66.00	56.00	-39.27	-36.11
2	0.365	0.11	26.40	22.76	26.51	22.87	58.62	48.62	-32.11	-25.75
3	1.598	0.15	27.19	19.09	27.34	19.24	56.00	46.00	-28.66	-26.76
4	1.910	0.17	28.28	18.02	28.45	18.19	56.00	46.00	-27.55	-27.81
5	3.535	0.22	26.76	19.77	26.98	19.99	56.00	46.00	-29.02	-26.01
6	20.570	0.67	24.94	19.37	25.61	20.04	60.00	50.00	-34.39	-29.96

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Emission level - Limit value
  4. Correction factor = Insertion loss + Cable loss
  5. Emission Level = Correction Factor + Reading Value.



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. Section 15.205 restricted bands of operation shall compliance with the limits in Section 15.209.

### 4.2.2 TEST INSTRUMENTS

Same as 4.1.6



A D T

<For Frequency Range below 1GHz>Test Date: Oct. 03, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250254	July 12, 2011	July 11, 2012
Agilent Pre-Selector	N9039A	MY46520311	July 12, 2011	July 11, 2012
Agilent Signal Generator	N5181A	MY49060517	July 12, 2011	July 11, 2012
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-03	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02578	July 04, 2011	July 03, 2012
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	Nov. 16, 2010	Nov. 15, 2011
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-360	Apr. 14, 2011	Apr. 13, 2012
AISI Horn_Antenna	AIH.8018	000032009111 0	Nov. 12, 2010	Nov. 11, 2011
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-201 RF104-203 RF104-204	Dec. 27, 2010	Dec. 26, 2011
RF Cable	NA	CHGCAB_001	Oct. 12, 2010	Oct. 11, 2011
Software	ADT_Radiated_ V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

3. The test was performed in 966 Chamber No. G.

4. The FCC Site Registration No. is 966073.

5. The VCCI Site Registration No. is G-137.

6. The CANADA Site Registration No. is IC 7450H-2.



A D T

<For Frequency Range above 1GHz>Test Date: Oct. 25, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250253	Aug. 29, 2011	Aug. 28, 2012
Agilent Pre-Selector	N9039A	MY46520310	Aug. 29, 2011	Aug. 28, 2012
Agilent Signal Generator	N5181A	MY49060347	July 25, 2011	July 24, 2012
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02465	Feb. 28, 2011	Feb. 27, 2012
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	Nov. 16, 2010	Nov. 15, 2011
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Apr. 14, 2011	Apr. 13, 2012
AISI Horn_Antenna	AIH.8018	0000220091110	Nov. 22, 2010	Nov. 21, 2011
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 07, 2011	Oct. 06, 2012
RF CABLE	NA	RF104-205 RF104-207 RF104-202	Dec. 28, 2010	Dec. 27, 2011
RF Cable	NA	CHHCAB_001	Oct. 08, 2011	Oct. 07, 2012
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
3. The test was performed in 966 Chamber No. H.  
4. The FCC Site Registration No. is 797305.  
5. The CANADA Site Registration No. is IC 7450H-3.

### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room test site for below 1GHz test and at a 10 meter Chamber room for above 1GHz test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

## 4.2.7 TEST RESULTS

### BELOW 1GHz WORST-CASE DATA : 802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 66%RH	TESTED BY	Nelson Teng

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.96	29.6 QP	46.0	-16.4	1.25 H	0	16.72	12.88
2	480.01	27.1 QP	46.0	-18.9	1.75 H	334	7.59	19.47
3	599.97	29.7 QP	46.0	-16.3	1.50 H	148	7.54	22.15
4	698.97	32.2 QP	46.0	-13.8	1.00 H	234	9.64	22.58
5	846.64	35.2 QP	46.0	-10.9	1.00 H	205	9.33	25.82
6	959.97	38.0 QP	46.0	-8.0	1.25 H	301	11.02	26.97
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	166.30	27.4 QP	43.5	-16.1	1.00 V	261	13.18	14.21
2	299.06	30.0 QP	46.0	-16.0	2.00 V	30	14.82	15.14
3	599.38	29.3 QP	46.0	-16.7	1.00 V	259	7.20	22.14
4	701.46	32.3 QP	46.0	-13.7	1.50 V	282	9.71	22.62
5	898.04	34.1 QP	46.0	-11.9	1.25 V	119	7.60	26.47
6	959.97	30.7 QP	46.0	-15.3	1.50 V	212	3.70	26.97

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.





A D T

**ABOVE 1GHz WORST-CASE DATA**

**802.11b DSSS MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	1.00 H	114	24.87	31.83
2	2390.00	44.4 AV	54.0	-9.6	1.00 H	114	12.57	31.83
3	*2412.00	103.6 PK			1.00 H	113	71.71	31.89
4	*2412.00	101.3 AV			1.00 H	113	69.41	31.89
5	4824.00	56.3 PK	74.0	-17.7	1.36 H	69	15.86	40.44
6	<b>4824.00</b>	<b>53.1 AV</b>	<b>54.0</b>	<b>-0.9</b>	<b>1.36 H</b>	<b>69</b>	<b>12.66</b>	<b>40.44</b>

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.5 PK	74.0	-17.5	1.00 V	247	24.67	31.83
2	2390.00	43.9 AV	54.0	-10.1	1.00 V	247	12.07	31.83
3	*2412.00	99.3 PK			1.00 V	248	67.41	31.89
4	*2412.00	96.9 AV			1.00 V	248	65.01	31.89
5	4824.00	53.3 PK	74.0	-20.7	1.05 V	258	12.86	40.44
6	4824.00	47.8 AV	54.0	-6.2	1.05 V	258	7.36	40.44

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.9 PK			1.00 H	111	72.94	31.96
2	*2437.00	102.7 AV			1.00 H	111	70.74	31.96
3	4874.00	55.6 PK	74.0	-18.4	1.34 H	70	14.92	40.68
4	4874.00	51.7 AV	54.0	-2.3	1.34 H	70	11.02	40.68
5	7311.00	52.3 PK	74.0	-21.7	1.00 H	35	7.07	45.23
6	7311.00	39.9 AV	54.0	-14.1	1.00 H	35	-5.33	45.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.2 PK			1.00 V	250	67.24	31.96
2	*2437.00	96.7 AV			1.00 V	250	64.74	31.96
3	4874.00	53.1 PK	74.0	-20.9	1.02 V	258	12.42	40.68
4	4874.00	47.2 AV	54.0	-6.8	1.02 V	258	6.52	40.68
5	7311.00	53.4 PK	74.0	-20.6	1.00 V	99	8.17	45.23
6	7311.00	39.8 AV	54.0	-14.2	1.00 V	99	-5.43	45.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.8 PK			1.00 H	111	71.76	32.04
2	*2462.00	101.6 AV			1.00 H	111	69.56	32.04
3	2483.50	56.0 PK	74.0	-18.0	1.00 H	110	23.90	32.10
4	2483.50	43.9 AV	54.0	-10.1	1.00 H	110	11.80	32.10
5	4924.00	52.8 PK	74.0	-21.2	1.35 H	69	11.89	40.91
6	4924.00	46.8 AV	54.0	-7.2	1.35 H	69	5.89	40.91
7	7386.00	52.2 PK	74.0	-21.8	1.00 H	34	6.84	45.36
8	7386.00	39.7 AV	54.0	-14.3	1.00 H	34	-5.66	45.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.9 PK			1.00 V	244	66.86	32.04
2	*2462.00	96.5 AV			1.00 V	244	64.46	32.04
3	2483.61	57.2 PK	74.0	-16.8	1.00 V	244	25.10	32.10
4	2483.61	43.9 AV	54.0	-10.1	1.00 V	244	11.80	32.10
5	4924.00	51.7 PK	74.0	-22.3	1.02 V	259	10.79	40.91
6	4924.00	44.1 AV	54.0	-9.9	1.02 V	259	3.19	40.91
7	7386.00	54.8 PK	74.0	-19.2	1.00 V	93	9.44	45.36
8	7386.00	42.9 AV	54.0	-11.1	1.00 V	93	-2.46	45.36

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11b MODE, CH1, HORIZONTAL )







A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, VERTICAL )



RESTRICTED BANDEDGE (802.11b MODE, CH11, HORIZONTAL )



RESTRICTED BANDEDGE (802.11b MODE, CH11, VERTICAL )





A D T

**802.11g OFDM MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.00 H	111	25.07	31.83
2	2390.00	44.7 AV	54.0	-9.3	1.00 H	111	12.87	31.83
3	*2412.00	104.8 PK			1.00 H	112	72.91	31.89
4	*2412.00	94.9 AV			1.00 H	112	63.01	31.89
5	4824.00	45.8 PK	74.0	-28.2	1.02 H	51	5.36	40.44
6	4824.00	34.1 AV	54.0	-19.9	1.02 H	51	-6.34	40.44

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.00 V	248	25.17	31.83
2	2390.00	44.3 AV	54.0	-9.7	1.00 V	248	12.47	31.83
3	*2412.00	99.6 PK			1.00 V	248	67.71	31.89
4	*2412.00	89.7 AV			1.00 V	248	57.81	31.89
5	4824.00	46.1 PK	74.0	-27.9	1.00 V	160	5.66	40.44
6	4824.00	33.8 AV	54.0	-20.2	1.00 V	160	-6.64	40.44

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	105.0 PK			1.00 H	111	73.04	31.96
2	*2437.00	94.6 AV			1.00 H	111	62.64	31.96
3	4874.00	47.1 PK	74.0	-26.9	1.00 H	56	6.42	40.68
4	4874.00	34.4 AV	54.0	-19.6	1.00 H	56	-6.28	40.68
5	7311.00	54.0 PK	74.0	-20.0	1.04 H	63	8.77	45.23
6	7311.00	41.1 AV	54.0	-12.9	1.04 H	63	-4.13	45.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.0 PK			1.00 V	246	68.04	31.96
2	*2437.00	89.4 AV			1.00 V	246	57.44	31.96
3	4874.00	46.9 PK	74.0	-27.1	1.00 V	166	6.22	40.68
4	4874.00	34.1 AV	54.0	-19.9	1.00 V	166	-6.58	40.68
5	7311.00	53.2 PK	74.0	-20.8	1.12 V	173	7.97	45.23
6	7311.00	41.1 AV	54.0	-12.9	1.12 V	173	-4.13	45.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.6 PK			1.00 H	110	71.56	32.04
2	*2462.00	93.3 AV			1.00 H	110	61.26	32.04
3	2483.50	57.4 PK	74.0	-16.6	1.10 H	109	25.30	32.10
4	2483.50	44.0 AV	54.0	-10.0	1.10 H	109	11.90	32.10
5	4924.00	46.5 PK	74.0	-27.5	1.03 H	70	5.59	40.91
6	4924.00	34.1 AV	54.0	-19.9	1.03 H	70	-6.81	40.91
7	7386.00	53.6 PK	74.0	-20.4	1.02 H	76	8.24	45.36
8	7386.00	40.6 AV	54.0	-13.4	1.02 H	76	-4.76	45.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.0 PK			1.00 V	244	66.96	32.04
2	*2462.00	88.9 AV			1.00 V	244	56.86	32.04
3	2483.50	57.3 PK	74.0	-16.7	1.00 V	244	25.20	32.10
4	2483.50	43.9 AV	54.0	-10.1	1.00 V	244	11.80	32.10
5	4924.00	46.8 PK	74.0	-27.2	1.03 V	163	5.89	40.91
6	4924.00	34.0 AV	54.0	-20.0	1.03 V	163	-6.91	40.91
7	7386.00	53.6 PK	74.0	-20.4	1.17 V	162	8.24	45.36
8	7386.00	41.6 AV	54.0	-12.4	1.17 V	162	-3.76	45.36

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH1, HORIZONTAL )





RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL )



RESTRICTED BANDEDGE (802.11g MODE, CH11, HORIZONTAL )



RESTRICTED BANDEDGE (802.11g MODE, CH11, VERTICAL )





A D T

**802.11n (20MHz) OFDM MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.00 H	112	24.77	31.83
2	2390.00	44.7 AV	54.0	-9.3	1.00 H	112	12.87	31.83
3	*2412.00	104.5 PK			1.00 H	113	72.61	31.89
4	*2412.00	94.5 AV			1.00 H	113	62.61	31.89
5	4824.00	47.3 PK	74.0	-26.7	1.05 H	50	6.86	40.44
6	4824.00	34.6 AV	54.0	-19.4	1.05 H	50	-5.84	40.44
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	1.00 V	245	24.77	31.83
2	2390.00	44.0 AV	54.0	-10.0	1.00 V	245	12.17	31.83
3	*2412.00	100.7 PK			1.00 V	244	68.81	31.89
4	*2412.00	90.2 AV			1.00 V	244	58.31	31.89
5	4824.00	46.6 PK	74.0	-27.4	1.03 V	148	6.16	40.44
6	4824.00	34.2 AV	54.0	-19.8	1.03 V	148	-6.24	40.44

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.7 PK			1.00 H	111	72.74	31.96
2	*2437.00	94.1 AV			1.00 H	111	62.14	31.96
3	4874.00	47.0 PK	74.0	-27.0	1.02 H	71	6.32	40.68
4	4874.00	34.1 AV	54.0	-19.9	1.02 H	71	-6.58	40.68
5	7311.00	53.4 PK	74.0	-20.6	1.06 H	55	8.17	45.23
6	7311.00	40.8 AV	54.0	-13.2	1.06 H	55	-4.43	45.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	98.0 PK			1.00 V	242	66.04	31.96
2	*2437.00	88.6 AV			1.00 V	242	56.64	31.96
3	4874.00	47.0 PK	74.0	-27.0	1.04 V	159	6.32	40.68
4	4874.00	34.4 AV	54.0	-19.6	1.04 V	159	-6.28	40.68
5	7311.00	53.0 PK	74.0	-21.0	1.12 V	183	7.77	45.23
6	7311.00	40.6 AV	54.0	-13.4	1.12 V	183	-4.63	45.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.3 PK			1.00 H	112	71.26	32.04
2	*2462.00	93.0 AV			1.00 H	112	60.96	32.04
3	2483.50	57.0 PK	74.0	-17.0	1.00 H	111	24.90	32.10
4	2483.50	44.2 AV	54.0	-9.8	1.00 H	111	12.10	32.10
5	4924.00	46.9 PK	74.0	-27.1	1.02 H	55	5.99	40.91
6	4924.00	34.6 AV	54.0	-19.4	1.02 H	55	-6.31	40.91
7	7386.00	53.7 PK	74.0	-20.3	1.03 H	86	8.34	45.36
8	7386.00	40.8 AV	54.0	-13.2	1.03 H	86	-4.56	45.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	97.7 PK			1.00 V	239	65.66	32.04
2	*2462.00	88.2 AV			1.00 V	239	56.16	32.04
3	2483.50	56.8 PK	74.0	-17.2	1.00 V	239	24.70	32.10
4	2483.50	43.9 AV	54.0	-10.1	1.00 V	239	11.80	32.10
5	4924.00	46.9 PK	74.0	-27.1	1.01 V	169	5.99	40.91
6	4924.00	34.3 AV	54.0	-19.7	1.01 V	169	-6.61	40.91
7	7386.00	53.9 PK	74.0	-20.1	1.17 V	165	8.54	45.36
8	7386.00	42.0 AV	54.0	-12.0	1.17 V	165	-3.36	45.36

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL )





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL )





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, HORIZONTAL )





A D T

RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL )





A D T

**802.11n (40MHz) OFDM MODULATION**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	1.00 H	110	35.87	31.83
2	2390.00	45.4 AV	54.0	-8.6	1.00 H	110	13.57	31.83
3	*2422.00	101.2 PK			1.00 H	112	69.28	31.92
4	*2422.00	91.1 AV			1.00 H	112	59.18	31.92
5	4844.00	46.9 PK	74.0	-27.1	1.00 H	80	6.36	40.54
6	4844.00	33.9 AV	54.0	-20.1	1.00 H	80	-6.64	40.54
7	7266.00	53.3 PK	74.0	-20.7	1.12 H	62	8.12	45.18
8	7266.00	40.7 AV	54.0	-13.3	1.12 H	62	-4.48	45.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.4 PK	74.0	-8.6	1.00 V	249	33.57	31.83
2	2390.00	44.6 AV	54.0	-9.4	1.00 V	249	12.77	31.83
3	*2422.00	95.8 PK			1.00 V	249	63.88	31.92
4	*2422.00	86.3 AV			1.00 V	249	54.38	31.92
5	4844.00	46.9 PK	74.0	-27.1	1.00 V	174	6.36	40.54
6	4844.00	34.4 AV	54.0	-19.6	1.00 V	174	-6.14	40.54
7	7266.00	52.5 PK	74.0	-21.5	1.18 V	179	7.32	45.18
8	7266.00	40.1 AV	54.0	-13.9	1.18 V	179	-5.08	45.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.4 PK			1.00 H	112	68.44	31.96
2	*2437.00	90.7 AV			1.00 H	112	58.74	31.96
3	4874.00	46.5 PK	74.0	-27.5	1.00 H	59	5.82	40.68
4	4874.00	34.2 AV	54.0	-19.8	1.00 H	59	-6.48	40.68
5	7311.00	53.9 PK	74.0	-20.1	1.04 H	101	8.67	45.23
6	7311.00	41.2 AV	54.0	-12.8	1.04 H	101	-4.03	45.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	95.4 PK			1.00 V	254	63.44	31.96
2	*2437.00	85.7 AV			1.00 V	254	53.74	31.96
3	4874.00	46.5 PK	74.0	-27.5	1.04 V	180	5.82	40.68
4	4874.00	33.8 AV	54.0	-20.2	1.04 V	180	-6.88	40.68
5	7311.00	54.3 PK	74.0	-19.7	1.17 V	151	9.07	45.23
6	7311.00	42.2 AV	54.0	-11.8	1.17 V	151	-3.03	45.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH	TESTED BY	Amos Chuang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	99.6 PK			1.00 H	110	67.59	32.01
2	*2452.00	90.2 AV			1.00 H	110	58.19	32.01
3	2483.50	66.8 PK	74.0	-7.2	1.00 H	111	34.70	32.10
4	2483.50	45.0 AV	54.0	-9.0	1.00 H	111	12.90	32.10
5	4904.00	47.6 PK	74.0	-26.4	1.00 H	73	6.77	40.83
6	4904.00	34.3 AV	54.0	-19.7	1.00 H	73	-6.53	40.83
7	7356.00	52.6 PK	74.0	-21.4	1.11 H	54	7.29	45.31
8	7356.00	40.2 AV	54.0	-13.8	1.11 H	54	-5.11	45.31
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	95.6 PK			1.00 V	251	63.59	32.01
2	*2452.00	85.5 AV			1.00 V	251	53.49	32.01
3	2483.50	64.7 PK	74.0	-9.3	1.00 V	251	32.60	32.10
4	2483.50	44.5 AV	54.0	-9.5	1.00 V	251	12.40	32.10
5	4904.00	46.3 PK	74.0	-27.7	1.00 V	161	5.47	40.83
6	4904.00	34.0 AV	54.0	-20.0	1.00 V	161	-6.83	40.83
7	7356.00	52.7 PK	74.0	-21.3	1.17 V	179	7.39	45.31
8	7356.00	40.2 AV	54.0	-13.8	1.17 V	179	-5.11	45.31



- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.





A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, HORIZONTAL )







A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, VERTICAL )





RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, HORIZONTAL )





A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, VERTICAL )



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Test date: Oct. 27, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.3.7 TEST RESULTS

#### 802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.14	0.5	PASS
6	2437	9.07	0.5	PASS
11	2462	8.69	0.5	PASS

CH1






A D T

### 802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.13	0.5	PASS
6	2437	15.75	0.5	PASS
11	2462	15.87	0.5	PASS

CH1






A D T

**802.11n (20MHz) OFDM MODULATION:**

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)		
1	2412	16.33	15.38	0.5	PASS
6	2437	16.02	15.14	0.5	PASS
11	2462	16.33	15.22	0.5	PASS

For CHAIN(0)  
CH1








A D T

### 802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)		
3	2422	35.27	35.24	0.5	PASS
6	2437	35.31	34.01	0.5	PASS
9	2452	35.30	35.28	0.5	PASS

For CHAIN(0)  
CH6



#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 INSTRUMENTS

Test date: Oct. 27, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Peak Power Meter	ML2495A	0824006	May 04, 2011	May 03, 2012
Power Sensor	MA2411B	0738172	May 03, 2011	May 02, 2012

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


##### 4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

##### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

##### 4.4.5 TEST SETUP



##### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



A D T

#### 4.4.7 TEST RESULTS

##### 802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	11.0	10.4	30	PASS
6	2437	9.3	9.7	30	PASS
11	2462	7.9	9.0	30	PASS

##### 802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	7.8	8.9	30	PASS
6	2437	7.9	9.0	30	PASS
11	2462	6.5	8.1	30	PASS

##### 802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2412	9.1	-1.9	8.8	9.4	30	PASS
6	2437	7.9	-2.0	6.8	8.3	30	PASS
11	2462	7.7	-3.8	6.3	8.0	30	PASS

##### 802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
3	2422	7.7	-2.4	6.5	8.1	30	PASS
6	2437	7.8	-3.0	6.5	8.1	30	PASS
9	2452	7.9	-1.6	6.9	8.4	30	PASS

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Test date: Oct. 25, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.5.5 TEST SETUP



### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




A D T

### 4.5.7 TEST RESULTS

#### 802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-16.2	8	PASS
6	2437	-16.5	8	PASS
11	2462	-17.4	8	PASS

CH1






A D T

### 802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz )	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-19.3	8	PASS
6	2437	-19.9	8	PASS
11	2462	-20.6	8	PASS

CH1






A D T

### 802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
1	2412	-20.0	-32.9	-19.8	8	PASS
6	2437	-20.3	-32.0	-20.0	8	PASS
11	2462	-21.2	-33.4	-20.9	8	PASS

For CHAIN(0)  
CH1






A D T

### 802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
3	2422	-20.1	-36.0	-20.0	8	PASS
6	2437	-20.4	-36.4	-20.3	8	PASS
9	2452	-20.9	-35.3	-20.7	8	PASS

For CHAIN(0)  
CH3





## 4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

**Test date: Oct. 27, 2011**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100MHz or 200MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.6.5 EUT OPERATING CONDITION



Same as Item 4.3.6

### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

## 802.11b DSSS MODULATION:


CH1






A D T

# CH11



A D T





A D T



A D T

## 802.11g OFDM MODULATION:



CH1





A D T



# CH11



### 802.11n (20MHz) OFDM MODULATION:

For Chain(0)



CH1





A D T



# For Chain(0) CH11





A D T

# For Chain(1) CH1









A D T



# For Chain(1) CH11



### 802.11n (40MHz) OFDM MODULATION:

For Chain(0)



CH3





A D T



# For Chain(0) CH9





A D T



# For Chain(1) CH3





A D T

# For Chain(1) CH9





## 5. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5.phtml](http://www.adt.com.tw/index.5.phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**  
Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**  
Tel: 886-3-3183232  
Fax: 886-3-3185050

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)  
**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also



A D T

## **6.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

--- END ---