

FCC PART 15.247

TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China.
518052

FCC ID: V7TW330A

Report Type: Original Report	Product Type: Wireless N300 Ceiling Access Point
Test Engineer: Dean Liu	<i>Dean Liu</i>
Report Number: RDG140918003-00	
Report Date: 2014-09-30	
Reviewed By: Sula Huang EMC Engineer	<i>Sula Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....48
APPLICABLE STANDARD48
TEST PROCEDURE48
TEST EQUIPMENT LIST AND DETAILS.....48
TEST DATA48

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....50
APPLICABLE STANDARD50
TEST PROCEDURE50
TEST EQUIPMENT LIST AND DETAILS.....50
TEST DATA50

FCC §15.247(e) - POWER SPECTRAL DENSITY59
APPLICABLE STANDARD59
TEST PROCEDURE59
TEST EQUIPMENT LIST AND DETAILS.....59
TEST DATA59

FEMVAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHENZHEN TENDA TECHNOLOGY CO.,LTD.*'s product, model number: *W330A(FCC ID: V7TW330A)* or ("EUT") in this report is a *Wireless N300 Ceiling Access Point*, which was measured approximately: 15.9 cm (L) x15.9 cm (W) x 3.9 cm (H), rated input voltage is supplied from 802.3af POE.

All measurement and test data in this report was gathered from production sample serial number: 140918003. (Assigned by applicant). The EUT was received on 2014-09-23.

Objective

This report is prepared on behalf of *SHENZHEN TENDA TECHNOLOGY CO.,LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communications Commission rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with Channel 1, 6 and 11. For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The software "MTool_2.0.0.3" was used for testing, which was provided by manufacturer. The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Software Version	MTool_2.0.0.3					
Test Frequency	2412(2422)MHz		2437MHz		2462(2452)MHz	
Antenna	Chain 0	Chain 1	Chain 0	Chain 1	Chain 0	Chain 1
802.11b	80	80	80	80	80	80
802.11g	65	65	65	65	65	65
802.11n ht20	60	60	60	60	60	60
802.11n ht40	48	48	48	48	49	49


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
GOSPELL DIGITAL	AC-DC Adapter	GP306A-510-125	N/A
IP-COM	PoE Switch	G10P	N/A
Dell	Laptop	PP11L	P145271E3

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	Yes	No	0.8	EUT	POE Switch
RJ45 Cable	Yes	No	10	POE Switch	Laptop
DC Cable	No	No	1.0	Adpater	POE Switch

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2462	3.5	2.24	21.82	152.05	20.00	0.06776	1.0
802.11g	2437	3.5	2.24	23.37	217.27	20.00	0.09682	1.0
802.11n HT20	2462	3.5	2.24	24.92	310.46	20.00	0.13834	1.0
802.11n HT40	2452	3.5	2.24	24.21	263.63	20.00	0.11748	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

This product used two internal antennas, the maximum gain is 3.5 dBi, which fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2013-11-20	2014-11-20
R&S	L.I.S.N	ESH3-Z5	843331/015	2013-09-25	2014-09-25
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-01-22	2015-01-22
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

2.20 dB at 0.436318 MHz in the **Neutral** conducted mode

Test Data


Environmental Conditions

Temperature:	28 °C
Relative Humidity:	61 %
ATM Pressure:	100.7 kPa

The testing was performed by Dean Liu on 2014-09-22.

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.429420	42.3	9.000	L1	10.5	15.0	57.3	Compliance
0.436318	48.1	9.000	L1	10.5	9.1	57.1	Compliance
1.407671	38.8	9.000	L1	10.4	17.2	56.0	Compliance
1.599078	37.9	9.000	L1	10.4	18.1	56.0	Compliance
10.484680	39.3	9.000	L1	10.6	20.7	60.0	Compliance
20.804674	40.3	9.000	L1	11.1	19.7	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.247802	33.5	9.000	L1	10.7	18.4	51.8	Compliance
0.419276	39.4	9.000	L1	10.5	8.0	47.5	Compliance
0.436318	44.7	9.000	L1	10.5	2.4*	47.1	Compliance
1.310256	30.6	9.000	L1	10.4	15.4	46.0	Compliance
1.611870	29.0	9.000	L1	10.4	17.0	46.0	Compliance
20.804674	39.0	9.000	L1	11.1	11.0	50.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.153629	43.9	9.000	N	10.3	21.9	65.8	Compliance
0.419276	42.5	9.000	N	10.7	15.0	57.5	Compliance
0.436318	48.0	9.000	N	10.6	9.2	57.1	Compliance
1.407671	38.1	9.000	N	10.5	17.9	56.0	Compliance
1.573796	37.0	9.000	N	10.5	19.0	56.0	Compliance
10.738330	38.9	9.000	N	10.6	21.1	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.247802	36.1	9.000	N	11.2	15.8	51.8	Compliance
0.283749	33.4	9.000	N	11.2	17.3	50.7	Compliance
0.419276	39.2	9.000	N	10.7	8.2	47.5	Compliance
0.436318	44.9	9.000	N	10.6	2.2*	47.1	Compliance
0.549741	32.4	9.000	N	10.3	13.6	46.0	Compliance
20.804674	39.5	9.000	N	11.1	10.5	50.0	Compliance

*Within measurement uncertainty!

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB

Table 2 – Values of U_{cispr}


Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS-Lindgren	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.14 dB at 2390MHz in the **Horizontal** polarization for 802.11n ht40 Mode.

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	51 %
ATM Pressure:	100.6 kPa

The testing was performed by Dean Liu on 2014-09-29.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	105.03	PK	H	25.67	4.42	27.33	107.79	N/A	N/A
2412	101.47	AV	H	25.67	4.42	27.33	104.23	N/A	N/A
2412	101.23	PK	V	25.67	4.42	27.33	103.99	N/A	N/A
2412	97.52	AV	V	25.67	4.42	27.33	100.28	N/A	N/A
2390	55.60	PK	H	25.61	4.39	27.32	58.28	74.00	15.72
2390	44.12	AV	H	25.61	4.39	27.32	46.80	54.00	7.20
4824	41.06	PK	H	30.64	6.03	27.41	50.32	74.00	23.68
4824	38.56	AV	H	30.64	6.03	27.41	47.82	54.00	6.18
7236	31.15	PK	H	34.17	7.47	25.90	46.89	74.00	27.11
7236	20.37	AV	H	34.17	7.47	25.90	36.11	54.00	17.89
9648	28.52	PK	H	36.06	8.81	27.46	45.93	74.00	28.07
9648	19.66	AV	H	36.06	8.81	27.46	37.07	54.00	16.93
1960	35.45	PK	H	24.52	3.80	27.49	36.28	74.00	37.72
1960	23.67	AV	H	24.52	3.80	27.49	24.50	54.00	29.50
162.6	40.13	QP	H	12.60	1.56	21.44	32.85	43.50	10.65
Middle Channel: 2437 MHz									
2437	105.02	PK	H	25.74	4.41	27.34	107.83	N/A	N/A
2437	101.50	AV	H	25.74	4.41	27.34	104.31	N/A	N/A
2437	100.58	PK	V	25.74	4.41	27.34	103.39	N/A	N/A
2437	97.08	AV	V	25.74	4.41	27.34	99.89	N/A	N/A
4874	41.66	PK	H	30.77	6.09	27.42	51.10	74.00	22.90
4874	39.49	AV	H	30.77	6.09	27.42	48.93	54.00	5.07
7311	30.89	PK	H	34.35	7.51	25.88	46.87	74.00	27.13
7311	19.77	AV	H	34.35	7.51	25.88	35.75	54.00	18.25
9748	30.07	PK	H	36.30	8.83	27.24	47.96	74.00	26.04
9748	18.32	AV	H	36.30	8.83	27.24	36.21	54.00	17.79
1922	35.98	PK	H	24.44	3.68	27.50	36.60	74.00	37.40
1922	23.75	AV	H	24.44	3.68	27.50	24.37	54.00	29.63
162.6	40.16	QP	H	12.60	1.56	21.44	32.88	43.50	10.62
High Channel: 2462 MHz									
2462	105.18	PK	H	25.80	4.43	27.35	108.06	N/A	N/A
2462	101.56	AV	H	25.80	4.43	27.35	104.44	N/A	N/A
2462	99.72	PK	V	25.80	4.43	27.35	102.60	N/A	N/A
2462	96.52	AV	V	25.80	4.43	27.35	99.40	N/A	N/A
2483.5	57.97	PK	H	25.86	4.49	27.36	60.96	74.00	13.04
2483.5	45.32	AV	H	25.86	4.49	27.36	48.31	54.00	5.69
4924	42.63	PK	H	30.90	5.97	27.43	52.07	74.00	21.93
4924	40.95	AV	H	30.90	5.97	27.43	50.39	54.00	3.61*
7386	30.21	PK	H	34.53	7.55	25.86	46.43	74.00	27.57
7386	20.82	AV	H	34.53	7.55	25.86	37.04	54.00	16.96
9848	28.73	PK	H	36.54	8.85	26.94	47.18	74.00	26.82
9848	18.72	AV	H	36.54	8.85	26.94	37.17	54.00	16.83
1828	35.47	PK	H	24.26	3.65	27.52	35.86	74.00	38.14
1828	24.01	AV	H	24.26	3.65	27.52	24.40	54.00	29.60
162.6	40.07	QP	H	12.60	1.56	21.44	32.79	43.50	10.71

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	104.96	PK	H	25.67	4.42	27.33	107.72	N/A	N/A
2412	94.18	AV	H	25.67	4.42	27.33	96.94	N/A	N/A
2412	99.48	PK	V	25.67	4.42	27.33	102.24	N/A	N/A
2412	89.46	AV	V	25.67	4.42	27.33	92.22	N/A	N/A
2390	65.60	PK	H	25.61	4.39	27.32	68.28	74.00	5.72
2390	47.52	AV	H	25.61	4.39	27.32	50.20	54.00	3.80*
4824	39.56	PK	H	30.64	6.03	27.41	48.82	74.00	25.18
4824	26.12	AV	H	30.64	6.03	27.41	35.38	54.00	18.62
7236	29.96	PK	H	34.17	7.47	25.90	45.70	74.00	28.30
7236	18.69	AV	H	34.17	7.47	25.90	34.43	54.00	19.57
9648	27.06	PK	H	36.06	8.81	27.46	44.47	74.00	29.53
9648	15.73	AV	H	36.06	8.81	27.46	33.14	54.00	20.86
1852	36.32	PK	H	24.30	3.76	27.52	36.86	74.00	37.14
1852	23.91	AV	H	24.30	3.76	27.52	24.45	54.00	29.55
162.6	40.16	QP	H	12.60	1.56	21.44	32.88	43.50	10.62
Middle Channel: 2437 MHz									
2437	104.30	PK	H	25.74	4.41	27.34	107.11	N/A	N/A
2437	94.34	AV	H	25.74	4.41	27.34	97.15	N/A	N/A
2437	99.74	PK	V	25.74	4.41	27.34	102.55	N/A	N/A
2437	89.50	AV	V	25.74	4.41	27.34	92.31	N/A	N/A
4874	39.70	PK	H	30.77	6.09	27.42	49.14	74.00	24.86
4874	26.36	AV	H	30.77	6.09	27.42	35.80	54.00	18.20
7311	30.04	PK	H	34.35	7.51	25.88	46.02	74.00	27.98
7311	18.55	AV	H	34.35	7.51	25.88	34.53	54.00	19.47
9748	27.48	PK	H	36.30	8.83	27.24	45.37	74.00	28.63
9748	15.94	AV	H	36.30	8.83	27.24	33.83	54.00	20.17
1805	35.55	PK	H	24.21	3.52	27.53	35.75	74.00	38.25
1805	23.97	AV	H	24.21	3.52	27.53	24.17	54.00	29.83
162.6	40.04	QP	H	12.60	1.56	21.44	32.76	43.50	10.74
High Channel: 2462 MHz									
2462	103.16	PK	H	25.80	4.43	27.35	106.04	N/A	N/A
2462	94.17	AV	H	25.80	4.43	27.35	97.05	N/A	N/A
2462	98.59	PK	V	25.80	4.43	27.35	101.47	N/A	N/A
2462	89.14	AV	V	25.80	4.43	27.35	92.02	N/A	N/A
2483.5	65.55	PK	H	25.86	4.49	27.36	68.54	74.00	5.46
2483.5	43.52	AV	H	25.86	4.49	27.36	46.51	54.00	7.49
4924	39.96	PK	H	30.90	5.97	27.43	49.40	74.00	24.60
4924	25.70	AV	H	30.90	5.97	27.43	35.14	54.00	18.86
7386	30.71	PK	H	34.53	7.55	25.86	46.93	74.00	27.07
7386	18.96	AV	H	34.53	7.55	25.86	35.18	54.00	18.82
9848	27.63	PK	H	36.54	8.85	26.94	46.08	74.00	27.92
9848	16.32	AV	H	36.54	8.85	26.94	34.77	54.00	19.23
1980	35.27	PK	H	24.56	3.81	27.49	36.15	74.00	37.85
1980	23.69	AV	H	24.56	3.81	27.49	24.57	54.00	29.43
162.6	40.11	QP	H	12.60	1.56	21.44	32.83	43.50	10.67

*Within measurement uncertainty!

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	102.16	PK	H	25.67	4.42	27.33	104.92	N/A	N/A
2412	92.36	AV	H	25.67	4.42	27.33	95.12	N/A	N/A
2412	98.38	PK	V	25.67	4.42	27.33	101.14	N/A	N/A
2412	87.43	AV	V	25.67	4.42	27.33	90.19	N/A	N/A
2390	66.25	PK	H	25.61	4.39	27.32	68.93	74.00	5.07
2390	47.19	AV	H	25.61	4.39	27.32	49.87	54.00	4.13*
4824	38.19	PK	H	30.64	6.03	27.41	47.45	74.00	26.55
4824	23.24	AV	H	30.64	6.03	27.41	32.50	54.00	21.50
7236	31.02	PK	H	34.17	7.47	25.90	46.76	74.00	27.24
7236	17.34	AV	H	34.17	7.47	25.90	33.08	54.00	20.92
9648	27.87	PK	H	36.06	8.81	27.46	45.28	74.00	28.72
9648	14.09	AV	H	36.06	8.81	27.46	31.50	54.00	22.50
1793	35.33	PK	H	24.19	3.52	27.54	35.50	74.00	38.50
1793	23.83	AV	H	24.19	3.52	27.54	24.00	54.00	30.00
162.6	40.08	QP	H	12.60	1.56	21.44	32.80	43.50	10.70
Middle Channel: 2437 MHz									
2437	103.19	PK	H	25.74	4.41	27.34	106.00	N/A	N/A
2437	92.22	AV	H	25.74	4.41	27.34	95.03	N/A	N/A
2437	97.91	PK	V	25.74	4.41	27.34	100.72	N/A	N/A
2437	87.89	AV	V	25.74	4.41	27.34	90.70	N/A	N/A
4874	38.01	PK	H	30.77	6.09	27.42	47.45	74.00	26.55
4874	23.14	AV	H	30.77	6.09	27.42	32.58	54.00	21.42
7311	30.87	PK	H	34.35	7.51	25.88	46.85	74.00	27.15
7311	17.12	AV	H	34.35	7.51	25.88	33.10	54.00	20.90
9748	27.42	PK	H	36.30	8.83	27.24	45.31	74.00	28.69
9748	13.79	AV	H	36.30	8.83	27.24	31.68	54.00	22.32
1828	35.34	PK	H	24.26	3.65	27.52	35.73	74.00	38.27
1828	23.77	AV	H	24.26	3.65	27.52	24.16	54.00	29.84
162.6	40.36	QP	H	12.60	1.56	21.44	33.08	43.50	10.42
High Channel: 2462 MHz									
2462	103.63	PK	H	25.80	4.43	27.35	106.51	N/A	N/A
2462	93.06	AV	H	25.80	4.43	27.35	95.94	N/A	N/A
2462	98.34	PK	V	25.80	4.43	27.35	101.22	N/A	N/A
2462	88.32	AV	V	25.80	4.43	27.35	91.20	N/A	N/A
2483.5	66.62	PK	H	25.86	4.49	27.36	69.61	74.00	4.39*
2483.5	43.92	AV	H	25.86	4.49	27.36	46.91	54.00	7.09
4924	37.96	PK	H	30.90	5.97	27.43	47.40	74.00	26.60
4924	23.02	AV	H	30.90	5.97	27.43	32.46	54.00	21.54
7386	30.85	PK	H	34.53	7.55	25.86	47.07	74.00	26.93
7386	16.91	AV	H	34.53	7.55	25.86	33.13	54.00	20.87
9848	27.24	PK	H	36.54	8.85	26.94	45.69	74.00	28.31
9848	13.97	AV	H	36.54	8.85	26.94	32.42	54.00	21.58
1840	35.77	PK	H	24.28	3.71	27.52	36.24	74.00	37.76
1840	23.89	AV	H	24.28	3.71	27.52	24.36	54.00	29.64
162.6	40.17	QP	H	12.60	1.56	21.44	32.89	43.50	10.61

*Within measurement uncertainty!

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	101.98	PK	H	25.70	4.41	27.33	104.76	N/A	N/A
2422	90.26	AV	H	25.70	4.41	27.33	93.04	N/A	N/A
2422	94.45	PK	V	25.70	4.41	27.33	97.23	N/A	N/A
2422	82.62	AV	V	25.70	4.41	27.33	85.40	N/A	N/A
2390	64.25	PK	H	25.61	4.39	27.32	66.93	74.00	7.07
2390	49.18	AV	H	25.61	4.39	27.32	51.86	54.00	2.14*
4844	36.49	PK	H	30.69	6.08	27.42	45.84	74.00	28.16
4844	23.43	AV	H	30.69	6.08	27.42	32.78	54.00	21.22
7266	28.51	PK	H	34.24	7.48	25.89	44.34	74.00	29.66
7266	15.39	AV	H	34.24	7.48	25.89	31.22	54.00	22.78
9688	26.23	PK	H	36.15	8.82	27.37	43.83	74.00	30.17
9688	13.84	AV	H	36.15	8.82	27.37	31.44	54.00	22.56
1782	35.16	PK	H	24.16	3.56	27.56	35.32	74.00	38.68
1782	23.01	AV	H	24.16	3.56	27.56	23.17	54.00	30.83
162.6	40.19	QP	H	12.60	1.56	21.44	32.91	43.50	10.59
Middle Channel: 2437 MHz									
2437	101.45	PK	H	25.74	4.41	27.34	104.26	N/A	N/A
2437	89.72	AV	H	25.74	4.41	27.34	92.53	N/A	N/A
2437	93.48	PK	V	25.74	4.41	27.34	96.29	N/A	N/A
2437	81.26	AV	V	25.74	4.41	27.34	84.07	N/A	N/A
4874	36.32	PK	H	30.77	6.09	27.42	45.76	74.00	28.24
4874	23.01	AV	H	30.77	6.09	27.42	32.45	54.00	21.55
7311	28.47	PK	H	34.35	7.51	25.88	44.45	74.00	29.55
7311	15.31	AV	H	34.35	7.51	25.88	31.29	54.00	22.71
9748	26.05	PK	H	36.30	8.83	27.24	43.94	74.00	30.06
9748	13.49	AV	H	36.30	8.83	27.24	31.38	54.00	22.62
1898	34.67	PK	H	24.40	3.61	27.51	35.17	74.00	38.83
1898	22.41	AV	H	24.40	3.61	27.51	22.91	54.00	31.09
162.6	40.28	QP	H	12.60	1.56	21.44	33.00	43.50	10.50
High Channel: 2452 MHz									
2452	102.51	PK	H	25.78	4.41	27.35	105.35	N/A	N/A
2452	90.29	AV	H	25.78	4.41	27.35	93.13	N/A	N/A
2452	94.05	PK	V	25.78	4.41	27.35	96.89	N/A	N/A
2452	82.47	AV	V	25.78	4.41	27.35	85.31	N/A	N/A
2483.5	62.25	PK	H	25.86	4.49	27.36	65.24	74.00	8.76
2483.5	47.98	AV	H	25.86	4.49	27.36	50.97	54.00	3.03*
4904	36.94	PK	H	30.85	6.06	27.43	46.42	74.00	27.58
4904	23.78	AV	H	30.85	6.06	27.43	33.26	54.00	20.74
7356	28.76	PK	H	34.45	7.53	25.87	44.87	74.00	29.13
7356	15.68	AV	H	34.45	7.53	25.87	31.79	54.00	22.21
9808	26.83	PK	H	36.44	8.84	27.09	45.02	74.00	28.98
9808	13.56	AV	H	36.44	8.84	27.09	31.75	54.00	22.25
1828	35.20	PK	H	24.26	3.65	27.52	35.59	74.00	38.41
1828	23.19	AV	H	24.26	3.65	27.52	23.58	54.00	30.42
162.6	40.37	QP	H	12.60	1.56	21.44	33.09	43.50	10.41

*Within measurement uncertainty!


Conducted Spurious Emissions at Antenna Port

Chain0:


802.11b Low Channel



802.11b Middle Channel




802.11b High Channel




Date: 29.SEP.2014 19:59:34

802.11g Low Channel




Date: 29.SEP.2014 20:07:41

802.11g Middle Channel




Date: 29.SEP.2014 20:06:29

802.11g High Channel




Date: 29.SEP.2014 20:05:15

802.11n ht20 Low Channel




Date: 29.SEP.2014 20:09:29

802.11n ht20 Middle Channel




Date: 29.SEP.2014 20:10:34

802.11n ht20 High Channel




Date: 29.SEP.2014 20:12:53

802.11n ht40 Low Channel




Date: 29.SEP.2014 20:20:17

802.11n ht40 Middle Channel



Date: 29.SEP.2014 20:15:06


802.11n ht40 High Channel



Date: 29.SEP.2014 20:13:59


Chain1:

802.11b Low Channel




Date: 29.SEP.2014 17:35:37

802.11b Middle Channel




Date: 29.SEP.2014 17:40:07

802.11b High Channel




Date: 29.SEP.2014 17:47:58

802.11g Low Channel




Date: 29.SEP.2014 18:21:35

802.11g Middle Channel



Date: 29.SEP.2014 18:06:17


802.11g High Channel



Date: 29.SEP.2014 18:00:42

802.11n ht20 Low Channel


Fundamental



Date: 29.SEP.2014 18:27:42


802.11n ht20 Middle Channel

Fundamental




Date: 29.SEP.2014 18:43:23

802.11n ht20 High Channel




Date: 29.SEP.2014 18:37:48

802.11n ht40 Low Channel




Date: 29.SEP.2014 18:53:15

802.11n ht40 Middle Channel



Date: 29.SEP.2014 19:00:16

802.11n ht40 High Channel



Date: 29.SEP.2014 19:09:11

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause8.1 Option 1:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	62 %
ATM Pressure:	100.6 kPa

The testing was performed by Dean Liu on 2014-09-29.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Limit (kHz)
			Chain 0	Chain 1	
802.11b	Low	2412	8.06	8.06	≥500
	Middle	2437	8.14	8.14	≥500
	High	2462	8.06	8.14	≥500
802.11g	Low	2412	16.53	16.53	≥500
	Middle	2437	16.45	16.53	≥500
	High	2462	16.53	16.53	≥500
802.11n ht20	Low	2412	17.64	17.72	≥500
	Middle	2437	17.64	17.72	≥500
	High	2462	17.64	17.72	≥500
802.11n ht40	Low	2422	35.93	35.61	≥500
	Middle	2437	36.09	36.41	≥500
	High	2452	36.09	35.45	≥500


Chain0:

802.11b Low Channel




Date: 29.SEP.2014 14:43:10

802.11b Middle Channel




Date: 29.SEP.2014 14:46:41

802.11b High Channel




Date: 29.SEP.2014 14:49:42

802.11g Low Channel




Date: 29.SEP.2014 15:27:33

802.11g Middle Channel




Date: 29.SEP.2014 15:23:46

802.11g High Channel




Date: 29.SEP.2014 14:53:09

802.11n ht20 Low Channel




Date: 29.SEP.2014 15:34:28

802.11n ht20 Middle Channel




Date: 29.SEP.2014 15:39:06

802.11n ht20 High Channel




Date: 29.SEP.2014 15:43:17

802.11n ht40 Low Channel




Date: 29.SEP.2014 15:49:15

802.11n ht40 Middle Channel



Date: 29.SEP.2014 15:58:56


802.11n ht40 High Channel



Date: 29.SEP.2014 16:08:57


Chain1:

802.11b Low Channel




Date: 29.SEP.2014 17:32:21

802.11b Middle Channel




Date: 29.SEP.2014 17:36:58

802.11b High Channel




Date: 29.SEP.2014 17:44:57

802.11g Low Channel




Date: 29.SEP.2014 18:17:21

802.11g Middle Channel




Date: 29.SEP.2014 18:02:11

802.11g High Channel




Date: 29.SEP.2014 17:57:05

802.11n ht20 Low Channel




Date: 29.SEP.2014 18:23:33

802.11n ht20 Middle Channel




Date: 29.SEP.2014 18:39:12

802.11n ht20 High Channel




Date: 29.SEP.2014 18:34:00

802.11n ht40 Low Channel




Date: 29.SEP.2014 18:49:06

802.11n ht40 Middle Channel



Date: 29.SEP.2014 18:55:25

802.11n ht40 High Channel



Date: 29.SEP.2014 19:04:22

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause9.2.2.2

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2013-12-12	2014-12-12
Agilent	Wideband Power Sensor	N1921A	MY54170013	2013-12-12	2014-12-12
Agilent	P-Series Power Meter	N1912A	MY5000448	2013-12-12	2014-12-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	62 %
ATM Pressure:	100.6 kPa

The testing was performed by Dean Liu on 2014-09-29.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)			Limit (dBm)	Result
			Chain 0	Chain 1	Total		
802.11b	Low	2412	21.34	20.38	/	30	PASS
	Middle	2437	21.58	20.55	/	30	PASS
	High	2462	21.82	20.72	/	30	PASS
802.11g	Low	2412	23.11	22.42	/	30	PASS
	Middle	2437	23.37	22.51	/	30	PASS
	High	2462	23.33	22.7	/	30	PASS
802.11n ht20	Low	2412	22.07	21.08	24.61	30	PASS
	Middle	2437	22.11	21.28	24.73	30	PASS
	High	2462	22.28	21.5	24.92	30	PASS
802.11n ht40	Low	2422	21.02	21.36	24.20	30	PASS
	Middle	2437	20.98	20.79	23.90	30	PASS
	High	2452	21.06	21.34	24.21	30	PASS

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	62 %
ATM Pressure:	100.6 kPa


The testing was performed by Dean Liu on 2014-09-29.

Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


Chain0:

802.11b: Band Edge, Left Side




Date: 29.SEP.2014 14:45:31

802.11b: Band Edge, Right Side




Date: 29.SEP.2014 14:52:05

802.11g: Band Edge, Left Side




Date: 29.SEP.2014 15:31:33

802.11g: Band Edge, Right Side




Date: 29.SEP.2014 14:56:38


802.11n ht20 Band Edge, Left Side



802.11n ht20 Band Edge, Right Side




802.11n ht40 Band Edge, Left Side



Date: 29.SEP.2014 15:54:07


802.11n ht40 Band Edge, Right Side



Date: 29.SEP.2014 16:12:30


Chain1:

802.11b: Band Edge, Left Side




Date: 29.SEP.2014 17:35:58

802.11b: Band Edge, Right Side




Date: 29.SEP.2014 17:48:21

802.11g: Band Edge, Left Side




Date: 29.SEP.2014 18:21:56

802.11g: Band Edge, Right Side




Date: 29.SEP.2014 18:01:03

802.11n ht20 Band Edge, Left Side




Date: 29.SEP.2014 18:28:21

802.11n ht20 Band Edge, Right Side




Date: 29.SEP.2014 18:38:09

802.11n ht40 Band Edge, Left Side



Date: 29.SEP.2014 18:53:58

802.11n ht40 Band Edge, Right Side



Date: 29.SEP.2014 19:09:41

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause10.2:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	62 %
ATM Pressure:	100.6 kPa

The testing was performed by Dean Liu on 2014-09-29.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)			Limit (dBm/3kHz)	Result
			Chain 0	Chain 1	Total		
802.11b	Low	2412	-4.13	-4.22	/	≤8	PASS
	Middle	2437	-3.66	-4.65	/	≤8	PASS
	High	2462	-3.33	-3.03	/	≤8	PASS
802.11g	Low	2412	-10.56	-10.45	/	≤8	PASS
	Middle	2437	-10.56	-10.58	/	≤8	PASS
	High	2462	-10.53	-10.49	/	≤8	PASS
802.11n ht20	Low	2412	-11.92	-12.57	-9.22	≤8	PASS
	Middle	2437	-12.21	-12.17	-9.18	≤8	PASS
	High	2462	-12.12	-11.5	-8.79	≤8	PASS
802.11n ht40	Low	2422	-17.01	-17.04	-14.01	≤8	PASS
	Middle	2437	-17.15	-16.65	-13.88	≤8	PASS
	High	2452	-15.97	-17.12	-13.50	≤8	PASS


Chain0:

Power Spectral Density, 802.11b Low Channel




Date: 29.SEP.2014 14:45:12

Power Spectral Density, 802.11b Middle Channel




Date: 29.SEP.2014 14:48:48

Power Spectral Density, 802.11b High Channel




Date: 29.SEP.2014 14:51:39

Power Spectral Density, 802.11g Low Channel




Date: 29.SEP.2014 15:31:13

Power Spectral Density, 802.11g Middle Channel




Date: 29.SEP.2014 15:03:13

Power Spectral Density, 802.11g High Channel




Date: 29.SEP.2014 14:56:14

Power Spectral Density, 802.11n ht20 Low Channel




Date: 29.SEP.2014 15:37:42

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 29.SEP.2014 15:42:16

Power Spectral Density, 802.11n ht20 High Channel




Date: 29.SEP.2014 15:46:30

Power Spectral Density, 802.11n ht40 Low Channel




Date: 29.SEP.2014 15:53:47

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 29.SEP.2014 16:02:18


Power Spectral Density, 802.11n ht40 High Channel



Date: 29.SEP.2014 16:12:10


Chain1:

Power Spectral Density, 802.11b Low Channel




Date: 29.SEP.2014 17:34:36

Power Spectral Density, 802.11b Middle Channel




Date: 29.SEP.2014 17:39:06

Power Spectral Density, 802.11b High Channel




Date: 29.SEP.2014 17:46:57

Power Spectral Density, 802.11g Low Channel




Date: 29.SEP.2014 18:20:54

Power Spectral Density, 802.11g Middle Channel




Date: 29.SEP.2014 18:05:16

Power Spectral Density, 802.11g High Channel




Date: 29.SEP.2014 18:00:01

Power Spectral Density, 802.11n ht20 Low Channel




Date: 29.SEP.2014 18:27:00

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 29.SEP.2014 18:42:29

Power Spectral Density, 802.11n ht20 High Channel




Date: 29.SEP.2014 18:36:54

Power Spectral Density, 802.11n ht40 Low Channel




Date: 29.SEP.2014 18:52:34

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 29.SEP.2014 18:59:22

Power Spectral Density, 802.11n ht40 High Channel



Date: 29.SEP.2014 19:08:30

***** END OF REPORT *****