



A D T

FCC TEST REPORT

REPORT NO.: RF990407E04

MODEL NO.: WMG623A

RECEIVED: Apr. 07, 2010

TESTED: Apr. 09 to 12, 2010

ISSUED: Apr. 14, 2010

APPLICANT: Accton Wireless Broadband Corp.

ADDRESS: 3F, No. 1 Creation Rd. III, Science-based
Industrial Park Hsinchu 30077, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB LOCATION (1): No.49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan (R.O.C.)

LAB LOCATION (2): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 77 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION.....	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	9
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3.4	DESCRIPTION OF SUPPORT UNITS.....	14
3.5	CONFIGURATION OF SYSTEM UNDER TEST	15
4.	TEST TYPES AND RESULTS	16
4.1	CONDUCTED EMISSION MEASUREMENT.....	16
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	16
4.1.2	TEST INSTRUMENTS	16
4.1.3	TEST PROCEDURES.....	17
4.1.4	DEVIATION FROM TEST STANDARD	17
4.1.5	TEST SETUP	18
4.1.6	EUT OPERATING CONDITIONS	18
4.1.7	TEST RESULTS	19
4.2	RADIATED EMISSION MEASUREMENT	21
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	21
4.2.2	TEST INSTRUMENTS	22
4.2.3	TEST PROCEDURES.....	23
4.2.4	DEVIATION FROM TEST STANDARD	23
4.2.5	TEST SETUP	24
4.2.6	EUT OPERATING CONDITIONS	24
4.2.7	TEST RESULTS	25
4.3	6dB BANDWIDTH MEASUREMENT	54
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	54
4.3.2	TEST INSTRUMENTS	54
4.3.3	TEST PROCEDURE.....	54
4.3.4	DEVIATION FROM TEST STANDARD	54
4.3.5	TEST SETUP	54
4.3.6	EUT OPERATING CONDITIONS	54
4.3.7	TEST RESULTS	55
4.4	MAXIMUM PEAK OUTPUT POWER.....	59
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	59
4.4.2	INSTRUMENTS.....	59
4.4.3	TEST PROCEDURES.....	59
4.4.4	DEVIATION FROM TEST STANDARD	59



A D T

4.4.5	TEST SETUP	59
4.4.6	EUT OPERATING CONDITIONS	59
4.4.7	TEST RESULTS	60
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	62
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	62
4.5.2	TEST INSTRUMENTS	62
4.5.3	TEST PROCEDURE	62
4.5.4	DEVIATION FROM TEST STANDARD	62
4.5.5	TEST SETUP	62
4.5.6	EUT OPERATING CONDITION.....	62
4.5.7	TEST RESULTS	63
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	67
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	67
4.6.2	TEST INSTRUMENTS	67
4.6.3	TEST PROCEDURE	67
4.6.4	DEVIATION FROM TEST STANDARD	67
4.6.5	EUT OPERATING CONDITION.....	67
4.6.6	TEST RESULTS	67
5.	INFORMATION ON THE TESTING LABORATORIES	76
6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	77



1. CERTIFICATION

PRODUCT: WLAN Module
BRAND NAME: AWB
MODEL NO.: WMG623A
TEST SAMPLE: R&D SAMPLE
TESTED: Apr. 09 to 12, 2010
APPLICANT: Accton Wireless Broadband Corp.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: WMG623A) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Carol Liao , **DATE:** Apr. 14, 2010
(Carol Liao, Specialist)

TECHNICAL ACCEPTANCE : Hank Chung , **DATE:** Apr. 14, 2010
(Hank Chung, Deputy Manager)

APPROVED BY : May Chen , **DATE:** Apr. 14, 2010
(May Chen, Deputy Manager)



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -16.79dB at 0.150MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.7dB at 375.0MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.76 dB
Radiated emissions (1GHz -18GHz)	2.19 dB
Radiated emissions (18GHz -40GHz)	2.56 dB



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WLAN Module
MODEL NO.	WMG623A
FCC ID	V8YFIXHI623A000W
POWER SUPPLY	DC 3.3V from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n (20 MHz, 800 ns GI): 195, 175.5, 156, 130, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6.5 Mbps 802.11n (40 MHz, 800 ns GI): 405, 364.5, 324, 270, 243, 216, 162, 135, 121.5, 108, 81, 54, 40.5, 27, 13.5Mbps 802.11n (20 MHz, 400ns GI): 216.7, 195, 173.3, 144.4, 130, 115.6, 86.7, 72.2, 65, 57.8, 43.3, 28.9, 21.7, 14.4, 7.2Mbps 802.11n (40 MHz, 400ns GI): 450, 405, 360, 300, 270, 240, 180, 150, 135, 120, 90, 60, 45, 30, 15 Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
MAXIMUM OUTPUT POWER	802.11b: 162.2mW 802.11g: 245.5mW 802.11n (20MHz): 422.7mW 802.11n (40MHz): 413.1mW
ANTENNA TYPE	Please see note 1
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA



A D T

NOTE:

1. There are three antennas provided to this EUT, please refer to the following table:

No.	Chain	Antenna Type	Antenna Connector	Antenna Gain (dBi)	Cable loss(dB)	Net Gain (dBi)	Cable Length (mm)	Frequency range (MHz)	Diversity Function
1	Chain (0)	PIFA	IPEX	4.5	1.0	3.5	190	2400-2490	N
2	Chain(1)	PIFA	IPEX	4.5	0.5	4.0	100	2400-2490	N
3	Chain (2)	PIFA	IPEX	4.5	1.0	3.5	190	2400-2490	N

2. The EUT incorporates a MIMO function with 802.11n. Physically, the EUT provides two completed transmitters and three completed receivers.
3. The EUT is 2 * 3 spatial MIMO (2Tx & 3Rx) without beam forming function. The antenna configurations are two transmitter antennas and three receiver antennas, as there are 3 PIFA antennas. Spatial multiplexing modes for simultaneous transmission using 2 antennas, and for simultaneous receiver using 3 antennas. The 11bg legacy mode is limited to single transmitter only.
4. The EUT complies with 802.11n standards and backwards compatible with 802.11b, 802.11g products.
5. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
6. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2422MHz	5	2442MHz
2	2427MHz	6	2447MHz
3	2432MHz	7	2452MHz
4	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	
-	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ≥ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

ANTENNA COMBINATION MODE:

COMBINATION MODE	OPERATION MODE	TX CHAIN(0)	TX CHAIN(1)
A	802.11 b	√	
B	802.11 b		√
C	802.11 g	√	
D	802.11 g		√
E	802.11n(20MHz) for MCS0~7	√	√
F	802.11n(20MHz) for MCS8~15	√	√
G	802.11n(40MHz) for MCS0~7	√	√
H	802.11n(40MHz) for MCS8~15	√	√

Note:

1. The above information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.
2. Mode A, C, E & G the worst modes, were selected as representative mode for the report.

-



A D T

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	E

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1	DSSS	DBPSK	1	A

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5	G



A D T

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13.5	G

※ After verification, conducted out band emission as show worst chain in report by investigations.

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX COMBINATION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	13.5	G

※ After verification, bandwidth as show worst chain in report by investigations.

※ **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE ³ 1G	21deg. C, 70%RH, 1023 hPa	120Vac, 60Hz	Eric Lee
RE<1G	19deg. C, 65%RH, 1023 hPa	120Vac, 60Hz	Rex Huang
PLC	27deg. C, 68%RH, 1023 hPa	120Vac, 60Hz	Rex Huang
APCM	24deg. C, 68%RH, 1023 hPa	120Vac, 60Hz	Eric Lee



A D T

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a WLAN Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
2	TEST TOOL	AWB	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST





A D T

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
0.15-0.5	Quasi-peak	Average
0.5-5	66 to 56	56 to 46
5-30	56	46
	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 09, 2010	Mar. 08, 2011
Line-Impedance Stabilization Network (for EUT)	NSLK 8127	8127-522	Sep. 23, 2009	Sep. 22, 2010
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Oct. 26, 2009	Oct. 25, 2010
RF Cable (JYBAO)	5DFB	COBCAB-001	Nov. 24, 2009	Nov. 23, 2010
50 ohms Terminator	50	3	Oct. 28, 2009	Oct. 27, 2010
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
- 3 The VCCI Con C Registration No. is C-3611.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Connect the EUT with the support unit 1 (Notebook Computer) which is placed in control room via the support unit 2 (test tool).
2. The support unit 1 (Notebook Computer) runs test program “RT3883QA.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

802.11n (20MHz) OFDM MODULATION:

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
--------------	----------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.150	0.05	49.16	-	49.21	-	66.00
2	0.466	0.06	39.29	-	39.35	-	56.58	46.58	-17.22	-
3	0.947	0.09	30.82	-	30.91	-	56.00	46.00	-25.09	-
4	3.855	0.19	31.74	-	31.93	-	56.00	46.00	-24.07	-
5	7.555	0.28	34.91	-	35.19	-	60.00	50.00	-24.81	-
6	18.484	0.49	26.31	-	26.80	-	60.00	50.00	-33.20	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
--------------	-------------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.190	0.06	44.06	-	44.12	-	64.03
2	0.459	0.07	36.38	-	36.45	-	56.72	46.72	-20.27	-
3	3.227	0.18	34.82	-	35.00	-	56.00	46.00	-21.00	-
4	3.656	0.19	34.99	-	35.18	-	56.00	46.00	-20.82	-
5	6.191	0.26	33.73	-	33.99	-	60.00	50.00	-26.01	-
6	18.258	0.49	26.32	-	26.81	-	60.00	50.00	-33.19	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250254	Aug. 03 , 2009	Aug. 02 , 2010
Agilent Pre-Selector	N9039A	MY46520310	Aug. 18 , 2009	Aug. 17 , 2010
Agilent Signal Generator	N5181A	MY49060347	July 18 , 2009	July 17 , 2010
LIG NEX1 Test Receiver	ER-265	L09068005	Aug. 31 , 2009	Aug. 30 , 2010
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 18 , 2009	Nov. 17, 2010
Agilent Pre-Amplifier	8449B	3008A02465	Mar. 01 , 2010	Feb. 28, 2011
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	NA	NA
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Sep.30 , 2009	Sep. 29 , 2010
AISI Horn_Antenna	AIH.8018	0000220091110	Nov. 16 , 2009	Nov. 15 , 2010
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Sep. 30 , 2009	Sep. 29 , 2010
RF CABLE	NA	RF104-205 RF104-207 RF104-208	Dec. 24, 2009	Dec. 23, 2010
RF Cable	NA	CHHCAB_001	NA	NA
Software	ADT_Radiated_ V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna, HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in 966 Chamber No. H.
 4. The FCC Chamber Registration No. is 797305.
 5. The CANADA Chamber Registration No. is IC 7450H-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the interference-receiving antenna.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



A D T

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : 802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	19deg. C, 65%RH 1023 hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	124.97	37.3 QP	43.5	-6.2	2.00 H	68	24.89	12.39
2	250.03	39.6 QP	46.0	-6.4	1.00 H	279	26.68	12.91
3	375.00	44.3 QP	46.0	-1.7	1.00 H	300	27.77	16.49
4	500.02	34.7 QP	46.0	-11.3	1.00 H	319	15.38	19.35
5	625.07	38.0 QP	46.0	-8.0	1.25 H	310	15.79	22.22
6	750.01	36.7 QP	46.0	-9.3	1.75 H	318	12.70	24.04
7	875.06	39.6 QP	46.0	-6.4	1.00 H	81	13.65	25.92
8	1000.00	37.0 QP	54.0	-17.0	1.25 H	338	9.99	27.01

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	47.53	34.3 QP	40.0	-5.7	1.25 V	0	20.31	13.99
2	124.97	39.3 QP	43.5	-4.2	1.00 V	360	26.95	12.39
3	250.03	34.2 QP	46.0	-11.8	1.00 V	274	21.30	12.91
4	375.01	43.6 QP	46.0	-2.4	1.16 V	351	27.09	16.49
5	500.02	33.3 QP	46.0	-12.7	2.00 V	360	13.94	19.35
6	624.96	37.8 QP	46.0	-8.2	1.00 V	43	15.60	22.21
7	750.01	35.6 QP	46.0	-10.4	1.25 V	360	11.57	24.04
8	875.06	40.4 QP	46.0	-5.6	1.25 V	45	14.52	25.92
9	1000.00	35.0 QP	54.0	-19.0	1.75 V	165	8.03	27.01

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



A D T

ABOVE 1GHz WORST-CASE DATA

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.2 PK	74.0	-18.8	1.02 H	70	27.84	27.36
2	1375.00	49.0 AV	54.0	-5.0	1.02 H	70	21.64	27.36
3	1625.00	48.5 PK	74.0	-25.5	1.21 H	338	20.16	28.34
4	1625.00	45.8 AV	54.0	-8.2	1.21 H	338	17.46	28.34
5	2389.87	56.5 PK	74.0	-17.5	1.08 H	158	25.33	31.21
6	2389.87	46.3 AV	54.0	-7.8	1.08 H	158	15.04	31.21
7	*2412.00	102.4 PK			1.08 H	158	71.15	31.27
8	*2412.00	100.1 AV			1.08 H	158	68.84	31.27
9	4824.00	52.1 PK	74.0	-21.9	1.00 H	290	12.68	39.42
10	4824.00	48.0 AV	54.0	-6.0	1.00 H	290	8.55	39.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.1 PK	74.0	-22.9	1.26 V	55	23.74	27.36
2	1375.00	45.0 AV	54.0	-9.0	1.26 V	55	17.64	27.36
3	1625.00	47.6 PK	74.0	-26.4	1.47 V	11	19.29	28.34
4	1625.00	44.5 AV	54.0	-9.5	1.47 V	11	16.16	28.34
5	2387.33	59.0 PK	74.0	-15.0	1.17 V	172	27.82	31.21
6	2387.33	50.1 AV	54.0	-3.9	1.17 V	172	18.87	31.21
7	*2412.00	105.8 PK			1.17 V	172	74.57	31.27
8	*2412.00	103.4 AV			1.17 V	172	72.08	31.27
9	4824.00	55.0 PK	74.0	-19.0	1.00 V	241	15.60	39.42
10	4824.00	52.0 AV	54.0	-2.0	1.00 V	241	12.58	39.42

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.1 PK	74.0	-18.9	1.02 H	69	27.74	27.36
2	1375.00	32.4 AV	54.0	-21.6	1.02 H	69	5.04	27.36
3	1625.00	48.3 PK	74.0	-25.7	1.23 H	350	19.96	28.34
4	1625.00	45.9 AV	54.0	-8.1	1.23 H	350	17.56	28.34
5	*2437.00	103.8 PK			1.07 H	160	72.42	31.34
6	*2437.00	101.6 AV			1.07 H	160	70.27	31.34
7	4874.00	49.9 PK	74.0	-24.1	1.00 H	289	10.32	39.62
8	4874.00	44.9 AV	54.0	-9.1	1.00 H	289	5.30	39.62
9	7311.00	51.3 PK	74.0	-22.7	1.01 H	301	7.18	44.10
10	7311.00	40.1 AV	54.0	-13.9	1.01 H	301	-3.99	44.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.3 PK	74.0	-22.7	1.30 V	60	23.94	27.36
2	1375.00	45.3 AV	54.0	-8.7	1.30 V	60	17.94	27.36
3	1625.00	47.2 PK	74.0	-26.8	1.50 V	20	18.87	28.34
4	1625.00	44.3 AV	54.0	-9.7	1.50 V	20	15.98	28.34
5	*2437.00	106.2 PK			1.16 V	179	74.90	31.34
6	*2437.00	104.1 AV			1.16 V	179	72.75	31.34
7	4874.00	53.8 PK	74.0	-20.2	1.00 V	243	14.18	39.62
8	4874.00	50.2 AV	54.0	-3.8	1.00 V	243	10.59	39.62
9	7311.00	52.8 PK	74.0	-21.3	1.10 V	325	8.65	44.10
10	7311.00	43.5 AV	54.0	-10.5	1.10 V	325	-0.59	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.3 PK	74.0	-18.7	1.26 H	99	27.94	27.36
2	1375.00	50.0 AV	54.0	-4.0	1.26 H	99	22.64	27.36
3	1625.00	48.9 PK	74.0	-25.1	1.32 H	62	20.56	28.34
4	1625.00	45.7 AV	54.0	-8.3	1.32 H	62	17.40	28.34
5	*2462.00	104.0 PK			1.06 H	152	72.60	31.40
6	*2462.00	101.8 AV			1.06 H	152	70.42	31.40
7	2483.66	59.0 PK	74.0	-15.0	1.06 H	152	27.55	31.46
8	2483.66	47.8 AV	54.0	-6.2	1.06 H	152	16.31	31.46
9	4924.00	44.0 PK	74.0	-30.1	1.00 H	288	4.13	39.82
10	4924.00	39.6 AV	54.0	-14.4	1.00 H	288	-0.20	39.82
11	7386.00	51.0 PK	74.0	-23.0	1.04 H	67	6.84	44.18
12	7386.00	39.8 AV	54.0	-14.2	1.04 H	67	-4.37	44.18



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.3 PK	74.0	-18.7	1.02 V	35	27.96	27.36
2	1375.00	48.2 AV	54.0	-5.8	1.02 V	35	20.88	27.36
3	1625.00	48.2 PK	74.0	-25.8	1.20 V	340	19.86	28.34
4	1625.00	45.7 AV	54.0	-8.4	1.20 V	340	17.31	28.34
5	*2462.00	106.9 PK			1.13 V	217	75.50	31.40
6	*2462.00	104.8 AV			1.13 V	217	73.44	31.40
7	2483.50	60.4 PK	74.0	-13.6	1.13 V	217	28.95	31.46
8	2483.50	51.1 AV	54.0	-2.9	1.13 V	217	19.65	31.46
9	4924.00	50.7 PK	74.0	-23.3	1.00 V	241	10.91	39.82
10	4924.00	47.3 AV	54.0	-6.7	1.00 V	241	7.50	39.82
11	7386.00	52.5 PK	74.0	-21.5	1.08 V	341	8.33	44.18
12	7386.00	43.9 AV	54.0	-10.1	1.08 V	341	-0.24	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE,CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11b MODE, CH11, VERTICAL)





A D T

802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.4 PK	74.0	-18.6	1.06 H	70	28.06	27.36
2	1375.00	49.0 AV	54.0	-5.0	1.06 H	70	21.62	27.36
3	1625.00	49.0 PK	74.0	-25.1	1.21 H	324	20.61	28.34
4	1625.00	46.0 AV	54.0	-8.0	1.21 H	324	17.66	28.34
5	2390.00	59.7 PK	74.0	-14.3	1.08 H	161	28.50	31.21
6	2390.00	44.8 AV	54.0	-9.2	1.08 H	161	13.63	31.21
7	*2412.00	101.9 PK			1.08 H	161	70.62	31.27
8	*2412.00	92.9 AV			1.08 H	161	61.62	31.27
9	4824.00	47.6 PK	74.0	-26.4	1.39 H	173	8.18	39.42
10	4824.00	34.6 AV	54.0	-19.4	1.39 H	173	-4.82	39.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.2 PK	74.0	-22.8	1.29 V	50	23.84	27.36
2	1375.00	45.0 AV	54.0	-9.0	1.29 V	50	17.62	27.36
3	1625.00	47.7 PK	74.0	-26.3	1.50 V	20	19.36	28.34
4	1625.00	44.5 AV	54.0	-9.6	1.50 V	20	16.11	28.34
5	2359.73	57.3 PK	74.0	-16.7	1.18 V	171	26.21	31.13
6	2359.73	47.3 AV	54.0	-6.7	1.18 V	171	16.20	31.13
7	2390.00	63.5 PK	74.0	-10.5	1.18 V	171	32.30	31.21
8	2390.00	46.3 AV	54.0	-7.7	1.18 V	171	15.06	31.21
9	*2412.00	105.7 PK			1.18 V	171	74.40	31.27
10	*2412.00	97.1 AV			1.18 V	171	65.78	31.27
11	4824.00	48.7 PK	74.0	-25.3	1.36 V	250	9.30	39.42
12	4824.00	36.7 AV	54.0	-17.3	1.36 V	250	-2.69	39.42

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).

3. The other emission levels were very low against the limit.

4. Margin value = Emission level – Limit value.

5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	56.0 PK	74.0	-18.0	1.08 H	77	28.65	27.36
2	1375.00	50.1 AV	54.0	-3.9	1.08 H	77	22.74	27.36
3	1625.00	49.2 PK	74.0	-24.8	1.20 H	350	20.86	28.34
4	1625.00	45.9 AV	54.0	-8.1	1.20 H	350	17.55	28.34
5	*2437.00	102.1 PK			1.06 H	192	70.80	31.34
6	*2437.00	93.4 AV			1.06 H	192	62.06	31.34
7	4874.00	46.7 PK	74.0	-27.3	1.03 H	215	7.08	39.62
8	4874.00	35.7 AV	54.0	-18.3	1.03 H	215	-3.88	39.62
9	7311.00	52.0 PK	74.0	-22.0	1.22 H	173	7.90	44.10
10	7311.00	39.5 AV	54.0	-14.5	1.22 H	173	-4.60	44.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.5 PK	74.0	-22.5	1.30 V	60	24.18	27.36
2	1375.00	45.3 AV	54.0	-8.7	1.30 V	60	17.96	27.36
3	1625.00	47.7 PK	74.0	-26.3	1.50 V	30	19.34	28.34
4	1625.00	44.7 AV	54.0	-9.4	1.50 V	30	16.31	28.34
5	*2437.00	105.9 PK			1.20 V	169	74.58	31.34
6	*2437.00	97.4 AV			1.20 V	169	66.06	31.34
7	4874.00	49.9 PK	74.0	-24.1	1.40 V	262	10.30	39.62
8	4874.00	38.9 AV	54.0	-15.1	1.40 V	262	-0.68	39.62
9	7311.00	51.7 PK	74.0	-22.3	1.29 V	301	7.59	44.10
10	7311.00	39.1 AV	54.0	-14.9	1.29 V	301	-4.99	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.8 PK	74.0	-18.2	1.09 H	75	28.48	27.36
2	1375.00	49.5 AV	54.0	-4.5	1.09 H	75	22.18	27.36
3	1625.00	49.0 PK	74.0	-25.0	1.23 H	353	20.62	28.34
4	1625.00	45.9 AV	54.0	-8.1	1.23 H	353	17.53	28.34
5	*2462.00	102.6 PK			1.00 H	252	71.21	31.40
6	*2462.00	93.8 AV			1.00 H	252	62.37	31.40
7	2483.61	63.5 PK	74.0	-10.5	1.00 H	250	32.00	31.46
8	2483.61	46.2 AV	54.0	-7.8	1.00 H	250	14.75	31.46
9	4924.00	45.9 PK	74.0	-28.1	1.05 H	124	6.08	39.82
10	4924.00	35.8 AV	54.0	-18.2	1.05 H	124	-4.02	39.82
11	7386.00	52.4 PK	74.0	-21.6	1.42 H	77	8.22	44.18
12	7386.00	39.9 AV	54.0	-14.1	1.42 H	77	-4.28	44.18



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.0 PK	74.0	-23.0	1.24 V	48	23.64	27.36
2	1375.00	47.0 AV	54.0	-7.0	1.24 V	48	19.62	27.36
3	1625.00	48.0 PK	74.0	-26.0	1.50 V	32	19.68	28.34
4	1625.00	45.2 AV	54.0	-8.8	1.50 V	32	16.86	28.34
5	*2462.00	106.6 PK			1.15 V	321	75.16	31.40
6	*2462.00	97.5 AV			1.15 V	321	66.05	31.40
7	2483.52	66.3 PK	74.0	-7.7	1.15 V	321	34.81	31.46
8	2483.52	48.0 AV	54.0	-6.0	1.15 V	321	16.58	31.46
9	4924.00	48.7 PK	74.0	-25.4	1.20 V	294	8.83	39.82
10	4924.00	36.3 AV	54.0	-17.7	1.20 V	294	-3.55	39.82
11	7386.00	52.3 PK	74.0	-21.7	1.42 V	58	8.09	44.18
12	7386.00	39.2 AV	54.0	-14.8	1.42 V	58	-4.96	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11g MODE,CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11g MODE, CH11, VERTICAL)





A D T

802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.1 PK	74.0	-18.9	1.24 H	51	27.74	27.36
2	1375.00	48.8 AV	54.0	-5.3	1.24 H	51	21.39	27.36
3	1625.00	48.5 PK	74.0	-25.6	1.54 H	58	20.11	28.34
4	1625.00	46.0 AV	54.0	-8.0	1.54 H	58	17.68	28.34
5	2390.00	66.4 PK	74.0	-7.6	1.56 H	271	35.19	31.21
6	2390.00	48.8 AV	54.0	-5.2	1.56 H	271	17.59	31.21
7	*2412.00	105.2 PK			1.56 H	271	73.95	31.27
8	*2412.00	96.0 AV			1.56 H	271	64.71	31.27
9	4824.00	47.6 PK	74.0	-26.4	1.06 H	67	8.22	39.42
10	4824.00	34.7 AV	54.0	-19.3	1.06 H	67	-4.75	39.42
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.5 PK	74.0	-22.6	1.30 V	35	24.09	27.36
2	1375.00	45.5 AV	54.0	-8.6	1.30 V	35	18.09	27.36
3	1625.00	47.9 PK	74.0	-26.1	1.50 V	32	19.53	28.34
4	1625.00	45.1 AV	54.0	-8.9	1.50 V	32	16.76	28.34
5	2389.87	68.6 PK	74.0	-5.4	1.08 V	189	37.39	31.21
6	2389.87	50.7 AV	54.0	-3.3	1.08 V	189	19.47	31.21
7	*2412.00	110.4 PK			1.08 V	189	79.13	31.27
8	*2412.00	101.1 AV			1.08 V	189	69.87	31.27
9	4824.00	55.7 PK	74.0	-18.3	1.38 V	318	16.28	39.42
10	4824.00	37.4 AV	54.0	-16.6	1.38 V	318	-1.98	39.42

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.6 PK	74.0	-18.4	1.00 H	80	28.24	27.36
2	1375.00	49.1 AV	54.0	-4.9	1.00 H	80	21.74	27.36
3	1625.00	48.3 PK	74.0	-25.8	1.20 H	350	19.91	28.34
4	1625.00	45.6 AV	54.0	-8.4	1.20 H	350	17.26	28.34
5	*2437.00	106.1 PK			1.60 H	70	74.76	31.34
6	*2437.00	96.2 AV			1.60 H	70	64.88	31.34
7	4874.00	48.2 PK	74.0	-25.8	1.24 H	237	8.58	39.62
8	4874.00	35.2 AV	54.0	-18.8	1.24 H	237	-4.42	39.62
9	7311.00	51.0 PK	74.0	-23.0	1.36 H	74	6.92	44.10
10	7311.00	39.7 AV	54.0	-14.3	1.36 H	74	-4.40	44.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	52.1 PK	74.0	-21.9	1.30 V	55	24.74	27.36
2	1375.00	46.5 AV	54.0	-7.5	1.30 V	55	19.18	27.36
3	1625.00	47.2 PK	74.0	-26.8	1.50 V	20	18.90	28.34
4	1625.00	44.2 AV	54.0	-9.8	1.50 V	20	15.87	28.34
5	*2437.00	110.1 PK			1.10 V	185	78.77	31.34
6	*2437.00	101.2 AV			1.10 V	185	69.88	31.34
7	4874.00	48.5 PK	74.0	-25.5	1.46 V	292	8.88	39.62
8	4874.00	35.1 AV	54.0	-18.9	1.46 V	292	-4.52	39.62
9	7311.00	51.3 PK	74.0	-22.7	1.00 V	242	7.20	44.10
10	7311.00	39.8 AV	54.0	-14.2	1.00 V	242	-4.30	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.2 PK	74.0	-18.8	1.02 H	65	27.88	27.36
2	1375.00	48.5 AV	54.0	-5.6	1.02 H	65	21.09	27.36
3	1625.00	48.5 PK	74.0	-25.5	1.21 H	323	20.16	28.34
4	1625.00	45.7 AV	54.0	-8.3	1.21 H	323	17.36	28.34
5	*2462.00	106.8 PK			1.59 H	65	75.44	31.40
6	*2462.00	97.5 AV			1.59 H	65	66.05	31.40
7	2484.54	64.4 PK	74.0	-9.6	1.59 H	65	32.93	31.46
8	2484.54	46.9 AV	54.0	-7.1	1.59 H	65	15.40	31.46
9	4924.00	47.9 PK	74.0	-26.1	1.40 H	255	8.08	39.82
10	4924.00	35.2 AV	54.0	-18.8	1.40 H	255	-4.62	39.82
11	7386.00	52.1 PK	74.0	-21.9	1.08 H	105	7.94	44.18
12	7386.00	40.3 AV	54.0	-13.7	1.08 H	105	-3.88	44.18



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.7 PK	74.0	-22.3	1.27 V	56	24.38	27.36
2	1375.00	45.3 AV	54.0	-8.7	1.27 V	56	17.96	27.36
3	1625.00	47.9 PK	74.0	-26.2	1.50 V	24	19.51	28.34
4	1625.00	44.8 AV	54.0	-9.3	1.50 V	24	16.41	28.34
5	*2462.00	110.6 PK			1.08 V	156	79.16	31.40
6	*2462.00	102.0 AV			1.08 V	156	70.59	31.40
7	2483.61	70.8 PK	74.0	-3.2	1.08 V	156	39.32	31.46
8	2483.61	49.9 AV	54.0	-4.1	1.08 V	156	18.41	31.46
9	4924.00	48.8 PK	74.0	-25.3	1.19 V	337	8.93	39.82
10	4924.00	35.4 AV	54.0	-18.6	1.19 V	337	-4.40	39.82
11	7386.00	52.7 PK	74.0	-21.4	1.24 V	43	8.47	44.18
12	7386.00	40.5 AV	54.0	-13.5	1.24 V	43	-3.64	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE, CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL)





A D T

802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.4 PK	74.0	-18.6	4.00 H	60	28.06	27.36
2	1375.00	49.3 AV	54.0	-4.7	4.00 H	60	21.96	27.36
3	1625.00	48.2 PK	74.0	-25.8	1.21 H	338	19.90	28.34
4	1625.00	45.3 AV	54.0	-8.7	1.21 H	338	16.98	28.34
5	2387.07	64.7 PK	74.0	-9.3	1.48 H	85	33.51	31.21
6	2387.07	49.9 AV	54.0	-4.1	1.48 H	85	18.68	31.21
7	*2422.00	106.6 PK			1.48 H	85	75.30	31.30
8	*2422.00	95.1 AV			1.48 H	85	63.83	31.30
9	4844.00	48.3 PK	74.0	-25.7	1.30 H	53	8.80	39.50
10	4844.00	34.9 AV	54.0	-19.1	1.30 H	53	-4.60	39.50
11	7266.00	51.0 PK	74.0	-23.0	1.14 H	334	6.94	44.06
12	7266.00	39.5 AV	54.0	-14.5	1.14 H	334	-4.54	44.06

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.0 PK	74.0	-23.0	1.30 V	35	23.66	27.36
2	1375.00	45.0 AV	54.0	-9.0	1.30 V	35	17.62	27.36
3	1625.00	47.9 PK	74.0	-26.2	1.50 V	5	19.51	28.34
4	1625.00	45.3 AV	54.0	-8.7	1.50 V	5	16.97	28.34
5	2386.80	65.5 PK	74.0	-8.5	1.10 V	157	34.32	31.20
6	2386.80	50.4 AV	54.0	-3.6	1.10 V	157	19.19	31.20
7	*2422.00	108.1 PK			1.10 V	157	76.80	31.30
8	*2422.00	98.4 AV			1.10 V	157	67.09	31.30
9	4844.00	48.5 PK	74.0	-25.5	1.36 V	314	9.02	39.50
10	4844.00	35.7 AV	54.0	-18.3	1.36 V	314	-3.76	39.50
11	7266.00	51.2 PK	74.0	-22.8	1.20 V	245	7.18	44.06
12	7266.00	40.0 AV	54.0	-14.0	1.20 V	245	-4.08	44.06

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.2 PK	74.0	-22.8	1.30 H	47	23.88	27.36
2	1375.00	45.2 AV	54.0	-8.8	1.30 H	47	17.84	27.36
3	1625.00	47.2 PK	74.0	-26.8	1.50 H	32	18.90	28.34
4	1625.00	44.2 AV	54.0	-9.8	1.50 H	32	15.87	28.34
5	*2437.00	107.3 PK			1.54 H	253	75.96	31.34
6	*2437.00	97.8 AV			1.54 H	253	66.48	31.34
7	4874.00	47.5 PK	74.0	-26.5	1.05 H	136	7.88	39.62
8	4874.00	35.1 AV	54.0	-18.9	1.05 H	136	-4.52	39.62
9	7311.00	51.5 PK	74.0	-22.5	1.23 H	177	7.40	44.10
10	7311.00	39.5 AV	54.0	-14.5	1.23 H	177	-4.60	44.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	52.0 PK	74.0	-22.0	1.30 V	35	24.64	27.36
2	1375.00	45.9 AV	54.0	-8.1	1.30 V	35	18.54	27.36
3	1625.00	47.7 PK	74.0	-26.4	1.50 V	23	19.31	28.34
4	1625.00	44.2 AV	54.0	-9.8	1.50 V	23	15.87	28.34
5	*2437.00	108.4 PK			1.11 V	163	77.06	31.34
6	*2437.00	98.6 AV			1.11 V	163	67.22	31.34
7	4874.00	48.1 PK	74.0	-25.9	1.16 V	303	8.48	39.62
8	4874.00	35.5 AV	54.0	-18.5	1.16 V	303	-4.08	39.62
9	7311.00	51.3 PK	74.0	-22.7	1.27 V	356	7.20	44.10
10	7311.00	39.7 AV	54.0	-14.3	1.27 V	356	-4.36	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 70%RH 1023 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	55.2 PK	74.0	-18.8	1.02 H	74	27.88	27.36
2	1375.00	49.1 AV	54.0	-4.9	1.02 H	74	21.74	27.36
3	1625.00	48.1 PK	74.0	-25.9	1.23 H	350	19.76	28.34
4	1625.00	45.3 AV	54.0	-8.7	1.23 H	350	16.96	28.34
5	*2452.00	106.8 PK			1.45 H	74	75.42	31.38
6	*2452.00	97.0 AV			1.45 H	74	65.63	31.38
7	2492.87	67.8 PK	74.0	-6.2	1.45 H	74	36.29	31.48
8	2492.87	49.9 AV	54.0	-4.1	1.45 H	74	18.45	31.48
9	4904.00	48.1 PK	74.0	-25.9	1.34 H	147	8.36	39.74
10	4904.00	35.2 AV	54.0	-18.8	1.34 H	147	-4.54	39.74
11	7356.00	51.2 PK	74.0	-22.8	1.05 H	179	7.05	44.15
12	7356.00	39.7 AV	54.0	-14.3	1.05 H	179	-4.45	44.15



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1375.00	51.5 PK	74.0	-22.5	1.30 V	60	24.18	27.36
2	1375.00	45.3 AV	54.0	-8.7	1.30 V	60	17.90	27.36
3	1625.00	47.9 PK	74.0	-26.1	1.50 V	24	19.52	28.34
4	1625.00	45.0 AV	54.0	-9.0	1.50 V	24	16.64	28.34
5	*2452.00	108.7 PK			1.10 V	151	77.27	31.38
6	*2452.00	98.9 AV			1.10 V	151	67.51	31.38
7	2486.82	71.2 PK	74.0	-2.8	1.10 V	151	39.76	31.47
8	2486.82	51.8 AV	54.0	-2.2	1.10 V	151	20.31	31.47
9	4904.00	48.3 PK	74.0	-25.7	1.36 V	316	8.56	39.74
10	4904.00	35.6 AV	54.0	-18.4	1.36 V	316	-4.14	39.74
11	7356.00	51.5 PK	74.0	-22.5	1.42 V	117	7.39	44.15
12	7356.00	39.9 AV	54.0	-14.1	1.42 V	117	-4.25	44.15

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH7, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH7, VERTICAL)



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




A D T

4.3.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	11.58	0.5	PASS
6	2437	11.58	0.5	PASS
11	2462	11.58	0.5	PASS

CH6






A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.48	0.5	PASS
6	2437	16.49	0.5	PASS
11	2462	16.54	0.5	PASS

CH11






A D T

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.66	0.5	PASS
6	2437	17.66	0.5	PASS
11	2462	17.65	0.5	PASS

CH6






A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2422	35.78	0.5	PASS
4	2437	35.55	0.5	PASS
7	2452	35.75	0.5	PASS

CH1



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Anritsu Power Meter	ML2495A	0824006	April 25, 2009	April 24, 2010
Pulse Power Sensor	MA2411B	0738172	April 25, 2009	April 24, 2010

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



4.4.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	21.4	138.0	30	PASS
6	2437	22.1	162.2	30	PASS
11	2462	22.1	162.2	30	PASS

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	23.9	245.5	30	PASS
6	2437	23.7	234.4	30	PASS
11	2462	23.6	229.1	30	PASS

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2412	22.8	23.1	394.7	26.0	30	PASS
6	2437	23.1	23.1	408.3	26.1	30	PASS
11	2462	23.2	23.3	422.7	26.3	30	PASS



A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2422	23.2	23.1	413.1	26.2	30	PASS
4	2437	23.2	23.0	408.5	26.1	30	PASS
7	2452	23.1	23.2	413.1	26.2	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




A D T

4.5.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-6.0	8	PASS
6	2437	-4.9	8	PASS
11	2462	-4.9	8	PASS

CH6






A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-11.7	8	PASS
6	2437	-13.8	8	PASS
11	2462	-13.4	8	PASS

CH1




A D T

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (mW)	TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2412	-13.1	-10.2	0.144	-8.4	8	PASS
6	2437	-13.3	-10.0	0.147	-8.3	8	PASS
11	2462	-14.0	-10.4	0.131	-8.8	8	PASS


For Chain(1): CH6



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (mW)	TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2422	-16.3	-10.4	0.115	-9.4	8	PASS
4	2437	-16.0	-10.7	0.110	-9.6	8	PASS
7	2452	-16.3	-11.0	0.103	-9.9	8	PASS

For Chain (1): CH1



4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 03, 2009	Aug. 02, 2010

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6

4.6.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION:

CH1




CH11






A D T

CH1




CH11




802.11g OFDM MODULATION:

CH1




CH11






A D T

CH1




CH11




802.11n (20MHz) OFDM MODULATION:

CH1




CH11






A D T

CH1




CH11




802.11n (40MHz) OFDM MODULATION:

CH1




CH7






A D T

CH1



CH7





A D T

5. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025:

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

6.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---