



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170300264802
Page: 1 of 34

TEST REPORT

Application No.: SZEM1703002648CR(SGS SZ No.:T51710200201EM)
Applicant: TOY STATE INTERNATIONAL LTD
Address of Applicant: Unit 905, 9/FL, West Wing, Tsimshatsui Centre, 66 Mody Road, Tsimshatsui East, Kowloon, Hong Kong

Equipment Under Test (EUT):

EUT Name: Air Elite 115, Air Elite 115 Race Set

Model No.: 22601, 22625 ♣

♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

FCC ID: V9Q-22625F24

Country of Origin: China

Labeled Age Grading: 8+

Standards: 47 CFR Part 15, Subpart C 15.249

Date of Receipt: 2017-03-31

Date of Test: 2017-05-11 to 2017-05-13

Date of Issue: 2017-05-25

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.





Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-05-25		Original

Authorized for issue by:				
				
		<hr/> Peter Geng /Project Engineer		
				
		<hr/> Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.249	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
20dB Bandwidth	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass
Field Strength of the Fundamental Signal (15.249(a))	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.5&6.6	47 CFR Part 15, Subpart C 15.249(a)	Pass
Restricted Band Around Fundamental Frequency	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.4&6.5&6.6	47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209	Pass
Radiated Emissions	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.4&6.5&6.6	47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)	Pass

Remark:

Model No.: 22601, 22625

Only the model 22625 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on colour, appearance and model name.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS.....	5
4.3 MEASUREMENT UNCERTAINTY.....	6
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 DEVIATION FROM STANDARDS.....	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST.....	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....	10
6.1 ANTENNA REQUIREMENT	10
6.1.1 Test Requirement:.....	10
6.1.2 Conclusion.....	10
7 RADIO SPECTRUM MATTER TEST RESULTS	11
7.1 20dB BANDWIDTH.....	11
7.1.1 E.U.T. Operation.....	11
7.1.2 Measurement Procedure and Data.....	11
7.2 FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL (15.249(A))	12
7.2.1 E.U.T. Operation.....	12
7.2.2 Measurement Procedure and Data.....	12
7.3 RESTRICTED BAND AROUND FUNDAMENTAL FREQUENCY.....	13
7.3.1 E.U.T. Operation.....	14
7.3.2 Measurement Procedure and Data.....	14
7.4 RADIATED EMISSIONS.....	15
7.4.1 E.U.T. Operation.....	15
7.4.2 Measurement Procedure and Data.....	15
8 PHOTOGRAPHS.....	16
8.1 RADIATED EMISSIONS (ABOVE 1GHZ)	16
8.2 RADIATED EMISSIONS(BELOW 1GHZ).....	16
8.3 EUT CONSTRUCTIONAL DETAILS	17
9 APPENDIX.....	18-34



4 General Information

4.1 Details of E.U.T.

Power supply: Remote: DC 6V by 4 x 1.5V "AA" batteries
Operation frequency: 2420MHz-2461MHz
Channel number: 24
Modulation type: GFSK
Antenna type: Monopole antenna
Antenna gain: 0dBi

Channel list

channel	Frequency(MHz)	channel	Frequency(MHz)	channel	Frequency(MHz)
1	2420	9	2434	17	2453
2	2423	10	2436	18	2454
3	2424	11	2438	19	2455
4	2425	12	2440	20	2456
5	2426	13	2443	21	2458
6	2428	14	2444	22	2459
7	2429	15	2445	23	2460
8	2430	16	2450	24	2461

CH1,CH12,CH24 were selected to conducted all tests.

4.2 Description of Support Units

The device was tested as an independently unit

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

RF connected test					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-14
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-10
EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-14
Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14



RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-10	2018-05-10
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203


6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.





7 Radio Spectrum Matter Test Results

7.1 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215
Test Method: ANSI C63.10 (2013) Section 6.9
Limit: N/A

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar
Test mode: c: TX mode_Keep the EUT in transmitting with modulation mode.(for remote)

7.1.2 Measurement Procedure and Data

Test result: Pass. please refer to the appendix for details.



7.2 Field Strength of the Fundamental Signal (15.249(a))

Test Requirement 47 CFR Part 15, Subpart C 15.249(a)
Test Method: ANSI C63.10 (2013) Section 6.5&6.6
Measurement Distance: 3m
Limit:

Frequency	Limit (dBuV/m @3m)	Remark
2400MHz-2483.5MHz	94.0	Average Value
	114.0	Peak Value

7.2.1 E.U.T. Operation

Operating Environment:
Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar
Test mode: c: TX mode_Keep the EUT in transmitting with modulation mode.(for remote)

7.2.2 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel,the middle channel,the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Test result: Pass. please refer to the appendix for details.



7.3 Restricted Band Around Fundamental Frequency

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Measurement Distance: 3m
Limit:

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
Above 1GHz	74.0	Peak Value

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.



7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1015 mbar

Test mode: c: TX mode_Keep the EUT in transmitting with modulation mode.(for remote)

7.3.2 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel,the middle channel,the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Test result: Pass. please refer to the appendix for details.

7.4 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30
30-88	100	40.0	QP	3
88-216	150	43.5	QP	3
216-960	200	46.0	QP	3
960-1000	500	54.0	QP	3
Above 1000	500	54.0	AV	3

7.4.1 E.U.T. Operation

Operating Environment:
Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1015 mbar
Test mode: c: TX mode_Keep the EUT in transmitting with modulation mode.(for remote)


7.4.2 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

Test result: Pass. please refer to the appendix for details.

8 Photographs

8.1 Radiated Emissions (above 1GHz)



8.2 Radiated Emissions(below 1GHz)








8.3 EUT Constructional Details

Refer to Appendix B - Photographs of EUT Constructional Details for SZEM1703002648CR.


9 Appendix

1. 20dB bandwidth






2. Radiated Emissions



Condition: 10m HORIZONTAL
Job No. : 2648CR
Test Mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	40.84	6.80	13.25	32.99	25.90	12.96	29.50	-16.54
2	58.00	7.00	12.15	32.96	26.43	12.62	29.50	-16.88
3	159.78	7.50	13.39	32.73	26.11	14.27	33.10	-18.83
4	404.67	8.31	14.99	32.60	27.18	17.88	35.60	-17.72
5	625.08	8.96	19.22	32.60	27.69	23.27	35.60	-12.33
6 pp	903.31	9.50	22.27	32.50	28.07	27.34	35.60	-8.26



Condition: 10m VERTICAL

Job No. : 2648CR

Test Mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	47.66	6.85	12.83	33.00	27.03	13.71	29.50	-15.79
2	59.03	7.00	12.07	32.95	26.28	12.40	29.50	-17.10
3	166.65	7.50	12.74	32.73	26.95	14.46	33.10	-18.64
4	454.31	8.44	16.23	32.60	27.01	19.08	35.60	-16.52
5	656.53	9.04	19.62	32.60	27.75	23.81	35.60	-11.79
6 pp	955.44	9.59	22.75	32.50	26.62	26.46	35.60	-9.14



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;


L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
47.66	13.71	4.85	16.16	24.17	40.00	-15.83	V
59.03	12.40	4.17	13.90	22.86	40.00	-17.14	V
166.65	14.46	5.28	17.61	24.92	43.50	-18.58	V
454.31	19.08	8.99	29.98	29.54	46.00	-16.46	V
656.53	23.81	15.51	51.69	34.27	46.00	-11.73	V
955.44	26.46	21.04	70.13	36.92	46.00	-9.08	V
40.84	12.96	4.45	14.82	23.42	40.00	-16.58	H
58.00	12.62	4.28	14.25	23.08	40.00	-16.92	H
159.78	14.27	5.17	17.23	24.73	43.50	-18.77	H
404.67	17.88	7.83	26.11	28.34	46.00	-17.66	H
625.08	23.27	14.57	48.57	33.73	46.00	-12.27	H
903.31	27.34	23.28	77.60	37.80	46.00	-8.20	H




Condition: 3m VERTICAL

Job No: : 02648CR

Mode: : 2420 TX RSE


: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1185.936	4.06	24.41	38.08	44.12	34.51	74.00	-39.49	Peak
2	1663.137	4.66	26.52	38.03	43.65	36.80	74.00	-37.20	Peak
3	4840.000	7.79	34.23	38.42	42.45	46.05	54.00	-7.95	Average
4	4840.000	7.79	34.23	38.42	54.25	57.85	74.00	-16.15	Peak
5	pp 7260.000	9.69	36.39	37.06	40.09	49.11	54.00	-4.89	Average
6	pk 7260.000	9.69	36.39	37.06	51.90	60.92	74.00	-13.08	Peak
7	9680.000	11.12	37.53	35.07	38.73	52.31	74.00	-21.69	Peak
8	14079.080	14.61	39.39	38.99	36.28	51.29	74.00	-22.71	Peak




Condition: 3m HORIZONTAL
Job No: : 02648CR
Mode: : 2420 TX RSE
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	4.16	24.75	38.07	43.45	34.29	74.00	-39.71	Peak
2	1751.955	4.76	26.88	38.02	44.38	38.00	74.00	-36.00	Peak
3	4840.000	7.79	34.23	38.42	42.54	46.14	54.00	-7.86	Average
4	4840.000	7.79	34.23	38.42	54.34	57.94	74.00	-16.06	Peak
5	pp 7260.000	9.69	36.39	37.06	38.34	47.36	54.00	-6.64	Average
6	pk 7260.000	9.69	36.39	37.06	50.14	59.16	74.00	-14.84	Peak
7	9680.000	11.12	37.53	35.07	38.00	51.58	74.00	-22.42	Peak
8	13135.540	13.57	38.75	38.14	37.10	51.28	74.00	-22.72	Peak




Condition: 3m HORIZONTAL
Job No: : 02648CR
Mode: : 2440 TX RSE
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1346.769	4.28	25.16	38.07	42.80	34.17	74.00	-39.83	Peak
2	1767.212	4.78	26.94	38.02	44.27	37.97	74.00	-36.03	Peak
3	2065.729	5.07	28.03	37.99	43.52	38.63	74.00	-35.37	Peak
4	4880.000	7.83	34.28	38.44	42.36	46.03	54.00	-7.97	Average
5	4880.000	7.83	34.28	38.44	54.16	57.83	74.00	-16.17	Peak
6 pp	7320.000	9.73	36.37	37.01	37.56	46.65	54.00	-7.35	Average
7 pk	7320.000	9.73	36.37	37.01	49.36	58.45	74.00	-15.55	Peak
8	9753.371	11.20	37.55	35.02	37.11	50.84	74.00	-23.16	Peak




Condition: 3m VERTICAL
 Job No: : 02648CR
 Mode: : 2440 TX RSE
 : Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1304.623	4.23	24.97	38.07	44.23	35.36	74.00	-38.64	Peak
2	1597.181	4.59	26.24	38.04	43.79	36.58	74.00	-37.42	Peak
3	1899.636	4.91	27.44	38.01	44.32	38.66	74.00	-35.34	Peak
4	4880.000	7.83	34.28	38.44	41.17	44.84	54.00	-9.16	Average
5	4880.000	7.83	34.28	38.44	52.97	56.64	74.00	-17.36	Peak
6 pp	7320.000	9.73	36.37	37.01	40.49	49.58	54.00	-4.42	Average
7 pk	7320.000	9.73	36.37	37.01	52.29	61.38	74.00	-12.62	Peak
8	9760.000	11.20	37.55	35.02	36.85	50.58	74.00	-23.42	Peak



Condition: 3m HORIZONTAL
Job No: : 02648CR
Mode: : 2461 TX RSE
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1520.598	4.50	25.89	38.05	45.32	37.66	74.00	-36.34	Peak
2	1798.127	4.81	27.06	38.02	44.13	37.98	74.00	-36.02	Peak
3	4181.768	6.92	33.60	38.09	44.09	46.52	74.00	-27.48	Peak
4	4920.000	7.88	34.36	38.46	43.16	46.94	54.00	-7.06	Average
5	4920.000	7.88	34.36	38.46	54.96	58.74	74.00	-15.26	Peak
6 pp	7380.000	9.78	36.34	36.95	38.82	47.99	54.00	-6.01	Average
7 pk	7380.000	9.78	36.34	36.95	50.62	59.79	74.00	-14.21	Peak
8	9838.312	11.28	37.57	34.98	38.40	52.27	74.00	-21.73	Peak



Condition: 3m VERTICAL
Job No: : 02648CR
Mode: : 2461 TX RSE
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1300.858	4.22	24.96	38.07	44.57	35.68	74.00	-38.32	Peak
2	1767.212	4.78	26.94	38.02	44.61	38.31	74.00	-35.69	Peak
3	4086.182	6.80	33.60	38.04	44.73	47.09	74.00	-26.91	Peak
4	4920.000	7.88	34.36	38.46	42.30	46.08	54.00	-7.92	Average
5	4920.000	7.88	34.36	38.46	54.10	57.88	74.00	-16.12	Peak
6 pp	7380.000	9.78	36.34	36.95	39.83	49.00	54.00	-5.00	Average
7 pk	7380.000	9.78	36.34	36.95	51.63	60.80	74.00	-13.20	Peak
8	9840.000	11.28	37.57	34.98	38.72	52.59	74.00	-21.41	Peak


Remark: 1) Tests were conducted in H/M/L channels and the worst case(low channel) is reported only for 30MHz to 1GHz.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$


3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .

3.Restricted Band Around Fundamental Frequency and Field Strength of the Fundamental Signal (15.249(a))




Condition: 3m VERTICAL
 Job No: : 02648CR
 Mode: : 2420 Field Strength
 : Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.065	5.34	29.07	37.96	35.45	31.90	54.00	-22.10	Average
2 pk	2387.065	5.34	29.07	37.96	62.15	58.60	74.00	-15.40	Peak
3	2400.000	5.35	29.11	37.96	33.73	30.23	54.00	-23.77	Average
4	2400.000	5.35	29.11	37.96	61.23	57.73	74.00	-16.27	Peak
5 pp	2420.000	5.36	29.17	37.96	89.02	85.59	94.00	-8.41	Average
6	2420.000	5.36	29.17	37.96	100.82	97.39	114.00	-16.61	Peak




Condition: 3m HORIZONTAL
Job No: : 02648CR
Mode: : 2420 Field Strength
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2397.849	5.34	29.10	37.96	32.52	29.00	54.00	-25.00 Average
2	2397.849	5.34	29.10	37.96	61.01	57.49	74.00	-16.51 Peak
3	2400.000	5.35	29.11	37.96	34.55	31.05	54.00	-22.95 Average
4	2400.000	5.35	29.11	37.96	55.62	52.12	74.00	-21.88 Peak
5 pp	2420.052	5.36	29.17	37.96	90.77	87.34	94.00	-6.66 Average
6 pk	2420.052	5.36	29.17	37.96	102.57	99.14	114.00	-14.86 Peak




Condition: 3m HORIZONTAL
Job No: : 02648CR
Mode: : 2440 Field Strength
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1 pp	2439.719	5.38	29.22	37.96	88.75	94.00	-8.61	Average
2 pk	2439.719	5.38	29.22	37.96	100.55	114.00	-16.81	Peak




Condition: 3m VERTICAL
Job No: : 02648CR
Mode: : 2440 Field Strength
: Remote

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2439.979	5.38	29.23	37.96	89.57	86.22	94.00	-7.78	Average
2 pk	2439.979	5.38	29.23	37.96	101.37	98.02	114.00	-15.98	Peak



Condition: 3m HORIZONTAL
 Job No: : 02648CR
 Mode: : 2461 Field Strength
 : Remote

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2460.715	5.39	29.29	37.95	88.72	85.45	94.00	-8.55 Average
2 pk	2460.715	5.39	29.29	37.95	100.52	97.25	114.00	-16.75 peak
3	2483.500	5.41	29.35	37.95	45.68	42.49	54.00	-11.51 Average
4	2483.500	5.41	29.35	37.95	57.48	54.29	74.00	-19.71 peak
5	2487.707	5.41	29.36	37.95	46.37	43.19	54.00	-10.81 Average
6	2487.707	5.41	29.36	37.95	58.17	54.99	74.00	-19.01 peak



Condition: 3m VERTICAL
Job No: : 02648CR
Mode: : 2461 Field Strength
: Remote

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.411	5.39	29.29	37.95	91.25	87.98	94.00	-6.02 Average
2	2461.411	5.39	29.29	37.95	99.78	96.51	114.00	-17.49 peak
3	2483.500	5.41	29.35	37.95	47.27	44.08	54.00	-9.92 Average
4	2483.500	5.41	29.35	37.95	59.07	55.88	74.00	-18.12 Peak
5	2488.059	5.41	29.37	37.95	49.59	46.42	54.00	-7.58 Average
6 pk	2488.059	5.41	29.37	37.95	61.39	58.22	74.00	-15.78 peak