



Valued Quality. Delivered.

## TEST REPORT

**Report No.: 17020767HKG-001**

**Toy State International Limited**

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: V9Q-77020R24)**

Transceiver

Prepared and Checked by:

Approved by:

Signed On File  
Xu Lap Ho, Leo  
Assistant Engineer

---

Wong Kwok Yeung, Kenneth  
Senior Lead Engineer  
Date: March 16, 2017

## INTERTEK TESTING SERVICES

---

### GENERAL INFORMATION

Grantee:	Toy State International Limited
Grantee Address:	Unit 905, 9/F., West Wing, Tsim Sha Tsui Centre, 66 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Contact Person:	Kenny Chik / Joe Hu
Tel:	755 28700378
Fax:	755 28700487
e-mail:	<a href="mailto:saleshk.Team.A@toystate.com">saleshk.Team.A@toystate.com</a>
Manufacturer:	Toy State International Limited
Manufacturer Address:	Unit 905, 9/F., West Wing, Tsim Sha Tsui Centre, 66 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Brand Name:	MARVEL
Model:	77021
Additional Model:	77022, 77023
Asst. Number:	77020
Type of EUT:	Transceiver
Description of EUT:	Hero Blaster – Spiderman (77021), Hero Blaster – Hulk (77022), Hero Blaster – Captain America (77023)
Serial Number:	N/A
FCC ID:	V9Q-77020R24
Date of Sample Submitted:	February 23, 2017
Date of Test:	February 23, 2017 to March 14, 2017
Report No.:	17020767HKG-001
Report Date:	March 16, 2017
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

## INTERTEK TESTING SERVICES

---

### SUMMARY OF TEST RESULT

TEST SPECIFICATION	REFERENCE	RESULTS
Radiated Emission Radiated Emission on the Bandedge	15.249, 15.209	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards:  
FCC Part 15, October 1, 2015 Edition

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>General Description</u></b> .....	1
1.1	Product Description .....	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology .....	1
1.4	Test Facility .....	1
2.0	<b><u>System Test Configuration</u></b> .....	2
2.1	Justification.....	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories .....	2
2.4	Measurement Uncertainty.....	2
2.5	Support Equipment List and Description.....	2
3.0	<b><u>Emission Results</u></b> .....	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph .....	4
3.3	Radiated Emission Data .....	4
4.0	<b><u>Equipment Photographs</u></b> .....	9
5.0	<b><u>Product Labelling</u></b> .....	9
6.0	<b><u>Technical Specifications</u></b> .....	9
7.0	<b><u>Instruction Manual</u></b> .....	9
8.0	<b><u>Miscellaneous Information</u></b> .....	10
8.1	Radiated Emission on the Bandedge.....	10
8.2	Discussion of Pulse Desensitization .....	11
8.3	Calculation of Average Factor.....	11
8.4	Emissions Test Procedures .....	13
9.0	<b><u>Equipment List</u></b> .....	16

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a 2.4GHz Transceiver (Car Unit) controlled by controller operating at a frequency range of 2410-2475MHz with 1MHz channel spacing. The EUT is powered by 4 x 1.5V AA batteries. After switching on the EUT and being paired with the controller, the EUT can be controlled to move forward, backward and turn left/ right by the controller.

The Model: 77022 and 77023 are the same as the Model: 77021 in hardware aspect. The difference in model number serves as marketing strategy. The models are different in package only.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

The Certification procedure of Controller for this transceiver (with FCC ID: V9Q-77020T24) is being processed as the same time of this application.

#### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

#### 1.4 Test Facility

The 3m Chamber facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new 4 x 1.5V AA batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.5 Support Equipment List and Description

N/A.

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB $\mu$ V/m
- RR = RA - AG - AV in dB $\mu$ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 52.0 \text{ dB}\mu\text{V/m} \\ AF &= 7.4 \text{ dB} & RR &= 18.0 \text{ dB}\mu\text{V} \\ CF &= 1.6 \text{ dB} & LF &= 9.0 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ AV &= 5.0 \text{ dB} \\ FS &= RR + LF \\ FS &= 18 + 9 = 27 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 2400 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 7.2 dB



## INTERTEK TESTING SERVICES

Applicant: Toy State International Limited.

Date of Test: March 14, 2017

Model: 77021 (Car)

Worst-Case Operating Mode: Transmission

Table 1  
**Radiated Emissions**  
Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2410.000	90.8	33	29.4	87.2	15.3	71.9	94.0	-22.1
V	2400.000	65.7	33	29.4	62.1	15.3	46.8	54.0	-7.2
<b>V</b>	<b>4820.000</b>	<b>54.6</b>	<b>33</b>	<b>34.9</b>	<b>56.5</b>	<b>15.3</b>	<b>41.2</b>	<b>54.0</b>	<b>-12.8</b>
V	7230.000	48.3	33	37.9	53.2	15.3	37.9	54.0	-16.1
H	9640.000	38.0	33	40.4	45.4	15.3	30.1	54.0	-23.9
<b>H</b>	<b>12050.000</b>	<b>38.8</b>	<b>33</b>	<b>40.5</b>	<b>46.3</b>	<b>15.3</b>	<b>31.0</b>	<b>54.0</b>	<b>-23.0</b>
H	14460.000	40.2	33	40.0	47.2	15.3	31.9	54.0	-22.1

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2410.000	90.8	33	29.4	87.2	114.0	-26.8
V	2400.000	65.7	33	29.4	62.1	74.0	-11.9
<b>V</b>	<b>4820.000</b>	<b>54.6</b>	<b>33</b>	<b>34.9</b>	<b>56.5</b>	<b>74.0</b>	<b>-17.5</b>
V	7230.000	48.3	33	37.9	53.2	74.0	-20.8
H	9640.000	38.0	33	40.4	45.4	74.0	-28.6
<b>H</b>	<b>12050.000</b>	<b>38.8</b>	<b>33</b>	<b>40.5</b>	<b>46.3</b>	<b>74.0</b>	<b>-27.7</b>
H	14460.000	40.2	33	40.0	47.2	74.0	-26.8

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

Applicant: Toy State International Limited

Date of Test: March 14, 2017

Model: 77021 (Car)

Worst-Case Operating Mode: Transmission

Table 2  
**Radiated Emissions**  
Pursuant to FCC Part 15 Section 15.249 Requirement

### Middle Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	94.0	33	29.4	90.4	15.3	75.1	94.0	-18.9
<b>V</b>	<b>4880.000</b>	<b>54.1</b>	<b>33</b>	<b>34.9</b>	<b>56.0</b>	<b>15.3</b>	<b>40.7</b>	<b>54.0</b>	<b>-13.3</b>
<b>V</b>	<b>7320.000</b>	<b>48.8</b>	<b>33</b>	<b>37.9</b>	<b>53.7</b>	<b>15.3</b>	<b>38.4</b>	<b>54.0</b>	<b>-15.6</b>
H	9760.000	38.4	33	40.4	45.8	15.3	30.5	54.0	-23.5
<b>H</b>	<b>12200.000</b>	<b>38.9</b>	<b>33</b>	<b>40.5</b>	<b>46.4</b>	<b>15.3</b>	<b>31.1</b>	<b>54.0</b>	<b>-22.9</b>
H	14640.000	41.6	33	38.4	47.0	15.3	31.7	54.0	-22.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2440.000	94.0	33	29.4	90.4	114.0	-23.6
<b>V</b>	<b>4880.000</b>	<b>54.1</b>	<b>33</b>	<b>34.9</b>	<b>56.0</b>	<b>74.0</b>	<b>-18.0</b>
<b>V</b>	<b>7320.000</b>	<b>48.8</b>	<b>33</b>	<b>37.9</b>	<b>53.7</b>	<b>74.0</b>	<b>-20.3</b>
H	9760.000	38.4	33	40.4	45.8	74.0	-28.2
<b>H</b>	<b>12200.000</b>	<b>38.9</b>	<b>33</b>	<b>40.5</b>	<b>46.4</b>	<b>74.0</b>	<b>-27.6</b>
H	14640.000	41.6	33	38.4	47.0	74.0	-27.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

Applicant: Toy State International Limited  
 Model: 77021 (Car)  
 Worst-Case Operating Mode: Transmission

Date of Test: March 14, 2017

Table 3  
**Radiated Emissions**  
 Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2475.000	95.7	33	29.4	92.1	15.3	76.8	94.0	-17.2
<b>V</b>	<b>2483.500</b>	<b>65.3</b>	<b>33</b>	<b>29.4</b>	<b>61.7</b>	<b>15.3</b>	<b>46.4</b>	<b>54.0</b>	<b>-7.6</b>
V	4950.000	55.0	33	34.9	56.9	15.3	41.6	54.0	-12.4
<b>V</b>	<b>7425.000</b>	<b>48.1</b>	<b>33</b>	<b>37.9</b>	<b>53.0</b>	<b>15.3</b>	<b>37.7</b>	<b>54.0</b>	<b>-16.3</b>
H	9900.000	37.7	33	40.4	45.1	15.3	29.8	54.0	-24.2
<b>H</b>	<b>12375.000</b>	<b>39.3</b>	<b>33</b>	<b>40.5</b>	<b>46.8</b>	<b>15.3</b>	<b>31.5</b>	<b>54.0</b>	<b>-22.5</b>
H	14850.000	41.6	33	38.4	47.0	15.3	31.7	54.0	-22.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2475.000	95.7	33	29.4	92.1	114.0	-21.9
<b>V</b>	<b>2483.500</b>	<b>65.3</b>	<b>33</b>	<b>29.4</b>	<b>61.7</b>	<b>74.0</b>	<b>-12.3</b>
V	4950.000	55.0	33	34.9	56.9	74.0	-17.1
<b>V</b>	<b>7425.000</b>	<b>48.1</b>	<b>33</b>	<b>37.9</b>	<b>53.0</b>	<b>74.0</b>	<b>-21.0</b>
H	9900.000	37.7	33	40.4	45.1	74.0	-28.9
<b>H</b>	<b>12375.000</b>	<b>39.3</b>	<b>33</b>	<b>40.5</b>	<b>46.8</b>	<b>74.0</b>	<b>-27.2</b>
H	14850.000	41.6	33	38.4	47.0	74.0	-27.0

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

---

Applicant: Toy State International Limited  
 Model: 77021 (Car)  
 Worst-Case Operating Mode: Transmission

Date of Test: March 14, 2017

Table 4  
**Radiated Emissions**  
 Pursuant to FCC Part 15 Section 15.209 Requirement

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
<b><i>H</i></b>	<b><i>37.517</i></b>	<b><i>32.0</i></b>	<b><i>16</i></b>	<b><i>10.0</i></b>	<b><i>26.0</i></b>	<b><i>40.0</i></b>	<b><i>-14.0</i></b>
H	100.325	22.9	16	12.0	18.9	43.5	-24.6
<b><i>V</i></b>	<b><i>112.813</i></b>	<b><i>24.6</i></b>	<b><i>16</i></b>	<b><i>14.0</i></b>	<b><i>22.6</i></b>	<b><i>43.5</i></b>	<b><i>-20.9</i></b>
<b><i>V</i></b>	<b><i>118.997</i></b>	<b><i>23.6</i></b>	<b><i>16</i></b>	<b><i>14.0</i></b>	<b><i>21.6</i></b>	<b><i>43.5</i></b>	<b><i>-21.9</i></b>
<b><i>V</i></b>	<b><i>252.008</i></b>	<b><i>26.5</i></b>	<b><i>16</i></b>	<b><i>20.0</i></b>	<b><i>30.5</i></b>	<b><i>46.0</i></b>	<b><i>-15.5</i></b>
<b><i>V</i></b>	<b><i>276.016</i></b>	<b><i>23.7</i></b>	<b><i>16</i></b>	<b><i>22.0</i></b>	<b><i>29.7</i></b>	<b><i>46.0</i></b>	<b><i>-16.3</i></b>
V	300.023	23.1	16	22.0	29.1	46.0	-16.9
<b><i>V</i></b>	<b><i>324.031</i></b>	<b><i>22.0</i></b>	<b><i>16</i></b>	<b><i>24.0</i></b>	<b><i>30.0</i></b>	<b><i>46.0</i></b>	<b><i>-16.0</i></b>
H	431.943	22.3	16	25.0	31.3	46.0	-14.7
V	724.035	22.9	16	30.0	36.9	46.0	-9.1

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

---

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## INTERTEK TESTING SERVICES

---

### 8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

### 8.1 Radiated Emission on the Bandedge

The test data of bandedge emissions were shown on the above radiated emissions table 1 & table 3 respectively.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

## INTERTEK TESTING SERVICES

---

### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 1.9ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100ms



Effective period of the cycle =  $1.9 \times 9 = 17.1\text{ms}$

DC =  $17.1/100 = 0.171\text{ms}$

Therefore, the averaging factor is found by  $20\log 0.171 = -15.3\text{dB}$ .

# INTERTEK TESTING SERVICES

## Average Factor





## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


## INTERTEK TESTING SERVICES

### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz

## INTERTEK TESTING SERVICES

---

### 9.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	EMI Test Receiver	Spectrum Analyzer
Registration No.	EW-3156	EW-3095	EW-2253
Manufacturer	R&S	R&S	R&S
Model No.	ESR26	ESCI	FSP40
Calibration Date	Dec. 06, 2016	Oct. 25, 2016	Jun. 15, 2016
Calibration Due Date	Dec. 06, 2017	Oct. 25, 2017	Jun. 15, 2017

Equipment	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-0447	EW-0571
Manufacturer	EMCO	EMCO
Model No.	3146	3104C
Calibration Date	May 18, 2016	May 18, 2016
Calibration Due Date	Nov. 18, 2017	Nov. 18, 2017

Equipment	Double Ridged Guide Antenna
Registration No.	EW-1133
Manufacturer	EMCO
Model No.	3115
Calibration Date	Nov. 05, 2015
Calibration Due Date	May 05, 2017

#### 2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Aug. 26, 2016
Calibration Due Date	Aug. 26, 2017

END OF TEST REPORT