

Analysis Report

Report No.: 14030927HKG-001

The Equipment Under Test (EUT) is a portable transmitter of a RC car operating at 27.145 MHz as dictated by a crystal. The EUT is powered by a 4.5 V DC source (3 x 1.5V AAA batteries). The EUT has a pair of control keys to control the left wheels and right wheel of the receiver of the RC Car to move forward, backward, left and right. The EUT has another pair of keys to control the receiver of the RC Car to jump.

After switching ON the EUT and the receiver of the RC Car, activating the control keys on the EUT can control the receiver moving forward, backward, left, right or jump.

Antenna Type: External integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 76.5dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 79.5dB μ V/m at 3m in frequency 27.145MHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.0267\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.0267mW.

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

= $[474 \cdot (1 + \log_{10}(f(\text{MHz}))) / 2]$

= 371.2mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.