

# Analysis Report

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Car Unit) for a RC Car at 2410 to 2475MHz with 1MHz channel spacing. The EUT is powered by 1 X 6.0V rechargeable battery. After switch on the EUT and paired with controller, the EUT can be controlled to move forward, backward, turning left/right direction by the corresponding controller.

Antenna Type: External integral antenna  
Antenna Gain: 0dBi  
Nominal rated field strength: 90.8dB $\mu$ V/m at 3m  
Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 93.8dB $\mu$ V/m at 3m in frequency 2.4GHz, thus;

The EIRP =  $[(FS * D)^2 * 1000 / 30] = 0.720mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain  
So;

Conducted Power = 0.720mW.

The SAR Exclusion Threshold Level:  
=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz}) = 3.0 * 5 / \text{sqrt}(2.475) mW$   
= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.