



June 4, 2008

Toy State International Limited  
G3-5, G/F New East Ocean Centre, 9 Science Museum Road,  
T.S.T. East, Kowloon, Hong Kong.

Dear Wayne Lee:

Enclosed you will find your file copy of a Part 15 report (FCC ID: V9Q-IR1004).

For your reference, TCB will normally take another 15-20 days for reviewing the report. Approval will then be granted when no query is sorted.

Please contact me if you have any questions regarding the enclosed material.

Sincerely,

A handwritten signature in black ink, appearing to read "Shawn Xing", with a stylized flourish extending from the end.

Shawn Xing  
Assistant Manager

Enclosure



## Toy State International Limited

Application  
For  
Certification  
**(FCC ID: V9Q-IR1004)**  
Computer Peripheral

*Billy Li*

GZ08050583-1

Billy Li

June 4, 2008

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C\_PC\_a

**Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch**

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: [www.china.intertek-etlsemko.com](http://www.china.intertek-etlsemko.com)

# INTERTEK TESTING SERVICES

---

## LIST OF EXHIBITS

### *INTRODUCTION*

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labeling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information

# INTERTEK TESTING SERVICES

## MEASUREMENT / TECHNICAL REPORT

**Toy State International Limited – MODEL: 91120F**

**FCC ID: V9Q-IR1004**

**June 4, 2008**

This report concerns (check one:)      Original Grant ☒ Class II Change ☐

Equipment Type: Class B Computing Device Peripheral (example: computer, printer, modem, etc.)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes ☐      No ☒

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?      Yes ☐      No ☒

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [09-20-07 Edition] provision.

Report prepared by:

Shawn Xing  
Intertek Testing Services Shenzhen Ltd.  
Kejiyuan Branch  
6F, D Block, Huahan Building, Langshan Road  
Nanshan District, Shenzhen, P. R. China  
Phone: (86 755) 8601 6288  
Fax: (86 755) 8601 6751

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0</b>	<b><u>General Description</u></b> .....	2
1.1	Product Description.....	2
1.2	Related Submittal(s) Grants.....	2
1.3	Test Methodology.....	3
1.4	Test Facility.....	3
<b>2.0</b>	<b><u>System Test Configuration</u></b> .....	5
2.1	Justification.....	5
2.2	EUT Exercising Software.....	5
2.3	Special Accessories.....	5
2.4	Equipment Modification.....	5
2.5	Measurement Uncertainty.....	6
2.6	Support Equipment List and Description.....	6
<b>3.0</b>	<b><u>Emission Results</u></b> .....	8
3.1	Field Strength Calculation.....	9
3.2	Radiated Emission Configuration Photograph.....	11
3.3	Radiated Emission Data.....	12
3.4	Conducted Emission Configuration Photograph.....	15
3.5	Conducted Emission Data.....	16
<b>4.0</b>	<b><u>Equipment Photographs</u></b> .....	19
<b>5.0</b>	<b><u>Product Labelling</u></b> .....	21
<b>6.0</b>	<b><u>Technical Specifications</u></b> .....	23
<b>7.0</b>	<b><u>Instruction Manual</u></b> .....	25
<b>8.0</b>	<b><u>Miscellaneous Information</u></b> .....	27
8.1	Emissions Test Procedures.....	28

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label / Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	agency.pdf

# **INTERTEK TESTING SERVICES**

---

## **EXHIBIT 1**

### **GENERAL DESCRIPTION**

## INTERTEK TESTING SERVICES

---

### 1.0 **General Description**

#### 1.1 Product Description

The Equipment Under Test (EUT) is a Mp3 player with 512MB memory size, model: 91120F. The main function of the EUT is to play music files, It also can store data and download the audio files from a PC. The device is powered by DC 1.5V (a AAA battery) for music playing mode and powered from PC USB port for data transfer mode.

#### 1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripheral.



## INTERTEK TESTING SERVICES

---

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data is **SHENZHEN ACADEMY OF METROLOGY AND QUALITY INSPECTION** and located at Bldg. of Metrology & Quality Inspection, Longzhu Road, Shenzhen, Guangdong, China. This test facility and site measurement data have been fully placed on file with the FCC.

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 2**

### **SYSTEM TEST CONFIGURATION**

---

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered from PC USB port

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 1GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by Toy State International Limited will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services.

## INTERTEK TESTING SERVICES

### 2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.6 Support Equipment List and Description

This product was tested in the following configuration:


Refer List:

Description	Manufacturer	Model No.	Serial No.
Test PC`	Compaq	P9111A#AB2	CN31104346
LCD Monitor	Compaq	P4825	CN3087A026
Keyboard	Compaq	KB-0133	CT:B55930DGAN N3NU
Mouse	Compaq	M-S69	CT:F466BOMMSNS05J2
Printer	Canon	BJC-265SP	EVX81604
Modem	TP-Link	TM-EC5658V	03402406009
DSLAM	Harbour	Hammer 3300	---
Adaptor for LCD	Liteon	PA-1400-02	3101571101LN
Adaptor for Printer	Canon	AD-300	---
Adaptor for Modem	---	EI-41-AD901	---

All the items listed under section 2.0 of this report are

*Confirmed by:*

*Shawn Xing*  
*Assistant Manager*  
*Intertek Testing Services Shenzhen Ltd.*  
*Kejiyuan Branch*  
*Agent for Toy State International Limited*



Signature

June 4, 2008

Date

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 3**

### **EMISSION RESULTS**

## INTERTEK TESTING SERVICES

---

### 3.0 **Emission Results**

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation (cont'd)

#### Example

Assume a receiver reading of 62.0dB $\mu$ V is obtained. The antenna factor of 7.4dB and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0\text{dB}\mu\text{V}$$

$$AF = 7.4\text{dB}$$

$$CF = 1.6\text{dB}$$

$$AG = 29.0\text{dB}$$

$$PD = 0\text{dB}$$

$$AV = -10\text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32\text{dB}\mu\text{V/m})/20] = 39.8\mu\text{V/m}$$



## **INTERTEK TESTING SERVICES**

---

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
At  
213.754MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

## INTERTEK TESTING SERVICES

---

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 1.0dB margin

#### **TEST PERSONNEL:**



---

*Signature*

Billy Li, Engineer

*Typed / Printed Name*

June 4, 2008

*Date*

## INTERTEK TESTING SERVICES

Company: Toy State International Limited  
Model: 91120F  
Worst Case Operating Mode: Download

Date of Test: May 28, 2008

**Table 1**

### **Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	191.568	46.4	20.0	10.4	36.8	43.5	-6.7
Horizontal	213.726	49.6	20.0	10.3	39.9	43.5	-3.6
Horizontal	217.284	51.1	20.0	10.4	41.5	46.0	-4.5
Vertical	191.263	44.1	20.0	10.4	34.5	43.5	-9.0
Vertical	211.392	48.9	20.0	10.3	39.2	43.5	-4.3
Vertical	213.754	52.2	20.0	10.3	42.5	43.5	-1.0
Vertical	240.045	42.0	20.0	12.2	34.2	46.0	-11.8
Vertical	480.125	38.8	20.0	17.4	36.2	46.0	-9.8

- NOTES: 1. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
2. Negative value in the margin column shows emission below limit.
3. All emissions are below the QP limit.

Test Engineer: Billy Li

---

## INTERTEK TESTING SERVICES

---

Company: Toy State International Limited  
Model: 91120F  
Worst Case Operating Mode: MP3 Playing

Date of Test: May 28, 2008

**Table 2**

**Radiated Emissions**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	190.048	35.9	20.0	10.4	26.3	43.5	-17.2
Horizontal	270.325	40.5	20.0	12.7	33.2	46.0	-12.8
Horizontal	407.319	39.0	20.0	16.4	35.4	46.0	-10.6
Vertical	32.857	30.9	20.0	17.5	28.4	40.0	-11.6
Vertical	58.143	34.8	20.0	7.8	22.6	40.0	-17.4
Vertical	465.518	31.1	20.0	17.3	28.4	46.0	-17.6

NOTES: 1. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

4. Negative value in the margin column shows emission below limit.

5. All emissions are below the QP limit.

Test Engineer: Billy Li

## INTERTEK TESTING SERVICES

---

### 3.4 Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration  
at  
16.728 MHz

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

## INTERTEK TESTING SERVICES

---

### 3.5 Conducted Emission Data

Judgement: Passed by 8.1 dB margin

#### **TEST PERSONNEL:**



---

*Signature*

Billy Li, Engineer  
*Typed/Printed Name*

June 4, 2008  
*Date*

---

## INTERTEK TESTING SERVICES

---

Company: Toy State International Limited  
Model: 91120F  
Worst Case Operating Mode: Download

Date of Test: May 21, 2008

**Table 3**  
**Conducted Emissions**

Live Line Data

Frequency (MHz)	Quasi-Peak		Average	
	Disturbance level dB( $\mu$ V)	Permitted limit dB( $\mu$ V)	Disturbance level dB( $\mu$ V)	Permitted limit dB( $\mu$ V)
0.354	34.3	58.9	28.3	48.9
10.238	49.3	60.0	39.5	50.0
10.758	50.7	60.0	40.1	50.0
16.044	42.9	60.0	39.6	50.0
16.453	48.6	60.0	35.9	50.0
16.715	47.4	60.0	38.2	50.0

Neutral Line Data

Frequency (MHz)	Quasi-Peak		Average	
	Disturbance level dB( $\mu$ V)	Permitted limit dB( $\mu$ V)	Disturbance level dB( $\mu$ V)	Permitted limit dB( $\mu$ V)
0.394	35.7	58.0	26.7	48.0
10.259	38.7	60.0	33.9	50.0
10.755	37.5	60.0	31.5	50.0
11.120	42.3	60.0	36.7	50.0
16.432	42.6	60.0	37.4	50.0
16.728	42.7	60.0	41.9	50.0

Test Engineer: Billy Li

TRF no.: FCC 15C\_PC\_a  
FCC ID: V9Q-IR1004

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 4**

### **EQUIPMENT PHOTOGRAPHS**



## INTERTEK TESTING SERVICES

---

### 4.0 **Equipment Photographs**

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 5**

### **PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 6**

### **TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 6.0 **Technical Specifications**

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 7**

### **INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

---

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 8**

### **MISCELLANEOUS INFORMATION**



## INTERTEK TESTING SERVICES

---

### 8.0 **Miscellaneous Information**

This miscellaneous information includes emission measuring procedure.

## **INTERTEK TESTING SERVICES**

---

### **8.1 Emissions Test Procedures**

The following is a description of the test procedure used by Intertek Testing Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2003.

The computer peripheral equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in QP mode from the frequency band 30MHz to 1GHz and RBW setting is 120kHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

## **INTERTEK TESTING SERVICES**

---

### **8.1 Emissions Test Procedures (cont'd)**

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 – 2003.