



MPE ESTIMATION

FCC ID: VA8-P665VXRSIBPSS

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm ²)
2.4GWIFI	14.03	14±1(15)	31.623	3.28	2.13	0.01340
BLE	-2.04	-3±1(-2)	0.631	3.28	2.13	0.00027
EDR	5.49	5±1(6)	3.981	3.28	2.13	0.00169

$$Pd = \frac{P_{out} * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2401170395-1E/2E/3E**, antenna gain= 3.28dBi

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01340mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

WiFi and Bluetooth cannot be transmitted at the same time.

-----The End-----