

CF HID 125Khz PROX Reader



Main Features:

- SMI's HID PROX Reader is a mobile reader for HID125Khz PROX cards.
- The reader will fit into any compact flash Type II slot (CF Type II) and is therefore compatible with most modern PDA's and many rugged devices.
- Specifically designed for mobile applications and is a low power device.
- Provided with a SDK that allows it to be easily integrated into most applications.
- Compatible with any HID prox card format.

Specifications	
Form factor	Compact Flash Type II
Dimensions	51mm high x 42mm wide x 5mm deep
Weight	40g approx
Power supply requirements	20mA @ 3 – 5 volts
Operating frequency	125 KHz
Approvals	CE, FCC
Software development	DLL based SDK with documentation and sample code
Card formats	H10301 (26-bit), H10302 (37-bit), H10304 (37-bit), Corporate 1000 (35-bit). Any other format, specified by simple text file



To purchase:

- ✓ Secure on-line purchasing is available on SMI's website at www.smi-global.co.uk
- ✓ Call Sales on +44 (0)1284 760900
- ✓ Email: Sales@smi-global.co.uk

Smart Media Innovations Ltd

www.smi-global.co.uk • info@smi-global.co.uk • Office: +44 (0)1284 760900 • Mobile: +44(0)7815 158203

Copyright © 2005, 06, 07 Smart Media Innovations Ltd. All rights reserved