## Exhibit 3 FCC REQUIRED INFORMATION

The following information is presented in the content and format requested by FCC:

#### Section 2.1033 (c)(1):

The full name and mailing address of the manufacturer of the device and the applicant for certification

Manufacturer: NOKIA SOLUTIONS AND NETWORKS OY

KARAKAARI 7, FI-02610 ESPOO

**FINLAND** 

Applicant:

**Nokia Solutions and Networks** 

3201 Olympus Blvd

Dallas, TX, 75019

Attention: Steve Mitchell Phone: 972-936-7500

email: steve.mitchell@nokia.com

Section 2.1033(c)(2): IC Identifier: VBNAEQM-01

**Section 2.1033(c)(4):** Type or types of emission:

The Nokia **AirScale MAA 64T64R 192AE B48 AEQM** is capable of amplifying transmission involving the following types of emissions:

BW (MHz)	<b>Emissions Designation</b>	
10	9M27F9W	
20	18M3F9W	
10+20	29M2F9W	
20+20	40M0F9W	

Public Page 1 of 2

### **Section 2.1033(c)(5):** Frequency range, Transmit / Receive:

Blocks	Transmit Range (MHz)	Receive Range (MHz)	Bandwidth (MHz)
B48	3550 - 3700	3550 - 3700	150

# Exhibit 3 FCC REQUIRED INFORMATION continued

**Section 2.1033(c)(6):** Range of operating power values or specific operating power levels, and description of any means provided for variation of operating power.

#### Response:

The AirScale MAA 64T64R 192AE B48 AEQM is capable operating from 14 dBm to 27 dBm/port in 0.5 dB steps.

**Section 2.1033(c)(7):** Maximum power rating as defined in the applicable part (s) of the rules.

### Response:

The maximum average power output of the AirScale MAA 64T64R 192AE B48 AEQM at the Antenna connection is summarized in the following table:

Max Power per Port	Total Max Power	Modulation
0.27W	8.6 WO	LTE

Public Page 2 of 2